BRAKES TECHNICAL DATA

id045000800100

Item	Specification
Brake fluid type [Rear brake (drum)]	SKYACTIV-G 1.3 or SKYACTIV-G 1.5: SAE J1703 or FMVSS116 DOT-3 or DOT-4 SKYACTIV-D 1.5: SAE J1703 or FMVSS116 DOT-4
Brake fluid type [Rear brake (disc)]	SAE J1703 or FMVSS116 DOT-3 or DOT-4
Brake pedal height (reference value)	131 mm {5.16 in}
Brake pedal play	0.0—5 mm {0.0—0.1 in}
Brake pedal-to-floor clearance (Brake pedal when depressed at 147 N {15.0 kgf, 33.0 lbf})	86 mm {3.4 in} or more
Front disc plate runout limit	0.04 mm {0.002 in}
Minimum front disc plate thickness	20.0 mm {0.787 in}
Minimum front disc plate thickness after machining using a brake lathe on-vehicle	20.8 mm {0.819 in}
Minimum front disc pad thickness	2.0 mm {0.079 in} min.
Rear disc plate runout limit	0.1 mm {0.004 in}
Minimum rear disc plate thickness	7.5 mm {0.30 in}
Minimum rear disc plate thickness after machining using a brake lathe on-vehicle	8.3 mm {0.33 in}
Minimum rear disc pad thickness	2.0 mm {0.079 in} min.
Minimum brake lining thickness	1.0 mm {0.039 in}
Brake drum wear maximum	201.5 mm {7.933 in}
Parking brake lever stroke when pulled at 98 N {10 kgf, 22 lbf}	2—3 notches

Master cylinder fluid pressure

Vacuum amount at 0 kPa {0 mmHg, 0 inHg}	
Brake pedal force	**Fluid pressure**
200 N {20.4 kgf, 45.0 lbt}	440 kPa {4.49 kgf/cm^2, 63.8 psi} or more

Master cylinder fluid pressure

Vacuum amount at 66.7 kPa {500 mmHg, 19.7 inHg}	
Brake pedal force	**Fluid pressure**
200 N {20.4 kgf, 45.0 lbt}	6,690 kPa {68.22 kgf/cm^2, 970.3 psi} or more

Degree of vacuum in vacuum pump standard (reference) [SKYACTIV-G 1.3, SKYACTIV-G 1.5]

Measurement condition				**Specification**
Engine rotation speed	**Brake pedal**	**Measurement-start vacuum**	**Measurement-stop vacuum**	
While idling (See ENGINE TUNE-UP [SKYACTIV-G 1.3, SKYACTIV-G 1.5].)	Depressed	60 kPa {450 mmHg, 18 inHg}	67 kPa {503 mmHg, 20 inHg}	Within 8 s

Degree of maximum attained vacuum in vacuum pump standard (reference) [SKYACTIV-G 1.3, SKYACTIV-G 1.5]

Measurement condition		**Specification**
Engine rotation speed	**Measurement time**	
While idling (See ENGINE TUNE-UP [SKYACTIV-G 1.3, SKYACTIV-G 1.5].)	No time designation	93.3 kPa {700 mmHg, 27.6 inHg} or more

Degree of vacuum in vacuum pump maximum (reference) [SKYACTIV-D 1.5]

Measurement condition				**Maximum value**
Engine rotation speed	**Brake pedal**	**Measurement-start vacuum**	**Measurement-stop vacuum**	
While idling (See ENGINE TUNE-UP [SKYACTIV-D 1.5].)	Depressed	0 kPa {0 mmHg, 0 inHg}	67 kPa {503 mmHg, 20 inHg}	15 s + Engine completely warmed up