ON-BOARD DIAGNOSTIC SYSTEM SIMULATION FUNCTION [TCM (EW6A-EL)]

id0502p7280700

Purpose/Function

- The simulation function can drive output parts based on use of the M-MDS.
- Inspection of an individual output part is facilitated by the simulation function because the output part is driven forcibly.

Construction/Operation

Simulation item table

Item	Output part name	Unit/Condition	Operation condition
EOP	Electric AT oil pump condition	Off/On	Under the following conditions: • Engine stopped • Accelerator pedal fully closed
EOP_DUTY	Electric AT oil pump duty cycle	%	Under the following conditions: • Engine stopped • Accelerator pedal fully closed
EOP_RLY	Electric AT oil pump relay condition	Off/On	Under the following conditions: • Engine stopped • Accelerator pedal fully closed
SS_ON-OFF	On/off solenoid condition	Off/On	Under the following conditions: • Vehicle stopped • Idling at P or N position
SS1_C	Shift solenoid No.1 target current	A	Under the following conditions: • Vehicle stopped • Idling at P or N position
SS2_C	Shift solenoid No.2 target current	A	Under the following conditions: • Vehicle stopped • Idling at P or N position
SS3_C	Shift solenoid No.3 target current	A	Under the following conditions: • Vehicle stopped • Idling at P or N position
SS4_C	Shift solenoid No.4 target current	A	Under the following conditions: • Vehicle stopped • Idling at P or N position
SSLU_C	TCC control solenoid target current	A	Under the following conditions: • ATF temperature (PID: TFT) is 20 °C {68 °F} or more. • Output shaft rotation speed (PID: OSS) is 10 rpm or more. • Turbine shaft rotation speed (PID: TSS) is 1,000 rpm or more. • Brake pedal released
SSP_C	Pressure control solenoid target current	A	Idling at P or N position