## ON-BOARD DIAGNOSTIC SYSTEM SIMULATION INSPECTION [TCM (EW6A-EL)]

id0502p7290400

1. Connect the M-MDS to the DLC-2.
2. After the vehicle is identified, select the following items from the initialization screen of the M-MDS.
   (1) Select “Data Logger”.
   (2) Select “Modules”.
   (3) Select “TCM”.
3. Select the simulation items from the PID table.
4. Perform the active command modes function, inspect the operations for each parts.
   - If the operation of output parts cannot be verified after the active command mode inspection is performed, this could indicate the possibility of an open or short circuit, sticking, or operation malfunction in the output parts.

**Simulation item table**

| Item | Description | Unit/ Condition | Operation condition |
|---|---|---|---|
| EOP | Electric AT oil pump condition | Off/On | Under the following conditions:<br>• Engine stopped<br>• Accelerator pedal fully closed |
| EOP_DUTY | Electric AT oil pump duty cycle | % | Under the following conditions:<br>• Engine stopped<br>• Accelerator pedal fully closed |
| EOP_RLY | Electric AT oil pump relay condition | Off/On | Under the following conditions:<br>• Engine stopped<br>• Accelerator pedal fully closed |
| SS_ON-OFF | On/off solenoid condition | Off/On | Under the following conditions:<br>• Vehicle stopped<br>• Idling at P or N position |
| SS1_C | Shift solenoid No.1 target current | A | Under the following conditions:<br>• Vehicle stopped<br>• Idling at P or N position |
| SS2_C | Shift solenoid No.2 target current | A | Under the following conditions:<br>• Vehicle stopped<br>• Idling at P or N position |
| SS3_C | Shift solenoid No.3 target current | A | Under the following conditions:<br>• Vehicle stopped<br>• Idling at P or N position |
| SS4_C | Shift solenoid No.4 target current | A | Under the following conditions:<br>• Vehicle stopped<br>• Idling at P or N position |
| SSLU_C | TCC control solenoid target current | A | Under the following conditions:<br>• ATF temperature (PID: TFT) is 20 °C {68 °F} or more.<br>• Output shaft speed (PID: OSS) is 10 rpm or more.<br>• Turbine/input shaft speed (PID: TSS) is 1,000 rpm or more.<br>• Brake pedal released |
| SSP_C | Pressure control solenoid target current | A | Idling at P or N position |