SAS CONTROL MODULE CONFIGURATION (USING READ/WRITE FUNCTION) [STANDARD DEPLOYMENT CONTROL SYSTEM]

id0810b2891500

Caution

- **When the configuration is performed, CAN communication between the SAS control module and control module connected to the CAN circuit is cut temporarily, and communication error DTCs may be detected. After performing the configuration, verify the DTCs for the control module connected to the CAN circuit and clear it if any DTC is detected.**

Note

- When performing configuration, it is necessary to read the vehicle specification information from the SAS control module before replacing it. Connect the M-MDS to the vehicle and perform vehicle identification before removing the SAS control module. The vehicle specification information is temporarily stored in the M-MDS.

1. Connect the M-MDS to the DLC-2.
2. After the vehicle is identified, select the following items from the initialization screen of the M-MDS.
   (1) Select “Module Programming”.
3. Then, select items from the screen menu in the following order.
   (1) Select “Programmable Module Installation”.
   (2) Select “RCM”.
4. Perform the configuration according to the directions on the screen.
5. Verify the DTCs for all of the control modules connected to the CAN circuit.
   - If any DTC is stored, clear it.
   - If the DTC is cleared, finish the procedure because the configuration has been completed normally.
   - If the DTC remains, perform troubleshooting according to the DTC.