DTC TABLE [i-ELOOP]

id130201000700

×: Applicable
—: Not applicable

DTC No.	i-ELOOP indicator light (green)	i-ELOOP warning light (amber)	i-stop warning light (amber)	Charging system warning light	Condition	Fail-safe function	Drive cycle	Self test type*1	Memory function	Page
P0A12:00	OFF	OFF	Flash	ON	DC-DC converter (i-ELOOP): low input	×	1	C	×	(See DTC P0A12:00 [i-ELOOP].)
P0C39:00	OFF	ON	OFF	OFF	Capacitor (i-ELOOP) temperature sensor system: function/circuit malfunction	—	1	C, D	×	(See DTC P0C39:00 [i-ELOOP].)
P1628:11	OFF	OFF	OFF	OFF	DC-DC converter (i-ELOOP) system: power supply voltage low input	—	1	C, D	×	(See DTC P1628:11 [i-ELOOP].)
P1794:00	OFF	ON	Flash	ON	Capacitor (i-ELOOP) system: Capacitor (i-ELOOP) malfunction	×	1	C, D	×	(See DTC P1794:00 [i-ELOOP].)
U0001:88	OFF	OFF	OFF	ON	CAN system communication error (HS-CAN)	×	1	C, D	×	(See DTC U0001:88, U0100:00, U0140:00, U0151:00 [i-ELOOP].)
U0100:00	OFF	OFF	OFF	ON	CAN communication: communication error to PCM	×	1	C, D	×	
U0140:00	OFF	OFF	OFF	OFF	CAN communication: communication error to BCM	—	1	C	×	
U0151:00	OFF	OFF	OFF	OFF	CAN communication: communication error to SAS control module	—	1	C	×	
U3000:49	OFF	ON	Flash	ON	DC-DC converter (i-ELOOP) internal malfunction	×	1	C, D	×	(See DTC U3000:49 [i-ELOOP].)

*1 : C: CMDTC self test, D: ODDTC self test