i-ELOOP TECHNICAL DATA

id135000000100

Item	Specification
Generator standard voltage [IG-ON]	Terminal 1A: Capacitor (i-ELOOP) voltage Terminal 2A: 6—8.5 V Terminal 2B: 6—8.5 V Terminal 2C: B+
Generator standard voltage [Idle, 20 °C {68 °F}]	Terminal 1A: Capacitor (i-ELOOP) voltage Terminal 2A, 2B: Turn the electrical loads (such as headlights, blower motor, rear window defogger, brake lights) on and verify that the voltage reading increases. Terminal 2C: B+
Generator rotor resistance (between slip rings) [20 °C {68 °F}]	1.8—2.1 ohms
Generator brush length	Standard: 22.5 mm {0.886 in} Minimum: 5.0 mm {0.20 in}
Generator brush spring force	Standard: 4.1—5.3 N {0.42—0.54 kgf, 1.0—1.1 lbf} Minimum: 1.7 N {0.17 kgf, 0.38 lbf}

Generator generated current maximum value (with i-ELOOP) (reference value) [Ambient temperature: 20 °C {68 °F}, Engine hot]

Engine speed (rpm)	Terminal 1A voltage (V)	Generator output current (A)
1,000	15	130
2,000	15	150