

Introduction

With a 64-voice poly system, you can record sequences that have 64 voices sounding simultaneously. If you also have 32 FM voices, you can record sequences with up to 96 voices.

64 poly voices

The 64 voices in a 64-voice poly system are stored in two separate poly bins. Each bin can hold up to 32 poly voices. A sound file can be loaded into one bin or the other, but not both.

Each of the two poly bins has a pair of composite outputs. There is no composite output for all 96 voices. Multichannel outputs are assigned from the Multichannel Display.

In the upper right corner of the Multichannel Display, the instructions list the number of poly bins in your system. The Poly column shows the number of the poly bin assigned to the keyboard and track timbres listed.

The Multichannel Display

KBD 1 2 3 4 5	- Instrument Name — RHODES ELECTRIC KIT PHASED BASS Cuelist 1 Cuelist 2 Cuelist 3 Cuelist 4	1 2	Right 1 2 3 *1* *2* *3* *4*	Poly _ 1 1 1 1 1 1	1. Move cursor with arrow keys 2. Assign new track numbers and routings 3. Press space bar to increment values 4. M/C Outputs: 32 Poly Bins:			
7 8 9 10 11 12 13 14 15 16 17 18 19 20	Cuellst 5	*5*	*5*		21 22 23 24 -L1 Track 1 L2 Track 2 L3 Track 3 L4 Track 4 L5 Track 5 L6 Track 6 L7 L8	*1* *1* *2* *2* *3* *3* *4* *4* *5* *5* *6* *6* *7* *7* *8* *8*		

Sound file loading

When you recall a timbre, all of the sound files associated with it are loaded into the poly bin assigned to the keyboard. When you recall a sequence, all of the sound files associated with each track timbre are loaded into the poly bin assigned to each track. (Assigning timbres to poly bins is discussed in the section "Assigning poly bins.")

As sound files associated with the keyboard timbre or a track timbre are loaded into their assigned poly bins, previously loaded sound files not part of the current sequence or the keyboard timbre are deleted from poly memory as more room is required.

If previously loaded sound files are deleted and the memory in the assigned poly bin is still insufficient for a given timbre, the sound file is loaded into the other poly bin. The assigned poly bin number remains the same, even if the sound file was forced into the other poly bin.

If there is no room in either poly bin, an error message appears.

Out of Room in Sample Memory

Once a sound file is loaded into one bin or the other, it remains there until it is erased from poly memory.

Recalling timbres

If the first timbre you recall to the keyboard is assigned to Poly Bin 1, its sound files are loaded into Poly Bin 1. If you then recall another timbre to the keyboard that is assigned to Poly Bin 2 and the sound files associated with it are the same as the sound files from the first timbre, the sound files remain in Poly Bin 1 unless you delete them from poly memory before recalling the second timbre.

Similarly, if you recall a sequence that has the same timbre recorded on two tracks and the tracks are assigned to different poly bins, the sound files associated with the timbre are loaded into one bin only—the bin assigned to the lowest numbered track.

If a sound file associated with a timbre has already been loaded into one poly bin, loading a second timbre that uses the same sound file but assigned to the other poly bin does not affect the location of the sound file. It remains in its current bin and does not move to the new bin assignment.


Viewing sound file poly bin assignments

You can see the current bin location of a sound file from the Sound File Directory.

- 1. Select the Sound File Directory.
- 2. Select the Poly Memory Display.
- 3. Under the Show option, select Poly Bin, or type H.

The sound files in the Directory are shown, each with its poly bin number following it. (The Poly Bin option may be selected in combination with other options.)

The Sound File Directory



Making sure sound files are recalled to the assigned poly bins

To avoid having the sound files of any timbre in the wrong poly bin, you should erase all currently loaded files from poly memory before recalling the timbre or sequence.

- 1. Recall the Extra System Commands screen from the Main Menu.
- 2. Select the Erase All Sound Files from Poly Memory command.

All sound files are erased from poly memory. When you recall a sequence, the sound files for each track timbre are loaded into their assigned poly bins.

You can also delete individual sound files from either poly bin.

- 1. Select the Sound File Directory.
- 2. Select the sound file.

The sound file is highlighted.

3. Select the Sound File Editor.

The Sound File Editor appears on the screen displaying the selected sound file.

- 4. Select Store/Recall menu.
- 5. Select the Unsave command.


The sound file is deleted.

WARNING: Be sure all wanted sound files are backed up before using the Erase All Sound Files from Poly Memory command.

The Main Menu

Directories	Memory Recorder
A. Timbre Directory	S. Sequence Editor
B. Sound File Directory	G. Recorder Display
C. Sequence Directory	H. Multichannel Display
D. Subcatalog Directory	J. Midi Display
M. Missing Sound Display	K. Music Notation Display
Sound Design	Direct-to-Disk
L. Sound File Editor	O. Project Directory
F. FM Timbre Display	P. Track Display
I. Patch Display	Q. Audio Event Editor
N. Name Keyboard Timbre	
	System Controls
Sound Archival	E: Extra System Commands
R. Optical Disk Storage	<pf1> Reverse Compiler</pf1>
	<pf3> Music Printing</pf3>
	<pf4> SFM</pf4>
	<break> Monitor</break>
elease O	Current Timbre: RHODES Current Catalog: W0:

The Sound File Editor



Assigning poly bins

You can assign a keyboard or track timbre to a poly bin before or after recording.

Making poly bin assignments

When you record a sequence, the poly bin assigned to the keyboard timbre becomes the poly bin assigned for the recorded track. Thus, before recalling a timbre to the keyboard to record a track, you should use the Multichannel Display or the TRACK ROUTING button to assign the sound files of the keyboard timbre to the desired poly bin.

When you bounce notes from one track to another, the poly bin assignment is also bounced.

If you record a sequence with the keyboard timbre in its default assignment, you can change the poly bin assignments for the recorded tracks after the sequence is recorded. You can also change poly bin assignments for sequences recorded with systems with only one poly bin, which have all tracks assigned to Poly Bin 1.


When you store the sequence, the poly bin assignment for each track is stored with the sequence. If you do not assign a poly bin to a track, it is automatically assigned to Poly Bin 1.

Note: To actually move the sound files from one bin to the other, you must erase the sequence, erase the sound files from poly memory and recall the sequence again.

The Multichannel Display

	Instrument Name —	LLeit	Right	Poly 7	MULTICHANNEL ROUTI	NG DISPL	AY.	
KBD	RHODES		1					
1	ELECTRIC KIT		2	1	 Move cursor with 	arrow	key	
2	PHASED BASS	3	3	1	2. Assign new track numbers			
3	Music cues	*1*	*1*		and routings 3. Press space bar to increment values 4. WC Outputs: 32 Poly Bins:			
4	Voiceover	*2*	*2*					
5	Effects 1	*3*	*3*					
6	Effects 2	*4*	*4*					
7	Effects 3	*5*	*5*		DTD Outputs: 8			
8								
9					21			
10					22			
11					23			
12					L ₂₄			
13					rL1 Vocals-Bob	*1*	*1	
14					L2 Vocals-Lynn	•2•	*2	
15					L3 Voiceover	*3*	13	
16					L4 Foley 1	1.4.	•4	
17					L5 Foley 2	*5*	1.5	
18					L6	-6*	1-6	
19					L7	1-7-	1.7	
20					L8			
					LO	*8*	*8	

Panel 2 Track routing button



Assigning the keyboard timbre to a poly bin

You can use either the Multichannel Display or the TRACK ROUTING button to make poly bin assignments for the keyboard timbre.

To make the poly bin assignments from the Multichannel Display:

- 1. Select the Multichannel Display.
- 2. Type "1" or "2" in the Poly column for the keyboard.

To make poly bin assignments using the TRACK ROUTING button:

1. Press and hold the TRACK ROUTING button.

The button lights. The first and second numbered buttons under TIMBRE/SEQUENCE STORAGE blink.

2. Press any key on the keyboard.

The first and second numbered buttons under TIMBRE/SEQUENCE STORAGE continue to blink.

3. Press the numbered button corresponding to the bin to which you want the keyboard timbre assigned.

The selected bin appears on the second line of the keyboard display window.

The assignments do not affect the current keyboard timbre. Any timbre recalled to the keyboard after you make the assignments are loaded into the assigned bins.


Panel 2
TRACK ROUTING button

START	STOP	RECORD	O PUNCH IN	CONTIN	JE REWIND	O F.F.	ERASE
MARK	START LOOP	END LOOP	SPEED	CLICK T	RANSPOSE	SMPTE MODE	EXT SYNC
CHAIN	INSERT	DELETE	O SMT	O SKT	BOUNCE	JUSTIFY	SEQUENC
OVERALL TUNING	OCTAVE RATIO	PITCH CLASS	KEY ONLY	SCALE RESET	TRACK VOLUME	C TRACK PAN	TRACK

Panel 4
Buttons 1 and 2

TIMBRE/SEQUENCE STORAGE TIMBRE SEQUENCE SEQ	
KEYBOARD CONTROL	
LEFT RIGHT REPEAT ARPEGGIATE RATE CHORUS POLYPHONY TIMBRE ONOFF ONOFF ONOFF ONOFF ONOFF ON ON	

Panel 3
The TRACK SELECT buttons



Assigning a track timbre to a poly bin from the keyboard control panel

You can also use the TRACK ROUTING button on the Synclavier keyboard control panel to assign a poly bin to each track timbre of the current sequence.

- 1. Recall the sequence to the Memory Recorder.
- 2. Press and hold the TRACK ROUTING button on the keyboard control panel.

The button lights. The first and second numbered buttons under TIMBRE/SEQUENCE STORAGE blink.

3. Press the TRACK SELECT button corresponding to the track you want to assign.

The TRACK SELECT button lights. The first and second numbered buttons under TIMBRE/SEQUENCE STORAGE continue to blink.

4. Press the numbered button corresponding to the bin to which you want the track timbre assigned.

The selected poly bin appears on the second line of the keyboard display window.

Poly Bin: 1

Whenever the sequence is recalled to the Memory Recorder, the sound files associated with each track timbre are loaded into the assigned bin.

Assigning a track timbre to a poly bin from the Multichannel Display

You use the Multichannel Display to assign each track timbre of the current sequence to a poly bin.

- 1. Recall the sequence to the Memory Recorder.
- 2. Select the Multichannel Display.
- 3. Type "1" or "2" in the Poly column for each track.

These are the selected poly bin assignments. The sound files are not actually recalled to these poly bins until the sequence is stored and recalled again.

4. Store the sequence using the Sequence store and recall buttons on the keyboard control panel.

The poly bin assignments to the sound files of each track timbre are stored with the sequence. If you do not assign a poly bin to a track, Poly Bin 1 is automatically assigned.

Whenever the sequence is recalled to the Memory Recorder, the sound files associated with each track timbre are loaded into the assigned bin.

Sampling

You can sample directly in Poly Bin 1.

Recording a sample

All samples are recorded directly into Poly Bin 1. You cannot record into Poly Bin 2. If there is not enough room in Poly Bin 1 to record the sample, you can move existing sound files from Poly Bin 1 to Poly Bin 2.

- 1. Select the Store/Recall menu on the Sound File Editor.
- 2. Select the Record command from the Store/Recall menu.

The following message appears.

Time available is [number] seconds.


3. If the time available for recording is insufficient, select the Max Time command.

As many sound files as will fit into Poly Bin 2 are moved from Poly Bin 1.

4. Select the Record command and record your sound file.

The sound file is recorded into Poly Bin 1 and remains there until it is erased from poly memory.

The Sound File Editor



*