

Published

Preview

Edit

Final Exam

⚠ This is a preview of the draft version of the quiz

- Quiz Type Graded Quiz
- Points 35
- Assignment Group Final Exam
- Shuffle Answers Yes
- Time Limit 120 Minutes
- Multiple Attempts No
- View Responses Always
- Show Correct Answers After Dec 15, 2020 at 12am
- One Question at a Time No

Due	For	Available from	Until
Dec 15, 2020	3 students	Dec 14, 2020 at 1pm	Dec 15, 2020 at 11:59pm
Dec 15, 2020	Everyone else	Dec 14, 2020 at 6pm	Dec 15, 2020 at 11:59pm
Dec 16, 2020	2 students	Dec 14, 2020 at 6pm	Dec 16, 2020 at 11:59pm
Dec 16, 2020	1 student	Dec 15, 2020 at 12am	Dec 16, 2020 at 11:59pm
Dec 18, 2020	1 student	Dec 15, 2020 at 12am	Dec 18, 2020 at 11:59pm
Dec 19, 2020	2 students	Dec 16, 2020 at 12am	Dec 19, 2020 at 11:59pm
Jan 6	1 student	Jan 4 at 12am	Jan 6 at 11:59pm

Preview

Score for this quiz: **0** out of 35

Submitted Apr 27 at 2:09pm

This attempt took less than 1 minute.

Unanswered

Question 1

0 / 1 pts

Please select from the following, statement(s) that are **false** for the `assert` statements. **Select all the false statements!**

Correct Answer

☐ `assert` does not require a condition

☐ An `AssertionError` is raised, if `assert` condition evaluates to `False`

Correct Answer

☐ If `assert` condition evaluates to `False`, then the code keeps running

☐

`Assert` statements enable us to convert semantic errors to runtime errors

Unanswered

Question 2

0 / 1 pts

Please select from the following, statement(s) that can be **executed more than once** during the invocation of a function.

☐ `return`

Correct Answer

☐ `continue`

Correct Answer

☐ `while`

Correct Answer

☐ `break`

Correct Answer

☐ `for`

Unanswered

Question 3

0 / 1 pts

If a function defined in Python doesn't have an explicit "return" statement, it automatically returns the last variable present in the body of the function.

☐ True

Correct Answer

☐ False

Unanswered

Question 4

0 / 1 pts

Please match the type of error to its corresponding code snippet.

You Answered

Syntax Error



Correct Answer

```
"Bye Bye CS220" =  
end_of_final
```

You Answered

Runtime Error



Correct Answer

42/0

You Answered

Semantic Error



Correct Answer

```
area_of_square =  
side_len * 2
```

Unanswered**Question 5****0 / 1 pts**

Which of the following **can be used** as a key for a Python dictionary?

Correct Answer☐ strings**Correct Answer**☐ negative integers☐ custom type created using recordclass☐ lists**Correct Answer**☐ tuples**Correct Answer**☐ custom type created using namedtuples**Unanswered****Question 6****0 / 1 pts**

Please select from the following, variable name(s) that are **valid**. **Select all valid options!**

☐ my-variable**Correct Answer**☐ _my_var☐ 007Secret☐ which exam

Correct Answer☐ this_is_theFinalExam**Correct Answer**☐ goodbye2020**Unanswered****Question 7****0 / 1 pts**

Assume this code is being used to scrape this html page:
`http://states.com:300/list_of_us_states.html` (part of the code is hidden by
????):

```
import requests
from bs4 import BeautifulSoup
try:
    r = requests.get("http://states.com:300/list_of_us_states.html")
    r.raise_for_status() # raises an HTTPError if page is missing
    doc = BeautifulSoup(????, "html.parser")
except requests.exceptions.HTTPError as e:
    print("WARNING! Could not fetch page")
```

If `list_of_us_states.html` is deleted from that website so that the server returns a 404 status, what will be the output of the above code?

Correct Answer☐ prints "WARNING! Could not fetch page"☐ HTTPError☐ Syntax Error☐ Does nothing**Unanswered****Question 8****0 / 1 pts**

Assume the content for the website

http://states.com:300/list_of_us_states.html is equivalent to the following HTML:

```
<table>
  <tr>
    <td><a href="Alabama.html" title="Alabama">Alabama</a></td>
    <td><i>Montgomery</i></td>
  </tr>
  <tr>
    <td><a href="Alaska.html" title="Alaska">Alaska</a></td>
    <td><b>Juneau</b></td>
  </tr>
  <tr>
    <td><a href="Wisconsin.html" title="Wisconsin">Wisconsin</a></td>
    <td><i>Madison</i></td>
  </tr>
  <tr>
    <td><a title="Wyoming">Wyoming</a></td>
    <td><b>Cheyenne</b></td>
  </tr>
</table>
```

Assume this code is being used to scrape that page (part of the code is hidden by ????):

```
import requests
from bs4 import BeautifulSoup
try:
    r = requests.get("http://states.com:300/list_of_us_states.html")
    r.raise_for_status() # raises an HTTPError if page is missing
    doc = BeautifulSoup(???, "html.parser")
except requests.exceptions.HTTPError as e:
    print("WARNING! Could not fetch page")
```

How many clickable links are there in the above HTML? Be careful!

☐ 4

Correct Answer

☐ 3

☐ 1

☐ 2

Unanswered

Question 9

0 / 1 pts

Assume the content for the website

http://states.com:300/list_of_us_states.html is equivalent to the following HTML:

```
<table>
  <tr>
    <td><a href="Alabama.html" title="Alabama">Alabama</a></td>
    <td><i>Montgomery</i></td>
  </tr>
  <tr>
    <td><a href="Alaska.html" title="Alaska">Alaska</a></td>
    <td><b>Juneau</b></td>
  </tr>
  <tr>
    <td><a href="Wisconsin.html" title="Wisconsin">Wisconsin</a></td>
    <td><i>Madison</i></td>
  </tr>
  <tr>
    <td><a title="Wyoming">Wyoming</a></td>
    <td><b>Cheyenne</b></td>
  </tr>
</table>
```

Assume this code is being used to scrape that page (part of the code is hidden by ????):

```
import requests
from bs4 import BeautifulSoup
try:
    r = requests.get("http://states.com:300/list_of_us_states.html")
    r.raise_for_status() # raises an HTTPError if page is missing
    doc = BeautifulSoup(???, "html.parser")
except requests.exceptions.HTTPError as e:
    print("WARNING! Could not fetch page")
```

Match the following expressions to the correct output

Unanswered

????



Correct Answer

r.text

Unanswered

`doc.find_all("td")`
`[-1].get_text()`



Correct Answer

'Cheyenne'

You Answered

`next(doc.find_all("tr")`
`[0].children)`



Correct Answer

`<td><a href="Alabama.html"`
`title="Alabama">Alabama`
`</td>`

You Answered

`doc.find_all("a")[-1].attrs`



Correct Answer

`{'title': 'Wyoming'}`

Other Incorrect Match Options:

- 'Alabama'
- `<td>Cheyenne</td>`
- `{'href': 'Wyoming.html', 'title': 'Wyoming'}`
- `r.text()`
- `r`
- `r.json()`
- `'\n'`
- `Cheyenne`

Unanswered

Question 10

0 / 1 pts

In URL `http://states.com:300/list_of_us_states.html`, what is `states.com`?

- ☐ a status code

☐ a port number

Correct Answer

☐ a domain name

☐ a resource

Unanswered

Question 11

0 / 1 pts

The following **vote_df** dataframe represents the votes for a county. Note: different states can contain same county name!

	state	county	Republicans Votes	Democrats Votes
2	Kansas	Allen	3552	2189
3	Kentucky	Anderson	6885	3462
0	Kansas	Anderson	2362	1175
1	Kentucky	Allen	5258	2024

The following **pop_df** dataframe represents the total population for each county.

	state	county	total populations
0	Kansas	Anderson	8001
1	Kentucky	Allen	19377
2	Kansas	Allen	13387
3	Kentucky	Anderson	21271

Which of the following statements will return **True**? **Select all that apply.**
Hint: Pay close attention to indexes of the dataframes!

Correct Answer

☐ (vote_df["Democrats Votes"]/vote_df["Republicans Votes"] > 0.5)[3]

Correct Answer

☐ vote_df.iloc[0,0] == vote_df.iloc[2,0]

☐ `vote_df['Republicans Votes'][0] == 3552`
☐ `vote_df.loc[:3,'county'][3] == 'Allen'`
Correct Answer
☐ `vote_df['county'][2] == pop_df['county'].iloc[2]`
Unanswered**Question 12****0 / 1 pts**

DataFrame **grade_df** is shown below:

	HW1	HW2	Final Project
Sheldon	94	88	90.0
Penny	78	75	NaN
Leonard	89	70	80.0
Howard	65	46	67.0

Which of the following are **true**? **Select all that apply!**

☐

After you run the below code, everyone's grade for HW2 in the original dataframe, `grade_df`, will be increased by 5.

```
grade_df['HW2'] + 5
```

☐

If $1 \leq x \leq 4$, `grade_df.iloc[[x]]` and `grade_df.iloc[x]` will output the same thing with the same type.

Correct Answer
☐

When you are calculating the average of the final project with `.mean()` method, all the NaN values will be skipped in the average calculation.

☐

grade_df.loc[['Sheldon','Leonard']] will output the grades of Sheldon, Penny, and Leonard.

Unanswered

Question 13

0 / 1 pts

Which of the following Python data structures can be used to create a pandas DataFrame? **Select all options that could work.**

Correct Answer

☐ dictionary of Series

Correct Answer

☐ dictionary of lists

Correct Answer

☐ list of dictionaries☐ None of the other options

Correct Answer

☐ dictionary of dictionaries

Correct Answer

☐ list of lists

Unanswered

Question 14

0 / 1 pts

The following **vote_df** dataframe represents the votes for a county. Note: different states can contain same county name!

	state	county	Republicans Votes	Democrats Votes
2	Kansas	Allen	3552	2189
3	Kentucky	Anderson	6885	3462
0	Kansas	Anderson	2362	1175
1	Kentucky	Allen	5258	2024

The following **pop_df** dataframe represents the total population for each county.

	state	county	total populations
0	Kansas	Anderson	8001
1	Kentucky	Allen	19377
2	Kansas	Allen	13387
3	Kentucky	Anderson	21271

Which of the following are true about the above pandas DataFrames?
Select all options that are true!

Correct Answer

☐

pop_df.iloc[0]["total populations"] enables us to extract total population of Anderson county in the state of Kansas.

☐

vote_df["Democrats Votes"] < 2500 will output a dataframe with rows where Democrats votes are less than 2500.

Correct Answer

☐

If $1 \leq x \leq 4$, pop_df.iloc[:x] will output a dataframe with x rows.

Correct Answer

☐

The ratio of Republicans votes to total population for each different county, can be computed with vote_df["Republicans Votes"]/pop_df["total populations"].

Unanswered

Question 15

0 / 1 pts

Assume that the below "books" table is inside a SQL database.

Title	Author	Date	Pages	Country

Anna Karenina	Leo Tolstoy	1877	864	Russia
The Great Gatsby	F. Scott Fitzgerald	1925	192	United States
War and Peace	Leo Tolstoy	1869	1225	Russia
Lolita	Vladimir Nabokov	1955	336	France
The Adventures of Huckleberry Finn	Mark Twain	1884	366	United States

Which SQL query answers the following question: **which authors belong to the "United States"?**

- ☐ SELECT Author, Country FROM books WHERE Country != "France";
- ☐ SELECT Author FROM books ORDER BY Date;
- ☐ SELECT * FROM books WHERE Country != "United States";
- ☐ SELECT Author FROM books GROUP BY Country HAVING Country = "United States";

Correct Answer

- ☐ SELECT Author FROM books WHERE Country = "United States";

Unanswered

Question 16

0 / 1 pts

Assume that the below "books" table is inside a SQL database.

Title	Author	Date	Pages	Country
Anna Karenina	Leo Tolstoy	1877	864	Russia
The Great Gatsby	F. Scott Fitzgerald	1925	192	United States
War and Peace	Leo Tolstoy	1869	1225	Russia

Lolita	Vladimir Nabokov	1955	336	France
The Adventures of Huckleberry Finn	Mark Twain	1884	366	United States

Which SQL query answers the following question: **which authors have published more than 1 book that has at least 800 pages?**

Note: The query should display one row for each author, along with the number of books that have at least 800 pages.

☐ SELECT Title FROM books;

☐ SELECT Author, COUNT() as c FROM books WHERE Pages>800
GROUP BY Pages HAVING c>1;

Correct Answer

☐ SELECT Author, COUNT(Country) as c FROM books WHERE Pages>800
GROUP BY Author HAVING c>1;

☐ SELECT Author, COUNT(Country) as c FROM books WHERE c>1
GROUP BY Author HAVING Pages>800;

☐ SELECT Author, COUNT(Pages) FROM books WHERE Pages>800
GROUP BY Pages;

Unanswered

Question 17

0 / 1 pts

Assume that the below "books" table is inside a SQL database.

Title	Author	Date	Pages	Country
-------	--------	------	-------	---------

Anna Karenina	Leo Tolstoy	1877	864	Russia
The Great Gatsby	F. Scott Fitzgerald	1925	192	United States
War and Peace	Leo Tolstoy	1869	1225	Russia
Lolita	Vladimir Nabokov	1955	336	France
The Adventures of Huckleberry Finn	Mark Twain	1884	366	United States

Choose the query that returns: **the book title and corresponding author name sorted by publication date with the newest book first.**

☐ SELECT Title, Author FROM books ORDER BY Date ASC;

☐ SELECT Title, Author FROM books ORDER BY Date;

☐ SELECT * FROM books ORDER BY Date DESC;

Correct Answer

☐ SELECT Title, Author FROM books ORDER BY Date DESC;

☐ SELECT Title, Author, SORT(Date) FROM books;

Unanswered

Question 18

0 / 1 pts

Assume that the below "books" table is inside a SQL database.

Title	Author	Date	Pages	Country
Anna Karenina	Leo Tolstoy	1877	864	Russia
The Great Gatsby	F. Scott Fitzgerald	1925	192	United States
War and Peace	Leo Tolstoy	1869	1225	Russia
Lolita	Vladimir Nabokov	1955	336	France

The Adventures of Huckleberry Finn	Mark Twain	1884	366	United States
------------------------------------	------------	------	-----	---------------

Which SQL query answers the following question: **how many books are available per country?**

- ☐ SELECT Country, SUM(books) FROM books GROUP BY Country;
- ☐ SELECT Country, COUNT(Country) FROM books GROUP BY Date;
- ☐ SELECT Country, COUNT(*) FROM books;
- ☐ SELECT Country, COUNT(*) FROM books GROUP BY Country;
- ☐ SELECT Country, MIN(Pages) FROM books GROUP BY Country;

Correct Answer

Unanswered

Question 19

0 / 1 pts

Assume that the below "books" table is inside a SQL database.

Title	Author	Date	Pages	Country
Anna Karenina	Leo Tolstoy	1877	864	Russia
The Great Gatsby	F. Scott Fitzgerald	1925	192	United States
War and Peace	Leo Tolstoy	1869	1225	Russia
Lolita	Vladimir Nabokov	1955	336	France
The Adventures of Huckleberry Finn	Mark Twain	1884	366	United States

What is the result of the following SQL query?

```
SELECT Author FROM books
WHERE Country != "Russia" AND Pages < 350
ORDER BY Date
LIMIT 1;
```


Correct Answer☐

	Author
0	F. Scott Fitzgerald

☐

	Author
0	F. Scott Fitzgerald
1	Vladimir Nabokov

☐

	Author
0	Mark Twain

☐

	Author
0	Leo Tolstoy

☐

	Author
0	Vladimir Nabokov

Unanswered**Question 20****0 / 1 pts**

Consider the following lines of code. Each line in the code is represented by a line number (for example, #1) to the right.

```
# Line 1 def predict(glucose = 120, bmi = 50, age = 30):
# Line 2     if glucose <= 127.5:
# Line 3         if age <= 28.5:
# Line 4             if bmi <= 45.4:
# Line 5                 return False
# Line 6             elif bmi <= 55.3:
# Line 7                 return True
```

```
# Line 8      else:
# Line 9      return False
# Line 10     else:
# Line 11     return True
```

Select the option that best describes the correct order of execution for the following case:

predict (glucose = 120, bmi = 60, age = 25)

☐ 1, 2, 3, 4, 6, 7

☐ 1, 2, 3, 4, 6, 8, 9

☐ 1, 2, 3, 4, 8, 10, 11

☐ 1, 2, 3, 4, 5, 6, 7

☐ 1, 2, 10, 11

Correct Answer

Unanswered

Question 21

0 / 1 pts

Code snippet

```
def predict(glucose = 120, bmi = 50, age = 30):
    #this function has some lines of code here!
```

Which of the following function calls have the correct syntax for the function call? **Select all that apply!**

☐ answer = predict(50, 30, glucose = 120)

☐ answer = predict(110, glucose = 120, 50, 30)

☐ answer = predict(70, 30)

☐ answer = predict(glucose = 120)

Correct Answer

Correct Answer

☐ answer = predict(glucose = 120, 50, 30)

Unanswered

Question 22

0 / 1 pts

Which of the following statements are **True**? **Select all that apply.**

Correct Answer

☐ sorted(["a", "C", "b", "D"]) will return ['C', 'D', 'a', 'b']☐

You need to iterate over the dictionary to get the value corresponding to a search key.

☐

When you open a file with mode 'r', if the file exists, the existing file is overwritten with the new file.

Correct Answer

☐

When you create a folder that already exists with os.mkdir(...), the code will produce FileNotFoundError!

Unanswered

Question 23

0 / 1 pts

Consider the following code snippet. Assume that this code snippet is executed and then answer the question below it.

```
movies = [
    {"title": "A", "year": "disaster year", "style": "long", "genres":
    ["g1", "g2"]},
    {"title": "B", "year": 19, "style": "short", "genres": ["g2", "g
3"]},
    {"title": "C", "year": 20, "style": "short", "genres": ["g1", "g
3"]},
    {"title": "D", "year": 20, "style": "long", "genres": ["g1", "g2",
    "g3"]},
    {"title": "E", "year": 20, "style": "long", "genres": ["g2"]}
]
```

What will be printed? Be careful!

```
buckets = {}  
bucket = []  
for movie in movies:  
    year = movie["year"]  
    if not year in buckets:  
        buckets[year] = bucket  
    for genre in movie["genres"]:  
        buckets[year].append(genre)  
print(len(buckets[19]))
```

☐ 2

☐ SyntaxError

☐ 4

Correct Answer

☐ 10

☐ KeyError

Unanswered

Question 24

0 / 1 pts

Which of the following statements are true after we successfully run the following code? **Select all the options that apply!**

```
import os  
os.mkdir("final_exam")  
  
problems = {"easy": "Question 1",  
            "medium": "Question 2",  
            "hard": "Question 3"}  
  
for difficulty in problems:  
    folder_path = os.path.join("final_exam", difficulty)  
    os.mkdir(folder_path)  
    f = open(os.path.join(folder_path, difficulty+".txt"), "w")  
    f.write(problems[difficulty])  
    f.close()  
  
if difficulty == "hard":  
    f = open("hard.txt", "w")  
    f.write("This question was challenging\n")  
    f.close()
```

☐ `os.path.isfile(os.path.join("final_exam", "hard.txt"))` will return True.

☐ `os.path.exists("easy.txt")` will return True.

☐ `os.path.isdir("medium")` will return True.

Correct Answer

☐ `os.path.isfile("hard.txt")` will return True.

Correct Answer

☐ `len(os.listdir("final_exam"))` will return 3.

Unanswered

Question 25

0 / 1 pts

Consider the following code snippet and then answer the question below it.

```
campus_id = {  
    1510121: "Yifan",  
    2010333: "Pikachu",  
    2194790: "Jay",  
    4328132: "Sehun",  
    4187523: "Oliver"  
}
```

What is the output for:

```
print(type(campus_id), type(campus_id.get("Jay")), type(campus_id.get("1510121", 0)), type(campus_id.get(2194790)))
```

☐ `<class 'dict'> <class 'int'> <class 'str'> <class 'NoneType'>`

☐ `<class 'dict'> <class 'int'> <class 'int'> <class 'str'>`

☐ `<class 'dict'> <class 'NoneType'> <class 'str'> <class 'str'>`

Correct Answer

☐ `<class 'dict'> <class 'NoneType'> <class 'int'> <class 'str'>`

☐ <class 'dict'> <class 'NoneType'> <class 'NoneType'> <class 'str'>

Unanswered

Question 26

0 / 1 pts

Which lines are executed in the following code? Use the marked line number (comment) to answer this question. Be careful!

Hint: Note the difference between "which lines are executed" and "which lines are successfully executed". The question is asking "which lines are executed".

```
#line 1 def f(a, b):  
#line 2     return a+b  
  
#line 3 def g(a):  
#line 4     return len(a)  
  
#line 5 def h():  
#line 6     try:  
#line 7         c = 3  
#line 8         d = 4  
#line 9         return g(a) * f(c,d)  
#line 10    except:  
#line 11        return "An error occurred!"  
  
#line 12 try:  
#line 13     c = 6  
#line 14     d = -100  
#line 15     print(f(c,d) + h())  
#line 16 except:  
#line 17     print("An error occurred!")
```

☐ All lines except line 17.

☐ All lines except line 11.

☐ All lines except line 4, 16, and 17.

Correct Answer

☐ All lines except line 4.

☐ All lines except line 9, 16, and 17.


Unanswered

Question 27


0 / 1 pts

```
df = pd.DataFrame({  
    "high": [26, 31, 43, 57, 68, 78, 82, 79, 72, 59, 44, 30],  
    "low": [11, 15, 25, 36, 46, 56, 61, 59, 50, 39, 28, 16]  
})  
  
ax = df.plot.line()
```

The above code generates the following plot:



In order to improve the plot, we executed a few statements and generated the below plot.



Select all functions that must be called to generate the second plot.

☐ ax.set_ylim☐ ax.set_yticks**Correct Answer**☐ ax.set_ylabel**Correct Answer**☐ ax.set_xticks☐ ax.set_yticklabels☐ ax.set_xlim☐ ax.set_title**Correct Answer**☐ ax.set_xticklabels**Correct Answer**☐ ax.set_xlabel**Unanswered****Question 28****0 / 1 pts**

Which of the following options creates a bar plot where the x-axis bars are ordered as "green", "blue", and "red" for the following code snippet:

```
s = Series(["red", "red", "red",  
           "green", "blue", "blue"])  
vc = s.value_counts()
```

☐ vc.plot.bar()**Correct Answer**☐ vc.sort_values().plot.bar()☐ s.set_index("color").plot.bar()☐ vc.sort_index().plot.bar()

Unanswered

Question 29

0 / 1 pts

Which of the following enables us to increase font size for plots?

- ☐ `ax["font.size"] = 16`
- ☐ `s.plot.PLOT_FN(figsize = (WIDTH, HEIGHT))`
- ☐ `matplotlib.font.size = 16`
- ☐ `matplotlib.rcParams["font.size"] = 16`

Correct Answer




Unanswered


Question 30

0 / 1 pts

Which plot corresponds to the following code snippet?

```
data = []
for i in range(3):
    data.append({"y": i+1, "x": i+2})
DataFrame(data).plot.scatter(x='y', y='x')
```

**Correct Answer**




Unanswered

Question 31

0 / 1 pts

Which code snippet produce the following plot?



Assume the df DataFrame was produced as follows:

```
df = pd.DataFrame({
    "fruit": ["apple", "apple", "pear", "pear", "orange"],
    "color": ["red", "green", "red", "green", "orange"],
    "count": [50, 25, 8, 10, 20]
})
```

☐ `df.set_index("fruit")["count"].sort_index()[: 3].plot.bar()`
`ax.set_xlabel("fruit")`
`ax.set_ylabel("count")`

☐ `s_fruit_count= Series()`
`s_fruit_count["apple"] = df[df["count"] == 75]["fruit"]`
`s_fruit_count["orange"] = df[df["count"] == 20]["fruit"]`
`s_fruit_count["pear"] = df[df["count"] == 18]["fruit"]`
`ax = s_fruit_count.plot.bar()`
`ax.set_xlabel("fruit")`
`ax.set_ylabel("count")`

Correct Answer

☐ `s_fruit_count = Series()`
`s_fruit_count["apple"] = df[df["fruit"] == "apple"]["count"].sum()`
`s_fruit_count["orange"] = df[df["fruit"] == "orange"]["count"].sum()`
`s_fruit_count["pear"] = df[df["fruit"] == "pear"]["count"].sum()`
`ax = s_fruit_count.plot.bar()`
`ax.set_xlabel("fruit")`
`ax.set_ylabel("count")`

☐ `ax = df.set_index("fruit").sum().plot.bar()`
`ax.set_xlabel("fruit")`
`ax.set_ylabel("count")`

Unanswered**Question 32****0 / 1 pts**

The following code attempts to draw a tic-tac-toe board.

```
#sample output
X| |
-+-+
| |
-+-+
| |
```

```
def draw(x=0, y=0, move="X"):
    i = 1
    while(i < 6):
        if i%2 == 0:
```

```

        print("-+-+", end="")
    else:
        j = 0
        while j < 5:
            if j % 2 != 0:
                print("|", end="")
            elif i == 2*x + 1 and j == 2*y:
                print(move, end="")
            else:
                print(" ", end="")
            j += 1
        print()
        i += 1

```

What will the following function call produce?

`draw(-1,-1,'O')`

Correct Answer

- ☐ An empty tic-tac-toe board.
- ☐ A tic-tac-toe board with an 'O' in the lower right corner.
- ☐ A tic-tac-toe board with an 'O' in the upper left corner.
- ☐ TypeError
- ☐ A tic-tac-toe board with an 'X' in the upper left corner.

Unanswered

Question 33

0 / 1 pts

The following code attempts to draw a tic-tac-toe board.

```

#sample output
X| |
-+-+
| |
-+-+
| |

```

```

def draw(x=0, y=0, move="X"):
    i = 1
    while(i < 6): # Highlighted for this question
        if i%2 == 0:
            print("-+-+", end="")
        else:
            j = 0
            while j < 5:

```

```

        if j % 2 != 0:
            print("|", end="")
        elif i == 2*x + 1 and j == 2*y:
            print(move, end="")
        else:
            print(" ", end="")
        j += 1
    print()
    i += 1

```

How many times does the outer while loop line of code (highlighted in above code) execute for the below function call?

draw(2, 2, "X")

☐ 3

☐ 5

☐ 30

Correct Answer

☐ 6

Unanswered

Question 34

0 / 1 pts

The following code attempts to draw a tic-tac-toe board.

```

#sample output
X| |
-+-+
| |
-+-+
| |

```

```

def draw(x=0, y=0, move="X"):
    i = 1
    while(i < 6):
        if i%2 == 0:
            print("-+-+", end="")
        else:
            j = 0
            while j < 5:
                if j % 2 != 0:
                    print("|", end="")
                elif i == 2*x + 1 and j == 2*y:
                    print(move, end="")
                else:

```

```

        print(" ", end="")
    j += 1
print ()
i += 1

```

Which of the following function calls will draw the board with an X in the top row center cell?

☐ draw(0,1,X)

☐ draw(1,2,"X")

☐ draw(1,0,'X')

Correct Answer

☐ draw(0,1)

Unanswered

Question 35

0 / 1 pts

The following code attempts to draw a tic-tac-toe board.

```

#sample output
X| |
-+-+
| |
-+-+
| |

```

```

def draw(x=0, y=0, move="X"):
    i = 1
    while(i < 6):
        if i%2 == 0:
            print("-+-+", end="")
        else:
            j = 0
            while j < 5:
                if j % 2 != 0:
                    print("|", end="")
                elif i == 2*x + 1 and j == 2*y:
                    print(move, end="")
                else:
                    print(" ", end="")
                j += 1
            print ()
        i += 1

```

What will the following code produce?

```
x=int("1")  
y="1"  
draw(x,y)
```

- ☐ A tic tac toe board with an X in the center.
- ☐ A tic tac toe board with an X in the upper left cell.
- ☐ TypeError
- ☐ An empty tic-tac-toe board.

Correct AnswerQuiz Score: **0** out of 35