MC-12 Plus specification sheet

Fictional document for Northfield Lab Supply, a fictional company created for a portfolio project. Not for real use.

Item	Value
Document ID	NLS-DOC-MC12-SPEC-PLS-R1
Product	Benchtop Microcentrifuge MC-12
Applies to	NLS-MC12-PLS
Revision	R1
Effective date	2026-03-01
Status	current

Specification: Plus

Item	Value
Rotors	12-place (1.5 ml and 2.0 ml tubes) and 8-place PCR strip rotor
Speed	500 to 15,000 rpm in 100 rpm steps
Maximum RCF	18,900 ×g at 15,000 rpm
Rotor radius (12-place)	7.5 cm
Display	Digital speed (rpm or ×g) and timer
Run time	10 s to 99 min, or continuous
Acceleration / braking	About 8 s / about 15 s
Noise	Below 60 dB(A) at 15,000 rpm
Safety	Lid lock and imbalance cut-out
Power	230 V AC, 50 Hz, 120 W
Dimensions (W × D × H)	24 × 28 × 16 cm
Weight	3.6 kg
Operating conditions	5 to 40 °C, 20 to 80 % humidity, non-condensing
Supplied with	Unit, both rotors, mains cable (UK plug), user manual
Warranty	2 years