VM-10 vortex mixer user manual

Fictional document for Northfield Lab Supply, a fictional company created for a portfolio project. Not for real use.

Item	Value
Document ID	NLS-DOC-VM10-MAN-R1
Product	Vortex Mixer VM-10
Applies to	NLS-VM10-BAS, NLS-VM10-VAR
Revision	R1
Effective date	2026-03-01
Status	current

1. Introduction

The VM-10 is a benchtop vortex mixer with a cup head. It is sold in two versions: the Basic (fixed speed) and the Variable speed (adjustable speed with touch and continuous modes).

Differences between the versions:

	Basic	Variable speed
Speed	Fixed, 2,800 rpm	Adjustable, 200 to 3,000 rpm
Modes	Continuous (on/off switch)	Touch and continuous
Power	50 W	60 W
Warranty	1 year	2 years

2. Safety

- Place the mixer on a level, non-slip surface.
- Hold tubes firmly and do not overfill them.
- Do not mix flammable or hazardous liquids unless you have assessed the risk.
- Unplug before cleaning.

3. Setting up

1. Check the contents against the packing list.
2. Place the mixer on a level surface and fit the cup head.
3. Connect the mains cable (230 V AC, 50 Hz).

4. Operation

1. Basic: switch on for continuous mixing at 2,800 rpm. Variable speed: set the speed with the dial (200 to 3,000 rpm).
2. Press the tube lightly into the cup head. In touch mode (Variable speed only) the mixer runs while the tube presses the head.
3. Mix for the time needed, then lift the tube away. Switch off when finished.
4. Do not run for more than 30 minutes continuously; rest for 10 minutes.

5. Cleaning and maintenance

- Wipe the head and casing with a damp cloth and mild detergent.

- Do not immerse in liquid.

6. Troubleshooting

Problem	Likely cause	What to do
Does not start	Mains cable not connected	Check the cable and socket
Tube does not mix well	Speed too low or tube overfilled	Increase the speed or reduce the volume

7. Warranty and contact

Warranty: Basic: 1 year. Variable speed: 2 years.

Warranty claims: contact Customer service with the order number and a description of the fault. The warranty covers manufacturing defects and does not cover damage from misuse, spills or unauthorised repair.

Contact: customerservice@northfieldlabsupply.example