

The AGM logo is positioned in the top right corner. It consists of the letters 'AGM' in a bold, black, sans-serif font. The background of the entire page is a photograph of a black and grey electric scooter parked on a paved surface, with a green field and hills in the background. The scooter's front wheel, handlebars, and deck are visible.

AGM

TIRES AND PARTS YOU CAN COUNT ON

CATALOG

Tires and Parts

2025/05

www.agmcreate.com

AGM

TIRES AND PARTS YOU CAN COUNT ON



CONTENTS

Company Profile	01
Main Products	02
<i>E-Scooter Tires</i>	02
<i>E-Bike Tires</i>	13
<i>Spare Parts</i>	16
Application Scenarios	18
Certifications	19
Business Flow	20
Contact Us	20

• **Company Profile**

AGM Technology (Brand: AGM) is dedicated to providing high-quality electric scooter and e-bike tires and components to customers worldwide. Founded in Guangzhou, China, in 2020, AGM has over five years of industry experience. We deliver reliable products and professional services globally.

• **Our Advantages:**

- *Over 5 years of export experience*
- *Full range of electric scooters and electric*
- *Global certification and strict quality control*
- *Provide OEM/ODM services*
- *Quick response and shipping*

• **Support and Services**

- *OEM/ODM customization*
- *Sample orders welcome*
- *24/7 rapid response*
- *Flexible minimum order quantity, global logistics*



AGM

TIRES AND PARTS YOU CAN COUNT ON



E-Scooter Tire

*Excellent wear resistance
Excellent puncture resistance
Airtight Integrated Technology*

G-X610



Specifications
200x50

Characteristic
TUBE TIRE

Size After Mounting High
200/50/134

G-X1017



Specifications
200x50

Characteristic
TUBE TIRE

Size After Mounting High
200/50/94

G-C9361



Specifications
8½x2 9x2 230 x 50
254 x 54 60/70-6.5

Characteristic
TUBE TIRE

Note
MIJIA SERIES

G-C9287



Specifications
8½x2

Characteristic
TUBE TIRE

Size After Mounting High
230/50/156

G-X608



Specifications
8.5x3.0

Characteristic
TUBE TIRE

Size After Mounting High
230/63/134

G-X609



Specifications
8.5x3.0

Characteristic
TUBE TIRE

Size After Mounting High
230/63/134

G-X608S



Specifications
8.5x3.0

Characteristic
TUBE TIRE

Size After Mounting High
230/63/156

G-X9009



Specifications
8.5x3.0
10x2.50
80/65-6

Characteristic
TUBE TIRE

G-X609A



Specifications
8.5x3.0

Characteristic
TUBE TIRE

Size After Mounting High
230/63/156

G-X609B



Specifications
8.5x3.0

Characteristic
TUBE TIRE

Size After Mounting High
230/70/134

G-X8032



Specifications
70/50-6.1

Characteristic
TUBELESS

Size After Mounting High
230/70/156

G-X8041



Specifications
9x3.0-5.5
80/65-6
80/50-6.5
10x3.5-6.5

Characteristic
TUBE TIRE

G-X040



Specifications
10x2-6.1
60/70-6.5

Characteristic
TUBELESS

Size After Mounting High
255/50/156

G-IA2145



Specifications
10x2.50

Characteristic
TUBE TIRE

Size After Mounting High
255/65/152

G-X433



Specifications
10x2.50-6.5

Characteristic
TUBELESS

Size After Mounting High
255/60/164.5

G-X8022



Specifications
10x2.75-6.5

Characteristic
TUBELESS

Size After Mounting High
260/70/164.5

G-X8033



Specifications

**250x54
60/70-6.5**

**Characteristic
TUBELESS
WITH GEL**

G-X060



Specifications

60/70-6.5

**Characteristic
TUBE TIRE**

**Size After Mounting High
255/60/164.5**

G-CY346



Specifications

60/70-6.5

**Characteristic
TUBELESS**

**Note
NINEBOT E LITE**

G-X011A



Specifications

10x2.75-6.5

**Characteristic
TUBELESS**

**Size After Mounting High
260/70/164.5**

G-X822



Specifications

70/80-6.5

**Characteristic
TUBELESS**

**Size After Mounting High
280/70/164.5**

G-X8012



Specifications

80/55-6.5

**Characteristic
TUBE TIRE/TUBELESS**

**Size After Mounting High
255/80/164.5**

G-X8016S



Specifications

80/65-6

**Characteristic
TUBE TIRE**

**Size After Mounting High
255/85/152**

G-X424



Specifications

80/65-6

90/55-6.5

**Characteristic
TUBELESS**

**Size After Mounting High
255/85/152**

G-IA1289



Specifications
80/65-6

Characteristic
TUBE TIRE

Size After Mounting High
255/85/152

G-X8021



Specifications
10.5x2.75
10.5x3.0

Characteristic
TUBELESS

G-X018



Specifications
90/55-6

Characteristic
TUBELESS

Size After Mounting High
280/100/152

G-X011



Specifications
90/65-6.5

Characteristic
TUBE TIRE

Size After Mounting High
280/90/164.5

G-CY350



Specifications
60/70-7.0

Characteristic
TUBELESS
WITH GEL

G-CY329



Specifications
FRONT 60/70-6.5
REAR 60/65-6.9

Characteristic
TUBELESS WITH GEL

Note
NINEBOT MAX2.0/E2PRO

G-CY397



Specifications
70/60-7.5

Characteristic
TUBELESS

Note
NINEBOT ZT3PRO

G-CY325



Specifications
70/60-7.5

Characteristic
TUBELESS WITH GEL

Note
NINEBOT G3

G-CY325



Specifications
80/55-7.5

Characteristic
TUBELESS WITH GEL

Note
NINEBOT GT3

G-CY396



Specifications
60/70-6.5

Characteristic
TUBELESS

Note
XIAO MI 5

G-C9316



Specifications
90/65-6.5

Characteristic
TUBELESS

Size After Mounting High
280/90/164.5

G-C9336



Specifications
10x2.5
11x2.5

Characteristic
TUBE TIRE

G-CM560



Specifications
10x3.00-6
9x2.50

Characteristic
TUBELESS

G-C6559S



Specifications
10x3.00-6

100/55-6.5

100/55-7

G-CM531



Specifications
10x2.25
10x2.5
10x2.5-6.5
10x2.7-6.5

G-X021



Specifications
100/55-6.5

Characteristic
TUBELESS

Size After Mounting High
245/100/164.1

G-C9299S



Specifications
80/55-7

Characteristic
TUBELESS

G-C858



Specifications
70/75-6.5(TT)
90/65-6.5(TT&TL)





Specifications
90°direction
Characteristic
INSIDE TURN



Specifications
90°direction
Characteristic
OUTSIDE TURN



Specifications
45°direction
Characteristic
INSIDE TURN



Specifications
45°direction
Characteristic
OUTSIDE TURN

Inner tube specifications



straight valve

200×50	70/65-6.5	10×2.5	121/2×2.215
81/2×2.0	85/65-6.5	10×3.0	14×2.125
8.5×3.0	10×2	90/65-6.5	14×2.50
9×2.0	10×2.125	12×2.215	16×2.50

INNER TUBE VALVE TYPE ALL SIZE AVAILABLE



DUNLOP VALVE (D/V)
(GERMANY TYPE)



AMERICAN VALVE (A/V)
(SCHRADER)



FRENCH VALVE (F/V)
(PR STA)



ENGLISH VALVE (E/V)



RECORD VALVE (RVT)



ITALIAN VALVE (I/V)

G-ST01

Line Honeycomb



Specifications

8.0x2.0

Suitable Rim Diameter

137MM

Suitable Rim Groove Width

25MM

G-ST02

Honeycomb



Specifications

8.0x2.0

Suitable Rim Diameter

137MM

Suitable Rim Groove Width

25MM

G-ST03

Honeycomb



Specifications

8.0x2.125

Suitable Rim Diameter

160MM

Suitable Rim Groove Width

42MM

G-ST04

Arrow Honeycomb



Specifications

8.5x2.0

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

32MM

G-ST05

Honeycomb



Specifications

8.5x2.0

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

32MM

G-ST06

Bihoneycomb



Specifications

8.5x2.0

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

34MM

G-ST07

Line honeycomb



Specifications

8.5x2.0

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

34MM

G-ST08

Off-road



Specifications

8.5x2.0

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

34MM

G-ST09

Line honeycomb



Specifications

8.5x3.0

Tread pattern
Off-road

G-ST10

Line honeycomb



Specifications

9.5x2.0

Suitable Rim Diameter
178MM

Suitable Rim Groove Width
35MM

G-ST11

Off-road



Specifications

9.5x2.5

Suitable Rim Diameter
171MM

Suitable Rim Groove Width
42MM

G-ST12

Line honeycomb



Specifications

10x2.125

Suitable Rim Diameter
169MM

Suitable Rim Groove Width
34MM

G-ST13

Off-road



Specifications

10x2.125F

Suitable Rim Diameter
179.5MM

Suitable Rim Groove Width
40.5MM

G-ST14

Honeycomb



Specifications

10x2.125

Suitable Rim Diameter
169MM

Suitable Rim Groove Width
34MM

G-ST15

Bihoneycomb



Specifications

10x2.125

Suitable Rim Diameter
169MM

Suitable Rim Groove Width
32MM

G-ST16

Line honeycomb



Specifications

10x2.125

Suitable Rim Diameter
178MM

Suitable Rim Groove Width
40.5MM

G-ST17

Honeycomb



Specifications

10x2.5

Suitable Rim Diameter

165MM

Suitable Rim Groove Width

34MM

G-ST18

Off-road



Specifications

10x2.5

Suitable Rim Diameter

178MM

Suitable Rim Groove Width

42MM

G-ST19

Bihoneycomb



Specifications

10x2.5

Suitable Rim Diameter

178MM

Suitable Rim Groove Width

42MM

G-ST20

Bihoneycomb



Specifications

10x2.5

Suitable Rim Diameter

165MM

Suitable Rim Groove Width

32MM

G-ST21

Line honeycomb



Specifications

10x2.5

Suitable Rim Diameter

169MM

Suitable Rim Groove Width

34MM

G-ST22

honeycomb



Specifications

10x2.75

Suitable Rim Diameter

179MM

Suitable Rim Groove Width

47MM

G-ST23

Off-road



Specifications

10x2.75

Suitable Rim Diameter

182MM

Suitable Rim Groove Width

50MM

G-ST24

Off-road



Specifications

10x2.75

Suitable Rim Diameter

178MM

Suitable Rim Groove Width

50MM

AGM

TIRES AND PARTS YOU CAN COUNT ON



E-Bike Tire

G-TT01Z



Specifications
12x2.125

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT02Z



Specifications
12.5x2.125

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT03Z



Specifications
14x2.125

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT04Z



Specifications
16x2.125

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT05Z



Specifications
20x1.75(47-406)

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT06Z



Specifications
20x1.95(47-406)

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT07Z



Specifications
20x2.125(54-406)

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE

G-TT08Z



Specifications
20x4

Characteristic
E-BIKE TIRE

Tire Type
OUTER TIRE



G-ST1201



Specifications
12x2.125
Tire Type
SOLID TIRE
Suitable Rim Diameter
218MM
Suitable Rim Groove Width
30MM

G-ST1202



Specifications
12x2.5
Tire Type
SOLID TIRE
Suitable Rim Diameter
218MM
Suitable Rim Groove Width
30MM

G-ST1401



Specifications
14x2.125
Tire Type
SOLID TIRE
Suitable Rim Diameter
270MM
Suitable Rim Groove Width
40.5MM

G-ST1402



Specifications
14x2.75
Tire Type
SOLID TIRE
Suitable Rim Diameter
272MM
Suitable Rim Groove Width
46MM

G-ST1601



Specifications
16x2.125
Tire Type
SOLID TIRE
Suitable Rim Diameter
320MM
Suitable Rim Groove Width
30MM

G-ST1602



Specifications
16x2.5
Tire Type
SOLID TIRE
Suitable Rim Diameter
320MM
Suitable Rim Groove Width
39MM

AGM

TIRES AND PARTS YOU CAN COUNT ON

Spare parts for E-Scooters

G-AC001

Helmet



Dimensions
240x275x165 MM

Weight
2.2 KG

Product color
RED/BLACK/WHITE

G-AC002

Disc brake

Minimum hole distance
25 MM

Maximum hole distance
40 MM

Suitable for
XIAOMI PRO/PRO 2



G-AC003

Speed Controller



Suitable for
NINEBOT G30
XIAOMI M365
XIAOMI PRO

G-AC004

Rear Light

Weight
0.38 KG

Suitable for
NINEBOT G2 MAX
NINEBOT ZT3 PRO



G-AC005

Brake Pads



Weight
0.1 KG
Suitable for
NINEBOT ZT3 PRO

G-AC006

Disc Brake Caliper

Weight
0.196 KG
Suitable for
NINEBOT ZT3 PRO



G-AC007

Dashboard



Weight
0.06 KG
Suitable for
NINEBOT G2 MAX

G-AC008

Li-ion Battery Charger

Main model
42V 2A, 54.6V 1.5A

Advantages
Shutoff protection, timing protection,
temperature control protection,
anti-sparking,
anti-reverse connection,
anti-backflow,
overcurrent protection,
overvoltage protection,
short circuit protection.



Application Scenarios



Segway-Ninebot



2021Y Ninebot Segway

1. P series

10.5x3.0CY320 Four
Season Tires
10.5x2.75 CY320 Four
Season Tires



2. G30 MAX

60/70-6.5 CY329 Self-sealing TL tires



2.6、2022Year

1、ST Super Smooth

80/55-7.0 CY325 TL self-sealing tire



2、Max2.0 Long Range

Front 60/70-6.5 CY329 TL Self-sealing tire
Rear 60/65-6.9 CY329 TL Self-sealing tire



2.7、2023Year

1、E2pro Long Range + Low Air Leakage Rate

Front 60/70-6.5 CY329 TL Long Range Self-Sealing tire
Rear 60/65-6.9 CY329 TL Long Range Self-Sealing tire



2、Sharing Max Plus X V7

60/65-9.0 CY320
60/55-8.5 CY320
Dual-density PU Tire



2.8、2024Year

1、ZT3 pro

70/60-7.5 CY397 TL
High Wear Resistance + High Air Retention



2、G3

70/60-7.5 CY325 TL
Long Range + High Air Retention + Self-sealing



CERTIFICATIONS



PSE



ROHS



UL



TUV-CB



KCC



CCC



EAC



EMC



KC



TUV-CE



TUV-GS

Business Flow





TIRES AND PARTS YOU CAN COUNT ON



Company Name: Guangzhou AGM Technology Co., Ltd

**Address: Room 402, Building 4, No.45, Shiguang Road,
Panyu District, Guangzhou, China 511495**

Phone: +86 13822229068

Whatsapp/Wechat: +86 13822229068

Email: kristin@agmcreate.com

www.agmcreate.com