Stepper Drives



**High Performance Step** 



Three versions: STR2, STR4 and STR8 capable of driving motors from HT08 to HT34.

- Switch Selectable Parameters
- ✓ Anti-Resonance
- ✓ Microstepping
- **✓** Microstep Emulation
- ✓ Self Test

# **Simple Setup - No Software Required**



Motor Selection - Optimized current settings for standard motors are stored on the drive and are selectable via on-board rotary or dip switches



Drive Configuration - On-board dip switches are used to configure running current, idle current, load inertia ratio and step resolution.




	_			-	ns
7.4		41	<b>c</b>	40	nc
	77		56		

AMPLIFIER TYPE	Dual H-bridge, 4 quadrant
CURRENT CONTROL	STR2: 4 state PWM at 16 kHz STR4/8: 4 state PWM at 20 kHz
OUTPUT CURRENT	STR2: 0.3 - 2.2 A/phase (peak of sine) STR4: 1.12 - 4.5 A/phase (peak of sine) STR8: 2.35 - 8.0 A/phase (peak of sine)
POWER SUPPLY	STR2: External 12 - 48 VDC power supply required STR4: External 24 - 48 VDC power supply required STR8: External 24 - 75 VDC power supply required
PROTECTION	Over-voltage, under-voltage, motor/wiring shorts (phase-to-phase, phase-to-ground)
IDLE CURRENT	50% or 90% of running current, switch selectable
MODES OF OPERATION	Step (pulse) & direction or CW/CCW pulse (pulse-pulse); selected via jumper under drive cover
STEP RESOLUTION	Dip switch selectable resolution: 200, 200 SM00TH, 400, 400 SM00TH, 2000, 5000, 12800, or 20000 s/r
ANTI-RESONANCE (Electronic Damping)	Raises the system damping ratio to eliminate midrange instability and allow stable operation throughout the speed range and improves settling time.  Dip switch setting for range of load-to-motor inertia ratio.
SELF TEST	Dip switch for automatically rotating step motor back and forth. Useful for testing motor and power supply connections.
MICROSTEP EMULATION	Performs high resolution stepping by synthesizing fine microsteps from coarse steps.  Available with full (200 SMOOTH) and half (400 SMOOTH) step resolutions.
STEP INPUT	5-24V, optically isolated, sinking (STR2) or differential (STR4/8). Minimum pulse width = 250 ns. Maximum pulse frequency = 150 kHz or 2 MHz, user selectable. Function = step or CW pulse.
DIRECTION INPUT	5-24V, optically isolated, sinking (STR2) or differential (STR4/8). Minimum pulse width = 250 ns. Maximum pulse frequency = 150 kHz or 2 MHz, user selectable. Function = direction or CCW pulse.
ENABLE INPUT	5-24V, optically isolated, sinking (STR2) or differential (STR4/8). Function = disable motor when closed.
FAULT OUTPUT	30V/80mA max, optically isolated, sinking or sourcing. Function = closes on drive fault.
DRIVE/MOTOR SETTINGS	Motor select (select part number from pre-defined list): dip switches (STR2) or rotary switch (STR4/8) Running current (100%, 90%, 80% or 70%): dip switches Idle current (50% or 90%): dip switch Load inertia ratio (0-4X or 5-10X): dip switch Step size (resolution): dip switches Step pulse type (step & direction or CW/CCW pulse): jumper under drive cover Step pulse noise filter (150 kHz or 2 MHz): dip switch (STR2) or jumper under drive cover (STR4/8) Self test (rotate motor back and forth): dip switch
DIMENSIONS	STR2: 3.65 x 2.2 x 0.82 inches (not including mating connectors) STR4/8: 4.65 x 2.97 x 1.3 inches (not including mating connectors)
WEIGHT	STR2: 4.7 oz (including mating connectors) STR4/8: 10.8 oz (including mating connectors)
OPERATING TEMPERATURE	0 to 85 °C (32 - 185 °F), interior of electronics section
AMBIENT TEMPERATURE	0 to 50 °C (32 - 122 °F), drive must be mounted to suitable heatsink
HUMIDITY	90% non-condensing
AGENCY APPROVALS	RoHS CE (EMC): EN 61800-3:2004 CE (LVD): EN 61800-5-1:2003

# **STR2 Motor Table & Dimensions**

STR2 Motors						
Switch	Motor	Wiring	Current	Holding Torque	Rotor Inertia	
			А	oz-in	g-cm²	
1 2 3	HT08-020	4 leads	0.42	2.4	1.9	
1 2 3	HT08-021	4 leads	0.42	4.4	4.0	
1 2 3	HT11-012	4 leads	1.20	7.4	8	
1 2 3	HT11-013	4 leads	1.20	15.3	18	
1 2 3	5014-842	4 leads	1.20	26	20	
1 2 3	HT17-268	parallel	1.61	31	38	
1 2 3	HT17-271	parallel	2.04	52	57	
1 2 3	HT17-275	parallel	2.04	78	82	
1 2 3	HT23-595	series	2.20	76	135	
1 2 3	HT23-598	series	2.20	158	260	
1 2 3	HT23-601	series	2.20	269	460	







# STR4/STR8 Motor Tables & Dimensions

STR4 Motors						
Switch	Motor	Wiring	Current	Holding Torque	Rotor Inertia	
			Α	oz-in	g-cm²	
0	Custom 1*	Reserved for custom configurations				
1	Custom 2*	Reserved for	or custom co	nfigurations		
3	HT17-278	Parallel	2.4	113	123	
3	HT17-268	Parallel	1.6	31.4	35	
4	HT17-271	Parallel	2	51	54	
5	HT17-275	Parallel	2	62.8	68	
6	HT23-594	Parallel	3.4	76.6	120	
7	HT23-598	Parallel	4.5	159.3	300	
8	HT23-601	Parallel	4.5	237	480	
9	HT24-100	Parallel	3.36	123	280	
А	HT24-105	Parallel	4.5	166	450	
В	HT24-108	Parallel	4.5	332	900	
С	HT34-485	Series	4.5	585	1400	
D	HT34-486	Series	4.5	1113	2680	
E	HT34-504	Series	3.816	396	1100	
F	HT34-505	Series	3.816	849	1850	

STR8 Motors						
Switch	Motor	Wiring	Current	Holding Torque	Rotor Inertia	
			Α	oz-in	g-cm²	
0	Custom 1*	Reserved for	or custom co	nfigurations		
1	Custom 2*	Reserved for custom configurations				
2	Custom 3*	Reserved for custom configurations				
3	HT23-603	Parallel	6	354	750	
4	HT23-594	Parallel	3.4	76.6	120	
5	HT23-598	Parallel	5	177	300	
6	HT23-601	Parallel	5	264	480	
7	HT24-100	Parallel	3.36	123	280	
8	HT24-105	Parallel	4.8	177	450	
9	HT24-108	Parallel	4.8	354	900	
A	HT34-485	Parallel	8	507	1400	
В	HT34-486	Parallel	8	965	2680	
С	HT34-487	Parallel	8	1439	4000	
D	HT34-504	Parallel	7.56	396	1100	
Е	HT34-505	Parallel	7.56	849	1850	
F	HT34-506	Parallel	6.72	1260	2750	






#### **STR4/STR8 Torque Curves** HT17 with STR4 —HT17-268 —HT17-271 —HT17-275 —HT17-278 HT17 with STR4 —HT17-268 —HT17-271 —HT17-275 —HT17-278 Connection: Parallel 24v Power Supply , 20,000 steps/rev Connection: Parallel 48v Power Supply , 20,000 steps/rev oz-in rps rps HT23 with STR4 ---HT23-603 (STR8) HT23 with STR4/8 24v Power Supply. 20,000 steps/rev Connection: Parallel, 48v Power Supply , 20,000 steps/rev ---HT23-601 (STR4) ---HT23-598 (STR4) ---HT23-594 (STR4) ₽<sup>200</sup> rps rps HT24 with STR8 —HT24-100 —HT24-105 —HT24-108 HT24 with STR8 —HT24-100 —HT24-105 —HT24-108 Connection: Parallel 24v Power Supply , 20,000 steps/rev Connection: Parallel, 48v Power Supply, 20,000 steps/rev ₽ 200 150 200 150 rps rps HT34 with STR8 HT34 with STR8 —HT34-485 —HT34-486 —HT34-487 Connection: Parallel Power Supply 48V, 20,000 steps/rev —HT34-504 —HT34-505 —HT34-506 Connection: Parallel, 60V Power Supply, 20,000 steps/rev **oz-in** 00

rps

#### **Step & Direction**


- Step & direction
- CW & CCW pulse



Best value for step & direction applications

## **Anti-Resonance/Electronic Damping**


Step motor systems have a natural tendency to resonate at certain speeds. The STR drives automatically calculate the system's natural frequency and apply damping to the control algorithm. This greatly improves midrange stability, allows for higher speeds, greater torque utilization, and improves settling times.



Delivers better motor performance and higher speeds

### **Microstep Emulation**

With Microstep Emulation, low resolution systems can still provide smooth motion. The drive can take low-resolution step pulses and create fine resolution micro-step motion.



**Delivers smoother motion in any application** 

### **Power Supplies**



Applied Motion also offers two matched power supplies for use with the STR drives. A 24VDC, 150W (part number PS150A24) and a 48VDC 320W version (part number PS320A48). These power supplies have current overload capability making them ideal for use with stepper drives.

# **RC-050 Regeneration Clamp**



The RC-050 regeneration clamp is for use where regeneration from the motor may cause damage to the drive. In these cases the RC-050 is connected between the drive and power supply and absorbs regenerated energy.



404 Westridge Dr. Watsonville, CA 95076 Tel: 800.525.1609 Fax: 831.761.6544 www.applied-motion.com

DISTRIBUTED BY:

925-0002E 11/15/2012

Accessories