

1 UK Constraints Derivation

We will simulate two six degree of freedom bodies joined by a revolute joint. Let the first object be object 1, and the second object be object 2. Each object has a position and an attitude. For each object, the state is comprised of the inertial position and the inertial to body orientation represented as MRPs.

$$x_i = \begin{bmatrix} r_{i/0}^0 \\ \sigma_i^0 \end{bmatrix} \quad (1)$$

The overall state being the concatenation of these two states:

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} r_{1/0}^0 \\ \sigma_0^1 \\ r_{2/0}^0 \\ \sigma_0^2 \end{bmatrix} \quad (2)$$

There are two parts of the constraint, positional and rotational. Let $r_{j/1}^1$ represent the position of the joint on body one in the body frame, and j_1 be the direction vector of the joint on body one in the body frame.

The position and rotation constraints are:

$$\phi_r = r_{1/0}^0 + C((\sigma_0^1)^{-1})r_{j/1}^1 - r_{2/0}^0 - C((\sigma_0^2)^{-1})r_{j/2}^2 \quad (3)$$

$$\phi_\sigma = (C((\sigma_0^1)^{-1})j_1) \times (C((\sigma_0^2)^{-1})j_2) \quad (4)$$

Where $C(\sigma)$ is the DCM derived from the MRPs (using the following formula):

$$C(\sigma) = I - \frac{4(1 - \sigma^T \sigma)}{(1 + \sigma^T \sigma)^2} \tilde{\sigma} + \frac{8}{(1 + \sigma^T \sigma)^2} \tilde{\sigma}^2 \quad (5)$$

With these two constraints defined, we can take the second derivative to get the constraint equations $A\ddot{x} = b$.

$$\phi_r = r_{1/0}^0 + C((\sigma_0^1)^{-1})r_{j/1}^1 - r_{2/0}^0 - C((\sigma_0^2)^{-1})r_{j/2}^2 \quad (6)$$

$$\begin{aligned} \frac{d\phi_r}{dt} &= \dot{r}_{1/0}^0 + \dot{C}((\sigma_0^1)^{-1})r_{j/1}^1 - \dot{r}_{2/0}^0 - \dot{C}((\sigma_0^2)^{-1})r_{j/2}^2 \\ &= \dot{r}_{1/0}^0 + C((\sigma_0^1)^{-1})\tilde{\omega}_{1/0}^1 r_{j/1}^1 - \dot{r}_{2/0}^0 - C((\sigma_0^2)^{-1})\tilde{\omega}_{2/0}^2 r_{j/2}^2 \end{aligned} \quad (7)$$

$$\begin{aligned} \frac{d^2\phi_r}{dt^2} &= \ddot{r}_{1/0}^0 + C((\sigma_0^1)^{-1})\ddot{\alpha}_{1/0}^1 r_{j/1}^1 + C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 r_{j/1}^1 \\ &\quad - \ddot{r}_{2/0}^0 - C((\sigma_0^2)^{-1})\ddot{\alpha}_{2/0}^2 r_{j/2}^2 - C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 r_{j/2}^2 \end{aligned} \quad (8)$$

$$\begin{aligned} \frac{d^2\phi_\sigma}{dt^2} &= \ddot{r}_{1/0}^0 - C((\sigma_0^1)^{-1})\ddot{r}_{j/1}^1 \alpha_{1/0}^1 + C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 r_{j/1}^1 \\ &\quad - \ddot{r}_{2/0}^0 + C((\sigma_0^2)^{-1})\ddot{r}_{j/2}^2 \alpha_{2/0}^2 - C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 r_{j/2}^2 \end{aligned} \quad (9)$$

Before stepping into ϕ_σ , let us define some terms that will be useful, and take their derivatives:

$$u = C((\sigma_0^1)^{-1})j_1 \quad (10)$$

$$\dot{u} = C((\sigma_0^1)^{-1})\tilde{\omega}_{1/0}^1 j_1 \quad (11)$$

$$\begin{aligned} \ddot{u} &= C((\sigma_0^1)^{-1})\tilde{\alpha}_{1/0}^1 j_1 + C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 j_1 \\ &= -C((\sigma_0^1)^{-1})\tilde{j}_1 \alpha_{1/0}^1 + C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 j_1 \end{aligned} \quad (12)$$

$$v = C((\sigma_0^2)^{-1})j_2 \quad (13)$$

$$\dot{v} = C((\sigma_0^2)^{-1})\tilde{\omega}_{2/0}^2 j_2 \quad (14)$$

$$\begin{aligned} \ddot{v} &= C((\sigma_0^2)^{-1})\tilde{\alpha}_{2/0}^2 j_2 + C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 j_2 \\ &= -C((\sigma_0^2)^{-1})\tilde{j}_2 \alpha_{2/0}^2 + C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 j_2 \end{aligned} \quad (15)$$

$$\phi_\sigma = u \times v \quad (16)$$

$$\begin{aligned} \frac{d\phi_\sigma}{dt} &= \dot{u} \times v + u \times \dot{v} \\ &= (C((\sigma_0^1)^{-1})\tilde{\omega}_{1/0}^1 j_1) \times v + u \times (C((\sigma_0^2)^{-1})\tilde{\omega}_{2/0}^2 j_2) \end{aligned} \quad (17)$$

$$\begin{aligned} \frac{d^2\phi_\sigma}{dt^2} &= \ddot{u} \times v + 2\dot{u} \times \dot{v} + u \times \ddot{v} \\ &= (-C((\sigma_0^1)^{-1})\tilde{j}_1 \alpha_{1/0}^1 + C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 j_1) \times v \\ &\quad + 2(C((\sigma_0^1)^{-1})\tilde{\omega}_{1/0}^1 j_1) \times (C((\sigma_0^2)^{-1})\tilde{\omega}_{2/0}^2 j_2) \\ &\quad + u \times (-C((\sigma_0^2)^{-1})\tilde{j}_2 \alpha_{2/0}^2 + C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 j_2) \end{aligned} \quad (18)$$

Let us define q as the "quasi-velocity" vector:

$$q_i = \begin{bmatrix} v_{i/0}^0 \\ \omega_{i/0}^i \end{bmatrix} \quad (19)$$

$$q = \begin{bmatrix} q_1 \\ q_2 \end{bmatrix} \quad (20)$$

Which is related to the derivative of the state $\dot{x}$ by the following relation.

$$\dot{x}_i = \begin{bmatrix} I_3 & 0_{3 \times 3} \\ 0_{3 \times 3} & \frac{1}{4}B(\sigma_0^i) \end{bmatrix} q_i = H_i q_i \quad (21)$$

$$\dot{x} = \begin{bmatrix} H_1 & 0_{6 \times 6} \\ 0_{6 \times 6} & H_2 \end{bmatrix} q = Hq \quad (22)$$

Where $B(\sigma)$ is defined as:

$$B(\sigma) = (1 - \sigma^T \sigma)I + 2\tilde{\sigma} + 2\sigma\sigma^T \quad (23)$$

Using q , we can leave our constraint equations in terms of q to get $\dot{q}$, and then integrate x by plugging in Hq . With this, we can get A and b for our UK constraint equation

$$A = \begin{bmatrix} I_3 & -C((\sigma_0^1)^{-1})\tilde{r}_{j/1}^1 & -I_3 & C((\sigma_0^2)^{-1})\tilde{r}_{j/2}^2 \\ 0_{3 \times 3} & \tilde{v}C((\sigma_0^1)^{-1})\tilde{j}_1 & 0_{3 \times 3} & -\tilde{u}C((\sigma_0^2)^{-1})\tilde{j}_2 \end{bmatrix} \quad (24)$$

$$b_r = -C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 r_{j/1}^1 + C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 r_{j/2}^2 \quad (25)$$

$$\begin{aligned} b_\sigma &= \tilde{v}C((\sigma_0^1)^{-1})(\tilde{\omega}_{1/0}^1)^2 j_1 - \tilde{u}C((\sigma_0^2)^{-1})(\tilde{\omega}_{2/0}^2)^2 j_2 \\ &\quad - 2(C((\sigma_0^1)^{-1})\tilde{\omega}_{1/0}^1 j_1) \times (C((\sigma_0^2)^{-1})\tilde{\omega}_{2/0}^2 j_2) \end{aligned} \quad (26)$$

2 UK Dynamics Derivation

The equations of motion for this rigidbody can be broken into two parts, the translational equations of motion, and the rotational equations of motion. The translational equations are pretty simple.

$$m_i \ddot{r}_{i/0}^0 = F \quad (27)$$

The rotational equations of motion come from euler equations:

$$I_i^i \dot{\omega} = T - \omega \times I_i^i \omega \quad (28)$$

This gives us the overall equations of motion (per body) as

$$\begin{bmatrix} m_i I_3 & 0_{3 \times 3} \\ 0_{3 \times 3} & I_i^i \end{bmatrix} \begin{bmatrix} \ddot{v}_{i/0}^0 \\ \dot{\omega}_0^i \end{bmatrix} = \begin{bmatrix} F \\ T - \tilde{\omega} I_i^i \omega \end{bmatrix} \quad (29)$$

3 State Integration