Getting Help

The Man Pages

The man (manual) pages are very structured documentation source, as you will see from the example below:

Type the command like this at the prompt, and press Enter:

```
an ls
```

The documentation for Is will be displayed on your screen after you press Enter:

```
LS(1) User Commands LS(1)

NAME

1s - list directory contents

SYNOPSIS

1s [OPTION]... [FILE]...

DESCRIPTION

List information about the FILEs (the current directory by default).

Sort entries alphabetically if none of

-cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short options too.

-a, --all

do not ignore entries starting with .

-A, --almost-all

do not list implied . and ..
```

Browse to the next page using the space bar. You can go back to the previous page using the b-key. When you reach the end, man will usually quit and you get the prompt back. Type q if you want to leave the man page before reaching the end, or if the viewer does not quit automatically at the end of the page.

Each man page usually contains a couple of standard sections, as we can see from the man Is example:

- The first line contains the name of the command you are reading about and the id of the section in which this man page is located. The man pages are ordered in chapters.
- The name of the command and a short description are given, which is used for building an index of the man pages.
- The synopsis of the command provides a technical notation of all the options and/or arguments this command can take. You can think of an option as a way of executing the command. The argument is what you execute it on.
- A longer description of the command is given.
- Options with their descriptions are listed. Options can usually be combined.
- There might also be author and copyright information.
- A reference to other man pages is given in the "SEE ALSO" section.
- Usually, there is also information about known bugs (anomalies) and where to report new bugs you may find.

The Info Pages

You can also read the Info pages about a command in addition to the man pages, using the info command.

Start by typing info Is in a terminal window.

```
info 1s
```

The documentation for Is will be displayed on your screen after you press Enter:

```
Next: dir invocation, Up: Directory listing

10.1 'ls': List directory contents

The 'ls' program lists information about files (of any type, including directories). Options and file arguments can be intermixed arbitrarily, as usual.

For non-option command-line arguments that are directories, by default 'ls' lists the contents of directories, not recursively, and omitting files with names beginning with '.' For other non-option arguments, by default 'ls' lists just the file name. If no non-option argument is specified, 'ls' operates on the current directory, acting as if it had been invoked with a single argument of '.'.

Also see *note Common options:..

* Menu:

* Which files are listed::

* Sorting the output::

* Details about version sort::

* General output formatting::

* Formatting file timestamps::

* Formatting the file names::
```

Use the arrow keys to browse through the text and move the cursor on a line starting with an asterisk, containing the keyword about which you want info, then hit Enter. Use the P and N keys to go to the previous or next subject. The space bar will move you one page further, no matter whether this starts a new subject or an Info page for another command. Use Q to quit.

The whatis Command

A short index of explanations for commands is available using the whatis command, like in the examples below:

```
user@clarusway:~$ whatis whatis whatis the whatis whatis (1) - display one-line manual page descriptions whatis ls

Is (1) - list directory contents
```

This displays short information about a command, and the first section in the collection of man pages that contains an appropriate page.

The apropos Command

If you don't know where to get started and which man page to read, apropos gives more information, apropos searches the manual pages for a keyword or regular expression.

```
user@clarusway:~$ whatis apropos apropos (1) - search the manual page names and descriptions

For example:

apropos find
```

Display all manual entries with the word "find" in the page name or description. The output will resemble the following:

```
btrfs-find-root (8) - filter to find btrfs root

ffs (3) - find first bit set in a word

ffs1 (3) - find first bit set in a word

ffs1 (3) - find first bit set in a word

ffs1 (3) - find first bit set in a word

find (1) - search for files in a directory hierarchy

findfs (8) - find a filesystem by label or UUID

findmut (8) - find a filesystem by label or UUID

git-cherry (1) - Find commits yet to be applied to upstream

git-merge-base (1) - Find commit yet to be applied to upstream

git-mame-rev (1) - Find commit yet to be applied to upstream

git-name-rev (1) - Find commit yet to be applied to upstream

git-pack-redundant (1) - Find redundant pack files

glob (3) - find pathnames matching a pattern, free memory from glob()

lifind (3) - find pathnames matching a pattern, free memory from glob()

lifind (3) - find files by name

pidof (8) - find files by name

pidof (8) - find the process ID of a running program.

systemd-delta (1) - Find overridden configuration files

ttyslot (3) - find the slot of the current user's terminal in some file

xdg-user-dir (1) - Find an XDG user dir
```

The --help Option

Most GNU commands support the --help, which gives a short explanation about how to use the command and a list of available options. Below is the output of this option with the Is command:

```
Usage: ls [OPTION]... [FILE]...
List information about the FILEs (the current directory by default).
Sort entries alphabetically if none of -cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short options too.
-a, --all do not ignore entries starting with .
-A, --almost-all do not list implied . and .
--author with -l, print the author of each file print C-style escapes for nongraphic characters scale sizes by SIZE before printing them; e.g.,
'--block-size=M' prints sizes in units of 1,948,576 bytes; see SIZE format below do not list implied entries ending with ~
```

Q: You want to do something from Linux command line but you have some doubts. How can you search a command or take information about a command from linux **terminal**?

A: There are many ways to searching information for commands. The **man** command gives you to very structured documentation for commands. You can also read the information about a command in addition to the man pages, using the **info** command. The shortest index of explanations for commands is available using the **whatis** command.

The parameter of the --help gives a short explanation about how to use the command and a list of available options (parameters).

If you don't know where to get started and **apropos** searches the manual pages for a keyword or regular expression.

– - Interview Q&A

90