

CANDY DIALOGUE ENGINE

Game State Tracker

1.0.0

A **Game State Tracker** is a variable your game uses to keep track of what the player or the game is currently doing.

Common examples include:

- "explore"
- "combat"
- "inventory"
- "dialogue"
- "cutscene"

At any given moment, your game logic may behave differently depending on this value. For example, movement might be enabled only in "explore", or enemies may attack only during "combat".

Some games also use a second variable to remember the previous state, allowing temporary state changes. For example, when the player opens the inventory during exploration, the game switches to "inventory". When the inventory closes, the game returns to "explore" and not "combat".

Candy DE doesn't enforce any specific game state system, but it provides a small helper function you can adapt: [change_game_state\(\)](#) located in [Candy_Functions.gd](#).

The function is entirely optional, so if you don't use a game state tracking system, you can ignore what follows and you don't need to do anything.

The [change_game_state\(\)](#) function lets Candy DE automatically switch your game into the "dialogue" state when dialogue begins, and restore the previous state when dialogue ends.

The function assumes your game uses a dual variable game state tracking logic, as described above, and requires that you replace the two default variables in the function with those you actually use: [global.game_state](#) and [global.previous_state](#).

Inside the function, you must also switch [use_game_state](#) to 'true', and change the value of [dialogue_state_value](#) to the value you prefer to use to indicate the "dialogue" game state.

If your game state tracking system is different, you'll need to make more modifications to the [change_game_state\(\)](#) function. This should be trivial if you know how to implement your own game state system in the first place.