

CANDY DIALOGUE ENGINE

Portrait Box Customization

1.0.0

The portrait box is used by the "Box" dialogue mode to display the speaker's portrait.

Nodes

Root

The root node should be named "Portrait".

This name can be modified provided you update the path to the dialogue box in **ui_elements_paths**, in **Candy_Engine.gd** under the "PATHS" region.

Required Nodes

The following nodes are required:

TextureRect, NinePatchRect, TextureButton, Sprite2D/3D, AnimatedSprite2D/3D or VideoStreamPlayer

- Displays the portrait file.
- The node type depends on your preferred method of displaying portraits.
- Script pointer: @onready var **portrait_node**

Optional Nodes

The following nodes are optional, and provided as suggestions:

Background

You can place an image node (TextureRect, Sprite2D/3D, etc) behind the portrait_node, to display a background that can be modified at runtime, independently of the speaker's portrait.

Foreground

You can place an image node (TextureRect, Sprite2D/3D, etc) over the portrait_node, to display a foreground, such as a frame, that can be modified at runtime.

Effect Player

You can add an AnimationPlayer node to the portrait box scene, to play visual effects of your creation specific to the portrait. No dedicated dialogue commands are provided for such visual effect player: use the various §Effect commands, and provide them the path to the portrait box's AnimationPlayer.

If you want to play tint or color overlays as effects, place a ColorRect node over the portrait and animate it (or use any other nodes you deem suitable for your purposes).

Script

Base

The script **Portrait.gd** should be attached to the scene's root node.

Variables

default_image_extension

The default extension to use for TextureRect, NinePatchRect or TextureButton if no extension is featured in the file reference.

default_sprite_extension

The default extension to use for Sprite2D or Sprite3D if no extension is featured in the file reference.

default_animated_sprite_extension

The default extension to use for AnimatedSprite2D or AnimatedSprite3D if no extension is featured in the file reference. Note that this refers to the Sprite Frames file to load.

default_video_extension

The default extension to use for VideoStreamPlayer if no extension is featured in the file reference.

sprite_fps

The speed, in frames-per-second, to play portrait animations (if using Sprite2D/3D or AnimatedSprite2D/3D nodes).

portrait_h / portrait_w

The size (height and width) that the **portrait_node** should be scaled to match.

Used only for Sprite2D/3D and AnimatedSprite2D/3D, as they cannot be assigned a specific size.

default_z

The default z_index value for the portrait box. Must be lower than the values of any video or image players.

Functions**receive_portrait()**

This function is called by the dialogue engine when a spoken line is processed.

The function receives the speaker's reference and the name of the portrait file to display, allowing it to find the correct file.

Depending on the node type of portrait_node, the function calls **animatedsprite_portrait()**, **texturerect_portrait()**, **texturebutton_portrait()**, **sprite_portrait()** or **video_portrait()** to correctly display the portrait.

If the spoken line has 'Play' enabled, **receive_portrait()** will pass this information to these subsequent functions so that the portrait's animation can be played.

write_begun()

This is a hook function, called just before dialogue starts writing (after everything else about the spoken line has been calculated). The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.

write_ended()

This is a hook function, called when dialogue has finished writing. The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.