

# CANDY DIALOGUE ENGINE

## Subtitles Customization

1.0.0

The Subtitles UI Element is used by the "Subtitles" dialogue mode. It's essentially a light dialogue box, without portrait display and without a dedicated RichTextLabel to display the speaker's name. Instead, users have the option to display the speaker's name inside the speech string.

## Nodes

### Root

The root node should be named "Subtitles".

This name can be modified provided you update the path to the dialogue box in **ui\_elements\_paths**, in **Candy\_Engine.gd** under the "PATHS" region.

## Required Nodes

The following node is required:

### RichTextLabel

- Displays the spoken text (and optionally the speaker's name).
- Requires BBCode enabled.
- Script pointer: @onready var **dialogue\_node**

## Script

### Base

The script **Subtitles.gd** should be attached to the scene's root node.

## Variables

### **default\_text\_color**

The default color to use for spoken text in the dialogue box.

Overrides **default\_subtitle\_font\_color** (**Candy\_Engine.gd**). Is overridden by "**Subtitle Text Color**" in the **actors** dictionary (**Candy\_Database.gd**)

### **default\_speaker\_color**

The default color to use for spoken text in the dialogue box.

Overrides **default\_subtitle\_speaker\_color** (**Candy\_Engine.gd**). Is overridden by "**Subtitle Speaker Color**" in the **actors** dictionary (**Candy\_Database.gd**)

### **default\_z**

The default z\_index value for the subtitles. Must be lower than the values of any video or image players.

## Functions

### **ready()**

Contains code to connect the "meta\_clicked" signal, in the event that you use the Lexicon feature with clickable keywords. See the **Lexicon** guide for details.

### **write\_begun()**

This is a hook function, called just before dialogue starts writing (after everything else about the spoken line has been calculated). The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.

### **write\_ended()**

This is a hook function, called when dialogue has finished writing. The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.