

CANDY DIALOGUE ENGINE

Text Color

1.1.0

Multiple methods exist to modify the color of spoken text and the color of the speaker's name:

- Directly setting text color in text nodes.
- Selecting a default text color for dialogue modes.
- Selecting a default text color for dialogue UI elements.
- Selecting a default text color for actors.
- Adding BBCode tags inside spoken text.
- Using the Lexicon feature.

Note that only the Dialogue Box has a dedicated text node for displaying the speaker's name. Speech Bubbles, Subtitles and Chat Boxes, instead, can display the speaker's name at the start of the spoken text string. For these dialogue modes, BBCode is used to assign a color to the speaker's name.

Text Nodes

You can modify the text color of the text node itself, by changing its `font_color` (Label node) or `default_color` (RichTextLabel node).

It's strongly recommended that you don't modify the node's `modulate` or `self_modulate` property, as that will conflict with other color overrides and BBCode.

Dialogue Modes

Custom colors can be specified for each dialogue mode in `Candy_Engine.gd`, in the 'Settings' region:

<code>var default_box_font_color</code>	→ Spoken text in the dialogue box
<code>var default_box_speaker_color</code>	→ Speaker name in the dialogue box
<code>var default_bubble_font_color</code>	→ Spoken text in bubbles
<code>var default_subtitle_font_color</code>	→ Spoken text in subtitle mode
<code>var default_subtitle_speaker_color</code>	→ Speaker name in subtitle mode

```
var default_chat_font_color    → Speaker name in the chat box
var default_chat_speaker_color → Speaker name in the chat box
```

For each of these variables, enter a color as a value if you want to setup a default override (e.g. 'Color(red)' or 'Color(1, 0, 0)').

Candy DE will modify the text node's default_color (RichTextLabel) or font_color (Label) through the node's theme_color_override property.

This will override whatever color was set by default for the node.

UI Elements

You also have the option of specifying an override color inside dialogue UI elements, such as dialogue boxes, speech bubbles, subtitles, and chat boxes.

This option is ideal to ensure the text color is visible over the UI's background.

Simply assign a color to either **text_color** or **speaker_color**. Set the value to 'null' to disable this override.

Candy DE will modify the text node's default_color (RichTextLabel) or font_color (Label) through the node's theme_color_override property.

This will override the previously-mentioned methods of setting color.

Actors

Each actor can be assigned a custom text and speaker color for each dialogue mode, in the **actors** dictionary (**Candy_Database.gd**):

```
"Box Text Color": null,
"Box Speaker Color": null,
"Bubble Text Color": null,
"Bubble Speaker Color": null,
"Subtitle Text Color": null,
"Subtitle Speaker Color": null,
"Chat Text Color": null,
"Chat Speaker Color": null,
```

As with previous methods, assign a color as a value, or set to 'null' to disable.

Candy DE will modify the text node's default_color (RichTextLabel) or font_color (Label) through the node's theme_color_override property.

This will override the previously-mentioned methods of setting color.

Spoken Text

BBCode can be added directly to spoken text strings in Spoken Lines.

This is useful when specific spoken lines (or just words) require specific colors.

This will override the previously-mentioned methods of setting color.

Lexicon

The Lexicon feature can be used (among other things) to color specific keywords or strings of words.

For details, see the [Lexicon](#) guide.

This will override the previously-mentioned methods of setting color.