

CANDY DIALOGUE ENGINE

Dialogue Box Customization

1.1.0

The dialogue box is used by the "Box" dialogue mode.

Nodes

Root

The root node should be named "Dialogue Box".

This name can be modified provided you update the path to the dialogue box in **ui_elements_paths**, in **Candy_Engine.gd** under the "PATHS" region.

Required Nodes

The following nodes are required:

RichTextLabel

- Displays the speaker's name.
- Requires BBCode enabled.
- Script pointer: @onexport var **speaker_node**

RichTextLabel

- Displays the spoken text.
- Requires BBCode enabled.
- Script pointer: @onexport var **dialogue_node**

Script

Base

The script **Dialogue_Box.gd** should be attached to the scene's root node.

Variables

enable_text_color

Enables override by **text_color** (see below)

text_color

The default color to use for spoken text in the dialogue box.

Overrides **default_box_font_color** (**Candy_Engine.gd**). Is overridden by **"Box Text Color"** in the **actors** dictionary (**Candy_Database.gd**)

enable_speaker_color

Enables override by **speaker_color** (see below)

speaker_color

The default color to use for spoken text in the dialogue box.

Overrides **default_box_speaker_color** (**Candy_Engine.gd**). Is overridden by **"Box Speaker Color"** in the **actors** dictionary (**Candy_Database.gd**)

default_z

The default z_index value for the dialogue box. Must be lower than the values of any video or image players.

Functions

ready()

Contains code to connect the "meta_clicked" signal, in the event that you use the Lexicon feature with clickable keywords. See the **Lexicon** guide for details.

write_began()

This is a hook function, called just before dialogue starts writing (after everything else about the spoken line has been calculated). The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.

write_ended()

This is a hook function, called when dialogue has finished writing. The function is intended to be edited if you want to trigger custom behavior at that moment.

The function is called with the 'await' method.