

CANDY DIALOGUE ENGINE

Audio Players Customization

1.0.0

Audio players are used for displaying static or animated images on-screen, through dialogues.

Nodes

Root

The root node can have any desired name. A folder of the same name must be created in Candy_DE/Media/General/Audio and any files the player is expected to play should be placed there.

Required Nodes

The following node is required:

AudioStreamPlayer / AudioStreamPlayer2D / AudioStreamPlayer3D

- Plays the audio file.
- Script pointer: @onready var **audio_player**

Script

Base

Attach either of the following scripts, depending on the root node you are using:

AudioStreamPlayer → **Audio_Player.gd**

AudioStreamPlayer2D → **Audio_Player_2D.gd**

AudioStreamPlayer3D → **Audio_Player_3D.gd**

Variables

default_audio_extension

The default extension to use for audio files, if none is provided with the file reference.

default_z

The default z_index value for the audio player. Must be higher than the values of the dialogue box, subtitles, speech bubbles and any other such UI elements for displaying dialogues.

Other variables in the script are used internally and must not be modified.

Functions

The various functions are designed to work with the various Candy DE \$Audio commands. They should not be modified.

Signals

The AudioStreamPlayer's **finished()** signal must be connected to the **_on_finished()** function inside the AudioStreamPlayer's script.