

CANDY DIALOGUE ENGINE

Custom BBCode

1.0.0

Godot's RichTextLabel supports custom BBCode tags.

If you use custom BBCode tags, you need to add them to the [Candy_Properties.gd](#) script, so that Candy DE can correctly support them.

Custom BBCode tags are added to either of the following arrays:

BBCODE_TAGS_SIMPLE

Add your custom tags here if they don't accept a value (e.g. [b], [center], etc.).

BBCODE_TAGS_EQUALS

Add your custom tags here if they accept a value denoted by the equals (=) sign (e.g. [color=red], [font_size=16], etc.).

BBCODE_TAGS_SPACE

Add your custom tags here if they accept parameters separated by a space (e.g. [img {options}], [url {options}], etc.).

Only the opening tags must be added in arrays. The closing tags (e.g. [/url]) should not be added.

Some tags may qualify for multiple arrays. For example, the [url] tag is featured in all three arrays.

Technically, the way Candy DE uses these tags, tags only need to be featured in one array (it does not matter which one).

For the purpose of future-proofing your custom tags (i.e. in case we make updated to Candy DE), we recommend adding your custom tags to all arrays they fit the criteria for.

Custom tags that don't follow the standard BBCode principles may not work. This can include, as hypothetical examples, tags what use a different separator than space or the equals sign (e.g. [color: red]) or tags that use a different closing tag (e.g. [bold] [end_bold]).

If you use such unusual tags, you might be able to make Candy DE support them by adding custom logic where relevant, such as in the `_is_valid_bbcode_tag()` function in **Candy_Engine.gd**.