

CANDY DIALOGUE ENGINE

Parallel Dialogues

1.1.0

Each instance of the **Candy_Engine.gd** script is its own self-contained dialogue engine.

This means that you can assign the script to multiple nodes, and run separate dialogues on each node, either at different times or simultaneously.

This can be used for triggering NPC 'barks' (NPCs making passing comments in the background), for keeping conversations separate while the game or the player alternates between them, or for multiplayer games where each player might engage in their own dialogues.

Instance UI

Each instance of the **Candy_Engine.gd** script should have its own dialogue UI to avoid conflicts.

The default dialogue UI is the **Candy_UI.tscn**, which is a CanvasLayer and usually made an autoload. This allows it to display dialogues on screen at any point in the game.

However, you may want a different setup for other dialogue instances.

Disabling Input

You may want to set `input_enabled` to 'false' in the **Candy_Engine.gd** script, so that these instances don't accidentally react when the player tries to interact with the main dialogue. Or alternately, you could setup different input keys to interact with bark instances, or even write code that selectively enables and disables input (e.g. enable input on a bark instance only when the player is near the NPC and looking directly at it).

Other Settings

Remember to carefully consider all the other settings in the **Candy_Engine.gd** script, as they could interfere in various ways if not configured correctly. It isn't very complicated, it's just a matter of common sense and logic.