

EXAMPLE 4

Instruction Memory's file: 5th_fig456_MemEx4/inst.rom

This Mips pipeline implementation can handle branches (with "nop" put by compiler) and forward data hazards

The user should set initial register values (linear) and DataRam (linear + 2). No data values are required.

Description: A simple sequence of six instructions with no data hazard.

LW r1,0(r4)
LW r2,4(r4)
NOP
NOP
ADD r3,r1,r2
SW r3, 8(r4)

LW r1,0(r4) – type I instruction

opcode = 35 rs = 4 rt = 1 immediate = 0
100011 00100 00001 0000000000000000
0x8C810000

LW r2,4(r4) – type I instruction

opcode = 35 rs = 4 rt = 2 immediate = 4
100011 00100 00010 0000000000000100
0x8C820004

NOP

0x00000000

NOP

0x00000000

ADD r3,r1,r2 – type R instruction

opcode = 0 rs = 1 rt = 2 rd = 3 sh = 0 func = 32
000000 00001 00010 00011 00000 100000
0x00221820

SW r3,8(r4) – type I instruction

opcode = 43 rs = 4 rt = 3 immediate = 8
101011 00100 00011 0000000000001000
0xAC830008

The hexadecimal code example is:

LW r1,0(r4) – **0x8C810000**
LW r2,4(r4) – **0x8C820004**
NOP – **0x00000000**
NOP – **0x00000000**
ADD r3,r1,r2 – **0x00221820**

SW r3, 8(r4) – 0xAC830008

Calculations check (with linear initial register values):

1. LW r1,0(r4) – $R1 = M[1] = 3$
2. LW r2,4(r4) – $R2 = M[2] = 4$
3. NOP
4. NOP
5. ADD r3,r1,r2 – $R3 = 7$
6. SW r3, 8(r4) – $M[3] = 7$