

COMBINED_HighEnergyData_runs_4775-7039_ASCII

general information

Set name	COMBINED_HighEnergyData_runs_4775-7039_ASCII		
Data selection	comb_1		
Data format	ASCII		
Number of events	general	1,738,231	
	combined	1,738,321	
	lopes	1430	
Zip-file name / size	COMBINED_HighEnergyData_runs_4775-7039_ASCII.zip / 180 MB		
Data file names / sizes	combined.txt	/ 170 MB	
	general.txt	/ 198 MB	
	lopes.txt	/ 343 kB	
	row_mapping.txt	/ 31 MB	
Creation date	17.4.2020		
Application	Analyses with high energetic particles		

KASCADE quantities selected

Quantity	Description	Range	Cut
E	Estimated primary energy	$10^{15.7} - 10^{19}$ eV	cut
Xc	X-core position	-500 - +91 m	full range
Yc	Y-core position	-550 - +91 m	full range
Ze	Zenith angle	0° - 30°	full range
Az	Azimuth angle	0° - 360°	full range
Ne*	Number of e/ γ particles	1e3.2 / 1e4.8 – 1.0e9	full range
Nmu	Number of Muons	1000 – 1.9e9	full range
Age	Shower age	0.15 – 1.48	full range
Age	Shower age	0.1 – 1.48	full range

* for Ne the range depends on the reconstructed shower core position; see manual

GENERAL quantities selected

Quantity	Description	Range	Cut
T	Air temperature	-20 ° - +50°	full range
P	Air pressure	960 -1040 hPa	full range
Gt	Global time (sec's since 1.1.1970)	1,078,737,917 – 1,288,855,193	full range
Mt	Micro time	0 – 999,999,999	full range
DateTime	Date & Time	8.3.2004 – 4.11.2010	full range
R	Run number	4775 - 7039	full range
Ev	Event number	1 – 4,100,000	full range
UUID	Universal Unique Identifier		full range

LOPES quantities selected

Quantity	Description	Range	Cut
EfieldMaxAbs	maximum atmospheric electric field	0 - 50,000 V/m	
Azimuth EW & NS	azimuth of LOPES CC beam; EW & NS	0 – 360°	
Elevation EW & NS	elevation of CC beam; EW & NS	0 – 360°	
CC Height EW & NS	amplitude of CC beam; EW & NS	0 – 20 $\mu\text{V/m/MHz}$	
XHeight EW & NS	amplitude of X-beam; EW & NS	0 – 20 $\mu\text{V/m/MHz}$	
ConeAngle EW & NS	cone angle of wavefront; EW & NS	0 – 0,1 rad	
NCCBeanAnt EW & NS	nr of antennas contributing; EW & NS	0 – 30	
Eta EW & NS	slope parameter of LDF; EW & NS	-0.04 - 0.11 /m	
Eps EW & NS	ampl parameter of LDF; EW & NS	-0.04 - 0.11 $\mu\text{V/m/MHz}$	
Geomag_Angle	angle between geomagnetic field and KASCADE shower axis	0 – 120 °	
Geomag_AngleG	angle between geomagnetic field and GRANDE shower axis	0 – 120 °	
Reconstruction	angle between geomagnetic field and GRANDE shower axis	65 or 71	
LOPES Comp ID	LOPES identifier	0 or 1	