

rinohype

Release 0.3.0

Brecht Machiels

December 07, 2016

1	Introduction	3
1.1	Usage Examples	3
2	Installation	5
2.1	Dependencies	5
3	Quickstart	7
3.1	Command-Line Renderer	7
3.2	Sphinx Builder	7
3.3	High-level PDF Library	8
4	Basic Document Styling	11
4.1	Style Sheets	11
4.2	Document Templates	13
5	Element Styling	17
5.1	Document Tree	17
5.2	Selectors	18
5.3	Matchers	20
5.4	Style Sheets	20
5.5	Style Logs	23
6	Document Templates	25
6.1	Subclassing a Template	25
6.2	Creating a Custom Template	26
7	Reference	27
7.1	rinoh	27
7.2	Sphinx Builder	28
7.3	Style Sheets	29
7.4	Standard Document Templates	98
8	API Documentation	105
8.1	Dimension (rinoh.dimension)	105
8.2	Document (rinoh.document)	106
8.3	Drawing Primitives (rinoh.draw)	107

8.4	Flowable (rinoh.flowable)	108
8.5	Fonts and Typefaces (rinoh.font)	110
8.6	Images and Figures (rinoh.image)	111
8.7	Index (rinoh.index)	112
8.8	Language (rinoh.language)	112
8.9	Paper sizes (rinoh.paper)	114
8.10	Paragraph (rinoh.paragraph)	115
8.11	Cross-References and Fields (rinoh.reference)	118
8.12	Structure (rinoh.structure)	118
8.13	Strings (rinoh.strings)	120
8.14	Style (rinoh.style)	120
8.15	Tables (rinoh.table)	121
8.16	Templates (rinoh.template)	121
9	Frequently Asked Questions	129
10	Release History	131
10.1	Release 0.3.0 (2016-11-23)	131
10.2	Release 0.2.1 (2016-08-18)	133
10.3	Release 0.2.0 (2016-08-10)	133
10.4	Release 0.1.3 (2015-08-04)	135
10.5	Release 0.1.2 (2015-07-31)	135
10.6	Release 0.1.1 (2015-04-12)	135
	Python Module Index	137
	Index	139

Release v0.3.0. ([Release History](#))

rinohtype is a Python library that transforms a structured document into a professionally typeset PDF guided by a document template and style sheet. It can be used to create any kind of document, but its focus is on complex documents such as technical manuals.

Included with rinohtype is the **rinoh** command line tool that renders reStructuredText and Markdown (CommonMark) documents. Support for [DITA](#) is available in the commercially supported Pro version.

rinohtype also includes support for [Sphinx](#), which helps writing large structured documents and supports a multitude of different output formats including searchable HTML. rinohtype adds support to produce PDF output.

Here is a list of rinohtype's main features:

- a powerful page layout system supporting columns, running headers/footers, floatable elements and footnotes
- figures, large tables and automatically generated table of contents
- automatic numbering and cross-referencing of sections, figures and tables
- use one of the highly configurable included document templates or create your own custom template
- the intuitive style sheets make it easy to change the style of individual document elements
- modular design allowing for multiple frontends (such as reStructuredText, Markdown, DocBook, ...) and backends (PDF, SVG, bitmap, ...)
- handles OpenType, TrueType and Type1 fonts with support for advanced typographic features such as kerning, ligatures and small capitals
- embeds PDF, PNG and JPEG images, preserving transparency and color profiles
- easy to deploy; pure-Python with few dependencies
- built on Unicode; ready for non-latin languages

rinohtype is currently in a beta phase. We are working toward a first stable release.

rinohtype is open source software licensed under the [GNU AGPL 3.0](#). Practically, this means you are free to use it in open-source software, but not in (commercial) closed-source software. For the latter, you need to obtain a commercial license (see <http://www.opqode.com/rinoh>). We are also available for consultancy projects involving rinohtype, so don't hesitate to [contact us](#).

Introduction

rinoh type was initially conceived as a modern replacement for [LaTeX](#). An important goal in the design of rinoh type is for documents to be much easier to customize than in LaTeX. By today's standards, the arcane TeX macro language upon which LaTeX is built makes customization unnecessarily difficult for one. Simply being built with Python makes rinoh type already much easier to approach than TeX. Additionally, rinoh type is built around the following core concepts to ensure customizability:

Document Templates

These determine the page layout and (for longer documents) the different parts of your document. The templates included with rinoh type are highly configurable and allow changing margins, headers, footers, chapter titles, etc. If this is not sufficient, a custom template can be created.

Style Sheets

The CSS-inspired style sheets determine the look of individual document elements. A style sheet assigns style attributes to each type of document element. For example, a paragraph's style is determined by the typeface, font weight, size and color, horizontal alignment of text etc.

Structured Input

rinoh type renders a document from a document tree that does not describe any style aspects but only semantics. The style sheet maps specific style properties to the elements in this document tree. The document tree can be automatically generated from a structured document format such as [reStructuredText](#) and [CommonMark](#) using one of the included frontends, or it can be constructed manually.

rinoh type is implemented as a Python package and doubles as a high-level PDF library. Its modular design makes it easy to to customize and extend for specific applications. Moreover, because rinoh type's source code is open, all of its internals can be inspected and even modified, making it customizable at all levels.

1.1 Usage Examples

rinoh type supports three modes of operation, which are discussed in more detail in the [Quickstart](#) guide. For each of these modes, you can choose to use one of the document templates included with rinoh type or a third-party template available from PyPI and optionally customize it to your needs. Or you can create a custom template from scratch. The same is true for the style sheet used to style the document elements.

1.1.1 Command-Line Renderer

rinoh type includes the **rinoh** command-line tool which renders structured text documents. Currently, [reStructuredText](#) and [CommonMark](#) documents are supported in the open-source version. Support for [DITA](#) is available in the commercially supported Pro version.

Rendering the reStructuredText demonstration article `demo.txt` (using the standard article template and style sheet) generates `demo.pdf`.

1.1.2 Sphinx Builder

Configuring rinohype as a builder for Sphinx allows rendering a Sphinx project to PDF without the need for a LaTeX installation. This very document you are reading was rendered using rinohype's Sphinx builder.

1.1.3 High-level PDF library

rinohype can also be used as a Python library to generate PDF documents. Just like with `rinoh` and the Sphinx builder, you can select which document template and style sheet to use.

Additionally, you need to supply a document tree. This document tree can be parsed from a structured document format such as reStructuredText by using one of the provided frontends or built manually using building blocks provided by rinohype. You can also write a frontend for a custom format such as an XML dialect.

All of these approaches allow for parts of the content to be fetched from a database or other data sources. When parsing the document tree from a structured document format, a templating engine like `Jinja2` can be used.

Installation

Rinohtype supports Python 3.3 and up. Depending on demand, it might be back-ported to Python 2.7, however¹.

Use `pip` to install the latest version of rinohtype and its dependencies:

```
pip install rinohtype
```

If you plan on using rinohtype as an alternative to LaTeX, you will want to install `Sphinx` as well:

```
pip install Sphinx
```

See *Sphinx Builder* in the *Quickstart* guide on how to render Sphinx documents with rinohtype.

2.1 Dependencies

For parsing reStructuredText documents, rinohtype depends on `docutils`. For parsing PNG images the pure-Python `PurePNG` package is required. `pip` takes care of these requirements automatically when you install rinohtype.

If you want to include images other than PDF, PNG or JPEG, you will need to install `Pillow` additionally.

¹ Be sure to contact us if you are interested in running rinohtype on Python 2.7.

Quickstart

This section gets you started quickly, discussing each of the three modes of operation introduced in *Introduction*. If you want to customize the style of the PDF document, please refer to *Basic Document Styling* which introduces style sheets and document templates.

3.1 Command-Line Renderer

Installing rinohtype places the **rino** script in the `PATH`. This can be used to render structured documents such as `demo.txt` (`reStructuredText`):

```
rino --format reStructuredText demo.txt
```

After rendering finishes, you will find `demo.pdf` alongside the input file.

rino allows specifying the document template and style sheet to use when rendering the `reStructuredText` document. See its *command-line options* for details.

Two rendering passes are required to make sure that cross-references to page numbers are correct. After a document has been rendered, rinohtype will save the page reference data to a `.rtc` file. Provided the document (or the template or style sheet) doesn't change a lot, this can prevent the need to perform a second rendering pass.

3.2 Sphinx Builder

To use rinohtype to render Sphinx documents, at a minimum you need to add `'rino.frontend.sphinx'` to the extensions list in the Sphinx project's `conf.py`.

If your Sphinx project is already configured for rendering with LaTeX, rinohtype will happily interpret `latex_documents` and other options for the LaTeX builder. Otherwise, you need to set the `rino_documents` configuration option:

```
rino_documents = [('index',          # top-level file (index.rst)
                  'target',         # output (target.pdf)
                  'Document Title', # document title
                  'John A. Uthor')] # document author
```

Other configuration variables are optional and allow configuring the style of the generated PDF document. See *Sphinx Builder* for details.

When building the documentation, select the *rino* builder by passing it to `sphinx-build -b` option:

```
sphinx-build -b rinoh . _build/rinoh
```

Just like the **rinoh** command line tool, the Sphinx builder requires two *rendering passes*.

3.3 High-level PDF Library

Note The focus of rinoh development is currently on the **rinoh** tool and Sphinx builder. Use as a Python library is possible, but documentation may be lacking. Please be patient.

The most basic way to use rinoh in an application is to hook up an included frontend, a document template and a style sheet:

```
from rinoh.frontend.rst import ReStructuredTextReader
from rinoh.templates import Article

# the parser builds a rinoh type document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# render the document to 'my_document.pdf'
document = Article(document_tree)
document.render('my_document')
```

This basic application can be customized to your specific requirements by customizing the document template, the style sheet and the way the document's content tree is built. The basics of document templates and style sheets are covered the the sections below.

The document tree returned by the `ReStructuredTextReader` in the example above can also be built manually. A `DocumentTree` is simply a list of `Flowables`, which can have child elements. These children in turn can also have children, and so on; together they form a tree.

Here is an example document tree of a short article:

```
from rinoh.document import DocumentTree
from rinoh.styleeds import *

document_tree = DocumentTree(
    [Paragraph('My Document', style='title'), # metadata!
     Section([Heading('First Section'),
               Paragraph('This is a paragraph with some '
                        + StyledText('emphasized text',
                                     style='emphasis')
                        + ' and an '
                        + InlineImage('image.pdf')),
               Section([Heading('A subsection'),
                         Paragraph('Another paragraph')
                       ])
             ]),
     Section([Heading('Second Section'),
               List([Paragraph('a list item'),
                       Paragraph('another list item')
                     ])
             ])
    ])
])
```

It is clear that this type of content is best parsed from a structured document format such as reStructured-Text or XML. Manually building a document tree is well suited for short, custom documents however.

Basic Document Styling

rinohype allows for fine-grained control over the style of its output. Most aspects of a document's style can be controlled by style sheet files and template configuration files which are being introduced in this chapter. These files are plain text files that are easy to create, read and modify.

4.1 Style Sheets

A style sheet defines the look of each element in a document. For each type of document element, the style sheet assign values to the style properties available for that element. Style sheets are stored in plain text files using the Windows INI² format with the `.rts` extension. Below is an excerpt from the *Sphinx style sheet* included with rinohype.

```
[STYLESHEET]
name=Sphinx
description=Mostly a copy of the LaTeX style included with Sphinx
pygments_style=friendly

[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
fallback_typeface=DejaVu Serif
thin_black_stroke=0.5pt, #000
blue=#20435c

[default:Paragraph]
typeface=$(serif_typeface)
font_weight=REGULAR
font_size=10pt
line_spacing=fixed(12pt, leading(0))
indent_first=0
space_above=0
space_below=0
text_align=JUSTIFY
kerning=True
ligatures=True
hyphen_lang=en_US
hyphen_chars=4

[fallback]
```

² see *Supported INI File Structure* in `configparser`

```
typeface=$(fallback_typeface)

[body]
base=default
space_above=5pt
space_below=0
text_align=justify

[emphasis]
font_slant=italic

[strong]
font_weight=BOLD

[literal emphasis]
base=emphasis
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[literal strong]
base=strong
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[quote]
font_slant=italic
```

Except for [STYLESHEET] and [VARIABLES], each configuration section in a style sheet determines the style of a particular type of document element. The `emphasis` style, for example, determines the look of emphasized text, which is displayed in an italic font. This is similar to how HTML's cascading style sheets work. In rinohtype however, document elements are identified by means of a descriptive label (such as *emphasis*) instead of a cryptic selector. rinohtype also makes use of selectors, but these are collected in a *matcher* which maps them to descriptive names to be used by many style sheets. Unless you are using rinohtype as a PDF library to create custom documents, the *default matcher* should cover your needs.

The following two subsections illustrate how to extend an existing style sheet and how to create a new, independent style sheet. For more in-depth information on style sheets, please refer to [Element Styling](#).

4.1.1 Extending an Existing Style Sheet

Starting from an existing style sheet, it is easy to make small changes to the style of individual document elements. The following style sheet file is based on the Sphinx stylesheet included with rinohtype.

```
[STYLESHEET]
name=My Style Sheet
description=Small tweaks made to the Sphinx style sheet
base=sphinx

[VARIABLES]
mono_typeface=Courier

[emphasis]
font_color=#00a

[strong]
base=DEFAULT_STYLE
font_color=#a00
```


By default, styles defined in a style sheet *extend* the corresponding style from the base style sheet. In this example, emphasized text will be set in an italic font (as configured in the [base style sheet](#)) and colored blue (#00a).

It is also possible to completely override a style definition. This can be done by setting the `base` of a style definition to `DEFAULT_STYLE` as illustrated by the *strong* style. This causes strongly emphasised text to be displayed in red (#a00) but **not** in a bold font as was defined in the [base style sheet](#) (the default for `font_weight` is *Medium*; see [TextStyle](#)). Refer to [Default Matcher](#) to find out which style attributes are accepted by each style (by following the hyperlink to the style class's documentation).

The style sheet also redefines the `mono_typeface` variable. This variable is used in the [base style sheet](#) in all style definitions where a monospaced font is desired. Redefining the variable in the derived style sheet affects all of these style definitions.

4.1.2 Starting from Scratch

If you don't specify a base style sheet in the `[STYLESHEET]` section, you create an independent style sheet. You should do this if you want to create a document style that is not based on an existing style sheet. If the style definition for a particular document element is not included in the style sheet, the default values for its style properties are used.

Note In the future, rinohtype will be able to generate an empty INI style sheet, listing all styles defined in the matcher with the supported style attributes along with the default values as comments. This generated style sheet can serve as a good starting point for developing a custom style sheet from scratch.

4.2 Document Templates

As with style sheets, you can choose to make use of a template provided by rinohtype and optionally customize it or you can create a custom template from scratch. This section discusses how you can configure an existing template. See [Document Templates](#) on how to create a custom template.

4.2.1 Configuring a Template

rinohtype provides a number of *Standard Document Templates*. These can be customized by means of a template configuration file; a plain text file in the INI² format with the `.rtt` extension. Here is an example configuration for the article template:

```
[TEMPLATE_CONFIGURATION]
name = my article configuration
template = article

parts =
    title
    ;front_matter
    contents
stylesheet = sphinx_base14
language = fr
abstract_location = title

[SectionTitles]
contents = 'Contents'

[AdmonitionTitles]
caution = 'Careful!'
```

```
warning = 'Please be warned'

[VARIABLES]
paper_size = A5

[title]
page_number_format = lowercase roman
end_at_page = left

[contents]
page_number_format = number

[title_page]
top_margin = 2cm
```

The `TEMPLATE_CONFIGURATION` sections collects global template options. Set *name* to provide a short label for your template configuration. *template* identifies the *document template* to configure.

All document templates consist of a number of document parts. The *Article* template defines three parts: *title*, *front_matter* and *contents*. The order of these parts can be changed (although that makes little sense for the article template), and individual parts can optionally be hidden by setting the *parts* configuration option. The configuration above hides the front matter part (commented out using a semicolon), for example.

The template configuration also specifies which style sheet is used for styling document elements. The `DocumentTemplate.stylesheet` option takes the name of an installed style sheet (see *rinoht --list-stylesheets*) or the filename of a stylesheet file (*.rts*).

The `language` option sets the default language for the document. It determines which language is used for standard document strings such as section and admonition titles.

The *Article* template defines two custom template options. The `abstract_location` option determines where the (optional) article abstract is placed, on the title page or in the front matter part. `table_of_contents` allows hiding the table of contents section. Empty document parts will not be included in the document. When the table of contents section is suppressed and there is no abstract in the input document or `abstract_location` is set to `title`, the front matter document part will not appear in the PDF.

The standard document strings configured by the `language` option described above can be overridden by user-defined strings in the `SectionTitles` and `AdmonitionTitles` sections of the configuration file. For example, the default title for the table of contents section (*Table of Contents*) is replaced with *Contents*. The configuration also sets custom titles for the caution and warning admonitions.

The others sections in the configuration file are the `VARIABLES` section, followed by document part and page template sections. Similar to style sheets, the variables can be referenced in the template configuration sections. Here, the `paper_size` variable is set, which is being referenced by by all page templates in *Article* (although indirectly through the page base page template).

For document part templates, `page_number_format` determines how page numbers are formatted. When a document part uses the same page number format as the preceding part, the numbering is continued.

The `DocumentPartTemplate.end_at_page` option controls at which page the document part ends. This is set to `left` for the title part in the example configuration to make the contents part start on a right page.

Each document part finds page templates by name. They will first look for specific left/right page templates by appending `_left_page` or `_right_page` to the document part name. If these page templates have not been defined in the template, it will look for the more general `<document part name>_page` template. Note that, if left and right page templates have been defined by the template

(such as the book template), the configuration will need to override these, as they will have priority over the general page template defined in the configuration.

The example configuration only adjusts the top margin for the `TitlePageTemplate`, but many more aspects of the page templates are configurable. Refer to *Standard Document Templates* for details.

4.2.2 Using a Template Configuration File

A template configuration file can be specified when rendering using the command-line **rinoht** tool by passing it to the `--template` command-line option. When using the *Sphinx Builder*, you can set the `rinoht_template` option in `conf.py`.

To render a document using this template configuration programmatically, load the template file using `TemplateConfigurationFile`:

```
from rinoht.frontend.rst import ReStructuredTextReader
from rinoht.template import TemplateConfigurationFile

# the parser builds a rinohtype document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# load the article template configuration file
config = TemplateConfigurationFile('my_article.rtt')

# render the document to 'my_document.pdf'
document = config.document(document_tree)
document.render('my_document')
```

The `TemplateConfigurationFile.document()` method creates a document instance with the template configuration applied. So if you want to render your document using a different template configuration, it suffices to load the new configuration file.

Refer to the *Article* documentation to discover all of the options accepted by it and the document part and page templates.

Element Styling

This section describes how styles defined in a style sheet are applied to document elements. Understanding how this works will help you when designing a custom style sheet.

rinohype's style sheets are heavily inspired by [CSS](#), but add some additional functionality. Similar to CSS, rinohype makes use of so-called *selectors* to select document elements in the *document tree* to style. Unlike CSS however, these selectors are not directly specified in a style sheet. Instead, all selectors are collected in a *matcher* where they are mapped to descriptive labels for the selected elements. A *style sheet* assigns style properties to these labels. Besides the usefulness of having these labels instead of the more cryptic selectors, a matcher can be reused by multiple style sheets, avoiding duplication.

Note This section currently assumes some Python or general object-oriented programming knowledge. A future update will move Python-specific details to another section, making things more accessible for non-programmers.

5.1 Document Tree

A *Flowable* is a document element that is placed on a page. It is usually a part of a document tree. Flowables at one level in a document tree are rendered one below the other.

Here is schematic representation of an example document tree:

```

|- Section
|   |- Paragraph
|   \- Paragraph
\-- Section
    |- Paragraph
    |- List
    |   |- ListItem
    |   |   |- Paragraph (item label; a number or bullet symbol)
    |   |   \- StaticGroupedFlowables (item body)
    |   |       \- Paragraph
    |   \- ListItem
    |       \- Paragraph
    |   \- StaticGroupedFlowables
    |       \- List
    |           \- ListItem
    |               \- ...
    |   \- ...
    \- Paragraph

```

This represents a document consisting of two sections. The first section contains two paragraphs. The second section contains a paragraph followed by a list and another paragraph. All of the elements in this tree are instances of *Flowable* subclasses.

Section and *List* are subclasses of *GroupedFlowables*; they group a number of flowables. In the case of *List*, these are always of the *ListItem* type. Each list item contains an item number (ordered list) or a bullet symbol (unordered list) and an item body. For simple lists, the item body is typically a single *Paragraph*. The second list item contains a nested *List*.

A *Paragraph* does not have any *Flowable* children. It is however the root node of a tree of *inline elements*. This is an example paragraph in which several text styles are combined:

```
Paragraph
|- SingleStyledText('Text with ')
|- MixedStyledText(style='emphasis')
|   |- SingleStyledText('multiple ')
|   \- MixedStyledText(style='strong')
|       |- SingleStyledText('nested ')
|       \- SingleStyledText('styles', style='small caps')
\-- SingleStyledText('.')
```

The visual representation of the words in this paragraph is determined by the applied style sheet. Read more about how this works in the next section.

Besides *SingleStyledText* and *MixedStyledText* elements (subclasses of *StyledText*), paragraphs can also contain *InlineFlowables*. Currently, the only inline flowable is *InlineImage*.

The common superclass for flowable and inline elements is *Styled*, which indicates that these elements can be styled using the style sheets.

5.2 Selectors

Selectors in rinohtype select elements of a particular type. The *class* of a document element serves as a selector for all instances of the class (and its subclasses). The *Paragraph* class is a selector that matches all paragraphs in the document, for example:

```
Paragraph
```

As with *CSS selectors*, elements can also be matched based on their context. For example, the following matches any paragraph that is a direct child of a list item or in other words, a list item label:

```
ListItem / Paragraph
```

Python's *ellipsis* can be used to match any number of levels of elements in the document tree. The following selector matches paragraphs at any level inside a table cell:

```
TableCell / ... / Paragraph
```

To help avoid duplicating selector definitions, context selectors can reference other selectors defined in the same *matcher* using *SelectorByName*:

```
SelectorByName('definition term') / ... / Paragraph
```

Selectors can select all instances of *Styled* subclasses. These include *Flowable* and *StyledText*, but also *TableSection*, *TableRow*, *Line* and *Shape*. Elements of some of the latter classes only appear as children of other flowables (such as *Table*).

Similar to a HTML element's *class* attribute, *Styled* elements can have an optional *style* attribute which can be used when constructing a selector. This one selects all styled text elements with the *emphasis* style, for example:

```
StyledText.like('emphasis')
```

The `Styled.like()` method can also match **arbitrary attributes** of elements by passing them as keyword arguments. This can be used to do more advanced things such as selecting the background objects on all odd rows of a table, limited to the cells not spanning multiple rows:

```
TableCell.like(row_index=slice(0, None, 2), rowspan=1) / TableCellBackground
```

The argument passed as *row_index* is a slice object that is used for extended indexing³. To make this work, `TableCell.row_index` is an object with a custom `__eq__()` that allows comparison to a slice.

Rinohtype borrows CSS's concept of *specificity* to determine the "winning" selector when multiple selectors match a given document element. Each part of a selector adds to the specificity of a selector. Roughly stated, the more specific selector will win. For example:

```
ListItem / Paragraph # specificity (0, 0, 0, 0, 2)
```

wins over:

```
Paragraph # specificity (0, 0, 0, 0, 1)
```

since it matches two elements instead of just one.

Specificity is represented as a 5-tuple. The last four elements represent the number of *location* (currently not used), *style*, *attribute* and *class* matches. Here are some selectors along with their specificity:

```
StyledText.like('emphasis') # specificity (0, 0, 1, 0, 1)
TableCell / ... / Paragraph # specificity (0, 0, 0, 0, 2)
TableCell.like(row_index=2, rowspan=1) # specificity (0, 0, 0, 2, 1)
```

Specificity ordering is the same as tuple ordering, so (0, 0, 1, 0, 0) wins over (0, 0, 0, 5, 0) and (0, 0, 0, 0, 3) for example. Only when the number of style matches are equal, the attributes match count is compared and so on.

In practice, the class match count is dependent on the element being matched. If the class of the element exactly matches the selector, the right-most specificity value is increased by 2. If the element's class is a subclass of the selector, it is only increased by 1.

The first element of the specificity tuple is the *priority* of the selector. For most selectors, the priority will have the default value of 0. The priority of a selector only needs to be set in some cases. For example, we want the `CodeBlock` selector to match a `CodeBlock` instance. However, because `CodeBlock` is a *Paragraph* subclass, another selector with a higher specificity will also match it:

```
CodeBlock # specificity (0, 0, 0, 0, 2)
DefinitionList / Definition / Paragraph # specificity (0, 0, 0, 0, 3)
```

To make sure the `CodeBlock` selector wins, we increase the priority of the `CodeBlock` selector by prepending it with a + sign:

```
+CodeBlock # specificity (1, 0, 0, 0, 2)
```

In general, you can use multiple + or - signs to adjust the priority:

```
++CodeBlock # specificity (2, 0, 0, 0, 2)
```

³ Indexing a list like this `lst[slice(0, None, 2)]` is equivalent to `lst[0::2]`.

```
---CodeBlock                                     # specificity (-3, 0, 0, 0, 2)
```

5.3 Matchers

At the most basic level, a *StyledMatcher* is a dictionary that maps labels to selectors:

```
matcher = StyledMatcher()
...
matcher['emphasis'] = StyledText.like('emphasis')
matcher['chapter'] = Section.like(level=1)
matcher['list item number'] = ListItem / Paragraph
matcher['nested line block'] = (GroupedFlowables.like('line block')
                               / GroupedFlowables.like('line block'))
...
```

Rinoh type currently includes one matcher which defines labels for all common elements in documents:

```
from rinoh.stylesheets import matcher
```

5.4 Style Sheets

A *StyleSheet* takes a *StyledMatcher* to provide element labels to assign style properties to:

```
styles = StyleSheet('IEEE', matcher=matcher)
...
styles['strong'] = TextStyle(font_weight=BOLD)
styles['emphasis', font_slant=ITALIC)
styles['nested line block', margin_left=0.5*CM)
...
```

Each *Styled* has a *Style* class associated with it. For *Paragraph*, this is *ParagraphStyle*. These style classes determine which style attributes are accepted for the styled element. Because the style class can automatically be determined from the selector, it is possible to simply pass the style properties to the style sheet by calling the *StyleSheet* instance as shown above.

Style sheets are usually loaded from a *.rts* file using *StyleSheetFile*. An example style sheet file is shown in *Style Sheets*.

A style sheet file contains a number of sections, denoted by a section title enclosed in square brackets. There are two special sections:

- [STYLESHEET] describes global style sheet information (see *StyleSheetFile* for details)
- [VARIABLES] collects variables that can be referenced elsewhere in the style sheet

Other sections define the style for a document elements. The section titles correspond to the labels associated with selectors in the *StyledMatcher*. Each entry in a section sets a value for a style attribute. The style for enumerated lists is defined like this, for example:

```
[enumerated list]
margin_left=8pt
space_above=5pt
space_below=5pt
ordered=true
flowable_spacing=5pt
```



```
number_format=NUMBER
label_suffix=') '
```

Since this is an enumerated list, *ordered* is set to `true`. *number_format* and *label_suffix* are set to produce list items labels of the style 1), 2), Other entries control margins and spacing. See [ListStyle](#) for the full list of accepted style attributes.

5.4.1 Base Styles

It is possible to define styles which are not linked to a selector. These can be useful to collect common attributes in a base style for a set of style definitions. For example, the Sphinx style sheet defines the *header_footer* style to serve as a base for the *header* and *footer* styles:

```
[header_footer : Paragraph]
base=default
typeface=$(sans_typeface)
font_size=10pt
font_weight=BOLD
indent_first=0pt
tab_stops=50% CENTER, 100% RIGHT

[header]
base=header_footer
padding_bottom=2pt
border_bottom=$(thin_black_stroke)
space_below=24pt

[footer]
base=header_footer
padding_top=4pt
border_top=$(thin_black_stroke)
space_above=18pt
```

Because there is no selector associated with *header_footer*, the element type needs to be specified manually. This is done by adding the name of the relevant *Styled* subclass to the section name, using a colon (:) to separate it from the style name, optionally surrounded by spaces.

5.4.2 Custom Selectors

It is also possible to define new selectors directly in a style sheet file. This allows making tweaks to an existing style sheet without having to create a new *StyledMatcher*. However, this should be used sparingly. If a great number of custom selectors are required, it is better to create a new *StyledMatcher*.

The syntax for specifying a selector for a style is similar to that when constructing selectors in a Python source code (see [Matchers](#)), but with a number of important differences. A *Styled* subclass name followed by parentheses represents a simple class selector (without context). Arguments to be passed to `Styled.like()` can be included within the parentheses.

```
[special text : StyledText('special')]
font_color=#FF00FF

[accept button : InlineImage(filename='images/ok_button.png')]
baseline=20%
```

Even if no arguments are passed to the class selector, it is important that the class name is followed by parentheses. If the parentheses are omitted, the selector is not registered with the matcher and the style can only be used as a base style for other style definitions (see [Base Styles](#)).

As in Python source code, context selectors are constructed using forward slashes (/) and the ellipsis (...). Another selector can be referenced in a context selector by enclosing its name in single or double quotes.

```
[admonition title colon : Admonition / ... / StyledText('colon')]
font_size=10pt

[chapter title : LabeledFlowable('chapter title')]
label_spacing=1cm
align_baselines=false

[chapter title number : 'chapter title' / Paragraph('number')]
font_size=96pt
text_align=right
```

5.4.3 Variables

Variables can be used for values that are used in multiple style definitions. This example declares a number of typefaces to allow easily replacing the fonts in a style sheet:

```
[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
thin_black_stroke=0.5pt, #000
blue=#20435c
```

It also defines the *thin_black_stroke* line style for use in table and frame styles, and a specific color labelled *blue*. These variables can be referenced in style definitions as follows:

```
[code block]
typeface=$(mono_typeface)
font_size=9pt
text_align=LEFT
indent_first=0
space_above=6pt
space_below=4pt
border=$(thin_black_stroke)
padding_left=5pt
padding_top=1pt
padding_bottom=3pt
```

Another stylesheet can inherit (see below) from this one and easily replace fonts in the document by overriding the variables.

5.4.4 Style Attribute Resolution

The style system makes a distinction between text (inline) elements and flowables with respect to how attribute values are resolved.

Text elements by default inherit the properties from their parent. Take for example the *emphasis* style definition from the example above. The value for style properties other than *font_slant* (which is defined in the *emphasis* style itself) will be looked up in the style definition corresponding to the parent element, which can be either another *StyledText* instance, or a *Paragraph*. If the parent element is a *StyledText* that neither defines the style attribute, lookup proceeds recursively, moving up in the document tree.

For **flowables**, there is no fall-back to the parent's style by default. A base style can be specified explicitly however. If a style attribute is not present in a particular style definition, it is looked up in the base style.

This can help avoid duplication of style information and the resulting maintenance difficulties. In the following example, the *unnumbered heading level 1* style inherits all properties from *heading level 1*, overriding only the *number_format* attribute:

```
[heading level 1]
typeface=$(sans_typeface)
font_weight=BOLD
font_size=16pt
font_color=$(blue)
line_spacing=SINGLE
space_above=18pt
space_below=12pt
number_format=NUMBER
label_suffix=' '

[unnumbered heading level 1]
base=heading level 1
number_format=None
```

When a value for a particular style attribute is set nowhere in the style definition lookup hierarchy, its default value is returned. The default values for all style properties are defined in the class definition for each of the *Style* subclasses.

For text elements, it is possible to override the default behavior of falling back to the parent's style. Setting *base* to the label of a *TextStyle* or *ParagraphStyle* prevents fallback to the parent element's style.

For flowables, *base* can be set to `PARENT_STYLE` to enable fallback, but this requires that the current element type is the same or a subclass of the parent type, so it cannot be used for all styles.

5.5 Style Logs

When rendering a document, rinohtype will create a style log. It is written to disk using the same base name as the output file, but with a *.stylelog* extension. The information logged in the style log is invaluable when debugging your style sheet. It tells you which style maps to each element in the document.

The style log lists the document elements (as a tree) that have been rendered to each page, and for each element all matching styles are listed together with their specificity. No styles are listed when there aren't any selectors matching an element and the default values are used. The winning style is indicated with a `>` symbol. Styles that are not defined in the style sheet or its base(s) are marked with an `x`. If none of the styles are defined, rinohtype falls back to using the default style.

Here is an example excerpt from a style log:

```
...
Paragraph('January 03, 2012', style='title page date')
  > (0,0,1,0,2) title page date
    (0,0,0,0,2) body
  SingleStyledText('January 03, 2012')
----- page 3 -----
#### ChainedContainer('column1')
DocumentTree()
  Section(id='structural-elements') demo.txt:62 <section>
    > (0,0,0,1,2) chapter
      Heading('1 Structural Elements') demo.txt:62 <title>
        > (0,0,0,1,2) heading level 1
          (0,0,0,0,2) other heading levels
        MixedStyledText('1 Structural Elements')
        SingleStyledText('1')
```

```

        MixedStyledText(' ')
        SingleStyledText(' ')
        SingleStyledText('Structural Elements')
Paragraph('A paragraph.')                                demo.txt:64 <paragraph>
  > (0,0,0,0,2) body
    MixedStyledText('A paragraph.')
    SingleStyledText('A paragraph.')
List(style='bulleted')                                    demo.txt:66 <bullet_list>
  > (0,0,1,0,2) bulleted list
    ListItem()
      x (0,0,1,0,4) bulleted list item
      > fallback to default style
    ListItemLabel('.')
      > (0,0,1,0,6) bulleted list item label
      (0,0,0,0,2) list item label
    MixedStyledText('.')
      SingleStyledText('')
      SingleStyledText('.')
StaticGroupedFlowables()                                demo.txt:66 <list_item>
  > (0,0,0,0,3) list item body
...

```

Document Templates

When it is not possible to achieve a particular document style using one of the existing templates and a custom template configuration, you can create a new template. A new template is programmed in Python and therefor it is required that you are familiar with Python, or at least with general object-oriented programming.

6.1 Subclassing a Template

If you need to customize a template beyond what is possible by configuration, you can subclass a template class and override document part and page templates with custom templates. The following example subclasses *Article*.

```
from rinoh.attribute import OverrideDefault
from rinoh.template import DocumentPartTemplate, PageTemplate
from rinoh.templates import Article

class BibliographyPartTemplate(DocumentPartTemplate):
    ...

class MyTitlePageTemplate(PageTemplate):
    ...

class MyArticle(Article):
    parts = OverrideDefault(['title', 'contents', 'bibliography'])

    # default document part templates
    bibliography = BibliographyPartTemplate()

    # default page templates
    title_page = MyTitlePageTemplate(base='page')
    bibliography_page = PageTemplate(base='page')
```

MyArticle extends the *Article* template, adding the extra bibliography document part, along with the page template *bibliography_page*. The new document part is included in *parts*, while also leaving out *front_matter* by default. Finally, the template also replaces the title page template with a custom one.

6.2 Creating a Custom Template

A new template can be created from scratch by subclassing `DocumentTemplate`, defining all document parts, their templates and page templates.

The `Article` and `Book` templates are examples of templates that inherit directly from `DocumentTemplate`. We will briefly discuss the article template. The `Article` template overrides the default style sheet and defines the two custom template attributes discussed in *Configuring a Template*. The document parts `title`, `front_matter` and `contents` are listed the in `parts` attribute and part templates for each are provided along with page templates:

```
class Article(DocumentTemplate):
    stylesheet = OverrideDefault(sphinx_article)
    table_of_contents = Attribute(Bool, True,
                                  'Show or hide the table of contents')
    abstract_location = Attribute(AbstractLocation, 'front matter',
                                  'Where to place the abstract')

    parts = OverrideDefault(['title', 'front_matter', 'contents'])

    # default document part templates
    title = TitlePartTemplate()
    front_matter = ArticleFrontMatter()
    contents = ContentsPartTemplate()

    # default page templates
    page = PageTemplate(page_size=Var('paper_size'),
                        chapter_title_flowables=None)
    title_page = TitlePageTemplate(base='page',
                                    top_margin=8*CM)
    front_matter_page = PageTemplate(base='page')
    contents_page = PageTemplate(base='page')
```

The custom `ArticleFrontMatter` template reads the values for the two custom template attributes defined in `Article` to determine which flowables are included in the front matter:

```
class ArticleFrontMatter(DocumentPartTemplate):
    toc_section = TableOfContentsSection()

    def _flowables(self, document):
        meta = document.metadata
        abstract_loc = document.get_option('abstract_location')
        if ('abstract' in meta
            and abstract_loc == AbstractLocation.FRONT_MATTER):
            yield meta['abstract']
        if document.get_option('table_of_contents'):
            yield self.toc_section
```

Have a look at the *Book template source code* for an example of a slightly more complex template that defines separate templates for left and right pages.

Reference

7.1 rinoh

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME OR FILENAME]
             [-s NAME OR FILENAME] [-p PAPER] [--list-templates]
             [--list-stylesheets] [--list-fonts [FILENAME]] [--list-formats]
             [--list-options FRONTEND] [--version]
             [input]
```

input

the document to render

-h, --help

show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

--list-templates

list the installed document templates and exit

--list-stylesheets

list the installed style sheets and exit

--list-fonts <filename>
list the installed fonts or, if FILENAME is given, write a PDF file displaying all the fonts

--list-formats
list the supported input formats and exit

--list-options <frontend>
list the options supported by the given frontend and exit

--version
show program's version number and exit

7.2 Sphinx Builder

The `rinoh.frontend.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name `rinoh`. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required:

rinoh_documents

Determines how to group the document tree into PDF output files. Its format is identical to that of `latex_documents`, with the exception that `targetname` should specify the name of the PDF file without the extension. If it is not specified, the value of `latex_documents` is used instead (with the `.tex` extension stripped from the `targetname`).

rinoh_template

Determines the template used to render the document. It takes:

- the filename of a template configuration file,
- a `TemplateConfiguration` instance,
- the name of an installed template (see `rinoh --list-templates`)
- a `DocumentTemplate` subclass

The default is 'book', which resolves to the `Book` template.

rinoh_stylesheet

If `rinoh_template_configuration` does not specify a style sheet, this variable specifies the style sheet used to style the document elements. It can be a `StyleSheet` instance or a string identifying an installed style sheet. Default: the default style sheet for the chosen document template.

If `pygments_style` is specified, it overrides the code highlighting style for the specified or default style sheet.

rinoh_paper_size

This overrides paper size defined in the template or template configuration (`rinoh_template`). This should be a `Paper` instance. A set of predefined paper sizes can be found in the `rinoh.paper` module. If not specified, the value of the 'papersize' entry in `latex_elements` is converted to the equivalent `Paper`. If this is not specified either, the value specified for `latex_paper_size` is used.

Note Since the interactions between `rinoh_template`, `rinoh_paper_size`, `rinoh_stylesheet` and `pygments_style` are fairly complex, this behavior may be changed (simplified) in the future.

rinoh_logo

Path (relative to the configuration directory) to an image file to use at the top of the title page. If not specified, the `latex_logo` value is used.

rinoh_domain_indices

Controls the generation of domain-specific indices. Identical to `latex_domain_indices`, which is used when `rinoh_domain_indices` is not specified.

7.3 Style Sheets

7.3.1 Included Style Sheets

These style sheets are included with rinohtype:

rinoh.stylesheets.sphinx

Mostly a copy of the LaTeX style included with Sphinx
Entry point name: `sphinx`

rinoh.stylesheets.sphinx_article

The Sphinx stylesheet adjusted for the article template
Entry point name: `sphinx_article`

rinoh.stylesheets.sphinx_base14

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)
Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinoh --list-stylesheets`.

7.3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

rinoh.stylesheets.matcher

The default matcher defines the following styles

- title page subtitle: *ParagraphStyle*
- man page: *TextStyle*
- literal strong: *TextStyle*
- italic: *TextStyle*
- MIME type: *TextStyle*
- title page author: *ParagraphStyle*
- file path: *TextStyle*
- title page date: *ParagraphStyle*
- mail header: *TextStyle*
- monospaced: *TextStyle*
- bold: *TextStyle*
- command: *TextStyle*

- window title: *TextStyle*
- title page logo: *HorizontallyAlignedFlowableStyle*
- emphasis: *TextStyle*
- literal emphasis: *TextStyle*
- newsgroup: *TextStyle*
- menu cascade: *TextStyle*
- regular expression: *TextStyle*
- title page title: *ParagraphStyle*
- title reference: *TextStyle*
- UI control: *TextStyle*
- UI control accelerator: *TextStyle*
- make variable: *TextStyle*
- front matter section title: *ParagraphStyle*
- code with variable: *TextStyle*
- body matter chapter label: *ParagraphStyle*
- body matter chapter number: *TextStyle*
- title page extra: *ParagraphStyle*
- strong: *TextStyle*
- program: *TextStyle*
- quote: *TextStyle*
- keystrokes: *TextStyle*
- body matter chapter title: *ParagraphStyle*
- fallback: *TextStyle*
- draft comment: *TextStyle*
- error: *TextStyle*
- linked reference: *TextStyle*
- unlinked reference: *TextStyle*
- internal hyperlink: *TextStyle*
- external hyperlink: *TextStyle*
- broken hyperlink: *TextStyle*
- body: *ParagraphStyle*
- code block: *CodeBlockStyle*
- attribution: *ParagraphStyle*
- centered: *ParagraphStyle*
- block quote: *GroupedFlowablesStyle*
- line block: *GroupedFlowablesStyle*
- nested line block: *GroupedFlowablesStyle*
- line block line: *ParagraphStyle*

- title: *ParagraphStyle*
- subtitle: *ParagraphStyle*
- date: *ParagraphStyle*
- author: *ParagraphStyle*
- affiliation: *ParagraphStyle*
- chapter: *SectionStyle*
- heading level 1: *HeadingStyle*
- unnumbered heading level 1: *HeadingStyle*
- heading level 2: *HeadingStyle*
- unnumbered heading level 2: *HeadingStyle*
- heading level 3: *HeadingStyle*
- unnumbered heading level 3: *HeadingStyle*
- heading level 4: *HeadingStyle*
- unnumbered heading level 4: *HeadingStyle*
- heading level 5: *HeadingStyle*
- unnumbered heading level 5: *HeadingStyle*
- other heading levels: *HeadingStyle*
- appendix: *SectionStyle*
- appendix heading level 1: *HeadingStyle*
- appendix heading level 2: *HeadingStyle*
- appendix heading level 3: *HeadingStyle*
- appendix heading level 4: *HeadingStyle*
- appendix heading level 5: *HeadingStyle*
- prerequisites: *GroupedFlowablesStyle*
- prerequisites title: *ParagraphStyle*
- post requirement: *GroupedFlowablesStyle*
- abstract: *GroupedFlowablesStyle*
- abstract paragraph: *ParagraphStyle*
- example: *GroupedFlowablesStyle*
- example title: *ParagraphStyle*
- topic: *GroupedFlowablesStyle*
- topic title: *ParagraphStyle*
- rubric: *ParagraphStyle*
- sidebar: *GroupedFlowablesStyle*
- sidebar title: *ParagraphStyle*
- sidebar subtitle: *ParagraphStyle*
- list item label: *ListItemLabelStyle*
- enumerated list: *ListStyle*

- enumerated list item: *LabeledFlowableStyle*
- enumerated list item label: *ListItemLabelStyle*
- nested enumerated list: *ListStyle*
- (table) enumerated list: *ListStyle*
- (table) enumerated list item: *LabeledFlowableStyle*
- (table) enumerated list item label: *ListItemLabelStyle*
- bulleted list: *ListStyle*
- compact bulleted list: *ListStyle*
- bulleted list item: *LabeledFlowableStyle*
- bulleted list item label: *ListItemLabelStyle*
- nested bulleted list: *ListStyle*
- (table) bulleted list: *ListStyle*
- (table) bulleted list item: *LabeledFlowableStyle*
- (table) bulleted list item label: *ListItemLabelStyle*
- steps list: *ListStyle*
- steps list title: *ParagraphStyle*
- steps list item: *LabeledFlowableStyle*
- steps list item label: *ListItemLabelStyle*
- choices list: *ListStyle*
- choices list item: *LabeledFlowableStyle*
- choices list item label: *ListItemLabelStyle*
- list item body: *GroupedFlowablesStyle*
- list item paragraph: *ParagraphStyle*
- definition list: *GroupedFlowablesStyle*
- definition list item: *LabeledFlowableStyle*
- definition term: *GroupedFlowablesStyle*
- definition term paragraph: *ParagraphStyle*
- definition term classifier: *TextStyle*
- definition: *GroupedFlowablesStyle*
- definition paragraph: *ParagraphStyle*
- related links: *GroupedFlowablesStyle*
- related links section title: *ParagraphStyle*
- related links list: *ListStyle*
- related links list item: *LabeledFlowableStyle*
- related links list item label: *ListItemLabelStyle*
- related links list item paragraph: *ReferencingParagraphStyle*
- related link title reference: *TextStyle*
- related link page reference: *TextStyle*

- related link number reference: *TextStyle*
- related link reference: *TextStyle*
- versionmodified: *TextStyle*
- object description: *LabeledFlowableStyle*
- object signatures: *GroupedFlowablesStyle*
- object signature: *ParagraphStyle*
- object name: *TextStyle*
- additional name part: *TextStyle*
- object type: *TextStyle*
- object returns: *TextStyle*
- object parentheses: *TextStyle*
- object parameter list: *TextStyle*
- object parameter: *TextStyle*
- object parameter (no emphasis): *TextStyle*
- object brackets: *TextStyle*
- object optional parameter: *TextStyle*
- object annotation: *TextStyle*
- object description content: *GroupedFlowablesStyle*
- object description content paragraph: *ParagraphStyle*
- production list: *GroupedFlowablesStyle*
- production: *LabeledFlowableStyle*
- token name: *ParagraphStyle*
- token definition: *ParagraphStyle*
- field list: *GroupedFlowablesStyle*
- field list item: *LabeledFlowableStyle*
- field name: *ParagraphStyle*
- option list: *GroupedFlowablesStyle*
- option list item: *LabeledFlowableStyle*
- option: *ParagraphStyle*
- option string: *TextStyle*
- option argument: *TextStyle*
- admonition: *AdmonitionStyle*
- admonition title: *ParagraphStyle*
- admonition inline title: *TextStyle*
- attention admonition: *AdmonitionStyle*
- attention admonition title: *ParagraphStyle*
- attention admonition inline title: *TextStyle*
- caution admonition: *AdmonitionStyle*

- caution admonition title: *ParagraphStyle*
- caution admonition inline title: *TextStyle*
- danger admonition: *AdmonitionStyle*
- danger admonition title: *ParagraphStyle*
- danger admonition inline title: *TextStyle*
- error admonition: *AdmonitionStyle*
- error admonition title: *ParagraphStyle*
- error admonition inline title: *TextStyle*
- hint admonition: *AdmonitionStyle*
- hint admonition title: *ParagraphStyle*
- hint admonition inline title: *TextStyle*
- important admonition: *AdmonitionStyle*
- important admonition title: *ParagraphStyle*
- important admonition inline title: *TextStyle*
- note admonition: *AdmonitionStyle*
- note admonition title: *ParagraphStyle*
- note admonition inline title: *TextStyle*
- tip admonition: *AdmonitionStyle*
- tip admonition title: *ParagraphStyle*
- tip admonition inline title: *TextStyle*
- warning admonition: *AdmonitionStyle*
- warning admonition title: *ParagraphStyle*
- warning admonition inline title: *TextStyle*
- seealso admonition: *AdmonitionStyle*
- seealso admonition title: *ParagraphStyle*
- seealso admonition inline title: *TextStyle*
- header: *ParagraphStyle*
- footer: *ParagraphStyle*
- footnote marker: *NoteMarkerStyle*
- citation marker: *NoteMarkerStyle*
- footnote paragraph: *ParagraphStyle*
- footnote label: *ParagraphStyle*
- figure: *FigureStyle*
- image: *HorizontallyAlignedFlowableStyle*
- inline image: *InlineFlowableStyle*
- caption: *CaptionStyle*
- figure legend: *GroupedFlowablesStyle*
- figure legend paragraph: *ParagraphStyle*

- table of contents section: *SectionStyle*
- table of contents title: *HeadingStyle*
- table of contents: *TableOfContentsStyle*
- toc level 1: *TableOfContentsEntryStyle*
- toc level 2: *TableOfContentsEntryStyle*
- toc level 3: *TableOfContentsEntryStyle*
- L3 toc level 3: *TableOfContentsEntryStyle*
- toc linked reference: *TextStyle*
- table: *TableStyle*
- table with caption: *GroupedFlowablesStyle*
- choices table: *TableStyle*
- table cell: *TableCellStyle*
- table body cell background on even row: *TableCellBackgroundStyle*
- table body cell background on odd row: *TableCellBackgroundStyle*
- table body cell paragraph: *ParagraphStyle*
- table first column paragraph: *ParagraphStyle*
- table body cell list item number: *ParagraphStyle*
- table head cell: *TableCellStyle*
- table head cell paragraph: *ParagraphStyle*
- table cell left border: *TableCellBorderStyle*
- table cell top border: *TableCellBorderStyle*
- table cell right border: *TableCellBorderStyle*
- table cell bottom border: *TableCellBorderStyle*
- table top border: *TableCellBorderStyle*
- table bottom border: *TableCellBorderStyle*
- table left border: *TableCellBorderStyle*
- table right border: *TableCellBorderStyle*
- table head cell left border: *TableCellBorderStyle*
- table head cell right border: *TableCellBorderStyle*
- table head bottom border: *TableCellBorderStyle*
- table head left border: *TableCellBorderStyle*
- table head right border: *TableCellBorderStyle*
- table body top border: *TableCellBorderStyle*
- table body left border: *TableCellBorderStyle*
- table body right border: *TableCellBorderStyle*
- horizontal rule: *HorizontalRuleStyle*
- index: *IndexStyle*
- index section label: *ParagraphStyle*

- level 1 index entry: *ParagraphStyle*
- level 2 index entry: *ParagraphStyle*
- level 3 index entry: *ParagraphStyle*
- level 4 index entry: *ParagraphStyle*
- domain index entry name: *TextStyle*

7.3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

<i>draw.LineStyle</i>	Style class for <i>Line</i>
<i>draw.ShapeStyle</i>	Style class for <i>Shape</i>
<i>flowable.FlowableStyle</i>	Style class for <i>Flowable</i>
<i>flowable.LabeledFlowableStyle</i>	Style class for <i>LabeledFlowable</i>
<i>flowable.GroupedFlowablesStyle</i>	Style class for <i>GroupedFlowables</i>
<i>flowable.HorizontallyAlignedFlowableStyle</i>	Style class for <i>HorizontallyAlignedFlowable</i>
<i>flowable.FloatStyle</i>	Style class for <i>Float</i>
<i>image.CaptionStyle</i>	Style class for <i>Caption</i>
<i>image.FigureStyle</i>	Style class for <i>Figure</i>
<i>index.IndexStyle</i>	Style class for <i>Index</i>
<i>paragraph.ParagraphStyle</i>	Style class for <i>Paragraph</i>
<i>highlight.CodeBlockStyle</i>	Style class for <i>CodeBlock</i>
<i>text.TextStyle</i>	Style class for <i>Text</i>
<i>inline.InlineFlowableStyle</i>	Style class for <i>InlineFlowable</i>
<i>reference.ReferencingParagraphStyle</i>	Style class for <i>ReferencingParagraph</i>
<i>reference.NoteMarkerStyle</i>	Style class for <i>NoteMarker</i>
<i>structure.SectionStyle</i>	Style class for <i>Section</i>
<i>structure.HeadingStyle</i>	Style class for <i>Heading</i>
<i>structure.ListStyle</i>	Style class for <i>List</i>
<i>structure.ListItemLabelStyle</i>	Style class for <i>ListItemLabel</i>
<i>structure.TableOfContentsStyle</i>	Style class for <i>TableOfContents</i>
<i>structure.TableOfContentsEntryStyle</i>	Style class for <i>TableOfContentsEntry</i>
<i>structure.AdmonitionStyle</i>	Style class for <i>Admonition</i>
<i>structure.HorizontalRuleStyle</i>	Style class for <i>HorizontalRule</i>
<i>table.TableStyle</i>	Style class for <i>Table</i>
<i>table.TableCellStyle</i>	Style class for <i>TableCell</i>
<i>table.TableCellBorderStyle</i>	Style class for <i>TableCellBorder</i>
<i>table.TableCellBackgroundStyle</i>	Style class for <i>TableCellBackground</i>

LineStyle

```
class rinoh.draw.LineStyle ( base=None, **attributes )
    Style class for Line
```


stroke*Stroke* -- Width and color used to draw the lineAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: 1pt, #000

ShapeStyle**class** rinoh.draw.**ShapeStyle** (*base=None, **attributes*)Style class for *Shape***fill_color**

Color -- Color to fill the shape

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #e5e5e5

stroke*Stroke* -- (*LineStyle*) Width and color used to draw the lineAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: 1pt, #000

FlowableStyle**class** rinoh.flowable.**FlowableStyle** (*base=None, **attributes*)Style class for *Flowable***space_above***Dimension* -- Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below*Dimension* -- Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left*Dimension* -- Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right*Dimension* -- Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left*Dimension* -- Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right*Dimension* -- Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for *LabeledFlowable*

label_min_width

Dimension -- Minimum label width

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 12pt

label_max_width

Dimension -- Maximum label width

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 80pt

label_spacing

Dimension -- Spacing between a label and the labeled flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3pt

align_baselines

Bool -- Line up the baselines of the label and the labeled flowable

Accepts: true or false

Default: true

wrap_label

Bool -- Wrap the label at *label_max_width*

Accepts: true or false

Default: false

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

GroupedFlowablesStyle

```
class rinohtype.flowable.GroupedFlowablesStyle ( base=None, **attributes )
```

Style class for *GroupedFlowables*

title*StyledText* -- Title to precede the flowables

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing*Dimension* -- Spacing between flowables

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_above*Dimension* -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below*Dimension* -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left*Dimension* -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right*Dimension* -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left*Dimension* -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right*Dimension* -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top*Dimension* -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom*Dimension* -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
 Accepts: `true` or `false`
 Default: `false`

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: `none`

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: `none`

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: `none`

border_top

Stroke -- (*FlowableStyle*) Border above the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: `none`

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: `none`

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
 Default: `none`

HorizontallyAlignedFlowableStyle

class `rinohtype.flowable.HorizontallyAlignedFlowableStyle` (*base=None*, ***attributes*)

Style class for *HorizontallyAlignedFlowable*

width

Dimension -- The width of the flowable
 Accepts: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/4`)
 Default: `none`

horizontal_align

HorizontalAlignment -- Horizontal alignment of the flowable
 Accepts: `left`, `right`, `center`
 Default: `left`

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

FloatStyle

class rinoh.flowable.**FloatStyle** (*base=None, **attributes*)

Style class for *Float*

float

Bool -- Float the flowable to the top or bottom of the page
 Accepts: true or false
 Default: false

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false
 Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

CaptionStyle

`class rinoh.image.CaptionStyle (base=None, **attributes)`

Style class for Caption

numbering_level

Integer -- At which section level to restart numbering
 Accepts: a natural number (positive integer)
 Default: 1

number_separator

StyledText -- Characters inserted between the section number and the caption number
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: ' . '

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text
 Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins
 Accepts: left, right, center, justify
 Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions
 Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in
 Accepts: the name of a typeface. See *rinoh --list-fonts* for a list of the available typefaces.
 Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height
 Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
 Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font
 Accepts: upright, oblique, italic
 Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters
 Accepts: normal, condensed, extended
 Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
 Accepts: normal, small capital, oldstyle figures
 Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
 Accepts: normal, superscript, subscript
 Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
 Accepts: true or false
 Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
 Accepts: true or false
 Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

number_format

NumberFormat -- (*NumberStyle*) How numbers are formatted
 Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix

StyledText -- (*LabelStyle*) Text to prepend to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix

StyledText -- (*LabelStyle*) Text to append to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label

Bool -- (*LabelStyle*) Use a custom label if specified
 Accepts: true or false
 Default: false

FigureStyle

```
class rinoh.image.FigureStyle ( base=None, **attributes )
    Style class for Figure
```

float

Bool -- (*FloatStyle*) Float the flowable to the top or bottom of the page
Accepts: true or false
Default: false

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
Accepts: true or false
Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or ") , optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

IndexStyle

class rinoh.index.**IndexStyle** (*base=None, **attributes*)

Style class for Index

initials

Bool -- Group index entries based on their first letter
 Accepts: true or false
 Default: true

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

ParagraphStyle

```
class rinoh.paragraph.ParagraphStyle ( base=None, **attributes )
```

Style class for *Paragraph*

indent_first

Dimension -- Indentation of the first line of text

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing

LineSpacing -- Spacing between the baselines of two successive lines of text

Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

TextAlign -- Alignment of text to the margins

Accepts: left, right, center, justify

Default: justify

tab_stops

TabStopList -- List of tab positions

Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.

Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height
Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font
Accepts: upright, oblique, italic
Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters
Accepts: normal, condensed, extended
Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font
Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
Accepts: normal, small capital, oldstyle figures
Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
Accepts: normal, superscript, subscript
Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
Accepts: true or false
Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
Accepts: true or false
Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
Accepts: true or false
Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

CodeBlockStyle

class rinoh.highlight.**CodeBlockStyle** (*base=None, **attributes*)

Style class for CodeBlock

hyphenate

Bool -- Overrides the default set in *TextStyle*
 Accepts: true or false
 Default: false

ligatures

Bool -- Overrides the default set in *TextStyle*
 Accepts: true or false
 Default: false

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text
 Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins
 Accepts: left, right, center, justify
 Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions
 Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.

Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black

Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font

Accepts: upright, oblique, italic

Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters

Accepts: normal, condensed, extended

Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
 Accepts: normal, small capital, oldstyle figures
 Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
 Accepts: normal, superscript, subscript
 Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

TextStyle

class rinoh.text.**TextStyle** (*base=None, **attributes*)

Style class for Text

typeface

Typeface -- Typeface to set the text in
 Accepts: the name of a typeface. See *rinoh --list-fonts* for a list of the available typefaces.
 Default: Times

font_weight

FontWeight -- Thickness of character outlines relative to their height
 Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
 Default: medium

font_slant

FontSlant -- Slope style of the font
 Accepts: upright, oblique, italic
 Default: upright

font_width

FontWidth -- Stretch of the characters
 Accepts: normal, condensed, extended
 Default: normal

font_size

Dimension -- Height of characters

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color

Color -- Color of the font

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

FontVariant -- Variant of the font

Accepts: normal, small capital, oldstyle figures

Default: normal

position

TextPosition -- Vertical text position

Accepts: normal, superscript, subscript

Default: normal

kerning

Bool -- Improve inter-letter spacing

Accepts: true or false

Default: true

ligatures

Bool -- Run letters together where possible

Accepts: true or false

Default: true

hyphenate

Bool -- Allow words to be broken over two lines

Accepts: true or false

Default: true

hyphen_chars

Integer -- Minimum number of characters in a hyphenated part of a word

Accepts: a natural number (positive integer)

Default: 2

hyphen_lang

Locale -- Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts: locale identifier in the <language ID>_<region ID> format

Default: en_US

InlineFlowableStyle

class rinoh.inline.InlineFlowableStyle (base=None, **attributes)

Style class for *InlineFlowable*

baseline

Dimension -- The location of the flowable's baseline relative to the bottom edge

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
 Accepts: true or false
 Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

ReferencingParagraphStyle

class rinoh.reference.**ReferencingParagraphStyle** (*base=None, **attributes*)

Style class for ReferencingParagraph

text

ReferenceText -- The text content of this paragraph

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '{TITLE}'

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text

Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins

Accepts: left, right, center, justify
Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions

Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.

Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black

Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font

Accepts: upright, oblique, italic

Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters

Accepts: normal, condensed, extended

Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font

Accepts: normal, small capital, oldstyle figures

Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position

Accepts: normal, superscript, subscript

Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing

Accepts: true or false

Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible

Accepts: true or false

Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines

Accepts: true or false

Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word

Accepts: a natural number (positive integer)

Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts: locale identifier in the <language ID>_<region ID> format

Default: en_US

NoteMarkerStyle

```
class rinohtype.reference.NoteMarkerStyle ( base=None, **attributes )
```

Style class for NoteMarker

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See `rinohtype --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font
Accepts: upright, oblique, italic
Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters
Accepts: normal, condensed, extended
Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font
Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
Accepts: normal, small capital, oldstyle figures
Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
Accepts: normal, superscript, subscript
Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
Accepts: true or false
Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
Accepts: true or false
Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
Accepts: true or false
Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
Accepts: a natural number (positive integer)
Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

number_format

NumberFormat -- (*NumberStyle*) How numbers are formatted
 Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix

StyledText -- (*LabelStyle*) Text to prepend to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix

StyledText -- (*LabelStyle*) Text to append to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label

Bool -- (*LabelStyle*) Use a custom label if specified
 Accepts: true or false
 Default: false

SectionStyle

class rinoh.structure.**SectionStyle** (base=None, **attributes)

Style class for *Section*

show_in_toc

Bool -- List this section in the table of contents
 Accepts: true or false
 Default: true

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right*Stroke* -- (*FlowableStyle*) Border right of the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top*Stroke* -- (*FlowableStyle*) Border above the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom*Stroke* -- (*FlowableStyle*) Border below the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color*Color* -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break*Break* -- (*PageBreakStyle*) Type of page break to insert before rendering this flowable

Accepts: none, any, left, right

Default: None

space_above*Dimension* -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below*Dimension* -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left*Dimension* -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right*Dimension* -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left*Dimension* -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right*Dimension* -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

HeadingStyle

```
class rinoh.structure.HeadingStyle ( base=None, **attributes )
```

Style class for *Heading*

number_separator

StyledText -- Characters inserted between the number label of the parent section and this section. If None, only show this section's number label.

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

keep_with_next

Bool -- Overrides the default set in *FlowableStyle*

Accepts: true or false

Default: true

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text

Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins

Accepts: left, right, center, justify

Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions

Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (*TabAlign*) and fill string (string enclosed in quotes) are optional.

Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in
 Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.
 Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height
 Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
 Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font
 Accepts: upright, oblique, italic
 Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters
 Accepts: normal, condensed, extended
 Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
 Accepts: normal, small capital, oldstyle figures
 Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
 Accepts: normal, superscript, subscript
 Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
 Accepts: true or false
 Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
 Accepts: true or false
 Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

number_format

NumberFormat -- (*NumberStyle*) How numbers are formatted
 Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix

StyledText -- (*LabelStyle*) Text to prepend to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix

StyledText -- (*LabelStyle*) Text to append to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label

Bool -- (*LabelStyle*) Use a custom label if specified
 Accepts: true or false
 Default: false

ListStyle

class rinoh.structure.**ListStyle** (base=None, **attributes)
 Style class for *List*

ordered

Bool -- This list is ordered or unordered
 Accepts: true or false
 Default: false

bullet

StyledText -- Bullet to use in unordered lists
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '•'

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
 Accepts: true or false
 Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

number_format

NumberFormat -- (*NumberStyle*) How numbers are formatted
 Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix

StyledText -- (*LabelStyle*) Text to prepend to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix

StyledText -- (*LabelStyle*) Text to append to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label

Bool -- (*LabelStyle*) Use a custom label if specified
 Accepts: true or false
 Default: false

ListItemLabelStyle

class rinoh.structure.**ListItemLabelStyle** (*base=None*, ***attributes*)

Style class for ListItemLabel

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text
 Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins
 Accepts: left, right, center, justify
 Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions
 Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (*TabAlign*) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.

Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black

Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font

Accepts: upright, oblique, italic

Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters

Accepts: normal, condensed, extended

Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font

Accepts: normal, small capital, oldstyle figures

Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position

Accepts: normal, superscript, subscript

Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing

Accepts: true or false

Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
 Accepts: true or false
 Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

label_prefix

StyledText -- (*LabelStyle*) Text to prepend to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix

StyledText -- (*LabelStyle*) Text to append to the label
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label

Bool -- (*LabelStyle*) Use a custom label if specified
 Accepts: true or false
 Default: false

TableOfContentsStyle

class rinoh.structure.**TableOfContentsStyle** (*base=None, **attributes*)

Style class for *TableOfContents*

depth

Integer -- The number of section levels to include in the table of contents
 Accepts: a natural number (positive integer)
 Default: 3

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding
Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
Accepts: true or false
Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of text

Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins

Accepts: left, right, center, justify
Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions

Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (*TabAlign*) and fill string (string enclosed in quotes) are optional.

Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page
 Accepts: true or false
 Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

typeface

Typeface -- (*TextStyle*) Typeface to set the text in

Accepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.
Default: Times

font_weight

FontWeight -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black
Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font

Accepts: upright, oblique, italic
Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters

Accepts: normal, condensed, extended
Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
 Accepts: normal, small capital, oldstyle figures
 Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
 Accepts: normal, superscript, subscript
 Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
 Accepts: true or false
 Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
 Accepts: true or false
 Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

TableOfContentsEntryStyle

class rinoh.structure.**TableOfContentsEntryStyle** (*base=None, **attributes*)

Style class for *TableOfContentsEntry*

text

ReferenceText -- Overrides the default set in *ReferencingParagraphStyle*
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: '{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}'

indent_first

Dimension -- (*ParagraphStyle*) Indentation of the first line of text
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0pt

line_spacing

LineSpacing -- (*ParagraphStyle*) Spacing between the baselines of two successive lines of

text

Accepts: a *predefined line spacing* type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

TextAlign -- (*ParagraphStyle*) Alignment of text to the margins

Accepts: left, right, center, justify

Default: justify

tab_stops

TabStopList -- (*ParagraphStyle*) List of tab positions

Accepts: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where <position> (*Dimension*) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom*Dimension* -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_nextBool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border*Stroke* -- (*FlowableStyle*) Border surrounding the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left*Stroke* -- (*FlowableStyle*) Border left of the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right*Stroke* -- (*FlowableStyle*) Border right of the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top*Stroke* -- (*FlowableStyle*) Border above the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom*Stroke* -- (*FlowableStyle*) Border below the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color*Color* -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

typeface*Typeface* -- (*TextStyle*) Typeface to set the text inAccepts: the name of a typeface. See *rinohtype --list-fonts* for a list of the available typefaces.

Default: Times

font_weight*FontWeight* -- (*TextStyle*) Thickness of character outlines relative to their height

Accepts: hairline, thin, ultra-light, extra-light, light, book, regular, medium, demi-bold, bold, extra-bold, heavy, black, extra-black, ultra-black

Default: medium

font_slant

FontSlant -- (*TextStyle*) Slope style of the font
 Accepts: upright, oblique, italic
 Default: upright

font_width

FontWidth -- (*TextStyle*) Stretch of the characters
 Accepts: normal, condensed, extended
 Default: normal

font_size

Dimension -- (*TextStyle*) Height of characters
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 10pt

font_color

Color -- (*TextStyle*) Color of the font
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant

FontVariant -- (*TextStyle*) Variant of the font
 Accepts: normal, small capital, oldstyle figures
 Default: normal

position

TextPosition -- (*TextStyle*) Vertical text position
 Accepts: normal, superscript, subscript
 Default: normal

kerning

Bool -- (*TextStyle*) Improve inter-letter spacing
 Accepts: true or false
 Default: true

ligatures

Bool -- (*TextStyle*) Run letters together where possible
 Accepts: true or false
 Default: true

hyphenate

Bool -- (*TextStyle*) Allow words to be broken over two lines
 Accepts: true or false
 Default: true

hyphen_chars

Integer -- (*TextStyle*) Minimum number of characters in a hyphenated part of a word
 Accepts: a natural number (positive integer)
 Default: 2

hyphen_lang

Locale -- (*TextStyle*) Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts: locale identifier in the <language ID>_<region ID> format
 Default: en_US

AdmonitionStyle

class rinohtype.structure.**AdmonitionStyle** (*base=None, **attributes*)

Style class for *Admonition*

inline_title

Bool -- Show the admonition's title inline with the body text, if possible

Accepts: true or false

Default: true

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top*Dimension* -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom*Dimension* -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_nextBool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border*Stroke* -- (*FlowableStyle*) Border surrounding the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left*Stroke* -- (*FlowableStyle*) Border left of the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right*Stroke* -- (*FlowableStyle*) Border right of the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top*Stroke* -- (*FlowableStyle*) Border above the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom*Stroke* -- (*FlowableStyle*) Border below the flowableAccepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color*Color* -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

HorizontalRuleStyle**class** rinohtype.structure.**HorizontalRuleStyle** (*base=None*, ***attributes*)Style class for *HorizontalRule***space_above***Dimension* -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

stroke

Stroke -- (*LineStyle*) Width and color used to draw the line

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: 1pt, #000

TableStyle

```
class rinohtable.TableStyle ( base=None, **attributes )
```

Style class for Table

split_minimum_rows

Integer -- The minimum number of rows to display when the table is split across pages

Accepts: a natural number (positive integer)

Default: (no value)

repeat_head

Bool -- Repeat the head when the table is split across pages

Accepts: true or false

Default: false

width

Dimension -- (*HorizontallyAlignedFlowableStyle*) The width of the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: none

horizontal_align

HorizontalAlignment -- (*HorizontallyAlignedFlowableStyle*) Horizontal alignment of the flowable

Accepts: left, right, center

Default: left

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false

Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable
 Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders
 Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

TableCellStyle

class rinoh.table.**TableCellStyle** (*base=None, **attributes*)

Style class for TableCell

vertical_align

VerticalAlign -- Vertical alignment of the cell contents within the available space
 Accepts: top, middle, bottom
 Default: middle

title

StyledText -- (*GroupedFlowablesStyle*) Title to precede the flowables
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or ") , optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing

Dimension -- (*GroupedFlowablesStyle*) Spacing between flowables
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_above

Dimension -- (*FlowableStyle*) Vertical space preceding the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

space_below

Dimension -- (*FlowableStyle*) Vertical space following the flowable
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_left

Dimension -- (*FlowableStyle*) Left margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

margin_right

Dimension -- (*FlowableStyle*) Right margin

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_left

Dimension -- (*FlowableStyle*) Left padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_right

Dimension -- (*FlowableStyle*) Right padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_top

Dimension -- (*FlowableStyle*) Top padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

padding_bottom

Dimension -- (*FlowableStyle*) Bottom padding

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 0

keep_with_next

Bool -- (*FlowableStyle*) Keep this flowable and the next on the same page

Accepts: true or false
 Default: false

border

Stroke -- (*FlowableStyle*) Border surrounding the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_left

Stroke -- (*FlowableStyle*) Border left of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_right

Stroke -- (*FlowableStyle*) Border right of the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_top

Stroke -- (*FlowableStyle*) Border above the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)
 Default: none

border_bottom

Stroke -- (*FlowableStyle*) Border below the flowable

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color -- (*FlowableStyle*) Color of the area within the flowable's borders

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

TableCellBorderStyle

```
class rinohtable.TableCellBorderStyle ( base=None, **attributes )
```

Style class for TableCellBorder

stroke

Stroke -- Overrides the default set in *LineStyle*

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

TableCellBackgroundStyle

```
class rinohtable.TableCellBackgroundStyle ( base=None, **attributes )
```

Style class for TableCellBackground

fill_color

Color -- Overrides the default set in *ShapeStyle*

Accepts: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

stroke

Stroke -- Overrides the default set in *LineStyle*

Accepts: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

7.4 Standard Document Templates

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

7.4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

```
class rinohtemplates.article.Article ( document_tree, configuration=None, backend=None )
```

stylesheet

StyleSheet -- Overrides the default set in *DocumentTemplate*

Accepts: the name of an *installed style sheet* or the filename of a stylesheet file (with the .rts extension)

Default: sphinx_article (= *rinohtypes.stylesheets.sphinx_article*)

table_of_contents

Bool -- Show or hide the table of contents
Accepts: true or false
Default: true

abstract_location

AbstractLocation -- Where to place the abstract
Accepts: title, front matter
Default: front matter

parts

PartsList -- Overrides the default set in *DocumentTemplate*
Accepts: a space-separated list of document part template names
Default: *title front_matter contents*

language

Language -- (*DocumentTemplate*) The main language of the document
Accepts: the code of one of the *supported languages*
Default: *EN* (English)

strings

Strings -- (*DocumentTemplate*) Strings to override standard element names
Accepts: strings need to be entered in INI sections named after the *StringCollection* subclasses
Default: none

title

TitlePartTemplate -- base: None

front_matter

ArticleFrontMatter -- base: None

contents

ContentsPartTemplate -- base: None

page

PageTemplate -- base: None
Overrides these defaults:

- *page_size* = \$(*paper_size*)
- *chapter_title_flowables* = None

title_page

TitlePageTemplate -- base: *page*
Overrides these defaults:

- *top_margin* = 8cm

front_matter_page

PageTemplate -- base: *page*

contents_page

PageTemplate -- base: *page*

class rinoh.templates.article.AbstractLocation

Where to place the article's abstract

Accepts: title, front matter

7.4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

class rinoh.templates.book.Book (*document_tree*, *configuration=None*, *backend=None*)

stylesheet

StyleSheet -- Overrides the default set in *DocumentTemplate*

Accepts: the name of an *installed style sheet* or the filename of a stylesheet file (with the *.rts* extension)

Default: sphinx (= *rinoh.stylesheets.sphinx*)

parts

PartsList -- Overrides the default set in *DocumentTemplate*

Accepts: a space-separated list of document part template names

Default: *title front_matter contents back_matter*

language

Language -- (*DocumentTemplate*) The main language of the document

Accepts: the code of one of the *supported languages*

Default: *EN* (English)

strings

Strings -- (*DocumentTemplate*) Strings to override standard element names

Accepts: strings need to be entered in INI sections named after the *StringCollection* subclasses

Default: none

cover

FixedDocumentPartTemplate -- base: None

Overrides these defaults:

- *end_at_page* = left
- *drop_if_empty* = False
- *page_number_format* = None

title

TitlePartTemplate -- base: None

Overrides these defaults:

- *end_at_page* = left
- *page_number_format* = number

front_matter*FixedDocumentPartTemplate* -- base: None

Overrides these defaults:

- *end_at_page* = left
- *flowables* = [TableOfContentsSection()]
- *page_number_format* = lowercase roman

contents*ContentsPartTemplate* -- base: None

Overrides these defaults:

- *end_at_page* = left
- *page_number_format* = number

back_matter*BackMatterTemplate* -- base: None

Overrides these defaults:

- *end_at_page* = left
- *page_number_format* = number

page*PageTemplate* -- base: None

Overrides these defaults:

- *bottom_margin* = 1in
- *right_margin* = 1in
- *top_margin* = 1in
- *left_margin* = 1in
- *page_size* = \$(paper_size)

cover_page*PageTemplate* -- base: *page***title_page***TitlePageTemplate* -- base: *page***front_matter_page***PageTemplate* -- base: *page*

Overrides these defaults:

- *header_text* = None
- *header_footer_distance* = 0

front_matter_right_page*PageTemplate* -- base: *front_matter_page*

Overrides these defaults:

- `footer_text = '\t' '\t' '{PAGE_NUMBER}'`
- `chapter_title_flowables = [Paragraph[Field({SECTION_TITLE})] (style=front matter section title)]`
- `chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'`
- `chapter_header_text = None`
- `chapter_title_height = 2.5in`

front_matter_left_page

PageTemplate -- base: *front_matter_page*

Overrides these defaults:

- `footer_text = '{PAGE_NUMBER}'`

contents_page

PageTemplate -- base: *page*

Overrides these defaults:

- `header_footer_distance = 0`

contents_right_page

PageTemplate -- base: *contents_page*

Overrides these defaults:

- `header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'`
- `chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'`
- `chapter_title_height = 2.4in`
- `footer_text = '{SECTION_NUMBER}' '. ' '{SECTION_TITLE}' '\t' '\t' '{PAGE_NUMBER}'`
- `chapter_title_flowables = [Paragraph[MixedStyledText [MixedStyledText [StringField(<class 'rinoh.structure.SectionTitles'>, 'chapter'), SingleStyledText(' ', style=None)] (style=None), Field({SECTION_NUMBER})] (style=None)] (style=body matter chapter label), Paragraph[Field({SECTION_TITLE})] (style=body matter chapter title)]`
- `chapter_header_text = None`

contents_left_page

PageTemplate -- base: *contents_page*

Overrides these defaults:

- `footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SectionTitles.chapter}' ' '{SECTION_NUMBER}' '. ' '{SECTION_TITLE}'`
- `header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'`

back_matter_page*PageTemplate* -- base: *page*

Overrides these defaults:

- *header_footer_distance* = 0
- *columns* = 2

back_matter_right_page*PageTemplate* -- base: *back_matter_page*

Overrides these defaults:

- *header_text* = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- *chapter_footer_text* = '\t' '\t' '{PAGE_NUMBER}'
- *chapter_title_height* = 2.5in
- *footer_text* = '{SECTION_TITLE}' '\t' '\t' '{PAGE_NUMBER}'
- *chapter_title_flowables* = [Paragraph[Field({SECTION_TITLE})] (style=front matter section title)]
- *chapter_header_text* = None

back_matter_left_page*PageTemplate* -- base: *back_matter_page*

Overrides these defaults:

- *footer_text* = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE}'
- *header_text* = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'

API Documentation

Note The API documentation is still incomplete.

8.1 Dimension (*rinoh.dimension*)

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```
height = 100*PT
width = 50*PERCENT
```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a `Flowable` is evaluated with respect to the total width available to it.

class `rinoh.dimension.Dimension` (*value=0, unit=None*)

A simple dimension

Parameters

- **value** (*int or float*) -- the magnitude of the dimension
- **unit** (*DimensionUnit*) -- the unit this dimension is expressed in. Default: *PT*.

grow (*value*)

Grow this dimension (in-place)

The *value* is interpreted as a magnitude expressed in the same unit as this dimension.

Parameters **value** (*int or float*) -- the amount to add to the magnitude of this dimension

Returns *Dimension* -- this (growed) dimension itself

`rinoh.dimension.PT = DimensionUnit(1.0, 'pt')`

PostScript points

`rinoh.dimension.INCH = DimensionUnit(72.0, 'in')`

imperial/US inch

`rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')`

computer pica

```
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
    millimeter
```

```
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
    centimeter
```

```
rinoh.dimension.PERCENT = FractionUnit(100, '%')
    fraction of 100
```

```
rinoh.dimension.QUARTERS = FractionUnit(4, '4')
    fraction of 4
```

8.2 Document (*rinoh.document*)

```
class rinoh.document.DocumentTree ( flowables, source_file=None, options=None )
```

Holds the document's contents as a tree of flowables

Parameters

- **flowables** (*list[Flowable]*) -- the list of top-level flowables
- **source_file** (*str*) -- absolute path of the source file, used to locate images and include in logging and error and warnings.
- **options** (*Reader*) -- frontend-specific options

```
class rinoh.document.Document ( document_tree, stylesheet, language, strings=None, backend=None )
```

Renders a document tree to pages

Parameters

- **document_tree** (*DocumentTree*) -- a tree of the document's contents
- **stylesheet** (*StyleSheet*) -- style sheet used to style document elements
- **language** (*Language*) -- the language to use for standard strings
- **strings** (*Strings*) -- overrides localized strings provided by *language*
- **backend** -- the backend used for rendering the document

```
render ( filename_root=None, file=None )
```

Render the document repeatedly until the output no longer changes due to cross-references that need some iterations to converge.

```
create_outlines ( )
```

Create an outline in the output file that allows for easy navigation of the document. The outline is a hierarchical tree of all the sections in the document.

```
class rinoh.document.DocumentPart ( template, document, flowables )
```

Part of a document.

Parameters

- **template** (*DocumentPartTemplate*) -- the template that determines the contents and style of this document part
- **document** (*Document*) -- the document this part belongs to
- **flowables** (*list[Flowable]*) -- the flowables to render in this document part

add_page (*page*)

Append *page* (*Page*) to this *DocumentPart*.

new_page (*page_number*, *new_chapter*, ***kwargs*)

Called by `render()` with the Chain`s that need more :class:`Container`s. This method should create a new :class:`Page` which contains a container associated with *chain*.

8.2.1 Pages

class rinoh.document.**Page** (*document_part*, *number*, *paper*, *orientation='portrait'*)

A single page in a document.

A *Page* is a *Container*, so other containers can be added as children.

Parameters

- **document_part** (*DocumentPart*) -- the document part this page is part of
- **number** (*int*) -- the 1-based index of this page in the document part
- **paper** (*Paper*) -- determines the dimensions of this page
- **orientation** (*PageOrientation*) -- the orientation of this page

page

Returns the page itself.

class rinoh.document.**PageOrientation**

Accepts: portrait, landscape

class rinoh.document.**PageType**

Accepts: left, right, any

8.3 Drawing Primitives (*rinoh.draw*)

class rinoh.draw.**Stroke** (*width*, *color*)

The display properties of a line

Parameters

- **width** (*Dimension*) -- the width of the line
- **color** (*Color*) -- the color of the line

class rinoh.draw.**Line** (*start*, *end*, *style=None*, *parent=None*)

Draws a line

Parameters

- **start** (*2-tuple*) -- coordinates for the start point of the line
- **end** (*2-tuple*) -- coordinates for the end point of the line

style_class

alias of *LineStyle*

class rinoh.draw.**Shape** (*style=None*, *parent=None*)

Base class for closed shapes

style_class
alias of *ShapeStyle*

8.4 Flowable (*rinoh.flowable*)

class rinoh.flowable.Flowable (*id=None, style=None, parent=None*)

A document element that can be "flowed" into a container on the page.

A flowable can adapt to the width of the container, or it can horizontally align itself in the container (see *HorizontallyAlignedFlowable*).

class rinoh.flowable.FlowableState (*flowable, _initial=True*)

Stores a flowable's rendering state, which can be copied.

This enables saving the rendering state at certain points in the rendering process, so rendering can later be resumed at those points, if needed.

8.4.1 No-Output Flowables

These flowables do not directly place anything on the page. All except *DummyFlowable* do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

class rinoh.flowable.DummyFlowable (*id=None, parent=None*)

A flowable that does not directly place anything on the page.

Subclasses can produce side-effects to affect the output in another way.

class rinoh.flowable.AnchorFlowable (*id=None, parent=None*)

A dummy flowable that registers a destination anchor.

Places a destination for the flowable's ID at the current cursor position.

class rinoh.flowable.SetMetadataFlowable (*parent=None, **metadata*)

A dummy flowable that stores metadata in the document.

The metadata is passed as keyword arguments. It will be available to other flowables during the rendering stage.

class rinoh.flowable.WarnFlowable (*message, parent=None*)

A dummy flowable that emits a warning during the rendering stage.

Parameters *message* (*str*) -- the warning message to emit

class rinoh.flowable.PageBreak (*id=None, style=None, parent=None*)

A flowable that optionally triggers a page break before rendering.

If this flowable's *page_break* style attribute is not *None*, it breaks to the page of the type indicated by *page_break* before starting rendering.

8.4.2 Labeled Flowables

class rinoh.flowable.LabeledFlowable (*label, flowable, id=None, style=None, parent=None*)

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the *label_max_width* style attribute value, the flowable is rendered below the label.

Parameters • **label** (*Flowable*) -- the label for the flowable

- **flowable** (*Flowable*) -- the flowable to label

style_class
alias of *LabeledFlowableStyle*

class rinoh.flowable.**LabeledFlowableState** (*flowable*, *content_flowable_state*, *_initial=True*)

8.4.3 Grouping Flowables

class rinoh.flowable.**GroupedFlowables** (*id=None*, *style=None*, *parent=None*)

Groups a list of flowables and renders them one below the other.

Makes sure that a flowable for which *keep_with_next* is enabled is not separated from the flowable that follows it.

Subclasses should implement *flowables()*.

style_class
alias of *GroupedFlowablesStyle*

flowables (*container*)
Generator yielding the *Flowables* to group

class rinoh.flowable.**GroupedFlowablesState** (*groupedflowables*, *flowables*, *first_flowable_state=None*, *_initial=True*)

class rinoh.flowable.**StaticGroupedFlowables** (*flowables*, *id=None*, *style=None*, *parent=None*)

Groups a static list of flowables.

Parameters *flowables* (*iterable[Flowable]*) -- the flowables to group

class rinoh.flowable.**GroupedLabeledFlowables** (*id=None*, *style=None*, *parent=None*)

Groups a list of labeled flowables, lining them up.

8.4.4 Horizontally Aligned Flowables

class rinoh.flowable.**HorizontallyAlignedFlowable** (**args*, ***, *align=None*, *width=None*, ***kwargs*)

A flowable with configurable width and horizontal alignment.

The *width* and *horizontal_align* control the width and horizontal alignment of the flowable.

style_class
alias of *HorizontallyAlignedFlowableStyle*

class rinoh.flowable.**HorizontallyAlignedFlowableState** (*flowable*, *_initial=True*)

8.4.5 Floating Flowables

class rinoh.flowable.**Float** (*id=None*, *style=None*, *parent=None*)

A flowable that can optionally be placed elsewhere on the page.

If this flowable's *float* style attribute is set to *True*, it is not flowed in line with the surrounding flowables, but it is instead flowed into another container pointed to by the former's *Container.float_space* attribute.

This is typically used to place figures and tables at the top or bottom of a page, instead of in between paragraphs.

8.5 Fonts and Typefaces (*rinohtype.font*)

Classes for fonts and typefaces.

class `rinohtype.font.Font` (*filename*, *weight*='medium', *slant*='upright', *width*='normal')

A collection of glyphs in a particular style

This is a base class for classes that parse different font formats. See `rinohtype.font.type1` and `rinohtype.font.opentype`.

Parameters

- **filename** (*str*) -- filename of the font file to load
- **weight** (*FontWeight*) -- weight of the font
- **slant** (*FontSlant*) -- slant of the font
- **width** (*FontWidth*) -- width of the font

encoding

If no encoding is set for the *Font*, glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

get_glyph (*char*, *variant*)

Return the glyph for a particular character

If the glyph of requested font variant is not present in the font, the *normal* variant is returned instead. If that is not present either, an exception is raised.

Parameters

- **char** (*str of length 1*) -- the character for which to find the glyph
- **variant** (*FontVariant*) -- the variant of the glyph to return

Returns *GlyphMetrics* -- the requested glyph

Raises *MissingGlyphException* -- when the requested glyph is not present in the font

get_ligature (*glyph*, *successor_glyph*)

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return *None*.

Parameters

- **glyph** (*GlyphMetrics*) -- the first of the glyphs to combine
- **successor_glyph** (*GlyphMetrics*) -- the second of the glyphs to combine

Returns *GlyphMetrics* or *None* -- the ligature to replace the given glyphs

get_kerning (*a*, *b*)

Look up the kerning for two glyphs

Parameters

- **a** (*GlyphMetrics*) -- the first of the glyphs
- **b** (*GlyphMetrics*) -- the second of the glyphs

Returns *float* -- the kerning value in font units

class `rinohtype.font.Typeface` (*name*, **fonts*)

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters ***fonts** (*Font*) -- the fonts that make up this typeface

fonts ()

Generator yielding all fonts of this typeface

Yields *Font* -- the next font in this typeface

get_font (*weight*='medium', *slant*='upright', *width*='normal')

Return the font matching or closest to the given style

If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters • **weight** (*FontWeight*) -- weight of the font

 • **slant** (*FontSlant*) -- slant of the font

 • **width** (*FontWidth*) -- width of the font

Returns *Font* -- the requested font

8.6 Images and Figures (*rinoht.image*)

class *rinoht.image.Scale*

Scaling factor for images

Can be a numerical value where a value of 1 keeps the image's original size or one of values.

Accepts: fit, fill or a float larger than 0

class *rinoht.image.BackgroundImageArgs* (*base=None*, ***attributes*)

Arguments accepted by attributes of type *BackgroundImage*

scale

Scale -- Scaling factor for the image

Accepts: fit, fill or a float larger than 0

Default: fit

width

Dimension -- The width to scale the image to

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: none

height

Dimension -- The height to scale the image to

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: none

dpi

Integer -- Overrides the DPI value set in the image

Accepts: a natural number (positive integer)

Default: (no value)

rotate

Integer -- The angle in degrees to rotate the image

Accepts: a natural number (positive integer)

Default: (no value)

limit_width

Dimension -- Limit the image width when none of *scale*, *width* and *height* are given and the image would be wider than the container

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: none

align

HorizontalAlignment -- How to align the image within the page

Accepts: left, right, center

Default: left

class rinoh.image.**BackgroundImage** (*filename_or_file*, *scale*=1.0, *width*=None, *height*=None, *dpi*=None, *rotate*=0, *limit_width*=None, *align*=None, *id*=None, *style*=None, *parent*=None)

Image to place in the background of a page

Takes the same arguments as Image. *BackgroundImageArgs* details how to set the keyword arguments when specifying a background image in a template configuration.

8.7 Index (*rinoh.index*)

8.8 Language (*rinoh.language*)

class rinoh.language.**Language** (*code*, *name*)

Collects localized strings for a particular language

Parameters

- **code** (*str*) -- short code identifying the language
- **name** (*str*) -- native name of the language

languages

Dictionary mapping codes to *Languages*

The following languages are supported:

rinoh.language.EN = Language('en', 'English')

Localized strings for English

AdmonitionTitles

Attention Attention!

Caution Caution!

Danger !DANGER!

Error Error

Hint Hint

Important Important

Note Note

Tip Tip

Warning Warning

Seealso See also

SectionTitles

Contents Table of Contents

Chapter Chapter

Index Index

`rinoh.language.FR = Language('fr', 'Français')`

Localized strings for Français

AdmonitionTitles

Attention Attention!

Caution Prudence!

Danger !DANGER!

Error Erreur

Hint Conseil

Important Important

Note Note

Tip Astuce

Warning Avertissement

Seealso Voir aussi

SectionTitles

Contents Table des Matières

Chapter Chapitre

Index Index

`rinoh.language.IT = Language('it', 'Italiano')`

Localized strings for Italiano

AdmonitionTitles

Attention Attenzione!

Caution Prudenza!

Danger !PERICOLO!

Error Errore

Hint Consiglio

Important Importante

Note Nota

Tip Suggestimento

Warning Avvertimento

Seealso Vedi anche

SectionTitles

Contents Contenuti

Chapter Capitolo

Index Indice

`rinohtype.language.NL = Language('nl', 'Nederlands')`

Localized strings for Nederlands

AdmonitionTitles

Attention Opgelet!

Caution Pas op!

Danger !GEVAAR!

Error Fout

Hint Hint

Important Belangrijk

Note Noot

Tip Tip

Warning Waarschuwing

Seealso Zie ook

SectionTitles

Contents Inhoudsopgave

Chapter Hoofdstuk

Index Index

8.9 Paper sizes (*rinohtype.paper*)

The *Paper* class and a number of predefined paper formats.

`class rinohtype.paper.Paper (name, width, height)`

Defines a paper size.

Parameters

- **name** (*str*) -- the name of this paper type
- **width** (*Dimension*) -- the (portrait) width of this paper type
- **height** (*Dimension*) -- the (portrait) height of this paper type

`rinohtype.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)`

`rinohtype.paper.A1 = Paper('A1', width=594*MM, height=841*MM)`

`rinohtype.paper.A2 = Paper('A2', width=420*MM, height=594*MM)`

`rinohtype.paper.A3 = Paper('A3', width=297*MM, height=420*MM)`

`rinohtype.paper.A4 = Paper('A4', width=210*MM, height=297*MM)`

`rinohtype.paper.A5 = Paper('A5', width=148*MM, height=210*MM)`

`rinohtype.paper.A6 = Paper('A6', width=105*MM, height=148*MM)`

`rinohtype.paper.A7 = Paper('A7', width=74*MM, height=105*MM)`

```

rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)
rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)
rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)
rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)
rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)
rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH, height=5*INCH)
rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)
rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)

```

8.10 Paragraph (*rinoh.paragraph*)

class `rinoh.paragraph.ParagraphBase` (*id=None, style=None, parent=None*)

Base class for paragraphs

A paragraph is a collection of mixed-styled text that can be flowed into a container.

style_class

alias of *ParagraphStyle*

render (*container, descender, state, first_line_only=False*)

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

- **container** (*Container*) -- the container to render to
- **descender** (*float or None*) -- descender height of the preceeding line
- **state** (*ParagraphState*) -- the state where rendering will continue
- **first_line_only** (*bool*) -- typeset only the first line

class `rinoh.paragraph.Paragraph` (*text_or_items, id=None, style=None, parent=None*)

A paragraph of static text

Parameters

- **text_or_items** -- see *MixedStyledText*
- **style** -- see *Styled*
- **parent** -- see *DocumentElement*

class `rinoh.paragraph.ParagraphState` (*paragraph, words, nested_flowable_state=None, _first_word=None, _initial=True*)

8.10.1 Styled Text (*rinoh.text*)

class `rinoh.text.StyledText` (*id=None, style=None, parent=None*)

Base class for text that has a *TextStyle* associated with it.

style_class

alias of *TextStyle*

to_string (*flowable_target*)

Return the text content of this styled text.

is_script (*container*)

Returns *True* if this styled text is super/subscript.

script_level (*container*)

Nesting level of super/subscript.

height (*container*)

Font size after super/subscript size adjustment.

y_offset (*container*)

Vertical baseline offset (up is positive).

items

The list of items in this StyledText.

spans (*container*)

Generator yielding all spans in this styled text, one item at a time (used in typesetting).

class `rinoh.text.SingleStyledText` (*text*, *style=None*, *parent=None*)

class `rinoh.text.MixedStyledText` (*text_or_items*, *style=None*, *parent=None*)

Concatenation of styled text

Parameters

- **text_or_items** (*str*, *StyledText* or *iterable of these*) -- mixed styled text
- **style** -- see *Styled*
- **parent** -- see *DocumentElement*

append (*item*)

Append *item* (*StyledText* or *str*) to the end of this mixed-styled text.

The parent of *item* is set to this mixed-styled text.

8.10.2 Inline Elements (*rinoh.inline*)

class `rinoh.inline.InlineFlowable` (*baseline=None*, *id=None*, *style=None*, *parent=None*)

style_class

alias of *InlineFlowableStyle*

8.10.3 Styling Properties

Line Spacing

class `rinoh.paragraph.LineSpacing`

Base class for line spacing types

Line spacing is defined as the distance between the baselines of two consecutive lines of text in a

paragraph.

advance (*line*, *last_descender*, *container*)

Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.**DefaultSpacing**

The default line spacing as specified by the font.

class rinoh.paragraph.**ProportionalSpacing** (*factor*)

Line spacing proportional to the line height

Parameters **factor** (*float*) -- amount by which the line height is multiplied to obtain the line spacing

class rinoh.paragraph.**FixedSpacing** (*pitch*, *minimum=ProportionalSpacing(1.0)*)

Fixed line spacing, with optional minimum spacing

Parameters

- **pitch** (*Dimension*) -- the distance between the baseline of two consecutive lines of text
- **minimum** (*LineSpacing*) -- the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to `None` if no minimum is required, set to `None`

class rinoh.paragraph.**Leading** (*leading*)

Line spacing determined by the space in between two lines

Parameters **leading** (*Dimension*) -- the space between the bottom of a line and the top of the next line of text

The following standard line spacings have been predefined:

rinoh.paragraph.**DEFAULT** = **DefaultSpacing**()

The default line spacing as specified by the font.

rinoh.paragraph.**STANDARD** = **ProportionalSpacing**(1.2)

Line spacing of 1.2 times the line height.

rinoh.paragraph.**SINGLE** = **ProportionalSpacing**(1.0)

Line spacing equal to the line height (no leading).

rinoh.paragraph.**DOUBLE** = **ProportionalSpacing**(2.0)

Line spacing of double the line height.

Tabulation

class rinoh.paragraph.**TabStop** (*position*, *align='left'*, *fill=None*)

Horizontal position for aligning text of successive lines.

get_position (*line_width*)

Return the absolute position of this tab stop.

8.10.4 Rendering Internals

class rinoh.paragraph.**Glyph** (*glyph*, *width*, *char*)

```
class rinoh.paragraph.GlyphsSpan ( span, chars_to_glyphs, glyphs_and_widths=[] )
```

8.10.5 Miscellaneous Internals

```
class rinoh.paragraph.HyphenatorStore
```

8.11 Cross-References and Fields (*rinoh.reference*)

```
class rinoh.reference.ReferenceType
    Accepts: reference, number, title, page
```

8.12 Structure (*rinoh.structure*)

8.12.1 Sections

```
class rinoh.structure.Section ( flowables, id=None, style=None, parent=None )
    A subdivision of a document
    A section usually has a heading associated with it, which is optionally numbered.
```

```
    style_class
        alias of SectionStyle
```

```
class rinoh.structure.Heading ( title, custom_label=None, id=None, style=None, parent=None )
    The title for a section
```

```
Parameters    • title (StyledText) -- the title text
               • custom_label (StyledText) -- a frontend can supply a custom label to use
               instead of an automatically determined section number
```

```
    style_class
        alias of HeadingStyle
```

```
class rinoh.structure.SectionTitles ( **strings )
    Collection of localized titles for common sections
```

```
    contents
        String -- Title for the table of contents section
```

```
    chapter
        String -- Label for top-level sections
```

```
    index
        String -- Title for the index section
```

8.12.2 Lists

```
class rinoh.structure.List ( flowables, id=None, style=None, parent=None )
```

```
style_class
    alias of ListStyle
```

```
class rinoh.structure.DefinitionList ( flowables, id=None, style=None, parent=None )
```

8.12.3 Table of Contents

```
class rinoh.structure.TableOfContentsSection
```

```
class rinoh.structure.TableOfContents ( local=False, id=None, style=None, parent=None )
```

```
style_class
    alias of TableOfContentsStyle
```

```
class rinoh.structure.TableOfContentsEntry ( flowable, id=None, style=None, parent=None )
```

```
style_class
    alias of TableOfContentsEntryStyle
```

8.12.4 Adminitions

```
class rinoh.structure.Admonition ( flowables, title=None, type=None, id=None, style=None, parent=None )
```

```
style_class
    alias of AdmonitionStyle
```

```
class rinoh.structure.AdmonitionTitles ( **strings )
    Collection of localized titles for common admonitions
```

```
attention
    String-- Title for attention admonitions
```

```
caution
    String-- Title for caution admonitions
```

```
danger
    String-- Title for danger admonitions
```

```
error
    String-- Title for error admonitions
```

```
hint
    String-- Title for hint admonitions
```

```
important
    String-- Title for important admonitions
```

```
note
    String-- Title for note admonitions
```

```
tip
    String-- Title for tip admonitions
```

warning
String -- Title for warning admonitions

seealso
String -- Title for see-also admonitions

8.12.5 Horizontal Rule

class rinoh.structure.**HorizontalRule** (*id=None, style=None, parent=None*)

style_class
 alias of *HorizontalRuleStyle*

8.13 Strings (*rinoh.strings*)

class rinoh.strings.**String** (*description*)
 Descriptor used to describe a configurable string

Parameters **description** (*str*) -- a short description for this string

class rinoh.strings.**StringCollection** (***strings*)
 A collection of related configurable strings

Subclasses

- *AdmonitionTitles*
- *SectionTitles*

class rinoh.strings.**Strings** (**string_collections*)
 Stores several *StringCollections*

class rinoh.strings.**StringField** (*strings_class, key, case=None, style=None, parent=None*)
 Styled text that will be substituted with a configured string
 The configured string is either the localized string as determined by the language set for the document or the user-supplied string passed to the *TemplateConfiguration*

8.14 Style (*rinoh.style*)

class rinoh.style.**Styled** (*id=None, style=None, parent=None*)
 A document element who's style can be configured.

Parameters **style** (*str, Style*) -- the style to associate with this element. If *style* is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class
 The *Style* subclass that corresponds to this *Styled* subclass.

class rinoh.style.**Style** (*base=None, **attributes*)
 Dictionary storing style attributes.
 The style attributes associated with this *Style* are specified as class attributes of type *Attribute*.
 Style attributes can also be accessed as object attributes.

8.14.1 Style Sheet

```
class rinoh.style.StyleSheet ( name, matcher=None, base=None, description=None,
    pygments_style=None, **user_options )
```

Dictionary storing a collection of related styles by name.

Styles stored in a *StyleSheet* can refer to their base style by name.

Parameters

- **name** (*str*) -- a label for this style sheet
- **matcher** (*StyledMatcher*) -- the matcher providing the selectors the styles contained in this style sheet map to. If no matcher is given and *base* is specified, the *base*'s matcher is used. If *base* is not set, the default matcher is used.
- **base** (*StyleSheet* or *str*) -- the style sheet to extend
- **description** (*str*) -- a short string describing this style sheet
- **pygments_style** (*str*) -- the Pygments style to use for styling code blocks

```
get_selector ( name )
```

Find a selector mapped to a style in this or a base style sheet.

Parameters **name** (*str*) -- a style name

Returns *Selector* -- the selector mapped to the style *name*

Raises *KeyError* -- if the style *name* was not found in this or a base style sheet

```
class rinoh.style.StyleSheetFile ( filename, base=None, **kwargs )
```

Loads styles defined in a *.rts* file (INI format).

Parameters **filename** (*str*) -- the path to the style sheet file

StyleSheetFile takes the same optional arguments as *StyleSheet*. These can also be specified in the [STYLESHEET] section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

```
class rinoh.style.StyledMatcher ( mapping_or_iterable=None, **kwargs )
```

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a *dict* by passing a mapping, an iterable and/or keyword arguments.

8.15 Tables (*rinoh.table*)

```
class rinoh.table.VerticalAlign
```

Accepts: top, middle, bottom

8.16 Templates (*rinoh.template*)

Document templates are created by subclassing *DocumentTemplate*, just like the *standard templates* shipped with rinohtype.

```
class rinoh.template.DocumentTemplate ( document_tree, configuration=None, backend=None )
```

Template for documents

- Parameters**
- **document_tree** (*DocumentTree*) -- a tree of the document's contents
 - **configuration** (*TemplateConfiguration*) -- configuration for this template
 - **backend** -- the backend used for rendering the document

language

Language -- The main language of the document

Accepts: the code of one of the *supported languages*

Default: *EN* (English)

strings

Strings -- Strings to override standard element names

Accepts: strings need to be entered in INI sections named after the *StringCollection* subclasses

Default: none

stylesheet

StyleSheet -- The stylesheet to use for styling document elements

Accepts: the name of an *installed style sheet* or the filename of a stylesheet file (with the *.rts* extension)

Default: *sphinx* (= *rinoh.stylesheets.sphinx*)

parts

PartsList -- The parts making up this document

Accepts: a space-separated list of document part template names

Default: (empty list)

Document templates can be customized by setting values for the configuration attributes defined in a *DocumentTemplate* subclass in a *TemplateConfiguration*. An template configuration can be passed as *configuration* on template instantiation. However, it is better to make use of the *document* method, however.

class *rinoh.template.TemplateConfiguration* (*name*, *base=None*, *template=None*, *description=None*, ***options*)

Stores a configuration for a *DocumentTemplate*

- Parameters**
- **name** (*str*) -- a label for this template configuration
 - **base** (*TemplateConfiguration*) -- the template configuration to extend
 - **template** (*DocumentTemplateMeta* or *str*) -- the document template to configure
 - **description** (*str*) -- a short string describing this style sheet
 - ****options** -- configuration values for the configuration attributes defined by the document *template*

template = None

The *DocumentTemplate* subclass to configure

document (*document_tree*, *backend=None*)

Create a *DocumentTemplate* object based on the given document tree and this template configuration

- Parameters**
- **document_tree** (*DocumentTree*) -- tree of the document's contents

- **backend** -- the backend to use when rendering the document

```
class rinoh.template.PartsList ( *parts )
```

Stores the names of the document part templates making up a document

Parameters ***parts** (*list[str]*) -- the names of the document parts

8.16.1 Document Parts

The document part templates which are listed by name in *DocumentTemplate.parts* are looked up as attributes of the *DocumentTemplate* subclass. They are instances of *DocumentPartTemplate* subclasses:

```
class rinoh.template.DocumentPartTemplate ( base=None, **attributes )
```

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the *TemplateConfiguration* where this part template was.

page_number_format

NumberFormat -- The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page

PageType -- The type of page to end this document part on

Accepts: left, right, any

Default: any

drop_if_empty

Bool -- Exclude this part from the document if it is empty (no flowables)

Accepts: true or false

Default: true

The following document part templates are used in the standard document templates:

```
class rinoh.template.TitlePartTemplate ( base=None, **attributes )
```

The title page of a document.

drop_if_empty

Bool -- Overrides the default set in *DocumentPartTemplate*

Accepts: true or false

Default: false

page_number_format

NumberFormat -- (*DocumentPartTemplate*) The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page

PageType -- (*DocumentPartTemplate*) The type of page to end this document part on

Accepts: left, right, any

Default: any

class rinoh.template.**ContentsPartTemplate** (base=None, **attributes)

The body of a document.

Renders all of the content present in the *DocumentTree* passed to the *DocumentTemplate*.

page_number_format

NumberFormat -- (*DocumentPartTemplate*) The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page

PageType -- (*DocumentPartTemplate*) The type of page to end this document part on

Accepts: left, right, any

Default: any

drop_if_empty

Bool -- (*DocumentPartTemplate*) Exclude this part from the document if it is empty (no flowables)

Accepts: true or false

Default: true

class rinoh.template.**FixedDocumentPartTemplate** (base=None, **attributes)

A document part template that renders a fixed list of flowables

flowables

FlowablesList -- The list of flowables to include in this document part

Accepts: Python source code that represents a list of *Flowables*

Default: []

page_number_format

NumberFormat -- (*DocumentPartTemplate*) The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page

PageType -- (*DocumentPartTemplate*) The type of page to end this document part on

Accepts: left, right, any

Default: any

drop_if_empty

Bool -- (*DocumentPartTemplate*) Exclude this part from the document if it is empty (no flowables)

Accepts: true or false

Default: true

8.16.2 Page Templates

The document templates make use of page templates:

```
class rinoh.template.PageTemplate ( base=None, **attributes )
```

header_footer_distance

Dimension -- Distance of the header and footer to the content area

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 14pt

columns

Integer -- The number of columns for the body text

Accepts: a natural number (positive integer)

Default: 1

column_spacing

Dimension -- The spacing between columns

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 1cm

header_text

StyledText -- The text to place in the page header

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER}' ' ' ' '{SECTION_TITLE}'

footer_text

StyledText -- The text to place in the page footer

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' '/' '{NUMBER_OF_PAGES}'

chapter_header_text

StyledText -- The text to place in the header on a page that starts a new chapter

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_footer_text

StyledText -- The text to place in the footer on a page that starts a new chapter

Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_title_flowables

FlowablesList -- Generator that yields the flowables to represent the chapter title

Accepts: Python source code that represents a list of *Flowables*

Default: [Paragraph[StringField(<class 'rinoh.structure.SectionTitles'>, 'chapter')] (style=None), Paragraph[Field({SECTION_NUMBER})] (style=None), Paragraph[Field({SECTION_TITLE})] (style=None)]

chapter_title_height

Dimension -- The height of the container holding the chapter title
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 150pt

page_size

Paper -- (*PageTemplateBase*) The format of the pages in the document
 Accepts: the name of a *predefined paper format* or <width> * <height> where width and height are *Dimensions*
 Default: A4

page_orientation

PageOrientation -- (*PageTemplateBase*) The orientation of pages in the document
 Accepts: portrait, landscape
 Default: portrait

left_margin

Dimension -- (*PageTemplateBase*) The margin size on the left of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

right_margin

Dimension -- (*PageTemplateBase*) The margin size on the right of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

top_margin

Dimension -- (*PageTemplateBase*) The margin size at the top of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

bottom_margin

Dimension -- (*PageTemplateBase*) The margin size at the bottom of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

background

BackgroundImage -- (*PageTemplateBase*) An image to place in the background of the page
 Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed
 Default: none

after_break_background

BackgroundImage -- (*PageTemplateBase*) An image to place in the background after a page break
 Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed
 Default: none

class rinoh.template.**TitlePageTemplate** (base=None, **attributes)

show_date

Bool -- Show or hide the document's date
 Accepts: true or false
 Default: true

show_author

Bool -- Show or hide the document's author
 Accepts: true or false
 Default: true

extra

StyledText -- Extra text to include on the title page below the title
 Accepts: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

page_size

Paper -- (*PageTemplateBase*) The format of the pages in the document
 Accepts: the name of a *predefined paper format* or <width> * <height> where width and height are *Dimensions*
 Default: A4

page_orientation

PageOrientation -- (*PageTemplateBase*) The orientation of pages in the document
 Accepts: portrait, landscape
 Default: portrait

left_margin

Dimension -- (*PageTemplateBase*) The margin size on the left of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

right_margin

Dimension -- (*PageTemplateBase*) The margin size on the right of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

top_margin

Dimension -- (*PageTemplateBase*) The margin size at the top of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

bottom_margin

Dimension -- (*PageTemplateBase*) The margin size at the bottom of the page
 Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)
 Default: 3cm

background

BackgroundImage -- (*PageTemplateBase*) An image to place in the background of the page
 Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed
 Default: none

after_break_background

BackgroundImage -- (*PageTemplateBase*) An image to place in the background after a page break

Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

The base class for these collects the common options:

```
class rinoh.template.PageTemplateBase ( base=None, **attributes )
```

page_size

Paper -- The format of the pages in the document

Accepts: the name of a *predefined paper format* or <width> * <height> where width and height are *Dimensions*

Default: A4

page_orientation

PageOrientation -- The orientation of pages in the document

Accepts: portrait, landscape

Default: portrait

left_margin

Dimension -- The margin size on the left of the page

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

right_margin

Dimension -- The margin size on the right of the page

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

top_margin

Dimension -- The margin size at the top of the page

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

bottom_margin

Dimension -- The margin size at the bottom of the page

Accepts: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /4)

Default: 3cm

background

BackgroundImage -- An image to place in the background of the page

Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

BackgroundImage -- An image to place in the background after a page break

Accepts: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

Frequently Asked Questions

PDFs produced by rinohtype contain mostly empty pages. What's up?

Old versions of some PDF viewers do not support the way rinohtype embeds fonts in a PDF (see [issue 2](#)). PDF viewers that are known to be affected are:

- pre-37.0 Firefox's built-in PDF viewer (pdf.js)
- pre-0.41 [poppler](#)-based applications such as Evince

Release History

10.1 Release 0.3.0 (2016-11-23)

New Features:

- support localization of standard document strings (en, fr, it, nl) (#53)
- localized strings can be overridden in the document template configuration
- make use of a fallback typeface when a glyph is not available (#55) (the 'fallback' style in the Sphinx stylesheet sets the fallback typeface)
- template configuration (INI) files: specify which document parts to include, configure document part and page templates, customize localized strings, ...
- support specifying more complex selectors directly in a style sheet file
- (figure and table) captions support hierarchical numbering (see CaptionStyle)
- make the frontends independent of the current working directory
- reStructuredText: support the table :widths: option (upcoming docutils 0.13)
- Sphinx frontend: provide styles for Sphinx's inline markup roles
- rinoh (command line renderer):
 - support template configuration files
 - support file formats for which a frontend is installed (see --list-formats)
 - accept options to configure the frontend (see --list-options)
 - option to list the installed fonts (on the command line or in a PDF file)
- show the current page number as part of the rendering progress indicator
- Book template: support for setting a cover page
- frontends: raise a more descriptive exception when a document tree node is not mapped
- validate the default value passed to an Attribute
- preliminary support for writing a style sheet to an INI file, listing default values for non-specified attributes (#23)

Changed:

- rinoh: the output PDF is now placed in the current directory, not in the same directory as the input file
- Sphinx builder configuration: replace the `rinoh_document_template` and `rinoh_template_configuration` options with `rinoh_template`
- if no base is given for a style, style attribute lookup proceeds to look in the style of the same name in the base style sheet (#66)
- `DEFAULT_STYLE` can be used as a base style to prevent style attribute lookup in the style of the same name in the base style sheet
- rename `FieldList` to `DefinitionList` and use it to replace uses (docutils and Sphinx frontends) of the old `DefinitionList` (#54)
- the new `DefinitionList` (`FieldList`) can be styled like the old `DefinitionList` by setting `max_label_width` to `None`, 0 or a 0-valued `Dimension`
- figures are now non-floating by default (float placement needs more work)
- hide the index chapter when there are no index entries (#51)
- style sheets: use the default matcher if none is specified
- Sphinx style sheet: copy the admonition style from the Sphinx LaTeX builder
- Sphinx style sheet: keep the admonition title together with the body
- Sphinx style sheet: color linked references as in the LaTeX output (#62)
- Sphinx style sheet: disable hyphenation/ligatures for literal strong text
- no more `DocumentSection`; a document now consists of parts (containing pages)
- template configuration:
 - refer to document part templates by name so that they can be replaced
 - the list of document parts can be changed in the template configuration
 - document parts take the 'end_at_page' option (left, right, or any)
 - find (left/right) page templates via the document part name they belong to
 - fall back to `<doc_part>_page` when the right or left template is not found
 - each template configuration requires a name
- `DocumentTree`: make the `source_file` argument optional
- don't abort when the document section hierarchy is missing levels (#67)
- use the PDF backend by default (no need to specify it)
- store the unit with `Dimension` instances (better printing)
- rename the `float` module to `image`

Fixed:

- improve compatibility with Windows: Windows path names and file encoding
- crash if a `StyledText` is passed to `HeadingStyle.number_separator`
- `GroupedLabeledFlowables` label width could be unnecessarily wide
- fix and improve automatic table column sizing
- Figures can now be referenced using the 'reference' format ("Figure 1.2")

- HorizontallyAlignedFlowable: make more robust
- make document elements referenceable by secondary IDs
- reStructuredText: only the first classifier for a definition term was shown
- Sphinx frontend: support the 'centered' directive
- Sphinx frontend: basic support for the 'hlist' directive
- Sphinx frontend: handle :abbr: without explanation
- Sphinx frontend: support nested inline nodes (guilabel & samp roles)
- PDF backend: fix writing of Type 1 fonts from a parsed PDF file
- PDF reader: handle multi-page PDFs (#71)
- PDF reader: fix parsing of XRef streams
- PDF reader: fix writing of parsed files

10.2 Release 0.2.1 (2016-08-18)

New Features:

- optionally limit the width of large images and make use of this to simulate the Sphinx LaTeX builder behavior (#46)
- reStructuredText/Sphinx: support for images with hyperlinks (#49)
- record the styled page numbers in the PDF as page labels (#41)
- unsupported Python versions: prevent installation where possible (sdist) or exit on import (wheel)
- support Python 3.6

Bugfixes:

- make StyleSheet objects picklable so the Sphinx builder's rinohtypesheet option can actually be used
- Fix #47: ClassNotFound exception in Literal_Block.lexers_getter()
- Fix #45: Images that don't fit are still placed on the page
- don't warn about duplicate style matches that resolve to the same style

10.3 Release 0.2.0 (2016-08-10)

Styling:

- generate a style log (show matching styles) to help style sheet development
- keep_with_next style attribute: prevent splitting two flowables across pages
- stylesheets can be loaded from files in INI format
- check the type of attributes passed to styles
- source code highlighting using Pygments
- table of contents entries can be styled more freely

- allow hiding the section numbers of table of contents entries
- allow for custom chapter titles
- selectors can now also select based on document part/section
- various small tweaks to selectors and matchers
- various fixes relating to style sheets

Templates:

- configurable standard document templates: article and book
- a proper infrastructure for creating custom document templates
- support for left/right page templates
- make the Article template more configurable
- pages now have background, content and header/footer layers
- support for generating an index
- make certain strings configurable (for localization, for example)

Frontends:

- Sphinx: interpret the LaTeX configuration variables if the corresponding rinohype variable is not set
- Sphinx: roughly match the LaTeX output (document template and style sheet)
- added a CommonMark frontend based on recomcommonmark
- added basic ePUB and DocBook frontends
- XML frontends: fix whitespace handling
- frontends now return generators yielding flowables (more flexible)

Command-line Renderer (rinoh):

- allow specifying a template and style sheet
- automatically install typefaces used in the style sheet from PyPI

Fonts:

- typefaces are discovered/loaded by entry point
- more complete support for OpenType fonts
- fix support for the 14 base Type 1 fonts

Images:

- more versatile image sizing: absolute width/height & scaling
- allow specifying the baseline for inline images
- several fixes in the JPEG reader

Miscellaneous:

- reorganize the Container class hierarchy
- fixes in footnote handling
- drop Python 3.2 support (3.3, 3.4 and 3.5 are supported)

10.4 Release 0.1.3 (2015-08-04)

- recover from the slow rendering speed caused by a bugfix in 0.1.2 (thanks to optimized element matching in the style sheets)
- other improvements and bugfixes related to style sheets

10.5 Release 0.1.2 (2015-07-31)

- much improved Sphinx support (we can now render the Sphinx documentation)
- more complete support for reStructuredText (docutils) elements
- various fixes related to footnote placement
- page break option when starting a new section
- fixes in handling of document sections and parts
- improvements to section/figure/table references
- native support for PNG and JPEG images (drops PIL/Pillow requirement, but adds PurePNG 0.1.1 requirement)
- new 'sphinx' stylesheet used by the Sphinx builder (~ Sphinx LaTeX style)
- restores Python 3.2 compatibility

10.6 Release 0.1.1 (2015-04-12)

First preview release

r

rinoh

- `rinoh.dimension`, 105
- `rinoh.document`, 106
- `rinoh.draw`, 107
- `rinoh.flowable`, 108
- `rinoh.font`, 110
- `rinoh.image`, 111
- `rinoh.index`, 112
- `rinoh.inline`, 116
- `rinoh.language`, 112
- `rinoh.paper`, 114
- `rinoh.paragraph`, 115
- `rinoh.reference`, 118
- `rinoh.strings`, 120
- `rinoh.structure`, 118
- `rinoh.style`, 120
- `rinoh.stylesheets`, 29
- `rinoh.table`, 121
- `rinoh.template`, 121
- `rinoh.templates.article`, 98
- `rinoh.templates.book`, 100
- `rinoh.text`, 115

Symbols

--list-fonts <filename>
 rinoh command line option, 27

--list-formats
 rinoh command line option, 28

--list-options <frontend>
 rinoh command line option, 28

--list-stylesheets
 rinoh command line option, 27

--list-templates
 rinoh command line option, 27

--version
 rinoh command line option, 28

-f <format>, --format <format>
 rinoh command line option, 27

-h, --help
 rinoh command line option, 27

-o <option=value>, --option <option=value>
 rinoh command line option, 27

-p <paper>, --paper <paper>
 rinoh command line option, 27

-s <name or filename>, --stylesheet <name or filename>
 rinoh command line option, 27

-t <name or filename>, --template <name or filename>
 rinoh command line option, 27

A

A0 (in module rinoh.paper), 114

A1 (in module rinoh.paper), 114

A10 (in module rinoh.paper), 115

A2 (in module rinoh.paper), 114

A3 (in module rinoh.paper), 114

A4 (in module rinoh.paper), 114

A5 (in module rinoh.paper), 114

A6 (in module rinoh.paper), 114

A7 (in module rinoh.paper), 114

A8 (in module rinoh.paper), 114

A9 (in module rinoh.paper), 115

abstract_location (rinoh.templates.article.Article attribute), 99

AbstractLocation (class in rinoh.templates.article), 100

add_page() (rinoh.document.DocumentPart method), 106

Admonition (class in rinoh.structure), 119

AdmonitionStyle (class in rinoh.structure), 91

AdmonitionTitles (class in rinoh.structure), 119

advance() (rinoh.paragraph.LineSpacing method), 117

after_break_background (rinoh.template.PageTemplate attribute), 126

after_break_background (rinoh.template.PageTemplateBase attribute), 128

after_break_background (rinoh.template.TitlePageTemplate attribute), 127

align (rinoh.image.BackgroundImageArgs attribute), 112

align_baselines (rinoh.flowable.LabeledFlowableStyle attribute), 39

AnchorFlowable (class in rinoh.flowable), 108

append() (rinoh.text.MixedStyledText method), 116

Article (class in rinoh.templates.article), 98

attention (rinoh.structure.AdmonitionTitles attribute), 119

B

back_matter (rinoh.templates.book.Book attribute), 101

back_matter_left_page (rinoh.templates.book.Book attribute), 103

back_matter_page (rinoh.templates.book.Book attribute), 102

back_matter_right_page (rinoh.templates.book-
 Book attribute), 103
 background (rinoh.template.PageTemplate
 attribute), 126
 background (rinoh.template.PageTemplateBase
 attribute), 128
 background (rinoh.template.TitlePageTemplate
 attribute), 127
 background_color (rinoh.flowable.FloatStyle
 attribute), 45
 background_color (rinoh.flowable.FlowableStyle
 attribute), 38
 background_color (rinoh.flowable.GroupedFlow-
 ablesStyle attribute), 42
 background_color (rinoh.flowable.Horizon-
 tallyAlignedFlowableStyle attribute), 44
 background_color (rinoh.flowable.LabeledFlow-
 ableStyle attribute), 40
 background_color (rinoh.highlight.CodeBlock-
 Style attribute), 60
 background_color (rinoh.image.CaptionStyle
 attribute), 48
 background_color (rinoh.image.FigureStyle
 attribute), 51, 53
 background_color (rinoh.index.IndexStyle
 attribute), 54
 background_color (rinoh.inline.InlineFlow-
 ableStyle attribute), 64
 background_color (rinoh.paragraph.Paragraph-
 Style attribute), 56
 background_color (rinoh.reference.Referencing-
 ParagraphStyle attribute), 66
 background_color (rinoh.structure.Admonition-
 Style attribute), 92
 background_color (rinoh.structure.HeadingStyle
 attribute), 74
 background_color (rinoh.structure.Horizontal-
 RuleStyle attribute), 94
 background_color (rinoh.structure.ListItemLabel-
 Style attribute), 80
 background_color (rinoh.structure.ListStyle
 attribute), 78
 background_color (rinoh.structure.SectionStyle
 attribute), 71, 72
 background_color (rinoh.structure.TableOfCon-
 tentsEntryStyle attribute), 89
 background_color (rinoh.structure.TableOfCon-
 tentsStyle attribute), 84, 86
 background_color (rinoh.table.TableCellStyle
 attribute), 98
 background_color (rinoh.table.TableStyle
 attribute), 96
 BackgroundImage (class in rinoh.image), 112
 BackgroundImageArgs (class in rinoh.image),
 111
 baseline (rinoh.inline.InlineFlowableStyle
 attribute), 62
 Book (class in rinoh.templates.book), 100
 border (rinoh.flowable.FloatStyle attribute), 45
 border (rinoh.flowable.FlowableStyle attribute),
 38
 border (rinoh.flowable.GroupedFlowablesStyle
 attribute), 42
 border (rinoh.flowable.HorizontallyAlignedFlow-
 ableStyle attribute), 43
 border (rinoh.flowable.LabeledFlowableStyle
 attribute), 40
 border (rinoh.highlight.CodeBlockStyle
 attribute), 59
 border (rinoh.image.CaptionStyle attribute), 47
 border (rinoh.image.FigureStyle attribute), 50, 52
 border (rinoh.index.IndexStyle attribute), 54
 border (rinoh.inline.InlineFlowableStyle
 attribute), 63
 border (rinoh.paragraph.ParagraphStyle
 attribute), 56
 border (rinoh.reference.ReferencingParagraph-
 Style attribute), 65
 border (rinoh.structure.AdmonitionStyle
 attribute), 92
 border (rinoh.structure.HeadingStyle attribute),
 74
 border (rinoh.structure.HorizontalRuleStyle
 attribute), 93
 border (rinoh.structure.ListItemLabelStyle
 attribute), 80
 border (rinoh.structure.ListStyle attribute), 78
 border (rinoh.structure.SectionStyle attribute), 70,
 72
 border (rinoh.structure.TableOfContentsEn-
 tryStyle attribute), 89
 border (rinoh.structure.TableOfContentsStyle
 attribute), 83, 85
 border (rinoh.table.TableCellStyle attribute), 97
 border (rinoh.table.TableStyle attribute), 95
 border_bottom (rinoh.flowable.FloatStyle
 attribute), 45
 border_bottom (rinoh.flowable.FlowableStyle
 attribute), 38
 border_bottom (rinoh.flowable.GroupedFlowab-
 lesStyle attribute), 42
 border_bottom (rinoh.flowable.Horizon-
 tallyAlignedFlowableStyle attribute), 44
 border_bottom (rinoh.flowable.LabeledFlow-
 ableStyle attribute), 40
 border_bottom (rinoh.highlight.CodeBlockStyle
 attribute), 60
 border_bottom (rinoh.image.CaptionStyle

attribute), 47

border_bottom (rinoh.image.FigureStyle attribute), 51, 52

border_bottom (rinoh.index.IndexStyle attribute), 54

border_bottom (rinoh.inline.InlineFlowableStyle attribute), 64

border_bottom (rinoh.paragraph.ParagraphStyle attribute), 56

border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 66

border_bottom (rinoh.structure.AdmonitionStyle attribute), 92

border_bottom (rinoh.structure.HeadingStyle attribute), 74

border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 94

border_bottom (rinoh.structure.ListItemLabelStyle attribute), 80

border_bottom (rinoh.structure.ListStyle attribute), 78

border_bottom (rinoh.structure.SectionStyle attribute), 71, 72

border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 89

border_bottom (rinoh.structure.TableOfContentsStyle attribute), 84, 86

border_bottom (rinoh.table.TableCellStyle attribute), 97

border_bottom (rinoh.table.TableStyle attribute), 96

border_left (rinoh.flowable.FloatStyle attribute), 45

border_left (rinoh.flowable.FlowableStyle attribute), 38

border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 42

border_left (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43

border_left (rinoh.flowable.LabeledFlowableStyle attribute), 40

border_left (rinoh.highlight.CodeBlockStyle attribute), 59

border_left (rinoh.image.CaptionStyle attribute), 47

border_left (rinoh.image.FigureStyle attribute), 51, 52

border_left (rinoh.index.IndexStyle attribute), 54

border_left (rinoh.inline.InlineFlowableStyle attribute), 64

border_left (rinoh.paragraph.ParagraphStyle attribute), 56

border_left (rinoh.reference.ReferencingParagraphStyle attribute), 66

border_left (rinoh.structure.AdmonitionStyle attribute), 92

border_left (rinoh.structure.HeadingStyle attribute), 74

border_left (rinoh.structure.HorizontalRuleStyle attribute), 93

border_left (rinoh.structure.ListItemLabelStyle attribute), 80

border_left (rinoh.structure.ListStyle attribute), 78

border_left (rinoh.structure.SectionStyle attribute), 70, 72

border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 89

border_left (rinoh.structure.TableOfContentsStyle attribute), 84, 85

border_left (rinoh.table.TableCellStyle attribute), 97

border_left (rinoh.table.TableStyle attribute), 95

border_right (rinoh.flowable.FloatStyle attribute), 45

border_right (rinoh.flowable.FlowableStyle attribute), 38

border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 42

border_right (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43

border_right (rinoh.flowable.LabeledFlowableStyle attribute), 40

border_right (rinoh.highlight.CodeBlockStyle attribute), 59

border_right (rinoh.image.CaptionStyle attribute), 47

border_right (rinoh.image.FigureStyle attribute), 51, 52

border_right (rinoh.index.IndexStyle attribute), 54

border_right (rinoh.inline.InlineFlowableStyle attribute), 64

border_right (rinoh.paragraph.ParagraphStyle attribute), 56

border_right (rinoh.reference.ReferencingParagraphStyle attribute), 66

border_right (rinoh.structure.AdmonitionStyle attribute), 92

border_right (rinoh.structure.HeadingStyle attribute), 74

border_right (rinoh.structure.HorizontalRuleStyle attribute), 93

border_right (rinoh.structure.ListItemLabelStyle attribute), 80

border_right (rinoh.structure.ListStyle attribute), 78

border_right (rinoh.structure.SectionStyle attribute), 70, 72

attribute), 70, 72
border_right (rinoh.structure.TableOfContentsEntryStyle attribute), 89
border_right (rinoh.structure.TableOfContentsStyle attribute), 84, 86
border_right (rinoh.table.TableCellStyle attribute), 97
border_right (rinoh.table.TableStyle attribute), 95
border_top (rinoh.flowable.FloatStyle attribute), 45
border_top (rinoh.flowable.FlowableStyle attribute), 38
border_top (rinoh.flowable.GroupedFlowablesStyle attribute), 42
border_top (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 44
border_top (rinoh.flowable.LabeledFlowableStyle attribute), 40
border_top (rinoh.highlight.CodeBlockStyle attribute), 60
border_top (rinoh.image.CaptionStyle attribute), 47
border_top (rinoh.image.FigureStyle attribute), 51, 52
border_top (rinoh.index.IndexStyle attribute), 54
border_top (rinoh.inline.InlineFlowableStyle attribute), 64
border_top (rinoh.paragraph.ParagraphStyle attribute), 56
border_top (rinoh.reference.ReferencingParagraphStyle attribute), 66
border_top (rinoh.structure.AdmonitionStyle attribute), 92
border_top (rinoh.structure.HeadingStyle attribute), 74
border_top (rinoh.structure.HorizontalRuleStyle attribute), 94
border_top (rinoh.structure.ListItemLabelStyle attribute), 80
border_top (rinoh.structure.ListStyle attribute), 78
border_top (rinoh.structure.SectionStyle attribute), 71, 72
border_top (rinoh.structure.TableOfContentsEntryStyle attribute), 89
border_top (rinoh.structure.TableOfContentsStyle attribute), 84, 86
border_top (rinoh.table.TableCellStyle attribute), 97
border_top (rinoh.table.TableStyle attribute), 96
bottom_margin (rinoh.template.PageTemplate attribute), 126
bottom_margin (rinoh.template.PageTemplateBase attribute), 128

bottom_margin (rinoh.template.TitlePageTemplate attribute), 127
bullet (rinoh.structure.ListStyle attribute), 76

C

CaptionStyle (class in rinoh.image), 46
caution (rinoh.structure.AdmonitionTitles attribute), 119
chapter (rinoh.structure.SectionTitles attribute), 118
chapter_footer_text (rinoh.template.PageTemplate attribute), 125
chapter_header_text (rinoh.template.PageTemplate attribute), 125
chapter_title_flowables (rinoh.template.PageTemplate attribute), 125
chapter_title_height (rinoh.template.PageTemplate attribute), 125
CM (in module rinoh.dimension), 106
CodeBlockStyle (class in rinoh.highlight), 58
column_spacing (rinoh.template.PageTemplate attribute), 125
columns (rinoh.template.PageTemplate attribute), 125
contents (rinoh.structure.SectionTitles attribute), 118
contents (rinoh.templates.article.Article attribute), 99
contents (rinoh.templates.book.Book attribute), 101
contents_left_page (rinoh.templates.book.Book attribute), 102
contents_page (rinoh.templates.article.Article attribute), 99
contents_page (rinoh.templates.book.Book attribute), 102
contents_right_page (rinoh.templates.book.Book attribute), 102
ContentsPartTemplate (class in rinoh.template), 124
cover (rinoh.templates.book.Book attribute), 100
cover_page (rinoh.templates.book.Book attribute), 101
create_outlines() (rinoh.document.Document method), 106
custom_label (rinoh.image.CaptionStyle attribute), 49
custom_label (rinoh.reference.NoteMarkerStyle attribute), 69
custom_label (rinoh.structure.HeadingStyle attribute), 76
custom_label (rinoh.structure.ListItemLabelStyle attribute), 82

custom_label (rinoh.structure.ListStyle attribute), 78

D

danger (rinoh.structure.AdmonitionTitles attribute), 119
 DEFAULT (in module rinoh.paragraph), 117
 DefaultSpacing (class in rinoh.paragraph), 117
 DefinitionList (class in rinoh.structure), 119
 depth (rinoh.structure.TableOfContentsStyle attribute), 82
 Dimension (class in rinoh.dimension), 105
 Document (class in rinoh.document), 106
 document() (rinoh.template.TemplateConfiguration method), 122
 DocumentPart (class in rinoh.document), 106
 DocumentPartTemplate (class in rinoh.template), 123
 DocumentTemplate (class in rinoh.template), 121
 DocumentTree (class in rinoh.document), 106
 DOUBLE (in module rinoh.paragraph), 117
 dpi (rinoh.image.BackgroundImageArgs attribute), 111
 drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 124
 drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 123
 drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 124
 drop_if_empty (rinoh.template.TitlePartTemplate attribute), 123
 DummyFlowable (class in rinoh.flowable), 108

E

EN (in module rinoh.language), 112
 encoding (rinoh.font.Font attribute), 110
 end_at_page (rinoh.template.ContentsPartTemplate attribute), 124
 end_at_page (rinoh.template.DocumentPartTemplate attribute), 123
 end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 124
 end_at_page (rinoh.template.TitlePartTemplate attribute), 123
 environment variable
 PATH, 7
 error (rinoh.structure.AdmonitionTitles attribute), 119
 extra (rinoh.template.TitlePageTemplate attribute), 127

F

FigureStyle (class in rinoh.image), 49

fill_color (rinoh.draw.ShapeStyle attribute), 37
 fill_color (rinoh.table.TableCellBackgroundStyle attribute), 98
 FixedDocumentPartTemplate (class in rinoh.template), 124
 FixedSpacing (class in rinoh.paragraph), 117
 Float (class in rinoh.flowable), 109
 float (rinoh.flowable.FloatStyle attribute), 44
 float (rinoh.image.FigureStyle attribute), 49
 FloatStyle (class in rinoh.flowable), 44
 Flowable (class in rinoh.flowable), 108
 flowable_spacing (rinoh.flowable.GroupedFlowablesStyle attribute), 41
 flowable_spacing (rinoh.image.FigureStyle attribute), 51
 flowable_spacing (rinoh.index.IndexStyle attribute), 53
 flowable_spacing (rinoh.structure.AdmonitionStyle attribute), 91
 flowable_spacing (rinoh.structure.ListStyle attribute), 77
 flowable_spacing (rinoh.structure.SectionStyle attribute), 69
 flowable_spacing (rinoh.structure.TableOfContentsStyle attribute), 82
 flowable_spacing (rinoh.table.TableCellStyle attribute), 96
 flowables (rinoh.template.FixedDocumentPartTemplate attribute), 124
 flowables() (rinoh.flowable.GroupedFlowables method), 109
 FlowableState (class in rinoh.flowable), 108
 FlowableStyle (class in rinoh.flowable), 37
 Font (class in rinoh.font), 110
 font_color (rinoh.highlight.CodeBlockStyle attribute), 60
 font_color (rinoh.image.CaptionStyle attribute), 48
 font_color (rinoh.paragraph.ParagraphStyle attribute), 57
 font_color (rinoh.reference.NoteMarkerStyle attribute), 68
 font_color (rinoh.reference.ReferencingParagraphStyle attribute), 66
 font_color (rinoh.structure.HeadingStyle attribute), 75
 font_color (rinoh.structure.ListItemLabelStyle attribute), 81
 font_color (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 font_color (rinoh.structure.TableOfContentsStyle attribute), 86
 font_color (rinoh.text.TextStyle attribute), 62
 font_size (rinoh.highlight.CodeBlockStyle

- attribute), 60
- font_size (rinoh.image.CaptionStyle attribute), 48
- font_size (rinoh.paragraph.ParagraphStyle attribute), 57
- font_size (rinoh.reference.NoteMarkerStyle attribute), 68
- font_size (rinoh.reference.ReferencingParagraphStyle attribute), 66
- font_size (rinoh.structure.HeadingStyle attribute), 75
- font_size (rinoh.structure.ListItemLabelStyle attribute), 81
- font_size (rinoh.structure.TableOfContentsEntryStyle attribute), 90
- font_size (rinoh.structure.TableOfContentsStyle attribute), 86
- font_size (rinoh.text.TextStyle attribute), 61
- font_slant (rinoh.highlight.CodeBlockStyle attribute), 60
- font_slant (rinoh.image.CaptionStyle attribute), 48
- font_slant (rinoh.paragraph.ParagraphStyle attribute), 57
- font_slant (rinoh.reference.NoteMarkerStyle attribute), 68
- font_slant (rinoh.reference.ReferencingParagraphStyle attribute), 66
- font_slant (rinoh.structure.HeadingStyle attribute), 75
- font_slant (rinoh.structure.ListItemLabelStyle attribute), 81
- font_slant (rinoh.structure.TableOfContentsEntryStyle attribute), 89
- font_slant (rinoh.structure.TableOfContentsStyle attribute), 86
- font_slant (rinoh.text.TextStyle attribute), 61
- font_variant (rinoh.highlight.CodeBlockStyle attribute), 60
- font_variant (rinoh.image.CaptionStyle attribute), 48
- font_variant (rinoh.paragraph.ParagraphStyle attribute), 57
- font_variant (rinoh.reference.NoteMarkerStyle attribute), 68
- font_variant (rinoh.reference.ReferencingParagraphStyle attribute), 67
- font_variant (rinoh.structure.HeadingStyle attribute), 75
- font_variant (rinoh.structure.ListItemLabelStyle attribute), 81
- font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 90
- font_variant (rinoh.structure.TableOfContentsStyle attribute), 86
- font_weight (rinoh.text.TextStyle attribute), 62
- font_weight (rinoh.highlight.CodeBlockStyle attribute), 60
- font_weight (rinoh.image.CaptionStyle attribute), 48
- font_weight (rinoh.paragraph.ParagraphStyle attribute), 56
- font_weight (rinoh.reference.NoteMarkerStyle attribute), 67
- font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 66
- font_weight (rinoh.structure.HeadingStyle attribute), 75
- font_weight (rinoh.structure.ListItemLabelStyle attribute), 81
- font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 89
- font_weight (rinoh.structure.TableOfContentsStyle attribute), 86
- font_weight (rinoh.text.TextStyle attribute), 61
- font_width (rinoh.highlight.CodeBlockStyle attribute), 60
- font_width (rinoh.image.CaptionStyle attribute), 48
- font_width (rinoh.paragraph.ParagraphStyle attribute), 57
- font_width (rinoh.reference.NoteMarkerStyle attribute), 68
- font_width (rinoh.reference.ReferencingParagraphStyle attribute), 66
- font_width (rinoh.structure.HeadingStyle attribute), 75
- font_width (rinoh.structure.ListItemLabelStyle attribute), 81
- font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 90
- font_width (rinoh.structure.TableOfContentsStyle attribute), 86
- font_width (rinoh.text.TextStyle attribute), 61
- fonts() (rinoh.font.Typeface method), 111
- footer_text (rinoh.template.PageTemplate attribute), 125
- FR (in module rinoh.language), 113
- front_matter (rinoh.templates.article.Article attribute), 99
- front_matter (rinoh.templates.book.Book attribute), 100
- front_matter_left_page (rinoh.templates.book.-Book attribute), 102
- front_matter_page (rinoh.templates.article.Article attribute), 99
- front_matter_page (rinoh.templates.book.Book attribute), 101
- front_matter_right_page (rinoh.templates.book.-

Book attribute), 101

G

get_font() (rinoh.font.Typeface method), 111
 get_glyph() (rinoh.font.Font method), 110
 get_kerning() (rinoh.font.Font method), 110
 get_ligature() (rinoh.font.Font method), 110
 get_position() (rinoh.paragraph.TabStop method), 117
 get_selector() (rinoh.style.StyleSheet method), 121
 Glyph (class in rinoh.paragraph), 117
 GlyphsSpan (class in rinoh.paragraph), 117
 GroupedFlowables (class in rinoh.flowable), 109
 GroupedFlowablesState (class in rinoh.flowable), 109
 GroupedFlowablesStyle (class in rinoh.flowable), 40
 GroupedLabeledFlowables (class in rinoh.flowable), 109
 grow() (rinoh.dimension.Dimension method), 105

H

header_footer_distance (rinoh.template.PageTemplate attribute), 125
 header_text (rinoh.template.PageTemplate attribute), 125
 Heading (class in rinoh.structure), 118
 HeadingStyle (class in rinoh.structure), 72
 height (rinoh.image.BackgroundImageArgs attribute), 111
 height() (rinoh.text.StyledText method), 116
 hint (rinoh.structure.AdmonitionTitles attribute), 119
 horizontal_align (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 42
 horizontal_align (rinoh.table.TableStyle attribute), 94
 HorizontallyAlignedFlowable (class in rinoh.flowable), 109
 HorizontallyAlignedFlowableState (class in rinoh.flowable), 109
 HorizontallyAlignedFlowableStyle (class in rinoh.flowable), 42
 HorizontalRule (class in rinoh.structure), 120
 HorizontalRuleStyle (class in rinoh.structure), 92
 hyphen_chars (rinoh.highlight.CodeBlockStyle attribute), 61
 hyphen_chars (rinoh.image.CaptionStyle attribute), 49
 hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 57
 hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 68
 hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 67
 hyphen_chars (rinoh.structure.HeadingStyle attribute), 76
 hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 82
 hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 87
 hyphen_chars (rinoh.text.TextStyle attribute), 62
 hyphen_lang (rinoh.highlight.CodeBlockStyle attribute), 61
 hyphen_lang (rinoh.image.CaptionStyle attribute), 49
 hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 58
 hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 68
 hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 67
 hyphen_lang (rinoh.structure.HeadingStyle attribute), 76
 hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 82
 hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 87
 hyphen_lang (rinoh.text.TextStyle attribute), 62
 hyphenate (rinoh.highlight.CodeBlockStyle attribute), 58
 hyphenate (rinoh.image.CaptionStyle attribute), 49
 hyphenate (rinoh.paragraph.ParagraphStyle attribute), 57
 hyphenate (rinoh.reference.NoteMarkerStyle attribute), 68
 hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 67
 hyphenate (rinoh.structure.HeadingStyle attribute), 75
 hyphenate (rinoh.structure.ListItemLabelStyle attribute), 82
 hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 hyphenate (rinoh.structure.TableOfContentsStyle attribute), 87
 hyphenate (rinoh.text.TextStyle attribute), 62
 HyphenatorStore (class in rinoh.paragraph), 118

I

important (rinoh.structure.AdmonitionTitles attribute), 119
 INCH (in module rinoh.dimension), 105
 indent_first (rinoh.highlight.CodeBlockStyle attribute), 58
 indent_first (rinoh.image.CaptionStyle attribute), 46
 indent_first (rinoh.paragraph.ParagraphStyle attribute), 55
 indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 64
 indent_first (rinoh.structure.HeadingStyle attribute), 73
 indent_first (rinoh.structure.ListItemLabelStyle attribute), 79
 indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 87
 indent_first (rinoh.structure.TableOfContentsStyle attribute), 84
 index (rinoh.structure.SectionTitles attribute), 118
 IndexStyle (class in rinoh.index), 53
 initials (rinoh.index.IndexStyle attribute), 53
 inline_title (rinoh.structure.AdmonitionStyle attribute), 91
 InlineFlowable (class in rinoh.inline), 116
 InlineFlowableStyle (class in rinoh.inline), 62
 input
 rinoh command line option, 27
 is_script() (rinoh.text.StyledText method), 116
 IT (in module rinoh.language), 113
 items (rinoh.text.StyledText attribute), 116

J

JUNIOR_LEGAL (in module rinoh.paper), 115

K

keep_with_next (rinoh.flowable.FloatStyle attribute), 45
 keep_with_next (rinoh.flowable.FlowableStyle attribute), 38
 keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 41
 keep_with_next (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
 keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 40
 keep_with_next (rinoh.highlight.CodeBlockStyle attribute), 59
 keep_with_next (rinoh.image.CaptionStyle attribute), 47
 keep_with_next (rinoh.image.FigureStyle

attribute), 50, 52
 keep_with_next (rinoh.index.IndexStyle attribute), 54
 keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 63
 keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 56
 keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 65
 keep_with_next (rinoh.structure.AdmonitionStyle attribute), 92
 keep_with_next (rinoh.structure.HeadingStyle attribute), 73
 keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 93
 keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 80
 keep_with_next (rinoh.structure.ListStyle attribute), 77
 keep_with_next (rinoh.structure.SectionStyle attribute), 70, 72
 keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 89
 keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 83, 85
 keep_with_next (rinoh.table.TableCellStyle attribute), 97
 keep_with_next (rinoh.table.TableStyle attribute), 95
 kerning (rinoh.highlight.CodeBlockStyle attribute), 61
 kerning (rinoh.image.CaptionStyle attribute), 48
 kerning (rinoh.paragraph.ParagraphStyle attribute), 57
 kerning (rinoh.reference.NoteMarkerStyle attribute), 68
 kerning (rinoh.reference.ReferencingParagraphStyle attribute), 67
 kerning (rinoh.structure.HeadingStyle attribute), 75
 kerning (rinoh.structure.ListItemLabelStyle attribute), 81
 kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 kerning (rinoh.structure.TableOfContentsStyle attribute), 87
 kerning (rinoh.text.TextStyle attribute), 62

L

label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 39
 label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 38

label_prefix (rinoh.image.CaptionStyle attribute), 49

label_prefix (rinoh.reference.NoteMarkerStyle attribute), 69

label_prefix (rinoh.structure.HeadingStyle attribute), 76

label_prefix (rinoh.structure.ListItemLabelStyle attribute), 82

label_prefix (rinoh.structure.ListStyle attribute), 78

label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 39

label_suffix (rinoh.image.CaptionStyle attribute), 49

label_suffix (rinoh.reference.NoteMarkerStyle attribute), 69

label_suffix (rinoh.structure.HeadingStyle attribute), 76

label_suffix (rinoh.structure.ListItemLabelStyle attribute), 82

label_suffix (rinoh.structure.ListStyle attribute), 78

LabeledFlowable (class in rinoh.flowable), 108

LabeledFlowableState (class in rinoh.flowable), 109

LabeledFlowableStyle (class in rinoh.flowable), 38

Language (class in rinoh.language), 112

language (rinoh.template.DocumentTemplate attribute), 122

language (rinoh.templates.article.Article attribute), 99

language (rinoh.templates.book.Book attribute), 100

languages (rinoh.language.Language attribute), 112

Leading (class in rinoh.paragraph), 117

LEDGER (in module rinoh.paper), 115

left_margin (rinoh.template.PageTemplate attribute), 126

left_margin (rinoh.template.PageTemplateBase attribute), 128

left_margin (rinoh.template.TitlePageTemplate attribute), 127

LEGAL (in module rinoh.paper), 115

LETTER (in module rinoh.paper), 115

ligatures (rinoh.highlight.CodeBlockStyle attribute), 58

ligatures (rinoh.image.CaptionStyle attribute), 49

ligatures (rinoh.paragraph.ParagraphStyle attribute), 57

ligatures (rinoh.reference.NoteMarkerStyle attribute), 68

ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 67

ligatures (rinoh.structure.HeadingStyle attribute), 75

ligatures (rinoh.structure.ListItemLabelStyle attribute), 81

ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 90

ligatures (rinoh.structure.TableOfContentsStyle attribute), 87

ligatures (rinoh.text.TextStyle attribute), 62

limit_width (rinoh.image.BackgroundImageArgs attribute), 112

Line (class in rinoh.draw), 107

line_spacing (rinoh.highlight.CodeBlockStyle attribute), 58

line_spacing (rinoh.image.CaptionStyle attribute), 46

line_spacing (rinoh.paragraph.ParagraphStyle attribute), 55

line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 64

line_spacing (rinoh.structure.HeadingStyle attribute), 73

line_spacing (rinoh.structure.ListItemLabelStyle attribute), 79

line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 87

line_spacing (rinoh.structure.TableOfContentsStyle attribute), 84

LineSpacing (class in rinoh.paragraph), 116

LineStyle (class in rinoh.draw), 36

List (class in rinoh.structure), 118

ListItemLabelStyle (class in rinoh.structure), 79

ListStyle (class in rinoh.structure), 76

M

margin_left (rinoh.flowable.FloatStyle attribute), 44

margin_left (rinoh.flowable.FlowableStyle attribute), 37

margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 41

margin_left (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43

margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 39

margin_left (rinoh.highlight.CodeBlockStyle attribute), 59

margin_left (rinoh.image.CaptionStyle attribute), 46

margin_left (rinoh.image.FigureStyle attribute), 50, 51

margin_left (rinoh.index.IndexStyle attribute), 53

margin_left (rinoh.inline.InlineFlowableStyle

attribute), 63
margin_left (rinoh.paragraph.ParagraphStyle attribute), 55
margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 65
margin_left (rinoh.structure.AdmonitionStyle attribute), 91
margin_left (rinoh.structure.HeadingStyle attribute), 73
margin_left (rinoh.structure.HorizontalRuleStyle attribute), 93
margin_left (rinoh.structure.ListItemLabelStyle attribute), 79
margin_left (rinoh.structure.ListStyle attribute), 77
margin_left (rinoh.structure.SectionStyle attribute), 70, 71
margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 88
margin_left (rinoh.structure.TableOfContentsStyle attribute), 83, 85
margin_left (rinoh.table.TableCellStyle attribute), 96
margin_left (rinoh.table.TableStyle attribute), 95
margin_right (rinoh.flowable.FloatStyle attribute), 44
margin_right (rinoh.flowable.FlowableStyle attribute), 37
margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 41
margin_right (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 39
margin_right (rinoh.highlight.CodeBlockStyle attribute), 59
margin_right (rinoh.image.CaptionStyle attribute), 47
margin_right (rinoh.image.FigureStyle attribute), 50, 51
margin_right (rinoh.index.IndexStyle attribute), 53
margin_right (rinoh.inline.InlineFlowableStyle attribute), 63
margin_right (rinoh.paragraph.ParagraphStyle attribute), 55
margin_right (rinoh.reference.ReferencingParagraphStyle attribute), 65
margin_right (rinoh.structure.AdmonitionStyle attribute), 91
margin_right (rinoh.structure.HeadingStyle attribute), 73
margin_right (rinoh.structure.HorizontalRuleStyle attribute), 93

margin_right (rinoh.structure.ListItemLabelStyle attribute), 79
margin_right (rinoh.structure.ListStyle attribute), 77
margin_right (rinoh.structure.SectionStyle attribute), 70, 71
margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 88
margin_right (rinoh.structure.TableOfContentsStyle attribute), 83, 85
margin_right (rinoh.table.TableCellStyle attribute), 97
margin_right (rinoh.table.TableStyle attribute), 95
matcher (in module rinoh.stylesheets), 29
MixedStyledText (class in rinoh.text), 116
MM (in module rinoh.dimension), 105

N

new_page() (rinoh.document.DocumentPart method), 107
NL (in module rinoh.language), 114
note (rinoh.structure.AdmonitionTitles attribute), 119
NoteMarkerStyle (class in rinoh.reference), 67
number_format (rinoh.image.CaptionStyle attribute), 49
number_format (rinoh.reference.NoteMarkerStyle attribute), 69
number_format (rinoh.structure.HeadingStyle attribute), 76
number_format (rinoh.structure.ListStyle attribute), 78
number_separator (rinoh.image.CaptionStyle attribute), 46
number_separator (rinoh.structure.HeadingStyle attribute), 72
numbering_level (rinoh.image.CaptionStyle attribute), 46

O

ordered (rinoh.structure.ListStyle attribute), 76

P

padding_bottom (rinoh.flowable.FloatStyle attribute), 45
padding_bottom (rinoh.flowable.FlowableStyle attribute), 38
padding_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 41
padding_bottom (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
padding_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 40

- padding_bottom (rinoh.highlight.CodeBlockStyle attribute), 59
- padding_bottom (rinoh.image.CaptionStyle attribute), 47
- padding_bottom (rinoh.image.FigureStyle attribute), 50, 52
- padding_bottom (rinoh.index.IndexStyle attribute), 54
- padding_bottom (rinoh.inline.InlineFlowableStyle attribute), 63
- padding_bottom (rinoh.paragraph.ParagraphStyle attribute), 56
- padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 65
- padding_bottom (rinoh.structure.AdmonitionStyle attribute), 92
- padding_bottom (rinoh.structure.HeadingStyle attribute), 74
- padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 93
- padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 80
- padding_bottom (rinoh.structure.ListStyle attribute), 77
- padding_bottom (rinoh.structure.SectionStyle attribute), 70, 72
- padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 88
- padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 83, 85
- padding_bottom (rinoh.table.TableCellStyle attribute), 97
- padding_bottom (rinoh.table.TableStyle attribute), 95
- padding_left (rinoh.flowable.FloatStyle attribute), 44
- padding_left (rinoh.flowable.FlowableStyle attribute), 37
- padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 41
- padding_left (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
- padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 39
- padding_left (rinoh.highlight.CodeBlockStyle attribute), 59
- padding_left (rinoh.image.CaptionStyle attribute), 47
- padding_left (rinoh.image.FigureStyle attribute), 50, 52
- padding_left (rinoh.index.IndexStyle attribute), 53
- padding_left (rinoh.inline.InlineFlowableStyle attribute), 63
- padding_left (rinoh.paragraph.ParagraphStyle attribute), 55
- padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 65
- padding_left (rinoh.structure.AdmonitionStyle attribute), 91
- padding_left (rinoh.structure.HeadingStyle attribute), 74
- padding_left (rinoh.structure.HorizontalRuleStyle attribute), 93
- padding_left (rinoh.structure.ListItemLabelStyle attribute), 80
- padding_left (rinoh.structure.ListStyle attribute), 77
- padding_left (rinoh.structure.SectionStyle attribute), 70, 71
- padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 88
- padding_left (rinoh.structure.TableOfContentsStyle attribute), 83, 85
- padding_left (rinoh.table.TableCellStyle attribute), 97
- padding_left (rinoh.table.TableStyle attribute), 95
- padding_right (rinoh.flowable.FloatStyle attribute), 45
- padding_right (rinoh.flowable.FlowableStyle attribute), 37
- padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 41
- padding_right (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
- padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 39
- padding_right (rinoh.highlight.CodeBlockStyle attribute), 59
- padding_right (rinoh.image.CaptionStyle attribute), 47
- padding_right (rinoh.image.FigureStyle attribute), 50, 52
- padding_right (rinoh.index.IndexStyle attribute), 53
- padding_right (rinoh.inline.InlineFlowableStyle attribute), 63
- padding_right (rinoh.paragraph.ParagraphStyle attribute), 55
- padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 65
- padding_right (rinoh.structure.AdmonitionStyle attribute), 91
- padding_right (rinoh.structure.HeadingStyle attribute), 74
- padding_right (rinoh.structure.HorizontalRuleStyle attribute), 93
- padding_right (rinoh.structure.ListItemLabel-

- Style attribute), 80
- padding_right (rinoh.structure.ListStyle attribute), 77
- padding_right (rinoh.structure.SectionStyle attribute), 70, 71
- padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 88
- padding_right (rinoh.structure.TableOfContentsStyle attribute), 83, 85
- padding_right (rinoh.table.TableCellStyle attribute), 97
- padding_right (rinoh.table.TableStyle attribute), 95
- padding_top (rinoh.flowable.FloatStyle attribute), 45
- padding_top (rinoh.flowable.FlowableStyle attribute), 38
- padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 41
- padding_top (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
- padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 40
- padding_top (rinoh.highlight.CodeBlockStyle attribute), 59
- padding_top (rinoh.image.CaptionStyle attribute), 47
- padding_top (rinoh.image.FigureStyle attribute), 50, 52
- padding_top (rinoh.index.IndexStyle attribute), 54
- padding_top (rinoh.inline.InlineFlowableStyle attribute), 63
- padding_top (rinoh.paragraph.ParagraphStyle attribute), 56
- padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 65
- padding_top (rinoh.structure.AdmonitionStyle attribute), 91
- padding_top (rinoh.structure.HeadingStyle attribute), 74
- padding_top (rinoh.structure.HorizontalRuleStyle attribute), 93
- padding_top (rinoh.structure.ListItemLabelStyle attribute), 80
- padding_top (rinoh.structure.ListStyle attribute), 77
- padding_top (rinoh.structure.SectionStyle attribute), 70, 72
- padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 88
- padding_top (rinoh.structure.TableOfContentsStyle attribute), 83, 85
- padding_top (rinoh.table.TableCellStyle attribute), 97
- padding_top (rinoh.table.TableStyle attribute), 95
- Page (class in rinoh.document), 107
- page (rinoh.document.Page attribute), 107
- page (rinoh.templates.article.Article attribute), 99
- page (rinoh.templates.book.Book attribute), 101
- page_break (rinoh.structure.SectionStyle attribute), 71
- page_number_format (rinoh.template.ContentsPartTemplate attribute), 124
- page_number_format (rinoh.template.DocumentPartTemplate attribute), 123
- page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 124
- page_number_format (rinoh.template.TitlePartTemplate attribute), 123
- page_orientation (rinoh.template.PageTemplate attribute), 126
- page_orientation (rinoh.template.PageTemplateBase attribute), 128
- page_orientation (rinoh.template.TitlePageTemplate attribute), 127
- page_size (rinoh.template.PageTemplate attribute), 126
- page_size (rinoh.template.PageTemplateBase attribute), 128
- page_size (rinoh.template.TitlePageTemplate attribute), 127
- PageBreak (class in rinoh.flowable), 108
- PageOrientation (class in rinoh.document), 107
- PageTemplate (class in rinoh.template), 125
- PageTemplateBase (class in rinoh.template), 128
- PageType (class in rinoh.document), 107
- Paper (class in rinoh.paper), 114
- Paragraph (class in rinoh.paragraph), 115
- ParagraphBase (class in rinoh.paragraph), 115
- ParagraphState (class in rinoh.paragraph), 115
- ParagraphStyle (class in rinoh.paragraph), 54
- parts (rinoh.template.DocumentTemplate attribute), 122
- parts (rinoh.templates.article.Article attribute), 99
- parts (rinoh.templates.book.Book attribute), 100
- PartsList (class in rinoh.template), 123
- PATH, 7
- PERCENT (in module rinoh.dimension), 106
- PICA (in module rinoh.dimension), 105
- position (rinoh.highlight.CodeBlockStyle attribute), 61
- position (rinoh.image.CaptionStyle attribute), 48
- position (rinoh.paragraph.ParagraphStyle attribute), 57
- position (rinoh.reference.NoteMarkerStyle attribute), 68
- position (rinoh.reference.ReferencingParagraph-

Style attribute), 67
 position (rinoh.structure.HeadingStyle attribute), 75
 position (rinoh.structure.ListItemLabelStyle attribute), 81
 position (rinoh.structure.TableOfContentsEntryStyle attribute), 90
 position (rinoh.structure.TableOfContentsStyle attribute), 87
 position (rinoh.text.TextStyle attribute), 62
 ProportionalSpacing (class in rinoh.paragraph), 117
 PT (in module rinoh.dimension), 105

Q

QUARTERS (in module rinoh.dimension), 106

R

ReferenceType (class in rinoh.reference), 118
 ReferencingParagraphStyle (class in rinoh.reference), 64
 render() (rinoh.document.Document method), 106
 render() (rinoh.paragraph.ParagraphBase method), 115
 repeat_head (rinoh.table.TableStyle attribute), 94
 right_margin (rinoh.template.PageTemplate attribute), 126
 right_margin (rinoh.template.PageTemplateBase attribute), 128
 right_margin (rinoh.template.TitlePageTemplate attribute), 127
 rinoh command line option
 --list-fonts <filename>, 27
 --list-formats, 28
 --list-options <frontend>, 28
 --list-stylesheets, 27
 --list-templates, 27
 --version, 28
 -f <format>, --format <format>, 27
 -h, --help, 27
 -o <option=value>, --option <option=value>, 27
 -p <paper>, --paper <paper>, 27
 -s <name or filename>, --stylesheet <name or filename>, 27
 -t <name or filename>, --template <name or filename>, 27
 input, 27
 rinoh.dimension (module), 105
 rinoh.document (module), 106
 rinoh.draw (module), 107
 rinoh.flowable (module), 108

rinoh.font (module), 110
 rinoh.image (module), 111
 rinoh.index (module), 112
 rinoh.inline (module), 116
 rinoh.language (module), 112
 rinoh.paper (module), 114
 rinoh.paragraph (module), 115
 rinoh.reference (module), 118
 rinoh.strings (module), 120
 rinoh.structure (module), 118
 rinoh.style (module), 120
 rinoh.stylesheets (module), 29
 rinoh.table (module), 121
 rinoh.template (module), 121
 rinoh.templates.article (module), 98
 rinoh.templates.book (module), 100
 rinoh.text (module), 115
 rinoh_documents
 Sphinx builder configuration value, 28
 rinoh_domain_indices
 Sphinx builder configuration value, 29
 rinoh_logo
 Sphinx builder configuration value, 28
 rinoh_paper_size
 Sphinx builder configuration value, 28
 rinoh_stylesheet
 Sphinx builder configuration value, 28
 rinoh_template
 Sphinx builder configuration value, 28
 rotate (rinoh.image.BackgroundImageArgs attribute), 111

S

Scale (class in rinoh.image), 111
 scale (rinoh.image.BackgroundImageArgs attribute), 111
 script_level() (rinoh.text.StyledText method), 116
 Section (class in rinoh.structure), 118
 SectionStyle (class in rinoh.structure), 69
 SectionTitles (class in rinoh.structure), 118
 seealso (rinoh.structure.AdmonitionTitles attribute), 120
 SetMetadataFlowable (class in rinoh.flowable), 108
 Shape (class in rinoh.draw), 107
 ShapeStyle (class in rinoh.draw), 37
 show_author (rinoh.template.TitlePageTemplate attribute), 127
 show_date (rinoh.template.TitlePageTemplate attribute), 126
 show_in_toc (rinoh.structure.SectionStyle attribute), 69
 SINGLE (in module rinoh.paragraph), 117

SingleStyledText (class in rinoh.text), 116
 space_above (rinoh.flowable.FloatStyle attribute), 44
 space_above (rinoh.flowable.FlowableStyle attribute), 37
 space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 41
 space_above (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 42
 space_above (rinoh.flowable.LabeledFlowableStyle attribute), 39
 space_above (rinoh.highlight.CodeBlockStyle attribute), 58
 space_above (rinoh.image.CaptionStyle attribute), 46
 space_above (rinoh.image.FigureStyle attribute), 50, 51
 space_above (rinoh.index.IndexStyle attribute), 53
 space_above (rinoh.inline.InlineFlowableStyle attribute), 62
 space_above (rinoh.paragraph.ParagraphStyle attribute), 55
 space_above (rinoh.reference.ReferencingParagraphStyle attribute), 65
 space_above (rinoh.structure.AdmonitionStyle attribute), 91
 space_above (rinoh.structure.HeadingStyle attribute), 73
 space_above (rinoh.structure.HorizontalRuleStyle attribute), 92
 space_above (rinoh.structure.ListItemLabelStyle attribute), 79
 space_above (rinoh.structure.ListStyle attribute), 77
 space_above (rinoh.structure.SectionStyle attribute), 69, 71
 space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 88
 space_above (rinoh.structure.TableOfContentsStyle attribute), 83, 84
 space_above (rinoh.table.TableCellStyle attribute), 96
 space_above (rinoh.table.TableStyle attribute), 94
 space_below (rinoh.flowable.FloatStyle attribute), 44
 space_below (rinoh.flowable.FlowableStyle attribute), 37
 space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 41
 space_below (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 43
 space_below (rinoh.flowable.LabeledFlowableStyle attribute), 39
 space_below (rinoh.highlight.CodeBlockStyle attribute), 59
 space_below (rinoh.image.CaptionStyle attribute), 46
 space_below (rinoh.image.FigureStyle attribute), 50, 51
 space_below (rinoh.index.IndexStyle attribute), 53
 space_below (rinoh.inline.InlineFlowableStyle attribute), 63
 space_below (rinoh.paragraph.ParagraphStyle attribute), 55
 space_below (rinoh.reference.ReferencingParagraphStyle attribute), 65
 space_below (rinoh.structure.AdmonitionStyle attribute), 91
 space_below (rinoh.structure.HeadingStyle attribute), 73
 space_below (rinoh.structure.HorizontalRuleStyle attribute), 93
 space_below (rinoh.structure.ListItemLabelStyle attribute), 79
 space_below (rinoh.structure.ListStyle attribute), 77
 space_below (rinoh.structure.SectionStyle attribute), 70, 71
 space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 88
 space_below (rinoh.structure.TableOfContentsStyle attribute), 83, 85
 space_below (rinoh.table.TableCellStyle attribute), 96
 space_below (rinoh.table.TableStyle attribute), 95
 spans() (rinoh.text.StyledText method), 116
 sphinx (in module rinoh.stylesheets), 29
 Sphinx builder configuration value
 rinoh_documents, 28
 rinoh_domain_indices, 29
 rinoh_logo, 28
 rinoh_paper_size, 28
 rinoh_stylesheets, 28
 rinoh_template, 28
 sphinx_article (in module rinoh.stylesheets), 29
 sphinx_base14 (in module rinoh.stylesheets), 29
 split_minimum_rows (rinoh.table.TableStyle attribute), 94
 STANDARD (in module rinoh.paragraph), 117
 StaticGroupedFlowables (class in rinoh.flowable), 109
 String (class in rinoh.strings), 120
 StringCollection (class in rinoh.strings), 120
 StringField (class in rinoh.strings), 120
 Strings (class in rinoh.strings), 120
 strings (rinoh.template.DocumentTemplate

attribute), 122
 strings (rinoh.templates.article.Article attribute), 99
 strings (rinoh.templates.book.Book attribute), 100
 Stroke (class in rinoh.draw), 107
 stroke (rinoh.draw.LineStyle attribute), 36
 stroke (rinoh.draw.ShapeStyle attribute), 37
 stroke (rinoh.structure.HorizontalRuleStyle attribute), 94
 stroke (rinoh.table.TableCellBackgroundStyle attribute), 98
 stroke (rinoh.table.TableCellBorderStyle attribute), 98
 Style (class in rinoh.style), 120
 style log, 23
 style_class (rinoh.draw.Line attribute), 107
 style_class (rinoh.draw.Shape attribute), 107
 style_class (rinoh.flowable.GroupedFlowables attribute), 109
 style_class (rinoh.flowable.HorizontallyAlignedFlowable attribute), 109
 style_class (rinoh.flowable.LabeledFlowable attribute), 109
 style_class (rinoh.inline.InlineFlowable attribute), 116
 style_class (rinoh.paragraph.ParagraphBase attribute), 115
 style_class (rinoh.structure.Admonition attribute), 119
 style_class (rinoh.structure.Heading attribute), 118
 style_class (rinoh.structure.HorizontalRule attribute), 120
 style_class (rinoh.structure.List attribute), 118
 style_class (rinoh.structure.Section attribute), 118
 style_class (rinoh.structure.TableOfContents attribute), 119
 style_class (rinoh.structure.TableOfContentsEntry attribute), 119
 style_class (rinoh.style.Styled attribute), 120
 style_class (rinoh.text.StyledText attribute), 115
 Styled (class in rinoh.style), 120
 StyledMatcher (class in rinoh.style), 121
 StyledText (class in rinoh.text), 115
 StyleSheet (class in rinoh.style), 121
 stylesheet (rinoh.template.DocumentTemplate attribute), 122
 stylesheet (rinoh.templates.article.Article attribute), 98
 stylesheet (rinoh.templates.book.Book attribute), 100
 StyleSheetFile (class in rinoh.style), 121

T

tab_stops (rinoh.highlight.CodeBlockStyle attribute), 58
 tab_stops (rinoh.image.CaptionStyle attribute), 46
 tab_stops (rinoh.paragraph.ParagraphStyle attribute), 55
 tab_stops (rinoh.reference.ReferencingParagraphStyle attribute), 64
 tab_stops (rinoh.structure.HeadingStyle attribute), 73
 tab_stops (rinoh.structure.ListItemLabelStyle attribute), 79
 tab_stops (rinoh.structure.TableOfContentsEntryStyle attribute), 88
 tab_stops (rinoh.structure.TableOfContentsStyle attribute), 84
 table_of_contents (rinoh.templates.article.Article attribute), 98
 TableCellBackgroundStyle (class in rinoh.table), 98
 TableCellBorderStyle (class in rinoh.table), 98
 TableCellStyle (class in rinoh.table), 96
 TableOfContents (class in rinoh.structure), 119
 TableOfContentsEntry (class in rinoh.structure), 119
 TableOfContentsEntryStyle (class in rinoh.structure), 87
 TableOfContentsSection (class in rinoh.structure), 119
 TableOfContentsStyle (class in rinoh.structure), 82
 TableStyle (class in rinoh.table), 94
 TABLOID (in module rinoh.paper), 115
 TabStop (class in rinoh.paragraph), 117
 template (rinoh.template.TemplateConfiguration attribute), 122
 TemplateConfiguration (class in rinoh.template), 122
 text (rinoh.reference.ReferencingParagraphStyle attribute), 64
 text (rinoh.structure.TableOfContentsEntryStyle attribute), 87
 text_align (rinoh.highlight.CodeBlockStyle attribute), 58
 text_align (rinoh.image.CaptionStyle attribute), 46
 text_align (rinoh.paragraph.ParagraphStyle attribute), 55
 text_align (rinoh.reference.ReferencingParagraphStyle attribute), 64
 text_align (rinoh.structure.HeadingStyle attribute), 73

text_align (rinoh.structure.ListItemLabelStyle attribute), 79

text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 88

text_align (rinoh.structure.TableOfContentsStyle attribute), 84

TextStyle (class in rinoh.text), 61

tip (rinoh.structure.AdmonitionTitles attribute), 119

title (rinoh.flowable.GroupedFlowablesStyle attribute), 40

title (rinoh.image.FigureStyle attribute), 51

title (rinoh.index.IndexStyle attribute), 53

title (rinoh.structure.AdmonitionStyle attribute), 91

title (rinoh.structure.ListStyle attribute), 77

title (rinoh.structure.SectionStyle attribute), 69

title (rinoh.structure.TableOfContentsStyle attribute), 82

title (rinoh.table.TableCellStyle attribute), 96

title (rinoh.templates.article.Article attribute), 99

title (rinoh.templates.book.Book attribute), 100

title_page (rinoh.templates.article.Article attribute), 99

title_page (rinoh.templates.book.Book attribute), 101

TitlePageTemplate (class in rinoh.template), 126

TitlePartTemplate (class in rinoh.template), 123

to_string() (rinoh.text.StyledText method), 116

top_margin (rinoh.template.PageTemplate attribute), 126

top_margin (rinoh.template.PageTemplateBase attribute), 128

top_margin (rinoh.template.TitlePageTemplate attribute), 127

Typeface (class in rinoh.font), 110

typeface (rinoh.highlight.CodeBlockStyle attribute), 60

typeface (rinoh.image.CaptionStyle attribute), 48

typeface (rinoh.paragraph.ParagraphStyle attribute), 56

typeface (rinoh.reference.NoteMarkerStyle attribute), 67

typeface (rinoh.reference.ReferencingParagraphStyle attribute), 66

typeface (rinoh.structure.HeadingStyle attribute), 75

typeface (rinoh.structure.ListItemLabelStyle attribute), 81

typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 89

typeface (rinoh.structure.TableOfContentsStyle attribute), 86

typeface (rinoh.text.TextStyle attribute), 61

V

vertical_align (rinoh.table.TableCellStyle attribute), 96

VerticalAlign (class in rinoh.table), 121

W

WarnFlowable (class in rinoh.flowable), 108

warning (rinoh.structure.AdmonitionTitles attribute), 119

width (rinoh.flowable.HorizontallyAlignedFlowableStyle attribute), 42

width (rinoh.image.BackgroundImageArgs attribute), 111

width (rinoh.table.TableStyle attribute), 94

wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 39

Y

y_offset() (rinoh.text.StyledText method), 116