

VIETNAM NATIONAL UNIVERSITY OF HO CHI MINH CITY
THE INTERNATIONAL UNIVERSITY
SCHOOL OF COMPUTER SCIENCE AND ENGINEERING



Hybrid Social Media Platform with Threaded Discussions and
Real-time Updates

By
Cao Ngoc Anh Tuan – ITCSIU21244

*A pre – thesis submitted to the School of Computer Science and Engineering
in partial fulfillment of the requirements for the degree of
Bachelor of Computer Science*

Ho Chi Minh City, Vietnam
2026

Hybrid Social Media Platform with Threaded Discussions and Real-time Updates

APPROVED BY:

MSc. Nguyen Trung Nghia

Committee name here

Committee name here

Committee name here

Committee name here

THESIS COMMITTEE

Acknowledgements

I would like to extend my sincerest gratitude to my advisor, MSc. Nguyen Trung Nghia. The valuable insights he provided, and his consistent motivation have been indispensable to the completion of this thesis. Moreover, I highly appreciate the numerous fruitful debates that honed my arguments. Not only did he guide me in this study but also helped me learn how to be an independent researcher.

I would also like to extend my heartfelt gratitude to my fellow researchers and friends who were part of my research team. I appreciate their openness in sharing ideas, helping in reviewing my experiment design, and spending time in pleasant conversations which lightened our research process.

My gratitude goes to the faculty and staff members of the School of Computer Science of International University. Through their intensive courses, seminars, and encouragement to pursue my interests, I gained the knowledge and confidence needed to embark on this journey.

Finally, I am deeply indebted to the members of my reading and examination committee. Their critical remarks, questions, and insightful feedback motivated me to improve the quality of the thesis and look at the issue from different angles. Without their effort, the thesis would not have reached its current level. They have spared their precious time in examining and criticizing my thesis.

Lastly, I am obliged to everyone who played a role in this research endeavor, no matter how minor their contribution is. From a timely remark of advice, a paper to share, to a comforting smile on a tough day, I will be forever grateful.

Table of Contents

Acknowledgements	iii
List of Tables	viii
List of Figures	x
Abstract	xi
1 INTRODUCTION	1
1.1 Background:	1
1.2 Problem Statement:	1
1.3 Research Contributions:	1
1.4 Objectives:	2
1.4.1 Vision Statement:	2
1.4.2 Stakeholders	2
1.4.3 Users	3
1.4.4 Risks	4
1.4.5 Feature List (Prioritized)	5
1.5 Requirements:	6
1.5.1 Functional – Requirements:	6
1.5.2 Non – Functional Requirements:	15
1.6 Assumption and Solution:	18
1.7 Structure of Pre - Thesis:	19
2 LITERATURE REVIEW	20
2.1 Overview of Social Networking Platform Architectures	20
2.2 Frontend Development Technologies	21
2.2.1 Overview of Frontend Frameworks	21
2.2.2 Rationale for Choosing Next.js:	21
2.3 Backend Development Technologies	21
2.3.1 Overview of Backend Languages	21
2.3.2 Rationale for Choosing Nest.js:	22
2.4 Database Technologies for Social Networking Platform Applications . .	22
2.4.1 Overview of Traditional Databases	22
2.4.2 Rationale for Choosing PostgreSQL and Redis:	22
2.5 Web Curation and Social Feed Ranking Algorithms	23
2.6 Threaded Discussion Curation and Comment Sorting	24
2.7 Real-Time Web Communication Protocols	24
2.8 Content Trending Systems in Social Platforms	25
2.9 Comparative Analysis of Existing Social Media Platforms	26

3	METHODOLOGY	27
3.1	Overview:	27
3.2	Development Process:	27
3.2.1	Architecture Design:	27
3.3	User Requirement Analysis:	76
3.3.1	User Interface Design:	76
3.4	Technology Summary:	77
3.4.1	Front – end:	78
3.4.2	Back – end:	79
3.4.3	Database:	81
3.4.4	Deployment	82
4	IMPLEMENTATION	86
4.1	Project Structure Overview:	86
4.2	Backend Implementation	87
4.2.1	Database Models	88
4.2.2	Module 1: Authentication & Account Verification	89
4.2.3	Module 2: Feeds & Discovery	91
4.2.4	Module 3: Post Management	92
4.2.5	Module 4: Post Interaction	94
4.2.6	Module 5: User Relationship Management	95
4.2.7	Module 6: Profile Management	96
4.2.8	Module 7: Direct Messaging	98
4.2.9	Module 8: Real-time Notifications	100
4.2.10	Module 9: Community Management	101
4.2.11	Module 10: Administrative Moderation	102
4.3	Frontend Implementation	103
4.3.1	Authentication & Onboarding Flow (/sign-up, /sign-in, /verify)	104
4.3.2	Main Feed & Discovery Page (/ - Home & Explore Feed)	106
4.3.3	Direct Messaging & Chat Interface (/messages)	107
4.3.4	User Profile Page (/[username])	109
4.3.5	Community Page (/c/[slug])	111
4.3.6	Administrative Console (/admin-console)	113
5	TEST CASES	115
5.1	Detailed Cases:	115
5.1.1	Authentication & Account Verification	115
5.1.2	Feeds & Discovery	117
5.1.3	Post Management	121
5.1.4	Post Interaction	123
5.1.5	User Relationship Management	125
5.1.6	Profile Management	128
5.1.7	Direct Messaging	129
5.1.8	Real-time Notifications	131
5.1.9	Community Management	133
5.1.10	Administrative Moderation	134
5.2	Evaluation:	136
5.2.1	Performance:	136
5.2.2	Scalability:	137
5.2.3	Usability:	137

5.2.4	Real-Time Performance: WebSocket Notification Latency: . . .	139
5.2.5	Content Discovery Algorithm:	139
6	DEMONSTRATION	141
6.1	User – Features:	141
6.1.1	Home Page:	141
6.1.2	Sign Up Page	142
6.1.3	Sign In Page	142
6.1.4	Forgot Password Page	143
6.1.5	User Profile Page	144
6.1.6	Search Page	145
6.1.7	Message Page	146
6.1.8	Bookmarks Page	147
6.1.9	Notifications Page	147
6.1.10	Blocked accounts Page	148
6.1.11	Communities Page	148
6.1.12	Connect Page	149
6.1.13	Community feeds Page	150
6.1.14	Community rules Page	151
6.1.15	Thread comments Page	152
6.2	Administrative Features	153
6.2.1	Admin Overview Page	153
7	CONCLUSION & FUTURE WORKS	154
7.1	Achievement of Research Contributions and Goals	154
7.2	System Limitations	155
7.3	Future Works	156
7.3.1	Multi-Platform Integration	156
7.3.2	Trending and Recommendation Module Upgrade	156
7.3.3	Enhanced AI Capabilities	157
7.3.4	Public API and Integration	157
7.3.5	Performance Optimization	158
7.3.6	Security Enhancements	158
	References	159
	APPENDIX	161

List of Tables

Table 1.	List of Project Stakeholders and Their Responsibilities	3
Table 2.	Primary User Groups and Their Key Needs	3
Table 3.	Top Risks	4
Table 4.	Feature Backlog (MoSCoW)	6
Table 5.	Authentication and Account Management	7
Table 6.	Feeds & Discovery	8
Table 7.	Post Management	9
Table 8.	Post Interaction	10
Table 9.	User Relationship Management	10
Table 10.	Profile Management	11
Table 11.	Direct Messaging	12
Table 12.	Real-time Notifications	13
Table 13.	Community Management	13
Table 14.	Administrative Moderation	15
Table 15.	Non-Functional Requirements	16
Table 16.	Table 16	27
Table 17.	Identity & Access - Related Tables	45
Table 18.	Content -Related Tables	47
Table 19.	Social Engagement – Related Tables	50
Table 20.	Community & Moderation Tables	53
Table 21.	Communication Tables	56
Table 22.	Identity & Access Domain Classes	59
Table 23.	Content Domain Classes	60
Table 24.	Social Engagement Domain Classes	62
Table 25.	Community & Moderation Domain Classes	64
Table 26.	Communication Domain Classes	65
Table 27.	UC01	116
Table 28.	UC04	117
Table 29.	UC26	118
Table 30.	UC27	119
Table 31.	UC30	120
Table 32.	UC08	121
Table 33.	UC09	122
Table 34.	UC15	124
Table 35.	UC10	125
Table 36.	UC18	126
Table 37.	UC21	127
Table 38.	UC22	128
Table 39.	UC40	130

Table 40.	UC43	131
Table 41.	UC37	132
Table 42.	UC51	133
Table 43.	UC62	134
Table 44.	UC65	136

List of Figures

Figure 1.	High-level architecture diagram	29
Figure 2.	Summary Goal Use Case	31
Figure 3.	Authentication & Account Management	33
Figure 4.	Feeds and Discovery	34
Figure 5.	Post Management	35
Figure 6.	Post Interaction	36
Figure 7.	User Relationship Management	37
Figure 8.	User Profile Management	38
Figure 9.	Direct Messaging	39
Figure 10.	Real-time Notifications	40
Figure 11.	Community Management	41
Figure 12.	Administrative Moderation	42
Figure 13.	Entity Relationship Diagram	43
Figure 14.	Identity & Access – Related Tables	44
Figure 15.	Content – Related Tables	46
Figure 16.	Social Engagement – Related Tables	49
Figure 17.	Community & Moderation - Related Tables	52
Figure 18.	Communication – Related Tables	54
Figure 19.	Class Diagram	58
Figure 20.	Authentication & Account Management Diagram	67
Figure 21.	Feeds and Discovery Diagram	68
Figure 22.	Post Management Diagram	69
Figure 23.	Post Interaction Diagram	70
Figure 24.	User Relationship Management Diagram	71
Figure 25.	User Profile Management Diagram	72
Figure 26.	Direct Messaging Diagram	73
Figure 27.	Real-time Notifications Diagram	74
Figure 28.	Community Management Diagram	75
Figure 29.	Administrative Moderation Diagram	76
Figure 30.	Project Structure	87
Figure 31.	Code Snippet – SiteUser Model Definition	89
Figure 32.	Code Snippet – Authentication & Account Verification	90
Figure 33.	Code Snippet – Authentication & Account Verification	91
Figure 34.	Code Snippet – Feed & Discovery	92
Figure 35.	Code Snippet – Feed & Discovery	92
Figure 36.	Code Snippet – Post Management	93
Figure 37.	Code Snippet – Post Management	94
Figure 38.	Code Snippet – Post Interaction	94
Figure 39.	Code Snippet – Post Interaction	95
Figure 40.	Code Snippet – User Relationship Management	96

Figure 41.	Code Snippet – User Relationship Management	96
Figure 42.	Code Snippet – Profile Management	97
Figure 43.	Code Snippet – Profile Management	98
Figure 44.	Code Snippet – Direct Messaging	99
Figure 45.	Code Snippet – Direct Messaging	100
Figure 46.	Code Snippet – Real-time Nofications	100
Figure 47.	Code Snippet – Real-time Nofications	101
Figure 48.	Code Snippet – Community Management	102
Figure 49.	Code Snippet – Community Management	102
Figure 50.	Code Snippet – Administrative Moderation	103
Figure 51.	Code Snippet – Administrative Moderation	103
Figure 52.	Code Snippet – Sign-Up Page	104
Figure 53.	Code Snippet – Sign-In Page	105
Figure 54.	Code Snippet – Verify Page	105
Figure 55.	Code Snippet – Feed Routing Layout	106
Figure 56.	Code Snippet – Main Home Page	107
Figure 57.	Code Snippet – Messages Layout	108
Figure 58.	Code Snippet – Real-time Message Thread	108
Figure 59.	Code Snippet – Typing Indicator Hook	109
Figure 60.	Code Snippet – Server-Side Profile Page	110
Figure 61.	Code Snippet – Profile Tab Switching	110
Figure 62.	Code Snippet – Profile Feed Fetcher	111
Figure 63.	Code Snippet – Community Server Component	112
Figure 64.	Code Snippet – Join / Leave State	113
Figure 65.	Code Snippet – Moderator Pending Posts Queue	113
Figure 66.	Code Snippet – Administrative Layout	114
Figure 67.	Code Snippet – Banning Dashboard	114
Figure 68.	Code Snippet – Report Queue	114
Figure 69.	Home Page	141
Figure 70.	Sign Up Page	142
Figure 71.	Sign In Page	142
Figure 72.	Forgot Password Page	143
Figure 73.	User Profile Page - Information Display	144
Figure 74.	Search Page	145
Figure 75.	Message Page	146
Figure 76.	Bookmarks Page	147
Figure 77.	Notifications Page	147
Figure 78.	Blocked accounts Page	148
Figure 79.	Communities Page	148
Figure 80.	Connect Page	149
Figure 81.	Community feeds Page	150
Figure 82.	Community rules Page	151
Figure 83.	Thread comments Page	152
Figure 84.	Admin Overview - Dashboard Access	153
Figure 85.	Admin Overview – Report Content	153

Abstract

The rapid evolution of web technologies has shifted digital communications from static networks to dynamic, real-time social ecosystems. The substantial volume of user-generated content presents challenges for modern platforms to sustain real-time performance, prevent information noise, and ensure platform security. This pre-thesis addresses these challenges by designing and implementing Breadit, a hybrid social media platform that integrates threaded discussions and real-time updates.

The platform is developed using a TypeScript-based monorepo architecture. It incorporates core social networking workflows, including custom JWT-based authentication with secure cookie propagation, media post management, and social graphs (follow/block relations). Real-time interactions, specifically private messaging and instant notifications, are achieved through Socket.IO integration at the gateway layer. The technical stack utilizes Next.js 15 for a responsive front end, NestJS with Fastify for a high-performance backend, Prisma ORM with PostgreSQL for persistent storage, and Redis for caching and managing Socket.IO adapters.

To address information noise, the platform implements an interaction-based content discovery module utilizing a linear time-decay heuristic ranking algorithm combined with author-diversity filtering. Performance evaluations conducted in a local containerized environment demonstrate that the Fastify-backed NestJS API handles concurrent requests with an average response time of under 45 milliseconds. Furthermore, the integration of Redis cache reduces direct PostgreSQL read operations by 85% for trending query lookups, and Socket.IO establishes real-time message delivery within 12 milliseconds of event emission. These results demonstrate that the proposed architecture provides a responsive, low-latency framework for community moderation and content discovery, laying a robust foundation for future machine-learning-driven personalization.

Chapter 1

INTRODUCTION

1.1 Background:

The exponential growth of user-generated content on modern social networking platforms has introduced "information noise," making it increasingly difficult for users to identify relevant discussions and communities within vast, continuous data streams. This challenge necessitates the development of interaction-based, time-aware content discovery systems capable of surfacing high-quality, recent content without relying on opaque algorithmic curation.

Breadit addresses this gap as a hybrid social networking platform that combines community-based sub-breadits with a transparent linear time-decay heuristic ranking algorithm, scoring posts by engagement signals (likes, comments, reposts) and enforcing author-diversity filtering to prevent content monopolization. By coupling this deterministic discovery engine with full-duplex real-time communication via Socket.IO, the platform delivers structured, community-centric social interactions within a low-latency architecture.

1.2 Problem Statement:

In contemporary social media, massive content volume creates information noise. Studies empirically link this overload to statistically significant increases in emotional exhaustion and systematic information avoidance behavior (Gupta, Bodhi, & Pandey, 2024; Stamenković & Aleksić, 2025). Furthermore, platforms like Meta and X prioritize engagement-centric algorithmic feeds, delaying post visibility and disrupting conversational context (Guess et al., 2023). Existing flat-reply architectures also lack structured thread organization, causing contextual fragmentation during multi-user discussions (Kwak et al., 2010). Consequently, a clear demand exists for a hybrid platform that integrates threaded discussions for structured context alongside WebSockets to deliver real-time updates and transparent heuristic content discovery.

1.3 Research Contributions:

C1. Hybrid social networking architecture: Breadit unifies Reddit-style community-based threaded discussions with Twitter-style microblogging into a single platform. Users engage in structured, multi-level comment threads within dedicated sub-breadit communities while maintaining a global personal timeline - a combination that existing platforms provide only in isolation. This directly addresses the contextual fragmenta-

tion caused by flat-reply architectures on current microblogging platforms.

C2. Transparent, deterministic Explore feed algorithm: Rather than opaque engagement-centric ranking, Breadit implements an auditable linear time-decay heuristic:

$$\text{Score} = (\text{Likes} \times 1) + (\text{Comments} \times 2) + (\text{Reposts} \times 3) - (\text{AgeHours} \times 0.25)$$

Combined with a greedy author-diversity filter — capping each author at a maximum of 3 posts per Explore page within a 7-day candidate window — this algorithm surfaces relevant, recent content while actively preventing content monopolization, without relying on non-interpretable machine learning models.

C3. Real-time social interaction layer: Breadit delivers instant private messaging and push notifications (likes, replies, follows, mentions) without page reload via Socket.IO WebSocket connections. This enables immediate, bidirectional social feedback loops across all platform interactions, fulfilling the core thesis requirement of real-time updates in a community-driven social context.

1.4 Objectives:

1.4.1 Vision Statement:

For online users and community creators who wish to experience social networking in a more effective manner, there is Breadit which represents a one-stop platform which can serve as a link between the large pool of information available and personalized discovery. Unlike social networks which bombard the user with large amounts of irrelevant information and delayed responses, the solution involves a real time synchronization process and a discovery engine based on user interaction. The result of this combination includes an interactive and secure social environment for its users.

1.4.2 Stakeholders

The development of the Breadit platform involves several key stakeholders, ranging from academic supervisors to the technical development team and active social participants.

Table 1: List of Project Stakeholders and Their Responsibilities

Name	Role	Responsibilities
MSc. Nguyen Trung Nghia	Project Supervisor	Provides academic guidance, reviews technical architecture, and approves the project scope and deliverables.
Cao Ngoc Anh Tuan	Student	Designs system architecture, implements Frontend/Backend, and executes testing.
Thesis Committee	Evaluators	Reviews the pre-thesis and final thesis, providing feedback on system quality and research depth.
Authenticated User	Platform Users	Browse feeds, interact with posts, participate in communities, and use real-time direct messaging and live notifications.
System Admin	Platform Administrator	Manage report queues, moderate violating content, and handle user life-cycle.

1.4.3 Users

Table 2: Primary User Groups and Their Key Needs

User Group	Primary Needs / Goals
Guest (Unauthenticated)	Browse public feeds, view poster-links and user profiles, search for content/hashtags, and smoothly sign up/log in to interact.

Continued on next page

(Continued from previous page)

User Group	Primary Needs / Goals
Authenticated User	Publish posts with multimedia, engage with others (likes, comments, reposts), follow users, manage profile, use real-time direct messaging, and receive live notifications.

1.4.4 Risks

Table 3: Top Risks

ID	Risk	Owner	Mitigation	Trigger
1	Real-time Connection Instability	Developer	Implement robust reconnect logic using Socket.IO and utilize Redis adapter for scalable Pub/Sub across instances.	Users fail to receive live notifications or direct messages in real-time.
2	Media Upload Handling Failures	Developer	Configure efficient multipart parsing in Fastify and integrate Cloudinary as a robust media CDN.	Errors or timeouts during post creation when uploading multiple high-resolution images/videos.

Continued on next page

(Continued from previous page)

ID	Risk	Owner	Mitigation	Trigger
3	Scalability & Client State Desync	Frontend Lead	Utilize TanStack Query for robust client-side state management and implement cursor-based pagination for infinite feeds.	Feed stutters, UI freezes, or out-of-sync data when scrolling through massive timelines.
4	Data Privacy & Security	System Admin	Implement JWT for session management and hash passwords (bcrypt).	Unauthorized access to user profiles, private direct messages, or session hijacking.
5	Database Query Performance	Backend Lead	Optimize Prisma ORM queries using precise include/select structures to prevent N+1 issues when fetching nested comments and likes.	Slow server response times when fetching complex user timelines or deeply nested threads.

1.4.5 Feature List (Prioritized)

The features are prioritized using the MoSCoW method (Must have, should have, could have, Won't have) to ensure the MVP (Minimum Viable Product)

Table 4: Feature Backlog (MoSCoW)

Feature	Priority (M/S/C/W)	Notes
User Authentication (Login/Register)	M	Secure access using JWT/OAuth.
Timeline Feeds & Discovery	M	Cursor-paginated home and explore feeds with infinite scrolling.
Post Creation & Media Upload	M	Text posts, hashtags, mentions, and Cloudinary media integration.
Social Graph & Interactions	M	Core engagement: following users, liking, replying, and reposting/quote-reposting.
Real-time Notifications and Chatting	M	Live system alerts (likes, replies, mentions, message) powered by Socket.IO and Redis.
AI-based Content Recommendation	S	Personalized feed suggestions based on interaction history to enhance user engagement (Planned for future refinement)
Admin Monitor Tools	C	System-wide moderation panel to manage users/groups, approve content, configure settings, and monitor analytics.
Native Mobile Application	W	Out of scope for this web-based thesis.

1.5 Requirements:

1.5.1 Functional – Requirements:

Authentication & Account Management:

Table 5: Authentication and Account Management

ID	Requirement Description	Priority	Related Use Case(s)
FR-AUTH-01	Users sign up with a unique username, email, and password	Must	Sign up/ Login
FR-AUTH-02	The system shall implement secure password hashing (e.g., bcrypt) before storing credentials.	Must	Sign up/ Login
FR-AUTH-03	The system shall send a 6-digit verification code (OTP) to the user's email to verify account ownership.	Must	Send verification
FR-AUTH-04	The system shall authenticate users and issue a secure httpOnly JWT session cookie named breadit_session.	Must	Sign up/ Login
FR-AUTH-05	The system should provide a "Forgot Password" feature allowing users to reset their credentials securely.	Should	Reset password

Feeds & Discovery:

Table 6: Feeds & Discovery

ID	Requirement Description	Priority	Related Use Case(s)
FR-DISC-01	The system shall generate a chronologically sorted home feed consisting of posts from followed users.	Must	View Public Feed
FR-DISC-02	The system shall provide an explore feed sorted by like count (trending), excluding community posts.	Must	View Public Feed
FR-DISC-03	The system should provide dedicated feed for specific hashtags and communities.	Must	View Public Feed
FR-DISC-04	The system shall perform case-insensitive global searches across posts, users, hashtags, and communities.	Must	Search Content
FR-DISC-05	The system shall debounce search input from the UI and provide a live dropdown of results.	Should	Search Content

Post Management:

Table 7: Post Management

ID	Requirement Description	Priority	Related Use Case(s)
FR-POST-01	The system shall allow authenticated users to create text posts with a limit of 255 characters.	Must	Create post
FR-POST-02	The system shall allow users to attach multi-media files managed via Cloudinary or local Sharp processing.	Must	Add media
FR-POST-03	The system shall automatically parse, and index hashtags (#tokens) included in the post text.	Must	Add hashtag
FR-POST-04	The system allows users to edit the text of their previously published posts or comments.	Should	Edit post/comment
FR-POST-05	The system shall allow users to softly delete their own posts, effectively hiding them from all feeds.	Must	Delete/ report post

Post Interaction:

Table 8: Post Interaction

ID	Requirement Description	Priority	Related Case(s)	Use
FR-INT-01	The system shall allow users to like or unlike posts and comments to express agreement.	Must	Like/Unlike	
FR-INT-02	The system shall allow users to reply to existing posts, creating a threaded comment.	Must	Comment/ Reply	
FR-INT-03	The system allows users to perform plain reports or quote-reposts to their own profile feed.	Must	Repost	
FR-INT-04	The system shall allow users to privately save posts to a bookmark list.	Should	Save posts	

User Relationship Management:

Table 9: User Relationship Management

ID	Requirement Description	Priority	Related Case(s)	Use
FR-REL-01	The system shall allow users to follow or unfollow other accounts.	Must	Follow/unfollow user	

Continued on next page

(Continued from previous page)

ID	Requirement Description	Priority	Related Use Case(s)
FR-REL-02	The system shall allow users to explicitly mention followed users using the @username syntax.	Should	Create post, Comment/ Reply
FR-REL-03	The system shall allow users to block accounts bidirectionally, restricting profile access and direct messaging.	Must	Block/unblock user

Profile Management:

Table 10: Profile Management

ID	Requirement Description	Priority	Related Use Case(s)
FR-PROF-01	The system shall allow users to view profiles with dedicated tabs for Posts, Replies, Media, and Likes.	Must	Edit/ view profile
FR-PROF-02	The system shall allow users to update personal info, including bio (up to 160 chars), location, and website.	Must	Edit/ view profile

Continued on next page

(Continued from previous page)

ID	Requirement Description	Priority	Related Case(s)	Use
FR-PROF-03	The system allows users to upload and crop custom images for their avatar and cover photo.	Should	Edit/ view profile	

Direct Messaging:

Table 11: Direct Messaging

ID	Requirement Description	Priority	Related Case(s)	Use
FR-MSG-01	The system shall allow users to establish 1:1 real-time direct messaging thread with database persistence.	Must	Send Direct Message	
FR-MSG-02	The system shall allow users to attach images and videos securely within direct message conversations.	Should	Send Direct Message	
FR-MSG-03	The system shall maintain and update unread message badge counts dynamically.	Must	Send Direct Message	

Real-time Notifications:

Table 12: Real-time Notifications

ID	Requirement Description	Priority	Related Use Case(s)
FR-NOTI-01	The system shall dispatch real-time Socket.IO alerts for likes, replies, reposts, mentions, and follows.	Must	View Notifications
FR-NOTI-02	The system shall securely store notifications in the database to track unread and read states over time.	Must	View Notifications
FR-NOTI-03	The system shall scale real-time broadcasting across multiple instances using a Redis adapter.	Must	View Notifications

Community Management:

Table 13: Community Management

ID	Requirement Description	Priority	Related Use Case(s)
FR-COMM-01	The system shall allow users to create communities and automatically inherit the Owner/Moderator role.	Must	Create Community

Continued on next page

(Continued from previous page)

ID	Requirement Description	Priority	Related Case(s)	Use
FR-COMM-02	The system shall allow users to browse existing communities and explicitly join or leave them.	Must	Join/Leave Community	
FR-COMM-03	The system shall allow community moderators to define and display specific rules for their community.	Must	Manage Community	
FR-COMM-04	The system shall allow members to submit posts within a community, entering a moderation queue if required.	Must	Create Post	
FR-COMM-05	The system shall allow moderators to approve/reject pending posts and ban users from the community.	Must	Manage Community	

Administrative Moderation:

Table 14: Administrative Moderation

ID	Requirement Description	Priority	Related Case(s)	Use
FR-MOD-01	The system should provide a global admin console to view and search a list of all registered users.	Must	Manage Users	
FR-MOD-02	The system shall allow administrators to temporarily or permanently ban users from the platform.	Must	Manage Users	
FR-MOD-03	The system shall maintain a queue of user-reported posts and push real-time REPORT alerts to admins.	Must	Handle Reports	
FR-MOD-04	The system shall allow administrators to permanently delete reported content or dismiss invalid reports.	Must	Moderate Content	

1.5.2 Non – Functional Requirements:

Table 15: Non-Functional Requirements

ID	Category	Requirement Description	Importance Level
NFR-SEC-01	Security	The system secure API endpoints using HTTP-only JSON Web Tokens (JWT) to mitigate Cross-Site Scripting (XSS) risks.	High
NFR-SEC-02	Security	User passwords must be securely hashed using the bcrypt algorithm with at least 10 salt rounds before database storage.	High
NFR-PERF-01	Performance	The system must utilize Redis for server-side caching of high-traffic queries (search results) to reduce database load.	High
NFR-PERF-02	Performance	Feed endpoints must implement cursor-based pagination to guarantee fast and consistent response times regardless of data volume.	High

Continued on next page

(Continued from previous page)

ID	Category	Requirement Description	Importance Level
NFR-SCA-01	Scalability	Real-time Web-Socket connections (Socket.IO) must use a Redis adapter to allow seamless horizontal scaling across multiple server instances.	High
NFR-SCA-02	Scalability	The system must enforce API rate limiting using a Redis-backed throttler.	High
NFR-REL-01	Reliability	The backend must employ global Exception Filters to ensure that all API errors return to a consistent, secure, and standardized JSON response.	High
NFR-USE-01	Usability	The frontend must utilize Next.js Server-Side Rendering (SSR) to ensure optimal Search Engine Optimization (SEO) and fast initial page loads.	High

Continued on next page

(Continued from previous page)

ID	Category	Requirement Description	Importance Level
NFR-USE-02	Usability	The user interface must implement seamless Infinite Scrolling for social feeds, leveraging TanStack Query to fetch data without page reloads.	Medium
NFR-MAINT-01	Maintainability	The project enforces Strict TypeScript typing and be structured as a Monorepo to ensure long-term stability and code sharing.	Medium

1.6 Assumption and Solution:

Key Assumptions:

- Breadit social networking platform assumes the following conditions:
- The target users have a stable Internet connection, know how to use micro-blogging (like, retweet, follow other people, start threads).
- Data Availability: Enough structured interaction data (like, retweets, comments, hashtags) needed for recommendations and trends algorithm.
- User engagement: People will generate content, join communities, interact with others in real time.
- Infrastructure: Node.js support for NestJS, Next.js, PostgreSQL, and Redis for real-time capabilities.
- Security & Privacy: Enough self-moderation and admin control to keep everything safe, Authentication via HTTP-only JWT, data protection, blocklist.

Solution:

- Breadit will provide a quick and interactive micro-blogging platform focused on user interests, real-time communication, and intelligent recommendation.

- Trends & Recommendations: A chronological follow-feed and Explore/Trending module for viral and personalized content based on user engagement (likes, replies, retweets).
- Real-time Communication: WebSocket-based (Socket.IO) instant direct messaging with real-time typing and notifications without page refresh.
- Media and interactions: Multi-media attachment capabilities (using Cloudinary/Sharp) as well as hashtag parsing and thread-based discussions.
- Seamless UX: Next.js frontend with Optimistic UI pattern and cursor-based pagination.
- Safety Features: Bidirectional blocking, community queueing system
- Scalability: A modular monorepo backend allowing for future development of AI-powered content curation or search engine.

1.7 Structure of Pre - Thesis:

The pre – thesis is structured into seven consecutive chapters:

Chapter 1: Introduction: Sets up the research context, clarifies the problem statement, outlines objectives and scope, and presents the proposed social networking solution.

Chapter 2: Literature Review: Discusses existing studies and established solutions in social networking and real-time communication systems, highlighting key technological strategies.

Chapter 3: Methodology: Details of the research approach, including system requirements analysis, UML system design, and technical architecture planning.

Chapter 4: Implementation: Documents the development process and details the implementation of core functionalities (e.g., real-time messaging, content trending/recommendation algorithms).

Chapter 5: Test Cases: Presents the testing strategies used to validate system functionalities, performance, and security measures.

Chapter 6: Demonstration: Provides an overview of the deployed platform, highlighting real-time user interactions, intelligent post trending/recommendations, and overall usability.

Chapter 7: Conclusion and Future Work: Synthesizes findings, evaluates the system against stated objectives, acknowledges limitations, and proposes directions for future development.

This structured progression ensures comprehensive coverage from conceptual foundations through technical implementation to critical evaluation.

Chapter 2

LITERATURE REVIEW

2.1 Overview of Social Networking Platform Architectures

Modern social networking platforms require high-throughput, low-latency architectures to handle the massive volumes of user-generated content and real-time interaction loops. Historically, social network designs relied on synchronous request-response patterns over traditional relational databases. However, research by Kwak et al. [1] demonstrates that the topology of modern social networks - characterized by low reciprocity, asymmetric follower-following relationships, and rapid information diffusion - fundamentally differs from classical human social networks, necessitating a shift toward event-driven architectures and distributed caching layers capable of handling real-time content propagation at scale.

A critical challenge arising from this scale of content production is information overload — the cognitive burden imposed on users when incoming content volume exceeds their processing capacity. Gupta et al. [11] empirically demonstrated, across a large-scale sample study published in the *Academy of Marketing Studies Journal*, that unmanaged information streams are a statistically significant driver of emotional exhaustion and user fatigue on social media platforms. This finding is further substantiated by Stamenković and Aleksić [12], who applied the Stressor-Strain-Outcome (SSO) model to confirm that unfiltered digital overload leads to systematic information avoidance — users disengaging from platforms entirely rather than engaging with irrelevant or overwhelming content. These findings collectively establish the academic necessity for intelligent content curation and ranking mechanisms within modern social networking systems.

Comparison & Breadit's Positioning

While legacy architectures utilize heavy database queries for feed generation, Breadit inherits the hybrid database model proposed by Carlson [2], combining PostgreSQL as the persistent relational source of truth with Redis as an in-memory database. Breadit differentiates itself by implementing this hybrid model within a TypeScript monorepo, using Prisma ORM to maintain strict type safety across database transactions while leveraging Redis to handle WebSocket adapter pub/sub states, minimizing backend connection overhead. Furthermore, directly addressing the information overload challenge identified by Gupta et al. [11] and Stamenković and Aleksić [12], Breadit incorporates a time-decay heuristic ranking algorithm on the Explore feed — a design choice motivated by the empirical finding of Kwak et al. [1] that engagement signals (retweets, replies) are stronger predictors of content relevance than simple follower counts.

2.2 Frontend Development Technologies

2.2.1 Overview of Frontend Frameworks

Frontend technologies have transitioned from static HTML/CSS pages to highly dynamic, component-based frameworks such as React, Vue, and Angular. These modern frameworks enable reusability, state management, and efficient rendering, capabilities essential for micro-blogging platforms that require real-time updates, dynamic social feeds, and seamless navigation.

2.2.2 Rationale for Choosing Next.js:

Next.js is a powerful React framework widely adopted for building production-ready applications.

Key advantages include:

- Server-Side Rendering (SSR) enhancing SEO and ensuring lightning-fast initial page loads for social feeds.
- Built-in Routing streamlining complex navigation across user profiles and communities.
- Seamless React Integration, leveraging component-based architecture and Virtual DOM for highly interactive user interfaces.
- Advanced optimization tools natively built-in for images, fonts, and external scripts.

For Breadit platform, where robust SEO, fast rendering, and real-time responsiveness are critical, Next.js provides the ultimate frontend foundation.

2.3 Backend Development Technologies

2.3.1 Overview of Backend Languages

Backend systems serve as the foundation for business logic, authentication, and database management. Common backend technologies include Java, Node.js, PHP, and Python frameworks.

Modern micro-blogging platforms require advanced backend architectures capable of fully supporting:

- High concurrency for real-time data streams
- Secure authentication and robust user moderation
- Efficient data pipelines utilizing both relational databases and caching layers
- Scalable REST APIs for frontend interfaces

2.3.2 Rationale for Choosing Nest.js:

Nest.js is widely adopted for building highly scalable server-side applications and real-time enterprise systems.

Reasons for choosing Nest.js for the backend.

- Modular architecture enforces strict design patterns, resulting in a highly maintainable and testable codebase.
- Deep TypeScript support out-of-the-box, ensuring robust type safety and accelerating development cycles.
- Excellent real-time capabilities with native support for WebSocket (Socket.IO), making it ideal for instant messaging and notification systems.
- Rich ecosystem offering seamless integration with powerful backend tools like Prisma ORM, Fastify, and Redis.
- High compatibility with PostgreSQL and modern containerized cloud deployment platforms (Docker).

In this project, Nest.js supports the high-concurrency API system, robust authentication, and the real-time communication engine, making it a natural fit for a highly interactive micro-blogging platform.

2.4 Database Technologies for Social Networking Platform Applications

2.4.1 Overview of Traditional Databases

Social networking platforms rely heavily on robust databases to store complex user relationships and real-time interactions. Traditional relational databases like PostgreSQL serve as the primary source of truth, ensuring strict data consistency and structural integrity. To complement this, in-memory NoSQL stores like Redis perfectly handle high-speed caching and real-time message brokering for scalable social feeds.

2.4.2 Rationale for Choosing PostgreSQL and Redis:

PostgreSQL is a powerful relational database system known for its reliability, ACID compliance, and strong data integrity, while Redis is an industry-leading, ultra-fast in-memory data store.

Reasons for selecting this combined database architecture:

- Advanced SQL capabilities (PostgreSQL) suitable for managing highly structured micro-blogging data.

- Strong support for relational modeling (PostgreSQL), crucial for managing complex user-post-community relationships.
- Ultra-fast in-memory processing (Redis), essential for caching API responses and scaling real-time WebSocket adapters.
- High performance and scalability across both systems to handle heavy concurrent read/write workloads.

In this project, PostgreSQL is used as the primary database to store core social networking data such as user profiles, posts, and comments, while Redis is utilized to power real-time messaging and optimize system latency.

2.5 Web Curation and Social Feed Ranking Algorithms

A primary challenge in social media platforms is filtering "information noise." In academic literature, this is addressed through content curation and ranking algorithms.

Early social networks utilized simple reverse-chronological ordering or basic popularity metrics (total likes). However, engagement-centric ranking algorithms often introduce bias and "filter bubbles," as examined in a large-scale empirical study by Guess et al. [3] published in Science.

To balance freshness with popularity, decay-based ranking algorithms have been extensively studied in social media contexts. Lerman and Ghosh [4] conducted an empirical study of information propagation on Digg (a community content-voting platform directly analogous to Bredit) and Twitter, demonstrating that social content engagement follows a characteristic decay pattern: posts reach a peak engagement window within the first few hours of publication, after which interaction rates decline exponentially as new content pushes them down the feed. Their findings provide empirical validation that time-decay functions are effective quantitative models for estimating content relevance in community-driven social platforms. Similarly, the Hacker News ranking heuristic, analyzed by Salihefendic [5], operationalizes this decay principle with a concrete scoring formula:

Where U represents engagement points, T represents time elapsed, and G represents a gravity decay factor.

Comparison & Bredit's Positioning

Bredit's Approach: Bredit inherits the linear time-decay ranking model:

$$\text{Score} = \text{Likes} + \text{Comments} \times 2 + \text{Reposts} \times 3 - \text{AgeHours} \times 0.25$$

but differentiates itself by executing this scoring logic dynamically over a recent candidate pool queried from PostgreSQL, applying sorting and diversity filtering in Node.js backend memory, and caching the resulting final feed pages in Redis. This eliminates the database query and compute overhead for subsequent requests. Furthermore, Bredit integrates a greedy author-diversity algorithm directly into the ranking pipeline, ensuring that no single author dominates the feed window (capping authors to a maximum of 3 posts per page). This solves the duplication issues common in basic time-decay implementations without requiring expensive database operations.

2.6 Threaded Discussion Curation and Comment Sorting

In discussion-based social media, comment sorting is critical to maintaining conversation context. In academic literature, the two most common sorting heuristics are:

1. Bayesian Average: Often used in product reviews to pull average ratings toward a global mean when the sample size is small.
2. Wilson Score Interval: Populated by Edwin B. Wilson [6] and applied to web ranking by Evan Miller [7]. It calculates the lower bound of a binomial proportion confidence interval:

$$\text{lower bound} = \frac{\hat{p} + \frac{z_{1-\alpha/2}^2}{2n} - z_{1-\alpha/2} \sqrt{\frac{\hat{p}(1-\hat{p})}{n} + \frac{z_{1-\alpha/2}^2}{4n^2}}}{1 + \frac{z_{1-\alpha/2}^2}{n}}$$

Where $\hat{p}$ is the fraction of positive votes, n is the total votes, and $z_{1-\alpha/2}$ is the confidence level statistical value. Sorting by this lower bound acts as a “skeptical” filter that prevents posts with few votes (e.g., 1 upvote, 0 downvotes) from outranking established quality content.

Comparison & Breadit’s Positioning

Wilson Score vs. Time-Decay: The Wilson Score (used by Reddit’s “Best” sort) is excellent for static comment trees where recency is secondary to quality. However, it lacks a temporal decay factor, meaning older comments with high upvotes remain pinned at the top indefinitely, discouraging new conversations.

Breadit’s Approach: For primary feeds, Breadit differs by utilizing a time-decay engagement algorithm () to ensure the feed remains dynamic and fresh. For comment sections, Breadit implements a nested, chronological threaded structure optimized for real-time thread-based conversations, leaving statistical confidence sorting (such as the Wilson Score Interval) as a planned upgrade for future iterations when active voting pools scale.

2.7 Real-Time Web Communication Protocols

Real-time notification delivery and private messaging require bi-directional communication channels. Historically, three main paradigms have co-existed:

1. AJAX Short/Long Polling: The client repeatedly requests updates from the server at fixed intervals. As evaluated by Pimentel and Nickerson [8], polling-based approaches introduce significant HTTP header overhead on each request cycle and consume excessive server CPU resources due to frequent TCP connection establishment sequences, particularly under high concurrency.

2. Server-Sent Events (SSE): A unidirectional, persistent HTTP connection where the server pushes updates. While memory-efficient, SSE does not natively support bidirectional messaging (such as client-to-server chat events).
3. WebSockets (RFC 6455): A full-duplex, bidirectional communication channel over a single TCP connection [9]. Once the initial HTTP handshake is upgraded, frame overhead is minimal (2-10 bytes per packet), making it the optimal protocol for low-latency bidirectional streams.

Comparison & Breadit’s Positioning

Breadit’s Approach: Breadit inherits the full-duplex WebSocket protocol (via Socket.IO). By integrating Socket.IO at the NestJS gateway layer, Breadit establishes a low-latency bidirectional messaging channel that avoids the polling interval constraints of legacy systems. Additionally, Breadit optimizes connection management by storing Socket.IO adapter states in Redis, allowing stateless backend instances to scale horizontally without losing real-time connection contexts.

2.8 Content Trending Systems in Social Platforms

Content recommendation is a foundational research area addressing the information overload problem [11][12] in social networking systems. Three primary algorithmic paradigms are established in the academic literature:

1. Collaborative Filtering (CF): Pioneered by Sarwar et al. [13] in their landmark item-based CF paper published at the WWW 2001 conference, this approach generates recommendations by identifying users with similar engagement patterns and surfacing content preferred by those users. The core limitation of CF is the cold-start problem: the algorithm requires a substantial volume of historical interaction data to produce meaningful recommendations, making it ineffective for new users or newly created content.
2. Content-Based Filtering (CBF): Content-based approaches analyze the attributes of items a user has previously engaged with (e.g., topic tags, hashtags, textual content similarity) to recommend semantically similar items. While avoiding the cold-start problem for items, CBF tends to create filter bubbles [3], where users are exclusively recommended content highly similar to their past behavior, significantly reducing exposure to diverse perspectives.
3. Hybrid Approaches: To mitigate the respective limitations of CF and CBF, hybrid recommendation architectures combine multiple signal sources simultaneously. Large-scale commercial platforms (e.g., YouTube, Netflix) deploy deep learning-based hybrid models that fuse collaborative signals, content embeddings, and contextual session features to generate diverse personalized recommendation lists at scale.

Comparison & Breadit’s Positioning

The Breadit platform does not currently implement a machine learning-based recommendation engine. This is a deliberate scope decision: implementing a robust

CF or hybrid recommendation system requires a sufficient interaction data volume (Sarwar et al. [13] estimate a cold-start threshold of tens of thousands of user-item interactions) and dedicated infrastructure for offline model training pipelines, both of which fall outside the defined scope of this project phase.

Instead, Breadit adopts a deterministic, heuristic-based "Explore Feed" implementing a linear time-decay engagement scoring model ($\text{score} = \text{likes} \times 1 + \text{comments} \times 2 + \text{reposts} \times 3 - \text{ageHours} \times 0.25$), complemented by a greedy author-diversity filter (capping any single author at 3 posts per page). This approach directly addresses the information overload problem [11][12] without incurring the cold-start dependency inherent in collaborative filtering, providing a transparent and auditable content ranking mechanism. The integration of a full collaborative filtering or hybrid recommendation engine is identified as a planned future development milestone, contingent on the platform accumulating sufficient user interaction data.

2.9 Comparative Analysis of Existing Social Media Platforms

Comparison Metric	Facebook	Twitter / X	Reddit	Breadit (Proposed)
System Architecture	Opaque Algorithmic (AI-based curation)	Hybrid Algorithmic / Chronological stream	Sub-community (Subreddit) & Forum aggregation	Hybrid sub-communities (Sub-breadsits) & Trending feeds
Discussion Structure	Linear / Semi-threaded (Limited depth)	Flat / Linear replies (Loss of context)	Highly structured nested threads (Tree structure)	Nested chronological threaded discussions (Tree structure)
Curation Method	Engagement-maximizing AI optimization	High-velocity activity scoring	Wilson Score Interval ("Best") & Chronological	Linear time-decay heuristic scoring with author diversity limits
Real-Time Synchronicity	Low-frequency polling (high latency)	Real-time push / Websockets	Polling-centric (delayed vote & comment sync)	Full-duplex WebSockets (Socket.IO + Redis Adapter)

Chapter 3

METHODOLOGY

3.1 Overview:

This chapter describes the design methodology, architectural approach, and key technical decisions made during the development of the Breadit hybrid social networking platform. The methodology centers on a systems engineering approach: each architectural decision is evaluated against concrete alternatives based on the platform's defined requirements - real-time content delivery, hybrid feed ranking, threaded discussion management, and community moderation.

The implementation follows a TypeScript-first monorepo strategy using Turborepo, comprising two independently deployable applications: a NestJS/Fastify backend and a Next.js 15 frontend. All major technical choices - architecture pattern, pagination strategy, real-time protocol, and rendering model - are justified by explicit trade-off analysis documented in the sections below.

3.2 Development Process:

3.2.1 Architecture Design:

Table 16: Table 16

Criterion	Modular (Chosen)	Monolith	Microservices
Deployment complexity	Single deployable unit per application		Each service requires independent orchestration (Docker Compose, Kubernetes)
Inter-module communication	Direct in-process function calls via NestJS DI		Network calls (REST/gRPC), introducing latency and failure points

Continued on next page

(Continued from previous page)

Criterion	Modular Monolith (Chosen)	Microservices
Data access	Single shared Prisma client with transactional integrity	Each service manages its own database, requiring distributed transaction patterns (SAGA)
Development overhead	Low - suitable for a single-developer pre-thesis project	High - requires service discovery, API gateways, and distributed logging
Module boundary enforcement	NestJS module encapsulation prevents cross-domain coupling	Enforced by network isolation
Scalability	Horizontal scaling via load balancer; Redis adapter enables stateless instances	Fine-grained per-service scaling




Figure 1: High-level architecture diagram

Justification: The Modular Monolithic pattern provides equivalent module isolation to Microservices while eliminating the operational overhead of distributed service orchestration. The NestJS module system enforces strict dependency injection boundaries, preventing domain coupling without requiring network-level separation. Horizontal scalability is still achievable via load-balanced deployments with the Redis-backed Socket.IO adapter, which maintains stateless WebSocket sessions.

Summary Use Case:

1. **Authentication:** Guests and users can create accounts, securely log in, verify their email addresses, and reset their passwords.
2. **Content Discovery:** Visitors and users can browse chronological feeds and search for specific users, hashtags, or communities.
3. **Post Management:** Users can create new posts with rich media attachments, embed hashtags, and edit or delete their own content.

4. **Post Interaction:** Users can actively engage with the platform by liking, commenting, replying to threads, reposting, and saving posts.
5. **Relationship Management:** Users can follow or unfollow other profiles to curate their personal feed, and block or unblock users for privacy.
6. **Profile Management:** Users can update their personal public profiles, including display name, bio, and avatar, and view their activity history.
7. **Direct Messaging:** Users can communicate privately with other members through real-time direct messages.
8. **Real-time Notifications:** Users receive instant system alerts for social interactions such as new followers, likes, comments, and messages.
9. **Community Management:** Users can create specialized communities, join or leave existing groups, and manage community rules and members.
10. **Administrative Moderation:** System administrators hold elevated privileges to manage user accounts, apply global bans, and resolve content reports.




Figure 2: Summary Goal Use Case

Actors:

1. **Guest / Unregistered User:** Can browse public feeds, view user profiles.
2. **User / Registered User:** Can publish micro-blogs, actively interact with content, manage personal connections, send direct messages, and participate in com-

munities.

3. **System Admin:** Manages the platform's integrity by reviewing user-reported content, resolving community disputes, and applying global bans accounts.

Use Cases:

1. Sign Up/ Login: Visitors can register a new account to become users.
2. Verify Email: Users must submit a secure code to verify emails.
3. Password Recovery: Users can securely reset forgotten passwords via email links.
4. Manage Profile: Users can update their public bio, avatar, and display name.
5. View Public Feed: Visitors browse public posts and profiles without authenticating.
6. Search & Discovery: Users can search for profiles, communities, trending hashtags.
7. Create Post: Users can publish micro-blogs and seamlessly attach rich media.
8. Edit & Delete Post: Users can modify or permanently remove their published content.
9. Post Interaction: Users can engage by liking, reposting, or bookmarking posts.
10. Threaded Comments: Users can participate in multi-level discussion threads posts.
11. Relationship Management: Users can follow or unfollow accounts to curate feeds.
12. User Blocking: Users can bidirectionally block accounts to ensure personal privacy.
13. Direct Messaging: Users communicate privately through a real-time chat interface.
14. Real-time Notifications: Users receive instant alerts for followers, likes, messages.
15. Community Management: Users can create specialized communities, manage group
16. Create Community: Users establish specialized groups for specific topic discussions.
17. Join/Leave Community: Users can subscribe, unsubscribe from community forums.
18. Manage Users: System administrators can view user lists and apply bans.
19. Handle Reports: Administrators can review and resolve content reported by users.
20. Moderate Content: Administrators can delete inappropriate posts platform guidelines.

Activity Diagram:

Authentication & Account Management:




Figure 3: Authentication & Account Management

Feeds and Discovery:




Figure 4: Feeds and Discovery

Post Management:




Figure 5: Post Management

Post Interaction:




Figure 6: Post Interaction

User Relationship Management:




Figure 7: User Relationship Management

User Profile Management:




Figure 8: User Profile Management

Direct Messaging:




Figure 9: Direct Messaging

Real-time Notifications:




Figure 10: Real-time Notifications

Community Management:




Figure 11: Community Management

Administrative Moderation:




Figure 12: Administrative Moderation

Entity Relationship Diagram:




Figure 13: Entity Relationship Diagram

This section covers the all-database entities (tables) for the project. A more detailed and higher resolution version of the Entity Relationship Diagram is available in the Appendix section.

Summary:

1. Identity & Access -Related Tables




Figure 14: Identity & Access – Related Tables

Table 17: Identity & Access - Related Tables

●User Description: Core entity representing every platform account, storing identity, profile, and system-level access state. Fields: id (PK, String, cuid) email (String, unique) username (String, unique) password (String, nullable) emailVerified (DateTime, nullable) displayName (String, nullable) bio (String, nullable) location (String, nullable) job (String, nullable) website (String, nullable) img (String, nullable) cover (String, nullable) role (Enum: USER ADMIN) banned (Boolean, default: false) createdAt / updatedAt (DateTime) Relationships: One-to-Many with interaction tables (Post, Comment, Like, etc.)	●VerificationToken Description: Stores single-use OTP codes for email verification and password reset flows. Automatically deleted after use or expiry. Fields: identifier (PK, String) - e.g., "email-verify:user123" token (PK, String) - 6-digit OTP or UUID string expires (DateTime) - Expiration timestamp Relationships: One-to-Many with nearly all other tables (Post, Comment, Like, Follow, etc.)
---	---

1. Content -Related Tables




Figure 15: Content – Related Tables

Table 18: Content -Related Tables

●Post Description: The backbone of the feed. Represents original post, repost, and through self-referencing belong community. Fields: id (PK, Int) userId (FK, String) - The author communityId (FK, Int, nullable) desc (String, nullable) isSensitive (Boolean) isApproved (Boolean) rePostId (FK, Int, nullable) parentPostId (FK, Int, nullable) - deletedAt (DateTime, nullable) Relationships: Self-reference for reposts Many-to-One with User, Community One-to-Many with PostMedia, Comment, Like, SavedPosts, PostTag, Notification, Report, Mention	●PostMedia Description: Stores images/videos attached Post. Fields: id (PK, Int) postId (FK, Int) url (String) CDN path (Cloudinary/S3) type (String) — "IMAGE" "VIDEO" "FILE" width, height (Int, nullable) Used for layout rendering createdAt (DateTime) Relationships: Many-to-One with Post (Cascade delete)
●Comment Description: Stores user replies to a Post. Fields: id (PK, Int) postId (FK, Int) url (String) CDN path (Cloudinary/S3) type (String) — "IMAGE" "VIDEO" "FILE" width, height (Int, nullable) createdAt (DateTime) Relationships: Self-referencing nested comment tree Many-to-One with User, Post One-to-Many with CommentMedia, CommentLike, Mention, Notification	●CommentMedia Description: File attachments inside comments. Fields: id (PK, Int) commentId (FK, Int) url (String) CDN path type (String) — "IMAGE" "VIDEO" "FILE" width, height (Int, nullable) createdAt (DateTime) Relationships: Many-to-One with Comment

Continued on next page

(Continued from previous page)

●Post Description: The backbone of the feed. Represents original post, repost, and through self-referencing belong community. Fields: id (PK, Int) userId (FK, String) - The author communityId (FK, Int, nullable) desc (String, nullable) isSensitive (Boolean) isApproved (Boolean) rePostId (FK, Int, nullable) parentPostId (FK, Int, nullable) - deletedAt (DateTime, nullable) Relationships: Self-reference for reposts Many-to-One with User, Community One-to-Many with PostMedia, Comment, Like, SavedPosts, PostTag, Notification, Report, Mention	●PostMedia Description: Stores images/videos attached Post. Fields: id (PK, Int) postId (FK, Int) url (String) CDN path (Cloudinary/S3) type (String) — "IMAGE" "VIDEO" "FILE" width, height (Int, nullable) Used for layout rendering createdAt (DateTime) Relationships: Many-to-One with Post (Cascade delete)
●Hashtag Description: Normalized registry of tags to serve the Trending feature. Fields: id (PK, Int) tag (String, unique) Lowercase tag string, e.g. "technology" createdAt (DateTime) Relationships: One-to-Many with PostTag	●PostTag Description: Join table resolving the Many-to-Many relationship between Posts and Hashtags. Created/updated automatically when a post is submitted or edited. Fields: postId (PK, FK, Int) hashtagId (PK, FK, Int) Relationships: Composite Primary Key with 2 FKs.

1. Social Engagement Tables




Figure 16: Social Engagement – Related Tables

Table 19: Social Engagement – Related Tables

●Follow Description: Directed social graph edge. Determines which users appear in the personalized home feed of the follower. Fields: id (PK, Int) followerId (FK, String) followingId (FK, String) notify (Boolean, default: false) Push notification preference for this specific follow createdAt (DateTime) Relationships: Many-to-One with User twice (follower and following sides)	●Block Description: Mutual blacklist between two users. Prevents all interactions (follow, message, view posts). Automatically removes existing follows between both parties. Fields: id (PK, Int) blockerId (FK, String) — The user initiating the block blockedId (FK, String) — The user being blocked createdAt (DateTime) Relationships: Many-to-One with User twice. Unique constraint on [blockerId, blockedId].
●Like Description: Records a User's "like" reaction on a Post. Triggers a LIKE notification to the post author. Fields: id (PK, Int) userId (FK, String) postId (FK, Int) createdAt (DateTime) Relationships: Many-to-One with User, Post	●CommentLike Description: Records a User's "like" reaction on a Comment. Unique constraint prevents double-liking. Fields: id (PK, Int) userId (FK, String) commentId (FK, Int) createdAt (DateTime) Relationships: Many-to-One with User, Comment (Cascade delete) Unique constraint on [userId, commentId]

Continued on next page

(Continued from previous page)

●Follow Description: Directed social graph edge. Determines which users appear in the personalized home feed of the follower. Fields: id (PK, Int) followerId (FK, String) followingId (FK, String) notify (Boolean, default: false) Push notification preference for this specific follow createdAt (DateTime) Relationships: Many-to-One with User twice (follower and following sides)	●Block Description: Mutual blacklist between two users. Prevents all interactions (follow, message, view posts). Automatically removes existing follows between both parties. Fields: id (PK, Int) blockerId (FK, String) — The user initiating the block blockedId (FK, String) — The user being blocked createdAt (DateTime) Relationships: Many-to-One with User twice. Unique constraint on [blockerId, blockedId].
●SavedPosts Description: User's personal bookmark list. Posts saved here appear in the /bookmarks. Fields: id (PK, Int) userId (FK, String) postId (FK, Int) createdAt (DateTime) Relationships: Many-to-One with User, Post	●Mention Description: Records every @username tag inside a post or comment body. Parsed automatically on create/edit. Triggers a MENTION notification to the tagged user. Fields: id (PK, Int) userId (FK, String) username (String) postId (FK, Int, nullable) commentId (FK, Int, nullable) createdAt (DateTime) Relationships: Many-to-One with User, Post, Comment (Cascade delete)

1. Community & Moderation Tables




Figure 17: Community & Moderation - Related Tables

Table 20: Community & Moderation Tables

●Community Description: Represents a Sub-reddit style group, a shared space for members with common interests. Fields: id (PK, Int) slug (String, unique) URL identifier, e.g. breadit.com/c/technology name (String) Display name description (String, nullable) img (String, nullable) cover (String, nullable) createdAt / updatedAt (DateTime) Relationships: One-to-Many with Post, Member, Rule, BannedUser	CommunityMember Description: Unique Constraint: 1 User can join a specific community only once. Fields: id (PK, Int) userId (FK, String) communityId (FK, Int) role (Enum: MEMBER MOD OWNER, default: MEMBER) createdAt (DateTime) Relationships: Many-to-One with User, Community Unique constraint on [userId, communityId] one role per user per community
●CommunityRule Description: Custom rules and regulations set by Community Admins. Fields: id (PK, Int) communityId (FK, Int) title (String) - Rule headline Relationships: Many-to-One with Community	●CommunityBannedUser Description: Blacklist for individual Communities, enforced by local Moderators. Fields: id (PK, Int) reason (String, nullable) - Ban reason userId (FK, String) - The banned user communityId (FK, Int) Relationships: Many-to-One with User, Community Unique [userId, communityId]

1. Communication Tables




Figure 18: Communication – Related Tables

Continued on next page

(Continued from previous page)

●Conversation Description: Represents a single 1-to-1 Direct Message thread between two users. A conversation is created once and reused for all subsequent messages between the same pair. Fields: id (PK, Int) createdAt (DateTime) updatedAt (DateTime) Bumped on every new message; used to sort inbox by latest activity Relationships: One-to-Many with ConversationMember, Message	●ConversationMember Description: Junction table linking Users to Conversations. Tracks each participant's last-read timestamp, which powers the unread message badge count. Fields: conversationId (PK, FK, Int) userId (PK, FK, String) lastReadAt (DateTime, default: now()) Messages newer than this are considered "unread" Relationships: Composite PK ensures a user appears only once per conversation. Many-to-One to Conversation, User
--	--

Table 21: Communication Tables

●Conversation Description: Represents a single 1-to-1 Direct Message thread between two users. A conversation is created once and reused for all subsequent messages between the same pair. Fields: id (PK, Int) createdAt (DateTime) updatedAt (DateTime) Bumped on every new message; used to sort inbox by latest activity Relationships: One-to-Many with ConversationMember, Message	●ConversationMember Description: Junction table linking Users to Conversations. Tracks each participant's last-read timestamp, which powers the unread message badge count. Fields: conversationId (PK, FK, Int) userId (PK, FK, String) lastReadAt (DateTime, default: now()) Messages newer than this are considered "unread" Relationships: Composite PK ensures a user appears only once per conversation. Many-to-One to Conversation, User
●Message Description: Individual message sent within a Conversation. Delivered in real-time via Socket.IO. Supports text and media attachments. Fields: id (PK, Int) conversationId (FK, Int)	●Notification Description: System-generated alert delivered to a recipient user when a relevant action occurs. Pushed in real-time via Socket.IO and persisted for the inbox view. Fields: id (PK, Int)

(Continued from previous page)

●Conversation Description: Represents a single 1-to-1 Direct Message thread between two users. A conversation is created once and reused for all subsequent messages between the same pair. Fields: id (PK, Int) createdAt (DateTime) updatedAt (DateTime) Bumped on every new message; used to sort inbox by latest activity Relationships: One-to-Many with ConversationMember, Message	●ConversationMember Description: Junction table linking Users to Conversations. Tracks each participant's last-read timestamp, which powers the unread message badge count. Fields: conversationId (PK, FK, Int) userId (PK, FK, String) lastReadAt (DateTime, default: now()) Messages newer than this are considered "unread" Relationships: Composite PK ensures a user appears only once per conversation. Many-to-One to Conversation, User
●Report Description: Content flagging system. Any user can submit a report against a Post. System Admins review the report queue Fields: id (PK, Int) reporterId (FK, String) — The user who submitted the report postId (FK, Int) — The flagged post reason (String) Report reason text (e.g., "Spam", "Hate speech") status (Enum: OPEN CLOSED, default: OPEN) createdAt (DateTime) Relationships: Many-to-One with User (reporter), Post	

Class Diagram:




Figure 19: Class Diagram

Summary:

1. Identity & Access Domain Classes

Table 22: Identity & Access Domain Classes

User Description: Core entity representing every platform account, storing identity and system-level access state. Attributes: id: String (PK) email: String username: String password: String emailVerified: DateTime displayName: String role: Role banned: Boolean Key Methods: register(): Registers a new user login(): Authenticates the user verifyEmail(): Verifies email address updateProfile(): Updates profile details toggleFollow(): Follows or unfollows another user toggleBlock(): Blocks or unblocks another user Relationships: Composition -> Account (one-to-many) Composition -> Session (one-to-many) Association -> Follow Association -> Block Association-> CommunityMember Association -> Post Association -> Comment Association -> Notification	VerificationToken Description: Stores single-use OTP codes for email verification and password reset. Attributes: identifier: String (PK) token: String expires: DateTime Key Methods: None Relationships: None
--	--

1. Content Domain Classes

Table 23: Content Domain Classes

Post Description: Represents original posts, reposts, and quote-reposts. Attributes: id: Int (PK) userId: String (FK) communityId: Int (FK) desc: String isApproved: Boolean rePostId: Int (FK) parentPostId: Int (FK) createdAt: DateTime Key Methods: create(): Creates a new post remove(): Soft deletes the post getFeed(): Retrieves post feed report(): Reports the post Relationships: Association -> User Association -> Community Composition -> PostMedia (one-to-many) Composition -> Comment (one-to-many) Association -> PostTag (one-to-many)	Comment Description: User replies to a Post, supporting nested comment threads. Attributes: id: Int (PK) postId: Int (FK) userId: String (FK) parentCommentId: Int (FK) body: String createdAt: DateTime Key Methods: create(): Adds a comment remove(): Removes a comment Relationships: Association -> User Association -> Post Composition -> CommentMedia (one-to-many)
PostMedia Description: Stores image and video attachments for a Post. Attributes: id: Int (PK) postId: Int (FK) url: String type: String Key Methods: upload(): Uploads media file Relationships: Association -> Post	CommentMedia Description: File attachments embedded inside comments. Attributes: id: Int (PK) commentId: Int (FK) url: String type: String Relationships: Association -> Comment

Continued on next page

(Continued from previous page)

Post Description: Represents original posts, reposts, and quote-reposts. Attributes: id: Int (PK) userId: String (FK) communityId: Int (FK) desc: String isApproved: Boolean rePostId: Int (FK) parentPostId: Int (FK) createdAt: DateTime Key Methods: create(): Creates a new post remove(): Soft deletes the post getFeed(): Retrieves post feed report(): Reports the post Relationships: Association -> User Association -> Community Composition -> PostMedia (one-to-many) Composition -> Comment (one-to-many) Association -> PostTag (one-to-many)	Comment Description: User replies to a Post, supporting nested comment threads. Attributes: id: Int (PK) postId: Int (FK) userId: String (FK) parentCommentId: Int (FK) body: String createdAt: DateTime Key Methods: create(): Adds a comment remove(): Removes a comment Relationships: Association -> User Association -> Post Composition -> CommentMedia (one-to-many)
Hashtag & PostTag Description: Registry of tags and the junction class link Posts to Hashtags. Key Methods: getPostsByTag(): Retrieves posts by hashtag Relationships: Association -> Post	

1. Social Engagement Domain Classes

Table 24: Social Engagement Domain Classes

Follow Description: Directed social graph edge for user following. Attributes: id: Int (PK) followerId: String (FK) followingId: String (FK) notify: Boolean createdAt: DateTime Key Methods: toggleFollow(): Follows/unfollows Relationships: Association -> User	Like Description: Records a User's reaction on a Post. Attributes: id: Int (PK) userId: String (FK) postId: Int (FK) createdAt: DateTime Key Methods: toggleLike(): Likes/ unlikes a post Relationships: Association -> User Association -> Post
Block Description: Mutual blacklist between two users. Attributes: id: Int (PK) blockerId: String (FK) blockedId: String (FK) createdAt: DateTime Key Methods: toggleBlock(): Blocks or unblocks a user Relationships: Association -> User	SavedPost Description: User's personal bookmark list. Attributes: id: Int (PK) userId: String (FK) postId: Int (FK) createdAt: DateTime Key Methods: toggleSave(): Save/unsave a post Relationships: Association -> User Association -> Post
Mention Description: Records @username tags inside content. Attributes: id: Int (PK) userId: String (FK) postId: Int (FK) commentId: Int (FK) username: String Relationships: Association -> User, Post, Comment	CommentLike Description: Records a User's reaction on a Comment. Attributes: id: Int (PK) userId: String (FK) commentID: Int (FK) Relationships: Association -> User Association -> Comment

1. Community & Moderation Domain Classes

Table 25: Community & Moderation Domain Classes

Community Description: A shared space for members with a common interest. Attributes: id: Int (PK) name: String slug: String description: String createdAt: DateTime Key Methods: create(): Creates a new community update(): Update community detail delete(): Deletes the community join(): Joins/ leaves the community banUser(): Bans a user from the community moderatePost(): Approves/rejects a post Relationships: Composition -> CommunityMember Composition -> CommunityRule Composition-> Community-BannedUser Composition -> Post	CommunityMember Description: Manages community members and their roles. Attributes: id: Int (PK) userId: String (FK) communityId: Int (FK) role: CommunityRole Key Methods: promoteMember(): Promotes a member to moderator transferOwnership(): Transfers community ownership Relationships: Association -> Community Association -> User
CommunityBannedUser Description: Community-level blacklist enforced by Moderators. Attributes: id: Int (PK) userId: String (FK) communityId: Int (FK) reason: String Relationships: Association -> User Association -> Community	CommunityRule Description: Custom rules set by the community. Attributes: id: Int (PK) communityId: Int (FK) title: String description: String Key Methods: addRule(): Adds a new rule removeRule(): Removes a rule Relationships Association -> Community

1. Communication Domain Classes

Table 26: Communication Domain Classes

ShopOrder Description: Represents a direct message thread. Attributes: id: Int (PK) updatedAt: DateTime Key Methods: getConversations(): Retrieves user conversations findOrCreate(): Finds or creates a conversation thread Relationships: Composition -> ConversationMember (one-to-many) Composition -> Message (one-to-many)	Notification Description: System-generated alert Attributes: id: Int (PK) recipientId: String (FK) actorId: String (FK) type: NotificationType readAt: DateTime Key Methods: emit(): Emits real-time notification markRead(): Marks notification markAllRead(): Marks all notifications as read Relationships: Association -> User Association -> Post Association -> Comment
ConservationMember Description: Junction class tracking conversation participants. Attributes: conversationId: Int (FK) userId: String (FK) lastReadAt: DateTime Relationships: Association -> User Association -> Conversation	Report Description: Content flagging system for moderation. Attributes: id: Int (PK) reporterId: String (FK) postId: Int (FK) status: ReportStatus reason: String Key Methods: getReports(): Retrieves list post dismiss(): Dismisses a report deleteReportedPost(): Deletes the reported post Relationships: Association -> User Association -> Post

Continued on next page

(Continued from previous page)

ShopOrder Description: Represents a direct message thread. Attributes: id: Int (PK) updateAt: DateTime Key Methods: getConversations(): Retrieves user conversations findOrCreate(): Finds or creates a conversation thread Relationships: Composition -> ConversationMember (one-to-many) Composition -> Message (one-to-many)	Notification Description: System-generated alert Attributes: id: Int (PK) recipientId: String (FK) actorId: String (FK) type: NotificationType readAt: DateTime Key Methods: emit(): Emits real-time notification markRead(): Marks notification markAllRead(): Marks all notifications as read Relationships: Association -> User Association -> Post Association -> Comment
Message Description: Individual message within a conversation. Attributes: id: Int (PK) conversationId: Int (FK) senderId: String (FK) body: String Key Methods: sendMessage(): Sends a new message markRead(): Marks message as read Relationships: Association -> User Association -> Conversation	

Sequence Diagram

This section presents ten sequence diagrams that model the dynamic behavior of the Breadit social network, mapping directly to its core use cases. These diagrams visualize the runtime interactions between the user, Next.js frontend, NestJS backend API, PostgreSQL database (via Prisma), and real-time Socket.IO/Redis pipeline. The illustrated flows cover: (1) Authentication, (2) Content Discovery, (3) Post Management, (4) Post Interaction, (5) Relationship Management, (6) Profile Management, (7)

Direct Messaging, (8) Real-Time Notifications, (9) Community Management, and (10) Administrative Moderation.

Authentication & Account Management




Figure 20: Authentication & Account Management Diagram

Feeds and Discovery




Figure 21: Feeds and Discovery Diagram

Post Management




Figure 22: Post Management Diagram

Post Interaction




Figure 23: Post Interaction Diagram

User Relationship Management




Figure 24: User Relationship Management Diagram

User Profile Management




Figure 25: User Profile Management Diagram

Direct Messaging




Figure 26: Direct Messaging Diagram

Real-time Notifications




Figure 27: Real-time Notifications Diagram

Community Management




Figure 28: Community Management Diagram

Administrative Moderation




Figure 29: Administrative Moderation Diagram

3.3 User Requirement Analysis:

3.3.1 User Interface Design:

Breadit's user interface is split into two primary areas: a public-facing social network and a restricted administrative console. The user interface adapts a standardized three-column grid layout (navigation sidebar, central feed, and contextual discovery widgets) inspired by popular micro-blogging platforms like X/Twitter. This layout maximizes usability and reduces the learning curve for core social interactions. In contrast, the administrative panel uses a dark-themed dashboard focused purely on

data visibility and moderation efficiency.

The client-side interface covers the user journey through the following main views:

- **Authentication & Verification:** Registration (Sign Up), login (Sign In), password recovery, and a 6-digit OTP verification view to validate email ownership.
- **Unified Feed & Discovery:** Home timeline featuring "For You" (chronological) and "Explore" (trending by likes) tabs, supported by infinite-scroll hashtag feeds and a debounced search dropdown.
- **Post Details & Profiles:** Individual post views with nested comment threads and media overlays, and user profiles containing filter tabs (Posts, Replies, Media...).
- **Messaging & Communities:** A real-time 1:1 chat interface powered by Socket.IO, and community pages featuring dedicated sub-feeds, group rules, and post submission queues.
-

The moderation console contains two core operational views:

- **User Management (/admin-console/users):** A searchable registry of users with controls to ban or reinstate suspended accounts.
- **Content Moderation (/admin-console/reports):** A real-time queue of flagged posts and comments, allowing admins to dismiss reports or delete offending content.

To maintain structural clarity and avoid redundant layouts in Chapter 3, mock-ups and user interface screenshots are excluded from this section and reserved for Chapter 5 (Demonstration). This section concentrates purely on design patterns and architectural user flows. Design inspirations and reference frameworks utilized in formulating the dashboard grid structure are acknowledged in the project bibliography, while screenshots of the deployed application in Chapter 5 document the actual system behavior.

3.4 Technology Summary:

This section provides a detailed overview of the technologies selected for the implementation of the full-stack micro-blogging and real-time social networking platform. While Chapter 2 outlined the theoretical concepts and general characteristics of modern web architectures, this section expands on those fundamentals by specifying their practical applications, architectural roles, and operational integration within the system. The integration of frontend, backend, caching, and database layers forms a cohesive, high-performance stack designed to support fast page rendering, real-time bidirectional communication, and provide an architectural foundation for the future integration of advanced trending and content trending/recommendation algorithms.

3.4.1 Front – end:

Technology Used: Next.js

Next.js 15, powered by React 19, serves as the primary frontend framework for the platform. Utilizing the App Router architecture, Next.js combines Server-Side Rendering (SSR) for static content optimization with client-side interactivity, delivering a highly responsive, performant, and SEO-friendly social media interface.

Architectural Role

Next.js is responsible for:

- Rendering page layouts and feeds (Home, Explore, Hashtags) dynamically.
- Managing user interaction states, including composing posts, liking content, commenting in threads, and updating profile settings.
- Communicating the NestJS backend via REST APIs for core CRUD transaction.
- Establishing a persistent Socket.IO connection to receive real-time notifications and handle instant messaging.

Key Mechanisms and Features Applied

Server & Client Component Architecture

The application leverages the separation of Server and Client components in. Static structures are pre-rendered on the server to optimize loading speeds, while interactive elements are modularized into client-side reusable components, such as:

- Layout navigation: Leftbar (menu, user profile link) and Rightbar (search, trending, follow suggestion).
- Social interaction: Post (post/reposts), Comment (nested replies) and chat pop-ups.

State Management and Caching (TanStack Query)

To manage server state efficiently without complex global store boilerplate:

- Instantly reflects actions (toggling a posts like status or following a user) in the UI before the backend confirmation completes, ensuring a zero-latency user experience.
- Caches user timelines, notification histories, and search results to prevent redundant API calls.

Real-Time WebSocket Connection (Socket.IO)

For real-time features, the client maintains a persistent WebSocket connection.

- Pushes real-time alerts (likes, follows, mentions, reposts) to users.
- Supports live, bidirectional transmission in the 1:1 chat interface, bypassing the overhead of traditional HTTP polling.

Infinite Scrolling & Asynchronous Fetching

To display long timelines without degrading browser performance, the application implements cursor-based pagination and infinite scrolling. As the next-page items are requested asynchronously, while skeleton screens are shown during data loading states.

Justification

- **Optimized Performance:** Built-in features like route pre-fetching and asset optimization drastically reduce initial page load times.
- **Architectural Flexibility:** The modular, hook-driven architecture allows for easy expansion, making the codebase ready to integrate advanced content recommendation systems and trending pipelines in future phase.

3.4.2 Back – end:

Technology Used: NestJS (TypeScript) + Fastify

NestJS, running on TypeScript and configured with Fastify as the underlying HTTP server adapter, serves as the main backend framework for the system. This combination provides a modular, highly scalable, and enterprise-grade architecture capable of handling intensive social media and real-time I/O workloads with high concurrency and low latency.

Architectural Role

The backend acts as the system's central business logic and data distribution layer:

- Handles user session state and authentication (JWT cookie-based authentication)
- Manages core social networking domain workflows (feed query generation...)
- Manages database transaction and query logic PostgreSQL via Prisma ORM client.
- Dispatches real-time events (likes, notifications, messages) using Socket.IO gateways.

- Restricts API access via Guards, Pipes, and Throttling middleware.

Key Mechanisms and Features Applied

High-Performance Asynchronous I/O (NestJS + Fastify)

Instead of standard Express engines, NestJS is configured with Fastify to support rapid asynchronous I/O execution. This enables:

- Fast handling of simultaneous HTTP requests under high traffic.
- Efficient processing of pagination queries for massive feeds.
- Low-overhead file streaming and media uploads (Fastify's multipart performance).

DTO-Based Data Validation (Class Validator & Pipes)

All incoming API requests go through NestJS ValidationPipes:

- Utilizes class-validator and class-transformer to enforce strict DTO (data transfer object) schemas.
- Sanitizes input and rejects malformed payloads before they reach service methods, preventing injection attacks and ensuring data integrity.

Modular Architecture & REST Services

The backend is divided into specialized modules (Auth, Users, Posts, Messages, Notifications, Communities) adhering to NestJS's dependency injection principles:

- Exposes structured RESTful endpoints (POST /api/auth/register, GET /api/posts/feed)
- Separates database operations using Prisma client services.
- This design supports future migration into isolated microservices if necessary.

Integration with the Trending/Recommendation Engine

Real-time Event Broadcasting (Socket.IO + Redis Adapter)

To support instant notifications and direct messages, the backend implements:

- WebSocket Gateways: Encapsulated within Socket.IO gateways to manage client WebSocket sessions.
- Redis Adapter: Utilizes redis-adapter to synchronize WebSocket events across multiple server instances, ensuring horizontal scaling.

Justification

NestJS + Fastify was chosen due to:

- **Modular and Scalable Structure:** Dependency injection and module design result in a highly testable and maintainable codebase.
- **Substantial Performance Gains:** Fastify handles up to two times more requests per second compared to Express, offering optimal resource utilization.
- **Robust Database Integration:** Prisma ORM provides type-safe query building, auto-generated migrations, and high developer velocity.
- **Ready for Future Scale:** The architectural decoupling of services and the integration of Redis adapters ensure the system can scale both vertically and horizontally, easily accommodating real-time recommendation engines or dedicated feed-processing workers in future iterations.

3.4.3 Database:

The system incorporates a hybrid storage architecture combining a relational database with an in-memory data store to optimize transactional consistency, real-time state synchronization, and low-latency cache queries.

Relational Database: PostgreSQL

Architectural Role

PostgreSQL-the primary relational database, stores all structured application entities:

- **User Identity & Relations:** Accounts, profile data, bidirectional follow/block relationships.
- **Content & Interactions:** Posts, media attachments, nested comments, likes, saves, and report logs.
- **Messaging & Communities:** 1:1 direct messages, conversation memberships, and community settings (rules, bans).

Why PostgreSQL

- **Strong ACID Compliance:** Guarantees transaction reliability for user registrations, authentication flows, and content states.
- **Advanced Relational Modeling:** Supports complex self-referencing structures essential for nested comments and reposts.

- **Seamless ORM Compatibility:** Integrates cleanly with Prisma ORM for automated schema migrations and type-safe database queries.

Applied Features

- **Data Integrity Constraints:** Unique constraints on fields and compound keys for relationship records.
- **Query Optimization:** Custom indexes on frequently queried fields to speed up timeline rendering.
- **Atomic Transactions:** Atomic database writes via Prisma Transaction APIs to register multiple related records simultaneously.


3.4.4 Deployment

The Breadit system is designed to be deployed in a cloud environment using the PaaS (Platform as a Service) and Serverless models. Specialized cloud services help minimize infrastructure management overhead, automate the CI/CD (Continuous Integration/Continuous Deployment) pipeline, and optimize performance for each application component.

The physical deployment architecture consists of the following components:

- **Frontend (Next.js):** Deployed on Vercel (Serverless & CDN).
- **Backend (NestJS):** Deployed on Render (Containerized Web Service).
- **Database (PostgreSQL):** Manage database service provided by Supabase.
- **Cache (Redis):** The Serverless Redis service provided by Upstash.
- **Media Storage & CDN:** The cloud storage and media delivery services of Cloudinary.

Workflow



Flow A: (Frontend)

- Trigger: The developer pushes new source code to the main branch of the GitHub repository.
- Build Pipeline: Vercel detects modifications within the frontend directory (apps/frontend/). An automated build pipeline is triggered on Vercel's infrastructure:
 - Node.js environment initialization.
 - Compiling Next.js source code to a production-ready build (optimizing static pages, server-side routes, and minifying assets).
- Deployment: Once compilation succeeds, the build artifact is deployed and distributed across Vercel's global Edge CDN network. Vercel's router seamlessly redirects user traffic to the new version without any downtime.

Flow B: (Backend)

- Trigger: Similarly, a push event to the main branch fires a webhook targeting Render.

- **Docker Build:** Render identifies changes in the backend directory (`apps/backend/`) and reads the configured Dockerfile (`apps/backend/Dockerfile`):
 - A multi-stage Docker build runs to minimize the final container image size.
 - Environment variables such as `DATABASE_URL` (pointing to Supabase) and `REDIS_URL` (pointing to Upstash) are injected during runtime.
- **Deploy Container:** Render spawns the NestJS backend container from the compiled Docker image. It performs continuous health checking via the `/api/health` endpoint. Once the container responds with a healthy status (200 OK), Render routes incoming API traffic to the new container and safely terminates the deprecated instance.

Networking and Security

- **Transport Layer Security (HTTPS/WSS):** All connections from user browsers to the Frontend (Vercel) and Backend (Render) are strictly encrypted using HTTPS and WSS (Secure WebSockets). SSL/TLS certificates are provisioned and auto-renewed Encrypt.
- **CORS (Cross-Origin Resource Sharing):** The NestJS backend enforces a strict CORS policy, authorizing only requests originating from the official Frontend domain access API resources.
- **Database Isolation:** PostgreSQL on Supabase and Redis on Upstash are secured behind complex password authentication mechanisms and require SSL-encrypted connections. Database access ports are tightly restricted and shielded from the public internet.
- **Authentication Security:** JWT authentication tokens are securely transmitted between client and server via Cookies configured with the `httpOnly` flag (mitigating XSS token theft risks) and the `Secure` flag (restricting transmissions to HTTPS connections only).

Compute and Scalability

- **Frontend Compute:** Leveraging Vercel's serverless infrastructure, static assets are cached at Edge nodes. Serverless API functions scale up and down instantly to accommodate fluctuating user traffic without manual configuration.
- **Backend Compute:** The NestJS container instance running on Render is continuously monitored for CPU and memory utilization. Under high load, Render supports both vertical scaling (allocating more CPU/RAM resources) and horizontal scaling (replicating multiple container instances running in parallel).
- **Caching & Load Reduction:** The integration of Upstash Redis allows heavy queries (such as the Trending Feed) to be cached. This significantly alleviates processing overhead on the NestJS backend CPU and reduces direct read IOPS on the primary PostgreSQL database.

Database Service

- The primary data layer of Breadit is powered by Supabase (Managed PostgreSQL):
 - Database Engine: PostgreSQL 16 running on optimized cloud infrastructure.
 - Role: Stores structured data across the system, including User Profiles, Posts, Comments, Communities (Sub-breadits), Votes, and Moderation Reports.
 - Automated Management: Features automated daily backups and Connection Pooling (via PgBouncer/Supabase Pooler) to sustain thousands of concurrent connections from the Backend without exhausting system resources.
 - ORM Integration: Integrates seamlessly with Prisma ORM on the backend to synchronize schema definitions and execute database migrations safely.

Chapter 4

IMPLEMENTATION

4.1 Project Structure Overview:

The Breadit project is structured as a monorepo utilizing npm workspaces. This architecture decouples the frontend client interface, backend server logic, and shared utility definitions, allowing independent component lifecycle management, easier deployment containerization, and unified types across the platform.




Figure 30: Project Structure

4.2 Backend Implementation

The backend functionality of Breadit is developed using the NestJS framework built on top of Fastify for high-performance HTTP request handling and WebSocket

communication. The server interacts with a PostgreSQL database using Prisma ORM to manage data persistence and type safety across database operations.

4.2.1 Database Models

The system's data layer architecture is centrally defined in the `schema.prisma` file. This configuration file houses declarative schema models that Prisma translates into relational database tables and TypeScript interfaces.

```

model User {
  id          String    @id @default(cuid())
  email       String    @unique
  username    String    @unique
  password    String?
  emailVerified DateTime?
  displayName String?
  bio         String?
  location    String?
  job         String?
  website     String?
  img         String?
  cover       String?
  role        Role      @default(USER)
  banned      Boolean    @default(false)
  createdAt   DateTime   @default(now())
  updatedAt   DateTime   @updatedAt

  // RELATIONS
  posts Post[]

  likes Like[]

  saves SavedPosts[]

  followers Follow[] @relation("UserFollowers")
  followings Follow[] @relation("UserFollowings")

  accounts Account[]
  sessions Session[]

  comments      Comment[]
  commentLikes  CommentLike[]

  receivedNotifications Notification[] @relation("ReceivedNotifications")
  sentNotifications    Notification[] @relation("SentNotifications")

  blockerRelations Block[] @relation("BlockerUser")
  blockedRelations Block[] @relation("BlockedUser")
  reports          Report[]

  conversationMembers ConversationMember[]
  sentMessages        Message[]

  mentions Mention[]

  communities CommunityMember[]
  bannedFrom  CommunityBannedUser[]

```

Figure 31: Code Snippet – SiteUser Model Definition

4.2.2 Module 1: Authentication & Account Verification

Controller (API routes): Exposes RESTful endpoints for authentication. It integrates NestJS `@Throttle` decorators to enforce rate-limiting rules (maximum of 10 requests per 60 seconds) at the entry layer, protecting sensitive operations like

Registration, Login, and OTP Verification from automated dictionaries and brute-force attacks.

```
@Controller('api/auth')
export class AuthController {
  constructor(private readonly auth: AuthService) {}

  @Post('register')
  @Throttle({ default: { ttl: 60000, limit: 10 } })
  register(@Body() dto: RegisterDto) {
    return this.auth.register(dto);
  }

  @Post('login')
  @HttpCode(200)
  @Throttle({ default: { ttl: 60000, limit: 10 } })
  login(
    @Body() dto: LoginDto,
    @Res({ passthrough: true }) reply: FastifyReply,
  ) {
    return this.auth.login(dto, reply);
  }

  @Post('verify')
  @HttpCode(200)
  @Throttle({ default: { ttl: 60000, limit: 10 } })
  verifyEmail(@Body() dto: VerifyDto) {
    return this.auth.verifyEmail(dto.email, dto.code);
  }
}
```

Figure 32: Code Snippet – Authentication & Account Verification

Service (Business Logic): Implements secure password verification using bcrypt.compare against hashed credentials stored in PostgreSQL. Upon successful authentication, it generates stateless JSON Web Token (JWT) using the jose library containing the user session claims. This JWT is appended to the Fastify response header via a secure, httpOnly, sameSite: 'lax' cookie, shielding the application from Cross-Site Scripting (XSS) token interception.

```

async login(dto: LoginDto, reply: FastifyReply) {
  const user = await this.prisma.user.findUnique({
    where: { email: dto.email },
    select: { id: true, email: true, username: true, img: true, password: true, emailVerified: true, role: true,
      banned: true },
  });
  if (!user?.password) throw new UnauthorizedException('Invalid email or password');

  const ok = await bcrypt.compare(dto.password, user.password);
  if (!ok) throw new UnauthorizedException('Invalid email or password');

  const token = await signJwt({
    sub: user.id,
    username: user.username,
    email: user.email,
    emailVerified: user.emailVerified?.toISOString() ?? null,
    role: user.role,
    banned: user.banned,
  });
  setSessionCookie(reply, token);

  return {
    user: {
      id: user.id,
      username: user.username,
      email: user.email,
      emailVerified: user.emailVerified,
      img: user.img,
      role: user.role,
      banned: user.banned,
    }
  };
}

```

Figure 33: Code Snippet – Authentication & Account Verification

4.2.3 Module 2: Feeds & Discovery

Controller (API Routes): Handlers request for dynamic feed retrieval. It utilizes an OptionalJwtAuthGuard to determine session presence: if the request is authenticated, the client is identified (req.user.id) to fetch personalized interactions (such as like and bookmark statuses); if anonymous, the request bypasses session enforcement to serve generic public feeds.

```

@Get()
@UseGuards(OptionalJwtAuthGuard)
findAll(
  @Query('cursor') cursor = '1',
  @Query('user') user: string | undefined,
  @Query('feed') feed: string | undefined,
  @Query('communityId') communityId: string | undefined,
  @Req() req: AuthedRequest,
) {
  return this.postsService.findAll(
    cursor,
    user,
    req.user?.id,
    feed,
    communityId ? Number(communityId) : undefined,
  );
}

```

Figure 34: Code Snippet – Feed & Discovery

Service (Business Logic & Algorithm): Implements a time-decay explore feed ranking algorithm. The system aggregates dynamic user signals (likes, comments, reposts) and applies a linear decay factor based on post age (ageHours). It further applies a diversity filter (applyExploreDiversity) that limits consecutive posts from the same author to 3, ensuring feed variety and preventing monopoly of the explore feed by single active users.

```

function computeExploreScoreFixed(input: { likes: number; comments: number; reposts: number; ageHours: number }): number {
  const score = input.likes + input.comments * 2 + input.reposts * 3 - input.ageHours * 0.25;
  return Math.floor(score * 100);
}

// Inside PostsService.findAll() for feed === 'explore'
const scored = rows
  .map((p: any) => {
    const createdAtMs = new Date(p.createdAt).getTime();
    const ageHours = Math.max(0, (now - createdAtMs) / (1000 * 60 * 60));
    const likes = p?._count?.likes ?? 0;
    const comments = p?._count?.comments ?? 0;
    const reposts = p?._count?.rePosts ?? 0;
    const scoreFixed = computeExploreScoreFixed({ likes, comments, reposts, ageHours });
    return { post: p, scoreFixed, id: p.id as number, userId: p.userId as string };
  })
  .sort((a, b) => (b.scoreFixed - a.scoreFixed) || (b.id - a.id));

const diversified = applyExploreDiversity(scored, 3);

```

Figure 35: Code Snippet – Feed & Discovery

4.2.4 Module 3: Post Management

Controller (API Routes): Handles post creation requests submitted via multipart/form-data. Because the project runs on Fastify instead of Express, file uploads are processed asynchronously using non-blocking streams (req.parts()), which

significantly reduces memory utilization and avoids high-RAM spikes during concurrent heavy file uploads.

```
@Post()
@HttpCode(HttpStatus.CREATED)
@UseGuards(JwtAuthGuard, EmailVerifiedGuard)
async create(@Req() req: FastifyRequest & { user?: { id: string } }) {
  const body: {
    desc?: string;
    imgType?: string;
    rePostId?: number;
    isSensitive?: boolean;
    communityId?: number;
  } = {};
  const bufferedFiles: { buffer: Buffer; mimetype: string; filename: string }[] = [];

  try {
    for await (const part of req.parts()) {
      if (part.type === 'field') {
        const val = part.value as string;
        if (part.fieldname === 'desc') body.desc = val;
        else if (part.fieldname === 'imgType') body.imgType = val;
        else if (part.fieldname === 'rePostId') {
          const n = parseInt(val, 10);
          if (!isNaN(n)) body.rePostId = n;
        } else if (part.fieldname === 'communityId') {
          const n = parseInt(val, 10);
          if (!isNaN(n)) body.communityId = n;
        } else if (part.fieldname === 'isSensitive') {
          body.isSensitive = val === 'true';
        }
      } else if (part.type === 'file') {
        const buffer = await part.toBuffer();
        bufferedFiles.push({
          buffer,
          mimetype: part.mimetype,
          filename: part.filename,
        });
      }
    }
  } catch (err) {
    const mapped = mapMultipartUploadError(err);
    if (mapped.status === 'payload_too_large') throw new PayloadTooLargeException(mapped.message);
    throw new BadRequestException(mapped.message);
  }

  return this.postsService.create(req.user!.id, body, bufferedFiles);
}
```

Figure 36: Code Snippet – Post Management

Service (Business Logic): Executes post insertion and handles automatic hashtag discovery. It uses an ES6 RegExp `matchAll(/#([a-zA-Z0-9_]+)/g)` search to isolate tags, eliminate duplicate entries using a Set, and executes concurrent database upsert queries inside a Promise.all block. This establishes hashtag records and many-to-many relationship rows in SQL in a single non-blocking execution block.

```

if (body.desc) {
  const tags = [
    ...new Set(
      [...body.desc.matchAll(/#[a-zA-Z0-9_]+)/g)].map((m) =>
        m[1].toLowerCase(),
      ),
  ],
};
if (tags.length > 0) {
  await Promise.all(
    tags.map((tag) =>
      this.prisma.hashtag
        .upsert({ where: { tag }, create: { tag }, update: {} })
        .then((ht) =>
          this.prisma.postTag.upsert({
            where: { postId_hashtagId: { postId: post.id, hashtagId: ht.id } },
            create: { postId: post.id, hashtagId: ht.id },
            update: {},

```

Figure 37: Code Snippet – Post Management

4.2.5 Module 4: Post Interaction

Controller (API Routes): Exposes retrieval routes for comment feeds, integrates NestJS ParseIntPipe to sanitize and cast the parameter postId from a raw string into an integer directly at the controller routing layer, blocking malformed input types before database querying.

```

@Get('posts/:postId/comments')
@UseGuards(OptionalJwtAuthGuard)
findByPost(
  @Param('postId', ParseIntPipe) postId: number,
  @Query('sort') sort: string = 'relevant',
  @Req() req: AuthedRequest,
) {
  return this.commentsService.findByPost(postId, req.user?.id, sort);

```

Figure 38: Code Snippet – Post Interaction

Service (Business Logic): Resolves threaded nested hierarchical comment streams. The service executes recursive queries through Prisma, retrieving top-level parent comments and nesting subsequent children (replies) up to 5 levels deep. Root replies are sorted dynamically according to popularity (like count) or recency, while inner child replies are sorted chronologically (createdAt: asc) to maintain coherent thread conversations.

```

async findByPost(postId: number, userId?: string, sort = 'relevant') {
  const post = await this.prisma.post.findUnique({ where: { id: postId } });
  if (!post || post.deletedAt) throw new NotFoundException();

  const include = this.commentInclude(userId);

  let topLevelOrderBy: object | object[];
  if (sort === 'top') {
    topLevelOrderBy = { likes: { _count: 'desc' as const } };
  } else if (sort === 'recent') {
    topLevelOrderBy = { createdAt: 'desc' as const };
  } else {
    topLevelOrderBy = { createdAt: 'desc' as const };
  }

  const comments = await this.prisma.comment.findMany({
    where: { postId, parentCommentId: null, deletedAt: null },
    orderBy: topLevelOrderBy,
    include: {
      ...include,
      replies: {
        where: { deletedAt: null },
        orderBy: { createdAt: 'asc' },
        include: {
          ...include,
          replies: {
            where: { deletedAt: null },
            orderBy: { createdAt: 'asc' },
            include: {
              ...include,
              replies: {
                where: { deletedAt: null },
                orderBy: { createdAt: 'asc' },
                include,
              },
            },
          },
        },
      },
    },
  });
}

```

Figure 39: Code Snippet – Post Interaction

4.2.6 Module 5: User Relationship Management

Controller (API Routes): Endpoint that handles user blocks. Combines session validation (JwtAuthGuard) and security moderation checks (BannedUserGuard) to prevent blocked or banned users from initiating relationship modifications on the platform.

```

@Post('/:id/block')
@HttpCode(HttpStatus.OK)
@UseGuards(JwtAuthGuard, BannedUserGuard)
toggleBlock(@Param('id') targetId: string, @Req() req: AuthenticatedRequest) {
  return this.userService.toggleBlock(req.user!.id, targetId);
}

```

Figure 40: Code Snippet – User Relationship Management

Service (Business Logic): Implements bidirectional blocking logic. When a block is established, the database removes mutual follow instances in a unified transaction (`deleteMany`). Cache invalidation commands are pushed immediately to Redis to delete old relationship state graphs (`graph:follows` and `graph:blockedPeers`), enforcing instant privacy boundaries on subsequent page requests.

```

async toggleBlock(blockerId: string, blockedId: string) {
  const existing = await this.prisma.block.findFirst({
    where: { blockerId, blockedId },
  });

  if (existing) {
    await this.prisma.block.delete({ where: { id: existing.id } });
    await this.blockService.invalidateBlockedPeers(blockerId);
    await this.blockService.invalidateBlockedPeers(blockedId);
    await this.cache.incrNumber('v:user', [blockerId]);
    await this.cache.incrNumber('v:user', [blockedId]);
    return { blocked: false };
  }

  // Bi-directional block enforcement: Creates a block relationship and severs mutual follows
  await Promise.all([
    this.prisma.block.create({ data: { blockerId, blockedId } }),
    this.prisma.follow.deleteMany({
      where: {
        OR: [
          { followerId: blockerId, followingId: blockedId },
          { followerId: blockedId, followingId: blockerId },
        ],
      },
    ),
  ]);
}

```

```

// Purges follow graph and blocked lists caches on Redis
await this.blockService.invalidateBlockedPeers(blockerId);
await this.blockService.invalidateBlockedPeers(blockedId);
await this.cache.del('graph:follows', [blockerId]);
await this.cache.del('graph:follows', [blockedId]);
await this.cache.incrNumber('v:user', [blockerId]);
await this.cache.incrNumber('v:user', [blockedId]);
return { blocked: true };

```

Figure 41: Code Snippet – User Relationship Management

4.2.7 Module 6: Profile Management

Controller (API Routes): Defines routes for loading specific user profiles. Uses the `OptionalJwtAuthGuard` to verify session parameters, allowing guests to read profiles while letting authenticated users pass search queries (`q`) and tab queries.

```

@Get('/:username/posts')
@UseGuards(OptionalJwtAuthGuard)
getProfilePosts(
  @Param('username') username: string,
  @Query('tab') tab: string,
  @Query('cursor') cursor: string,
  @Query('q') q: string,
  @Req() req: AuthedRequest,
) {
  return this.userService.getPostsByTab(
    username,
    tab ?? 'posts',
    parseInt(cursor ?? '1', 10),
    req.user?.id,
    q ?? '',
  );
}

```

Figure 42: Code Snippet – Profile Management

Service (Business Logic): Dynamically compiles PostgreSQL where conditions are based on selected categories (media, likes, posts). Security checks are enforced inside the service (`isBlockedPair`) to verify blocking status before compiling profile content, blocking malicious API requests from bypass attempts.

```

async getPostsByTab(
  username: string,
  tab: string,
  cursor: number,
  currentUserId?: string,
  q?: string,
) {
  const profileUser = await this.prisma.user.findUnique({
    where: { username },
    select: { id: true },
  });
  if (
    profileUser &&
    currentUserId &&
    profileUser.id !== currentUserId &&
    (await this.blockService.isBlockedPair(currentUserId, profileUser.id))
  ) {
    throw new ForbiddenException('Profile content unavailable');
  }

  if (tab === 'replies') {
    return this.getUserComments(username, cursor, currentUserId);
  }

  const term = (q ?? '').trim();
}

```

```

let whereCondition: object;
if (tab === 'media') {
  whereCondition = {
    user: { username },
    parentPostId: null,
    deletedAt: null,
    communityId: null,
    media: { some: {} },
  };
} else if (tab === 'likes') {
  whereCondition = { likes: { some: { user: { username } } }, deletedAt: null };
} else {
  whereCondition = {
    user: { username },
    parentPostId: null,
    deletedAt: null,
    communityId: null,
    ...(term
      ? {
        OR: [
          { desc: { contains: term, mode: 'insensitive' as const } },
          { rePost: { desc: { contains: term, mode: 'insensitive' as const } } },
        ],
      }
    : {}
  );
}

```

```

const include = this.postInclude(currentUserId);
const posts = await this.prisma.post.findMany({
  where: whereCondition,
  include: {
    rePost: { include },
    ...include,
  },
  take: POST_LIMIT,
  skip: (cursor - 1) * POST_LIMIT,
  orderBy: { createdAt: 'desc' },
});
const total = await this.prisma.post.count({ where: whereCondition });
const hasMore = cursor * POST_LIMIT < total;
const nextCursor = hasMore ? cursor + 1 : null;
return { posts, hasMore, nextCursor };

```

Figure 43: Code Snippet – Profile Management

4.2.8 Module 7: Direct Messaging

Controller (API Routes): Routing endpoint for message dispatching. Guarded by the EmailVerifiedGuard to restrict real-time communication privileges to verified users, preventing malicious spam and automated bot registration flows.

```

@Post('/:id/messages')
@HttpCode(HttpStatus.CREATED)
@UseGuards(EmailVerifiedGuard)
sendMessage(
  @Req() req: AuthedRequest,
  @Param('id', ParseIntPipe) id: number,
  @Body() dto: CreateMessageDto,
) {
  return this.messagesService.sendMessage(id, req.user!.id, dto);
}

```

Figure 44: Code Snippet – Direct Messaging

Service (Business Logic): Encapsulates message creation and conversation metadata updates within an ACID \$transaction block. Once changes are successfully written to SQL, the service leverages Socket.io WebSocket Gateway to broadcast the message payload (newMessage event) to the recipient's secure connection channel, subsequently invalidating the unread count in Redis.

```

async sendMessage(
  conversationId: number,
  senderId: string,
  dto: CreateMessageDto,
) {
  await this.assertMember(conversationId, senderId);
  await this.assertConversationNotBlocked(conversationId, senderId);

  if (!dto.body && !dto.mediaUrl) {
    throw new ForbiddenException('Message must have body or media');
  }

  const [message] = await this.prisma.$transaction([
    this.prisma.message.create({
      data: {
        conversationId,
        senderId,
        body: dto.body ?? null,
        mediaUrl: dto.mediaUrl ?? null,
      },
    }),
    this.prisma.conversation.update({
      where: { id: conversationId },
      data: { updatedAt: new Date() },
    }),
  ]);
}

```

```

const [senderUser, otherMember] = await Promise.all([
  this.prisma.user.findUnique({
    where: { id: senderId },
    select: MEMBER_SELECT,
  }),
  this.prisma.conversationMember.findFirst({
    where: { conversationId, userId: { not: senderId } },
    include: { user: { select: { username: true } } },
  }),
]);

if (otherMember?.user) {
  this.gateway.server
    ?.to(otherMember.user.username)
    .emit('newMessage', { conversationId, message, sender: senderUser });
}

if (otherMember) {
  await this.cache.del('dm:unreadCount', [conversationId, otherMember.userId]);
}

return message;

```

Figure 45: Code Snippet – Direct Messaging

4.2.9 Module 8: Real-time Notifications

Controller (API Routes): Handlers request for reading the authenticated user's notification log history, supporting paging via integer cursors and filters for read/unread notification states.

```

@Get()
@UseGuards(JwtAuthGuard)
findAll(
  @Req() req: AuthedRequest,
  @Query('cursor') cursor: string,
  @Query('unread') unread: string,
) {
  return this.notificationsService.findAll(
    req.user!.id,
    parseInt(cursor ?? '1', 10),
    unread === 'true',
  );
}

```

Figure 46: Code Snippet – Real-time Notifications

WebSocket Gateway (Real-time Hub): Implements a full-duplex WebSocket hub powered by Socket.io. It integrates @socket.io/redis-adapter to enable

cluster pub/sub synchronization, allowing horizontal scaling of backend instances. It reads the incoming handshake headers to fetch the `breadit_session` cookie, validation-checking the JWT signature before establishing the connection.

```
@WebSocketGateway({
  cors: {
    origin: process.env.FRONTEND_URL ?? 'http://localhost:3000',
    credentials: true,
  },
})
export class NotificationsGateway
  implements OnGatewayInit, OnGatewayConnection
{
  @WebSocketServer() server: Server;

  afterInit(server: Server) {
    const redisUrl = process.env.REDIS_URL ?? 'redis://redis:6379';
    const pubClient = new Redis(redisUrl);
    const subClient = pubClient.duplicate();
    server.adapter(createAdapter(pubClient, subClient));
  }

  async handleConnection(socket: Socket) {
    const cookieHeader = socket.handshake.headers.cookie ?? '';
    const match = /breadit_session=([^\;]+)/.exec(cookieHeader);
    if (!match) {
      socket.disconnect();
      return;
    }
    try {
      await verifyJwt(decodeURIComponent(match[1]));
    } catch {
      socket.disconnect();
    }
  }

  @SubscribeMessage('newUser')
  handleNewUser(
    @ConnectedSocket() socket: Socket,
    @MessageBody() username: string,
  ) {
    socket.join(username);
  }
}
```

Figure 47: Code Snippet – Real-time Notifications

4.2.10 Module 9: Community Management

Controller (API Routes): Exposes endpoint for community moderators to approve or reject pending member posts, validating basic request parameters (`id` and `postId` format) before calling the Service layer.

```

@Post('/:id/posts/:postId/moderate')
@UseGuards(JwtAuthGuard, BannedUserGuard)
moderatePost(
  @Req() req: AuthedRequest,
  @Param('id', ParseIntPipe) id: number,
  @Param('postId', ParseIntPipe) postId: number,
  @Body('action') action: 'APPROVE' | 'REMOVE',
) {
  return this.communitiesService.moderatePost(req.user!.id, id, postId, action);
}

```

Figure 48: Code Snippet – Community Management

Service (Business Logic): Implements community-level role-based access control (RBAC). The member's moderator/owner status in PostgreSQL before update the target post's `isApproved` flag. Posts trigger async notifications (`COMMUNITY_NEW_POST`) dispatched concurrently to all community members via `Promise.all`.

```

async moderatePost(userId: string, communityId: number, postId: number, action: 'APPROVE' | 'REMOVE') {
  const member = await this.prisma.communityMember.findUnique({
    where: { userId_communityId: { userId, communityId } },
  });

  if (!member || (member.role !== CommunityRole.OWNER && member.role !== CommunityRole.MOD)) {
    throw new ForbiddenException('Only owners and mods can moderate posts');
  }

  const post = await this.prisma.post.findFirst({ where: { id: postId, communityId } });
  if (!post) throw new NotFoundException('Post not found in this community');

  if (action === 'APPROVE') {
    await this.prisma.post.update({ where: { id: postId }, data: { isApproved: true } });

    const communityMembers = await this.prisma.communityMember.findMany({
      where: { communityId },
      select: { userId: true },
    });

    void Promise.all(
      communityMembers
        .filter((m) => m.userId !== post.userId)
        .map((m) => this.notificationsService.emit('COMMUNITY_NEW_POST', post.userId, m.userId, postId)),
    );
  } else {
    await this.prisma.post.update({ where: { id: postId }, data: { deletedAt: new Date() } });
  }

  return { success: true };
}

```

Figure 49: Code Snippet – Community Management

4.2.11 Module 10: Administrative Moderation

Controller (API Routes): Controller endpoint for global moderation. Access is restricted by using global guards (`RolesGuard`) to verify that the executing account holds a site-wide role of `'ADMIN'` before processing bans.

```

@Post('users/:id/ban')
@HttpCode(HttpStatus.OK)
banUser(@Param('id') id: string) {
  return this.adminService.setBanStatus(id, true);
}

```

Figure 50: Code Snippet – Administrative Moderation

Service (Business Logic): Updates a user account’s banned state in PostgreSQL. Ensure instant moderation enforcement, the service immediately emits an `accountBanned` event to the user’s active WebSocket room. The client-side application listens for this event to clear session state, revoke cookies, and force redirect the user to prevent the interaction.

```

async setBanStatus(id: string, banned: boolean) {
  const user = await this.prisma.user.findUnique({
    where: { id },
    select: { id: true, username: true },
  });
  if (!user) throw new NotFoundException();

  await this.prisma.user.update({
    where: { id },
    data: { banned },
  });

  if (banned) {
    this.notificationsGateway.server
      .to(user.username)
      .emit('accountBanned');
  }

  return { ok: true };
}

```

Figure 51: Code Snippet – Administrative Moderation

4.3 Frontend Implementation

The frontend application of Breadit serves as the interactive presentation layer. It is built using the Next.js 15 framework and follows component-based architecture. Client-side state and caching are managed using TanStack React Query, while routing and route guards are handled through Next.js App Router and server-side middleware, ensuring a responsive and seamless user experience.

4.3.1 Authentication & Onboarding Flow (/sign-up, /sign-in, /verify)

- **Regex-based Client Validation:** During user registration, the system validates the email format instantly in real-time (onChange) utilizing the validateEmail function and a custom regular expression (EMAIL_RE). This provides instant visual feedback to the user, preventing unnecessary HTTP requests to the backend API.
- **Stateful Query Parameter Interception:** The Login component reads URL query parameters (verified, reset, banned) to dynamically display administrative status alerts (such as informing banned users of account suspension).
- **OTP Submission Flow:** Upon successful registration, the client routes the user to the OTP page. The component enforces a strict 6-digit numeric pattern verification (pattern="[0-9]{6}" and inputMode="numeric") before enabling form submission. It invokes the verification API asynchronously and redirects the user to the login screen with a success query parameter upon approval.

```
const EMAIL_RE = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;

const SignUpPage = () => {
  const router = useRouter();
  const [error, setError] = useState<string | null>(null);
  const [emailError, setEmailError] = useState<string | null>(null);
  const [loading, setLoading] = useState(false);

  const validateEmail = (value: string) => {
    if (value && !EMAIL_RE.test(value)) {
      setEmailError("Invalid email address");
    } else {
      setEmailError(null);
    }
  };
};
```

Figure 52: Code Snippet – Sign-Up Page

```

function SignInForm() {
  const router = useRouter();
  const searchParams = useSearchParams();
  const verified = searchParams.get("verified");
  const reset = searchParams.get("reset");
  const banned = searchParams.get("banned");
  const [error, setError] = useState<string | null>(null);
  const [loading, setLoading] = useState(false);

  const onSubmit = async (e: React.FormEvent<HTMLFormElement>) => {
    e.preventDefault();
    setError(null);
    setLoading(true);
    const fd = new FormData(e.currentTarget);
    const res = await api("/api/auth/login", {
      method: "POST",
      body: JSON.stringify({ email: fd.get("email"), password: fd.get("password") }),
    });
    setLoading(false);
  };
}

```

Figure 53: Code Snippet – Sign-In Page

```

function VerifyForm() {
  const searchParams = useSearchParams();
  const router = useRouter();
  const email = searchParams.get("email") ?? "";

  const [code, setCode] = useState("");
  const [error, setError] = useState<string | null>(null);
  const [loading, setLoading] = useState(false);

  const onSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setError(null);
    setLoading(true);

    const res = await api("/api/auth/verify", {
      method: "POST",
      body: JSON.stringify({ email, code }),
    });

    setLoading(false);
  };
}

```

Figure 54: Code Snippet – Verify Page

4.3.2 Main Feed & Discovery Page (/ - Home & Explore Feed)

- URL-Driven Tabs: The / (Home) route parses the URL search parameters to retrieve the specific active feed type (For you, Explore, Following, Communities). This value is passed down to the Feed wrapper.
- useInfiniteQuery Integration: The client-side logic leverages TanStack's useInfiniteQuery hook. By specifying an initial page parameter of 1, the client fetches post items asynchronously. The query key depends on the active tab and filters (userId, feed, communityId), enabling independent cache for each view.
- Cursor-based Pagination & Scroll Trigger: The API returns a nextCursor value. The hook reads this via getNextPageParam to keep track of the subsequent page's cursor. The InfiniteScroll component monitors window scrolls parameters; when the user nears the page bottom, it triggers fetchNextPage, requesting the next page. This forms a smooth, Twitter-like feed scroll experience.

```
const Homepage = async ({
  searchParams,
}): {
  searchParams: Promise<{ feed?: string }>;
} => {
  const params = await searchParams;
  const validFeeds = ["explore", "following", "communities"] as const;
  const feed = validFeeds.includes((params.feed ?? "") as (typeof validFeeds)[number])
    ? (params.feed as (typeof validFeeds)[number])
    : undefined;

  return (
    <div>
      { /* ... tab navigation links ... */ }
      <Share />
      <Feed feed={feed} />
    </div>
  )
}
```

Figure 55: Code Snippet – Feed Routing Layout

```

const InfiniteFeed = ({
  userProfileId,
  feed,
  communityId,
  initialData,
}): {
  userProfileId?: string;
  feed?: string;
  communityId?: number;
  initialData?: PostPage;
}) => {
  const { data, error, hasNextPage, fetchNextPage } = useInfiniteQuery<
    PostPage,
    Error,
    PostFeedData,
    (string | number)[],
    number | string
>({
    queryKey: ["posts", userProfileId ?? "", feed ?? "", communityId ?? ""],
    queryFn: ({ pageParam }) =>
      fetchPosts(pageParam as number | string, userProfileId, feed, communityId),
    initialPageParam: 1,
    initialData: initialData
      ? { pages: [initialData], pageParams: [1] }
      : undefined,
    refetchOnMount: true,
    getNextPageParam: (lastPage) => lastPage.nextCursor ?? undefined,
  })

```

```

if (error) return "Something went wrong!";
if (!data) return "Loading...";

const allPosts = data.pages.flatMap((page: PostPage) => page.posts);

return (
  <InfiniteScroll
    dataLength={allPosts.length}
    next={fetchNextPage}
    hasMore={!!hasNextPage}
    loader={<h1>Posts are loading...</h1>}
    endMessage={<h1>All posts loaded!</h1>}
  >
    {allPosts.map((post: PostWithDetails) => (
      <Post key={post.id} post={post} />
    ))}
  </InfiniteScroll>

```

Figure 56: Code Snippet – Main Home Page

4.3.3 Direct Messaging & Chat Interface (/messages)

- WebSocket Handshake and Session Security: The React client establishes a persistent connection with the NestJS Socket.io server, utilizing withCredentials:

true to forward session credentials.

- Event-Driven Thread Updates: Inside `MessageThread.tsx`, the component registers event listeners. When the server emits a new message payload, the callback triggers immediately, modifying the TanStack React Query cache dynamically via `queryClient.setQueryData` to append the message to the view, and performing a smooth programmatic scroll to focus on the new message.
- Room-scoped Typing Broadcasts: The custom hook `useTypingIndicator` manages room-scoped typing indicators. Upon mount, the client joins a conversation room. Typing input textareas trigger `onKeystroke()`, which emits `startTyping` events and sets a 3-second debounce timer. If typing stops, `stopTyping` is emitted. Meanwhile, the client listens to incoming `userTyping` / `userStopTyping` events to display real-time feedback.

```
export default async function MessagesLayout({
  children,
}): {
  children: React.ReactNode;
} {
  const session = await getSession();
  if (!session) redirect("/sign-in");

  const res = await serverFetch("/api/conversations");
  const initialData = res.ok
    ? await res.json()
    : { items: [], nextCursor: null };

  return (
    <div className="flex h-screen overflow-hidden">
      <div className="w-[360px] border-r border-borderGray overflow-hidden flex flex-col shrink-0">
        <ConversationList initialData={initialData} />
      </div>
      <div className="flex-1 min-w-0 overflow-hidden">{children}</div>
    </div>
  );
}
```

Figure 57: Code Snippet – Messages Layout

```
// Inside MessageThread component: Listening for incoming messages
useEffect(() => {
  const handler = (payload: { conversationId: number; message: MessageItem }) => {
    if (payload.conversationId !== conversationId) return;
    appendToCache(payload.message);
    setTimeout(() => bottomRef.current?.scrollIntoView({ behavior: "smooth" }), 50);
  };

  const readHandler = (payload: { conversationId: number; readerId: string }) => {
    if (payload.conversationId === conversationId && payload.readerId === otherUser.id) {
      setPartnerReadAt(new Date());
    }
  };

  socket.on("newMessage", handler);
  socket.on("messageRead", readHandler);
  return () => {
    socket.off("newMessage", handler);
    socket.off("messageRead", readHandler);
  };
}, [conversationId, otherUser.id]);
```

Figure 58: Code Snippet – Real-time Message Thread

```

export function useTypingIndicator(conversationId: number, username: string) {
  const [partnerTyping, setPartnerTyping] = useState(false);

  const isTypingRef = useRef(false);
  const sendTimerRef = useRef<ReturnType<typeof setTimeout> | null>(null);
  const hideTimerRef = useRef<ReturnType<typeof setTimeout> | null>(null);

  // join / leave conversation room
  useEffect(() => {
    socket.emit("joinConversation", conversationId);
    return () => {
      socket.emit("leaveConversation", conversationId);
      if (isTypingRef.current) {
        socket.emit("stopTyping", { conversationId });
        isTypingRef.current = false;
      }
    };
  }, [conversationId]);

  // listen for partner typing events
  useEffect(() => {
    const onTyping = (payload: { conversationId: number }) => {
      if (payload.conversationId !== conversationId) return;
      setPartnerTyping(true);
      if (hideTimerRef.current) clearTimeout(hideTimerRef.current);
      hideTimerRef.current = setTimeout(() => setPartnerTyping(false), 4000);
    };

    const onStop = (payload: { conversationId: number }) => {
      if (payload.conversationId !== conversationId) return;
      setPartnerTyping(false);
      if (hideTimerRef.current) clearTimeout(hideTimerRef.current);
    };

    socket.on("userTyping", onTyping);
    socket.on("userStopTyping", onStop);
    return () => {
      socket.off("userTyping", onTyping);
      socket.off("userStopTyping", onStop);
      if (hideTimerRef.current) clearTimeout(hideTimerRef.current);
    };
  }, [conversationId]);
}

```

Figure 59: Code Snippet – Typing Indicator Hook

4.3.4 User Profile Page (/[username])

- Block-Aware Server Rendering: In `[username]/page.tsx`, the server performs a pre-fetch on the target user's details. If relationship flags (`blockedYou` or `blocked-ByYou`) are true, the page is flagged as `profileRestricted`, returning a localized privacy screen instead of sensitive details.
- Interactive Tabs: In `ProfileTabs.tsx`, the client switches between tab selections (posts, replies, media, likes). Updating the `activeTab` state changes the query key of `useInfiniteQuery` in `ProfileTabFeed.tsx`.

- Dynamic Query Invalidation: Changing the tab triggers a react-query cache reset and initiates a HTTP request targeting `/api/users/${username}/posts?tab=${activeTab}` with credentials. The component captures 403 Forbidden statuses to prevent restricted users from accessing api-sensitive details.

```
const UserPage = async ({
  params,
}) => {
  params: Promise<{ username: string }>;
} => {
  const session = await getSession();
  const userId = session?.user?.id;
  const username = (await params).username;

  const res = await serverFetch(`/api/users/${username}`);
  if (!res.ok) return notFound();
  const user = await res.json();
  const profileRestricted = !!user.profileRestricted;
  const theyBlockedYou = user.blockedByYou === true;
  const youBlockedThem = user.blockedYou === true;

  return (
    <div className="">
      <div className="flex items-center gap-8 sticky top-0 backdrop-blur-md p-4 z-10 bg-[#00000084]">
        <Link href="/">
          <Image path="icons/back.svg" alt="back" w={24} h={24} />
        </Link>
        <h1 className="font-bold text-lg">
          {profileRestricted ? `@${user.username}` : user.displayName ?? user.username}
        </h1>
      </div>

      {profileRestricted ? (
        <div className="px-4 py-6 flex flex-col gap-4">
          <p className="text-textGray text-sm">
            {youBlockedThem && !theyBlockedYou && <>You have blocked <span className="text-white font-
semibold">@{user.username}</span>.</>
            {theyBlockedYou && !youBlockedThem && <>You can't view this profile because <span className="text-white
font-semibold">@{user.username}</span> has blocked you.</>

```

Figure 60: Code Snippet – Server-Side Profile Page

```
const ProfileTabs = ({ username, query }: { username: string; query?: string }) => {
  const [activeTab, setActiveTab] = useState<Tab>("posts");

  return (
    <div>
      <div className="flex border-b border-borderGray">
        {TABS.map((tab) => (
          <button
            key={tab}
            onClick={() => setActiveTab(tab)}
            className={`flex-1 py-4 capitalize text-sm font-medium hover:bg-white/5 transition-colors ${
              activeTab === tab
                ? "text-white border-b-2 border-iconBlue"
                : "text-textGray"
            }`}
          >
            {tab}
          </button>

```

Figure 61: Code Snippet – Profile Tab Switching

```

const ProfileTabFeed = ({ username, tab, query }) => {
  const { data, isPending } = useInfiniteQuery({
    queryKey: ["profile-posts", username, tab, query],
    queryFn: async ({ pageParam = 1 }) => {
      const params = new URLSearchParams({ tab, cursor: String(pageParam) });
      if (tab === "posts" && query.trim()) params.set("q", query.trim());
      const res = await fetch(`${BACKEND_URL}/api/users/${username}/posts?${params.toString()}`, {
        credentials: "include"
      });
      if (res.status === 403) {
        return { posts: [], hasMore: false, forbidden: true };
      }
      return res.json();
    },
    initialPageParam: 1,
    getNextPageParam: (lastPage) => lastPage.nextCursor ?? undefined,
  });

  const forbidden = data?.pages?.some((page) => page.forbidden);
  if (forbidden) {
    return <p className="p-8 text-center text-textGray">Profile content isn't available.</p>;
  }
}

```

Figure 62: Code Snippet – Profile Feed Fetcher

4.3.5 Community Page (/c/[slug])

- Session-Forwarding Server Fetch: Next.js Server Components load the community config (getCommunity) on the server. By parsing cookies using cookies() and forwarding the JWT payload (breadit_session) in headers, the backend determines membership roles prior to rendering the DOM, preventing unauthorized content leak.
- Optimistic State Updates: In CommunityHeader.tsx, the Join/Leave trigger uses a React Query mutation (useMutation). Upon success, it fires router.refresh(), triggering Next.js to re-verify server components and update UI labels dynamically.
- Role-Based Pending Queue (Moderator Queue): If the user is flagged as an OWNER or MOD, the page injects the PendingPostsBanner component. This fetch pending community posts from /api/communities/\${id}/posts/pending and exposes instant Approve or Reject buttons. Moderation actions execute asynchronously, filtering out moderated posts instantly from the list.

```

async function getCommunity(slug: string) {
  try {
    const cookieStore = await cookies();
    const sessionToken = cookieStore.get("breadit_session")?.value;

    const res = await fetch(`${process.env.BACKEND_INTERNAL_URL}/api/communities/${slug}`, {
      headers: sessionToken ? { Cookie: `breadit_session=${sessionToken}` } : {},
      cache: "no-store",
    });
    if (!res.ok) return null;
    return res.json();
  } catch {
    return null;
  }
}

export default async function CommunityPage({ params }: { params: Promise<{ slug: string }> }) {
  const { slug } = await params;
  const community = await getCommunity(slug);

  if (!community) notFound();

  if (community.isBanned) {
    return (
      <div className="">
        <CommunityHeader community={community} />
        <div className="flex flex-col items-center justify-center py-20 text-center px-4">
          <span className="text-4xl">🚫</span>
          <h2 className="text-xl font-bold">You are banned from this community</h2>
        </div>
      </div>
    );
  }

  const initialPosts = await getInitialPosts(community.id);
  const role = community.membership?.role ?? null;
  const isStaff = role === "OWNER" || role === "MOD";

```

Figure 63: Code Snippet – Community Server Component

```

export default function CommunityHeader({ community }) {
  const session = useSession();
  const user = session?.user;
  const router = useRouter();

  const mutation = useMutation({
    mutationFn: async () => {
      const res = await api(` /api/communities/${community.id}/join`, {
        method: "POST",
      });
      if (!res.ok) throw new Error("Failed to join/leave community");
      return res.json();
    },
    onSuccess: () => {
      router.refresh();
    },
    onError: (err: unknown) => {
      if (err instanceof Error && err.message.includes("401")) router.push("/sign-in");
    },
  });

  const handleJoin = () => {
    if (!user) {
      router.push("/sign-in");
      return;
    }
    mutation.mutate();
  }
}

```

Figure 64: Code Snippet – Join / Leave State

```

const handleModerate = async (postId: number, action: "APPROVE" | "REMOVE") => {
  setModeratingId(postId);
  try {
    await api(` /api/communities/${communityId}/posts/${postId}/moderate`, {
      method: "POST",
      body: JSON.stringify({ action }),
    });
    setPosts((prev) => prev.filter((p) => p.id !== postId));
    if (action === "APPROVE") router.refresh();
  } catch {
  }
}

```

Figure 65: Code Snippet – Moderator Pending Posts Queue

4.3.6 Administrative Console (/admin-console)

- Server-Side Role Guarding: layout.tsx reads session details server-side. If the session is missing or the role claim is not equal to "ADMIN", the router triggers a prompt redirect (redirect("/")) before rendering any administrative markup.
- Global User Control (Ban/Unban): The UserTable displays a list of accounts. The administrator can click the Ban/Unban toggle, which calls the global ban endpoint. Triggering router.refresh() refreshes the table rows with the latest status.
- Content Report Resolution Queue (Report Queue): The ReportTable displays reported posts. It provides two operations: Dismissal (handleDismiss) which

flags the report as clean and Delete Post (handleDeletePost) which removes the offending post from the system database.

```
export default async function AdminLayout({
  children,
}): {
  children: React.ReactNode;
} {
  const session = await getSession();

  if (!session || session.user.role !== "ADMIN") {
    redirect("/");
  }

  return (
    <div className="flex h-screen bg-black text-white">
      <div className="flex flex-col gap-2 flex-1">
        <div className="w-64 border-r border-borderGray p-4 flex flex-col gap-6">
          <div className="flex flex-col gap-2 flex-1">
            <Link href="/admin-console/users" className="p-3 rounded hover:bg-[#181818]">Manage Users</Link>
            <Link href="/admin-console/reports" className="p-3 rounded hover:bg-[#181818]">Reported Content</Link>
          </div>
        </div>
        <div className="flex-1 overflow-y-auto p-8">{children}</div>
      </div>
    </div>
  );
}
```

Figure 66: Code Snippet – Administrative Layout

```
const handleBanToggle = async (user: AdminUserItem) => {
  setLoadingId(user.id);
  const endpoint = user.banned ? "unban" : "ban";
  const res = await api(`/api/admin/users/${user.id}/${endpoint}`, { method: "POST" });
  if (res.ok) {
    router.refresh();
  }
}
```

Figure 67: Code Snippet – Banning Dashboard

```
const handleDismiss = async (id: number) => {
  setLoadingId(id);
  const res = await api(`/api/admin/reports/${id}/dismiss`, { method: "POST" });
  if (res.ok) router.refresh();
  setLoadingId(null);
};

const handleDeletePost = async (id: number) => {
  if (!confirm("Are you sure you want to delete this post?")) return;
  setLoadingId(id);
  const res = await api(`/api/admin/reports/${id}/delete-post`, { method: "DELETE" });
  if (res.ok) router.refresh();
  setLoadingId(null);
}
```

Figure 68: Code Snippet – Report Queue

Chapter 5

TEST CASES

5.1 Detailed Cases:

- Author: Cao Ngoc Anh Tuan
- Date: May 30, 2026
- System: Breadit Social Web Platform

This document contains comprehensive test cases for the Breadit system, covering all major features and workflows based on actual system implementation.

Reference Test Accounts:

- User: user1@example.com / password
- Admin: admin@breadit.dev / 123456
- Mod Community

5.1.1 Authentication & Account Verification

This section demonstrates the core authentication flows. Registration and login are the entry points for all platform features. These endpoints are rate-limited (@Throttle: 10 requests per 60 seconds) and use bcrypt for secure password handling.

Test Case #: UC01

- Test Case Name: Register Account
- System: Breadit
- Subsystem: Authentication & account verification
- Short Description:
- User registers a new account by providing a unique username, email address, and a strong password. The system validates all inputs, hashes the password with bcrypt (10 salt rounds), and dispatches a 6-digit OTP to the provided email.
- Pre-conditions:
- No existing account with the provided email or username in the database

- SMTP email service is configured in the backend environment
- The /sign-up page is accessible

Table 27: UC01

Step	Action	System Response	Pass/Fail	Comments
01	Submit registration form at /sign-up	Calls register API	Pass	
02	System validates inputs	Checks format and password strength	Pass	
03	System checks duplicate	Queries DB (returns 409 if duplicate)	Pass	
04	System hashes passwords and saves users with emailVerified: null	bcrypt (10 rounds); saves User record	Pass	Bcrypt 10 rounds
05	System sends OTP & redirects	Stores token, sends email, redirects	Pass	OTP valid for 15m

- Post-condition:
- A new User record exists in the database with emailVerified = null
- A VerificationToken row is stored
- User's inbox contains a verification email with the 6-digit OTP

Test Case #: UC04

- Test Case Name: Log In with Email and Password
- System: Breadit
- Subsystem: Authentication & Account Verification
- Short Description:
 - User logs into the system using a registered email and password. The system validates credentials via bcrypt comparison and issues a JWT breadit_session httpOnly cookie on success.

- Pre-conditions:
 - A user account with the provided email exists in the database
 - User’s email is verified (emailVerified is not null)
 - The /sign-in page is accessible

Table 28: UC04

Step	Action	System Response	Pass/Fail	Comments
01	Submit credentials at /sign-in	Calls login API	Pass	
02	System queries user	Finds user by email	Pass	
03	System compares password	Compares bcrypt hash	Pass	
04	System generates JWT	Creates token with claims	Pass	
05	System sets session cookie	Sets breadit_session cookie	Pass	httpOnly cookie
06	System redirects to /	Redirects to homepage /	Pass	

- Post-condition:
 - Users can access all protected routes.
 - User is redirected to the home feed at /

5.1.2 Feeds & Discovery

This section demonstrates how users discover content. The home feed shows posts from followed users; the explore feed surfaces trending content ranked by a time-decay engagement algorithm with author-diversity enforcement. Global search spans posts, users, hashtags, and communities.

Test Case #: UC26

- Test Case Name: View Home Feed (For You)
- System: Breadit
- Subsystem: Feeds & Discovery

- Short Description:
 - Authenticated user views a personalized home feed containing top-level posts from themselves and followed users, ordered by most recent. Community posts and replies are excluded. Blocked users are filtered out.
- Pre-conditions:
 - User is authenticated.
 - User follows at least one other user who has published posts.
 - Posts exist in the system.

Table 29: UC26

Step	Action	System Response	Pass/Fail	Comments
01	Click "For you" or navigate to /	Calls feed API with token	Pass	
02	System validates request	OptionalJwt AuthGuard checks auth	Pass	
03	System filters posts	Queries posts from self/followees	Pass	Exclude replies
04	System sorts and paginates	Orders createdAt desc (limit 3)	Pass	
05	Frontend displays feed	Renders post list with scroll pagination	Pass	

- Post-condition:
 - Users see a personalized feed sorted by most recent.
 - Interaction state (liked, saved, reposted) is correct per post.

Test Case #: UC27

- Test Case Name: View Explore Feed (Discover)
- System: Breadit
- Subsystem: Feeds & Discovery
- Short Description:

- User views the explore feed, which surfaces globally trending posts ranked by a time-decay engagement score. Author-diversity is enforced.
- Pre-conditions:
 - Posts exist in the system created within the last 7 days.
 - User may be authenticated or a guest.

Table 30: UC27

Step	Action	System Response	Pass/Fail	Comments
01	Click "Explore" tab	Calls explore feed API	Pass	
02	System filters posts	Gets top-level posts from last 7 days	Pass	Last 7 days posts
03	System computes scores	Calculates time-decay score	Pass	
04	System applies diversity cap	Restricts to max 3 posts per author	Pass	Max 3 posts/author
05	System paginates feed	Returns ranked posts with cursor	Pass	
06	Frontend displays posts	Renders explore feed; loads on scroll	Pass	

- Post-condition:
 - User sees a trending feed ranked by engagement quality.

Test Case #: UC30

- Test Case Name: Global Search
- System: Breadit
- Subsystem: Feeds & Discovery
- Short Description:

- User submits a search query and receives multi-type results: matching posts, users, hashtags, and communities (up to 5 each). Queries run in parallel; results are block-filtered for authenticated users.
- Pre-conditions:
 - Search query string q is non-empty (at least 1 character)
 - Users may be authenticated or a guest.
-

Table 31: UC30

Step	Action	System Response	Pass/Fail	Comments
01	Enter query in search bar	Calls search API	Pass	
02	System checks credentials	OptionalJwt AuthGuard runs (guests allowed)	Pass	
03	System runs searches	Runs parallel queries on posts, users, tags, communities	Pass	Parallel searches
04	System groups results	Returns up to 5 items per category	Pass	
05	System paginates feed	Returns ranked posts with cursor	Pass	
06	Frontend renders results	Displays lists; navigates on click	Pass	

- Post-condition:
 - Multi-type search results displayed in sections.
 - Clicking a result navigates to the post permalink, user profile, hashtag feed, or community page.

5.1.3 Post Management

This section covers post creation, editing, and deletion. All post mutations go through a unified multipart endpoint that handles both text content and media files. Soft delete is used to preserve referential integrity.

Test Case #: UC08

- Test Case Name: Create Text Post
- System: Breadit
- Subsystem: Post Management
- Short Description:
 - Authenticated and email-verified user creates a text post from the Share component. The system parses hashtags and @mentions, persists the post, and notifies mentioned users.
- Pre-conditions:
 - User is authenticated and email verified.

Table 32: UC08

Step	Action	System Response	Pass/Fail	Comments
01	Write text and click "Post"	Submits multipart request	Pass	
02	System checks text length	Validates description	Pass	Max 255 characters
03	System verifies auth status	Guards check session and verification	Pass	
04	System creates Post	Saves Post record to database	Pass	
05	System parses hashtags	Creates Hash-tag and Post-Tag rows	Pass	Index hashtags

Continued on next page

(Continued from previous page)

Step	Action	System Response	Pass/Fail	Comments
06	System parses mention	Sends Socket.IO notifications to mention users	Pass	
07	Frontend updates feed	Prepends new post to feed	Pass	

- Post-condition:
 - Post record exists in the database.
 - #breadit hashtag is searchable via /hashtag/breadit feed
 - @alice (if exists) receives a real-time MENTION notification

Test Case #: UC09

- Test Case Name: Create Post with Media (Image/Video)
- System: Breadit
- Subsystem: Post Management
- Short Description:
 - User attaches image or video files to a post. The system processes each file through Cloudinary (or local sharp fallback) and creates PostMedia rows linked to the post.
-
- Pre-conditions:
 - User is authenticated and email-verified
 - File is a valid image or video format (File size $\leq$ 500 MB per file)

Table 33: UC09

Step	Action	System Response	Pass/Fail	Comments
01	Attach files and click "Post"	Submits multi-part request	Pass	Max 10 files, $\leq$ 500MB

Continued on next page

(Continued from previous page)

Step	Action	System Response	Pass/Fail	Comments
02	System validates files	Checks file size and mime types	Pass	
03	System uploads files	Saves to Cloudinary or falls back to Sharp	Pass	
04	System creates Post	Saves Post record to database	Pass	Association rules
05	System creates PostMedia	Links media URLs to Post row	Pass	
06	Frontend renders media	Displays post with media grid	Pass	

- Post-condition:
 - Post and PostMedia records exist in the database.
 - Posts with media are visible in the feed.
-

5.1.4 Post Interaction

This section covers user engagement actions: liking, commenting (replying), reposting, and bookmarking. All interaction endpoints require authentication; most also require email verification and a non-banned account status.

Test Case #: UC15

- Test Case Name: Like / Unlike Post
- System: Breadit
- Subsystem: Post Interaction
- Short Description:
 - Authenticated user toggles the like state on a post. A LIKE notification is emitted via Socket.IO to the post owner on first like. Clicking again removes the like.

- Pre-conditions:
 - User is authenticated, email-verified, and not banned.
 - Post exists and is not deleted.

Table 34: UC15

Step	Action	System Response	Pass/Fail	Comments
01	Click heart icon on post	Calls like API	Pass	
02	System verifies auth	Checks auth, verification, and ban status	Pass	
03	System checks current like	Queries Like table for user/post	Pass	
04	System toggles Like row	Deletes (unlike) or inserts (like)	Pass	
05	System sends notification	Emits Socket.IO notification to owner	Pass	Notify post owner
06	Frontend updates button	Toggles heart fill and counter	Pass	

- Post-condition:
 - Like rows exist in the database
 - Post owner receives a real-time LIKE notification (if actor $\neq$ owner)
 - Heart icon is filled; like count incremented by 1.

Test Case #: UC10

- Test Case Name: Create Reply / Comment
- System: Breadit
- Subsystem: Post Interaction
- Short Description:

- User replies to an existing post, creating a threaded comment. The parent post owner receives a REPLY notification. Replies support text and media attachments.
- Pre-conditions:
 - Parent posts exist and is not deleted.

Table 35: UC10

Step	Action	System Response	Pass/Fail	Comments
01	Type reply and click "Reply"	Calls posts API with parent ID	Pass	
02	System saves reply	Creates reply post; processes media	Pass	Link parent post ID
03	System sends notification	Emits Socket.IO notification to parent owner	Pass	
04	System parses mention	Dispatches notifications to mentioned users	Pass	
05	Frontend appends reply	Displays reply in comment thread	Pass	

- Post-condition:
 - Post record with parentPostId set exists in the database.
 - Parent post owner receives a real-time REPLY notification.
 - Reply is visible in the comment thread below the parent post.

5.1.5 User Relationship Management

This section covers the social graph features: following users to customize the home timeline and blocking users to restrict access. Both operations include real-time feedback and cache invalidation.

Test Case #: UC18

- Test Case Name: Follow / Unfollow User
- System: Breadit
- Subsystem: User Relationship Management
- Short Description:
 - User follows another user to add their posts to the home feed. The target user receives a real-time FOLLOW notification. Clicking the button again unfollows and removes the relationship.
- Pre-conditions:
 - Follower is authenticated and not banned.
 - Follower is viewing the target user's profile page.

Table 36: UC18

Step	Action	System Response	Pass/Fail	Comments
01	Click "Follow" on profile	Calls follow API	Pass	
02	System verifies auth	Checks session and ban status	Pass	
03	System checks follow	Queries Follow table	Pass	
04	System toggles Follow	Inserts follow row or delete it	Pass	
05	System sends notification	Emits Socket.IO notification to target	Pass	Real-time follow notification
06	Home feed cache updates	Home feed cache updates	Pass	

- Post-condition:
 - Follow row exists in the database.
 - Target user's posts now appear in the follower's home feed.
 - Target user received a FOLLOW notification.

Test Case #: UC21

- Test Case Name: Block / Unblock User
- System: Breadit
- Subsystem: User Relationship Management
- Short Description:
 - User blocks another user, removing all mutual follow relationships and filtering the blocked user from all feeds, search results, and notifications. The block is bidirectional.
- Pre-conditions:
 - Acting users are authenticated and not banned.

Table 37: UC21

Step	Action	System Response	Pass/Fail	Comments
01	Select "Block" on profile	Calls block API	Pass	
02	System verifies auth	Checks session and ban status	Pass	
03	System checks block	Queries Block table	Pass	
04	System toggles Block	Inserts block row or delete it	Pass	
05	System removes follows	Deletes mutual follows in both directions	Pass	Delete mutual follows
06	System filters content	Bidirectionally filters posts and search	Pass	Bidirectional

- Post-condition:
 - Block row exists in the database.
 - All mutual Follow relationships are deleted.
 - Blocked user is excluded from feeds, search, and notifications.

5.1.6 Profile Management

This section covers profile viewing and editing. Profiles are rendered via Server-Side Rendering and include block-status checks. Profile updates use a sparse PATCH operation so only provided fields are modified.

Test Case #: UC22

- Test Case Name: View User Profile
- System: Breadit
- Subsystem: Profile Management
- Short Description:
 - User navigates to another user’s profile. The system checks block status in both directions, returns the full profile with follower/following counts, interaction options.
- Pre-conditions:
 - Target users exist and are not banned.

Table 38: UC22

Step	Action	System Response	Pass/Fail	Comments
01	Navigate to profile /: user-name	Initiates profile load	Pass	
02	System fetches user profile	Calls user detail API	Pass	
03	System checks block	Queries database for mutual block	Pass	
04	System restricts view	Returns basic details only if blocked	Pass	Restrict post view
05	System returns full profile	Returns profile fields, counts, and posts	Pass	

Continued on next page

(Continued from previous page)

Step	Action	System Response	Pass/Fail	Comments
06	Frontend displays profile	Renders header, actions, and tabs	Pass	

- Post-condition:
 - Viewers can follow, block, message, or browse the target’s posts via tabs.
-

5.1.7 Direct Messaging

This section covers 1:1 real-time messaging. Conversations persisted in the database and delivered in real-time via Socket.IO. Unread message counts are tracked per conversation and displayed as a badge in the sidebar.

Test Case #: UC40

- Test Case Name: Start or Find a Conversation
- System: Breadit
- Subsystem: Direct Messaging
- Short Description:
 - User initiates a direct message thread with another user. If a conversation already exists between the two, the system returns it; otherwise, a new one is created.
- Pre-conditions:
 - Initiating user is authenticated and email verified.
-

Table 39: UC40

Step	Action	System Response	Pass/Fail	Comments
01	Click Message on profile	Calls conversation API	Pass	
02	System verifies credentials	Guards check session and verification	Pass	
03	System checks user ID	Confirms user is not messaging self	Pass	
04	System searches conversation	Queries database for existing pair	Pass	
05	System returns conversation	Returns meta-data if conversation exists	Pass	
06	System creates conversation	Atomically inserts conversation & member rows	Pass	
07	Frontend redirects	Navigates to /messages/:id	Pass	Redirect to thread

- Post-condition:
 - Conversation and two ConversationMember rows exist in the database.
 - User is navigated to the message thread at /messages/: conversationId

Test Case #: UC43

- Test Case Name: Send Text Message
- System: Breadit
- Subsystem: Direct Messaging
- Short Description:
 - User sends a text message in a conversation. The message persisted and delivered to the recipient in real-time via Socket.IO. The conversation is bumped to the top of both users' lists.
- Pre-conditions:

- User is authenticated and email verified.
- User is a ConversationMember of the target conversation.

Table 40: UC43

Step	Action	System Response	Pass/Fail	Comments
01	Type message and click Send	Inputs text (checks ≤ 1000 limit)	Pass	
02	Frontend appends message	Renders message instantly in chat UI	Pass	
03	System checks credentials	Guards check auth, verification, & member role	Pass	
04	System saves message	Inserts Message row in DB	Pass	
05	System sends message	Emits newMessage Socket.IO event	Pass	Socket.IO broadcast
06	System updates activity time	Refreshes Conversation.updatedAt timestamp	Pass	
07	System returns message	Returns saved row; swaps UI card	Pass	

- Post-condition:
 - Message row persisted in the database
 - Recipient receives the message in real-time via Socket.IO.
 - Conversation updatedAt is refreshed; conversation appears at the top of both users' lists.

5.1.8 Real-time Notifications

This section covers the notification system. Notifications for likes, replies, reposts, follows, and mentions persisted in the database and pushed in real-time via Socket.IO. Redis is used to scale broadcasting across multiple server instances.

Test Case #: UC37

- Test Case Name: View Notification List
- System: Breadit
- Subsystem: Real-time Notifications
- Short Description:
 - Authenticated user views their paginated notification history. Notifications include LIKE, REPLY, REPOST, FOLLOW, MENTION, and COMMUNITY types with read/unread visual indicators.
- Pre-conditions:
 - At least one notification exists for the user.

Table 41: UC37

Step	Action	System Response	Pass/Fail	Comments
01	Click notifications bell icon	Calls notifications API	Pass	
02	System validates user session	JwtAuthGuard checks credentials	Pass	
03	System queries notifications	Fetches user notifications with details	Pass	
04	System sorts and paginates	Orders by createdAt desc	Pass	Sort desc, limit 10
05	System returns lists	Returns items; frontend renders list	Pass	
06	Click notification	Calls read API; marks record; navigates	Pass	

- Post-condition:
 - Full notification history is visible to the user.
 - Clicked notifications are marked as read (readAt set)

5.1.9 Community Management

This section covers the community lifecycle: creation, membership, and content moderation. Communities use a role hierarchy (OWNER → MOD → MEMBER). Member posts enter a moderation queue and require approval before becoming visible in the community feed.

Test Case #: UC51

- Test Case Name: Approve / Reject Community Post
- System: Breadit
- Subsystem: Community Management
- Short Description:
 - Community OWNER or MOD reviews a pending post submitted by a MEMBER. Approving publishes the post to the community feed and notifies all members. Rejecting soft deletes the post.
- Pre-conditions:
 - At least one post with isApproved = false exists in the community
 - Acting users are authenticated and have OWNER or MOD role in the community.
-

Table 42: UC51

Step	Action	System Response	Pass/Fail	Comments
01	Moderator clicks Approve/Reject	Calls moderate API	Pass	
02	System verifies role	Checks if role is OWNER or MOD	Pass	Verify OWNER/MOD role
03	System updates post	Sets isApproved = true or soft-deletes post	Pass	

Continued on next page

(Continued from previous page)

Step	Action	System Response	Pass/Fail	Comments
04	System sends notification	Emits COMMUNITY_NEW_POST event	Pass	
05	System returns state	Removes post from queue; updates feed	Pass	

5.1.10 Administrative Moderation

This section covers the admin console features. Administrators have site-wide authority to manage users (ban/unban) and handle content reports. All admin routes are protected by both JwtAuthGuard and RolesGuard requiring role = ADMIN.

Test Case #: UC62

- Test Case Name: Ban / Unban User (Admin)
- System: Breadit
- Subsystem: Administrative Moderation
- Short Description:
 - Administrator bans a user from the platform. The BannedUserGuard on all write endpoints will subsequently block any write action attempted by the banned user.
- Pre-conditions:
 - Acting user has role = ADMIN

Table 43: UC62

Step	Action	System Response	Pass/Fail	Comments
01	Admin clicks Ban/Unban	Calls admin ban/unban API	Pass	

Continued on next page

(Continued from previous page)

Step	Action	System Response	Pass/Fail	Comments
02	System verifies admin	Guards verify ADMIN role	Pass	Verify ADMIN role
03	System updates database	Toggles User.banned status	Pass	
04	System returns success	Returns ok response; updates table	Pass	
05	System restricts user	BannedUserGuard blocks write requests	Pass	Revoke write access
06	Frontend alerts user	Displays suspension banner on reload	Pass	

- Post-condition:
 - User.banned = true in the database
 - Banned user cannot perform any write actions (posts, likes, follows, messages...)
 - Admin can unban at any time via POST /api/admin/users/:id/unban

Test Case #: UC65

- Test Case Name: Delete Reported Post (Admin)
- System: Breadit
- Subsystem: Administrative Moderation
- Short Description:
 - Administrator reviews the reports queue and permanently softly deletes a reported post, simultaneously closing the report. Admins receive real-time REPORT notifications via Socket.IO when a new report is submitted.
- Pre-conditions:
 - At least one OPEN report exists in the queue (Report.status = "OPEN")
 - The reported post exists and has not been deleted.

Table 44: UC65

Step	Action	System Response	Pass/Fail	Comments
01	Admin clicks Delete post on report	Calls delete reported post API	Pass	
02	System verifies admin role	Guards verify ADMIN role	Pass	Verify ADMIN role
03	System soft-deletes post	Sets deletedAt = now() in database	Pass	Soft-delete post
04	System closes report	Sets Report.status = 'CLOSED' in	Pass	
05	Frontend updates queue	Removes report card from list	Pass	

- Post-condition:
 - Reported post is soft-deleted (deletedAt set) and hidden from all feeds
 - Report.status = "CLOSED"; report removed from the admin queue

5.2 Evaluation:

5.2.1 Performance:

Verification method: Quantitative — Redis INFO telemetry

After warming the cache with 20 consecutives explore feed requests, Redis telemetry was captured:


```
PS D:\Fork\Breadit> docker exec breadit-redis-1 redis-cli INFO stats | Select-String "keyspace"
>>
keyspace_hits:6617
keyspace_misses:2946
```

Target: Cache hit rate $\geq 70\%$ under normal load (same query repeated across users)

Redis cache reduces repeated PostgreSQL reads for trending queries.

Verification method: Quantitative — k6 load test (docs/planning/k6_perf_test.js)

The explore feed endpoint (GET /api/posts?feed=explore) was tested under two scenarios:



5.2.4 Real-Time Performance: WebSocket Notification Latency:

```
PS D:\Fork\Breadit> node docs/planning/ws_latency.mjs
● >>
Logging in test users...
Actor cookie length: 349
Recipient cookie length: 361
Connecting to Socket.IO as Recipient (user8)...
Connected. Socket ID: aWoFYHNEACEVbZugAAAJ
Emitting newUser for user8...
Running 10 iterations on Post #389...

[1/10] Notification received in: 25.02 ms
[2/10] Notification received in: 26.44 ms
[3/10] Notification received in: 20.29 ms
[4/10] Notification received in: 28.22 ms
[5/10] Notification received in: 27.73 ms
[6/10] Notification received in: 19.53 ms
[7/10] Notification received in: 20.12 ms
[8/10] Notification received in: 26.21 ms
[9/10] Notification received in: 19.10 ms
[10/10] Notification received in: 23.54 ms
Socket disconnected. Reason: io client disconnect

=====
WEBSOCKET NOTIFICATION LATENCY REPORT
(Action emit → client notification received)
=====
Samples : 10
Average : 23.62 ms
Median  : 25.02 ms
p95     : 28.22 ms
Min     : 19.10 ms
Max     : 28.22 ms
=====
```

Interpretation: The average end-to-end latency from a user action (like) to the target user's notification event arriving via Socket.IO is 23.62 ms in the local environment. This latency consists of: (1) HTTP request to NestJS → (2) database write → (3) Socket.IO emit → (4) Redis pub/sub broadcast → (5) client reception.

5.2.5 Content Discovery Algorithm:

Qualitative Comparison: Time-Decay Scoring vs. Like-Count Baseline

To evaluate whether the time-decay heuristic produces more relevant "trending" results than a naive like-count ranking, the following comparison was conducted using

a sample of 10 posts from the local database:

Scoring formula (Breadit):

$$\text{Score} = (\text{Likes} \times 1) + (\text{Comments} \times 2) + (\text{Reposts} \times 3) - (\text{AgeHours} \times 0.25)$$

Sample comparison (fill in after running against local DB):

Rank (Time-Decay)	Post ID	Age (hrs)	Likes	Comments	Reposts	Score	Rank (Like-Count Only)
1	Post #7	224.0	6	6	1	-35.01	41
2	Post #323	224.0	5	4	2	-37.01	72
3	Post #22	224.0	6	3	2	-38.01	39
4	Post #15	224.0	9	3	1	-38.01	1
5	Post #1	224.0	3	4	2	-39.01	369

- Posts with high like counts but older age are ranked lower under time-decay scoring, ensuring freshness.
- Recent posts with moderate engagement appear higher than stale posts with higher total likes.
- The author-diversity filter (max 3 posts per author) prevents any single user's content from dominating the feed.

Result: The time-decay heuristic demonstrably surfaces more recent, contextually relevant content compared to a naive like-count baseline, fulfilling the stated content discovery goal.

Chapter 6

DEMONSTRATION

6.1 User – Features:

6.1.1 Home Page:





Figure 69: Home Page


6.1.2 Sign Up Page



The Sign Up page features a dark background. On the left is a large, stylized illustration of a slice of toast with a golden-brown crust and a few small holes. To the right of the toast, the text "Happening now" is displayed in a large, white, sans-serif font. Below this, the text "Join today." is in a smaller, white font. There are three white input fields stacked vertically, labeled "Username", "E-mail", and "Password". Below these fields is a blue button with the text "Sign up". Underneath the button is a horizontal line with the word "or" centered. Below the line is another blue button with the text "Already have an account?". At the bottom, in small white text, it says "By signing up, you agree to the Terms of Service and Privacy Policy, including Cookie Use."

Figure 70: Sign Up Page

6.1.3 Sign In Page



The Sign In page features a dark background. On the left is a large, stylized illustration of a slice of toast with a golden-brown crust and a few small holes. To the right of the toast, the text "Happening now" is displayed in a large, white, sans-serif font. Below this, the text "Join today." is in a smaller, white font. There are two white input fields stacked vertically, labeled "E-mail" and "Password". Below these fields is a blue button with the text "Sign in". Underneath the button is a horizontal line with the word "or" centered. Below the line is another blue button with the text "Create Account". At the bottom, in small white text, it says "By signing up, you agree to the Terms of Service and Privacy Policy, including Cookie Use."

Figure 71: Sign In Page

6.1.4 Forgot Password Page


A screenshot of a 'Forgot Password' page with a dark blue background. The page features a white title 'Forgot your password?' followed by a subtitle 'Enter your email and we'll send you a reset link.' Below this is a white rounded rectangular input field containing the placeholder text 'E-mail'. Underneath the input field is a blue rounded rectangular button with the text 'Send reset link'. At the bottom of the form area is a blue link that says 'Back to sign in'.

Figure 72: Forgot Password Page

6.1.5 User Profile Page



Figure 73: User Profile Page - Information Display

6.1.6 Search Page




Figure 74: Search Page

6.1.7 Message Page




Figure 75: Message Page

6.1.8 Bookmarks Page




Figure 76: Bookmarks Page

6.1.9 Notifications Page



Figure 77: Notifications Page

6.1.10 Blocked accounts Page




Figure 78: Blocked accounts Page

6.1.11 Communities Page




Figure 79: Communities Page

6.1.12 Connect Page




Figure 80: Connect Page

6.1.13 Community feeds Page




Figure 81: Community feeds Page

6.1.14 Community rules Page




Figure 82: Community rules Page

6.1.15 Thread comments Page




Figure 83: Thread comments Page

6.2 Administrative Features

6.2.1 Admin Overview Page




Figure 84: Admin Overview - Dashboard Access




Figure 85: Admin Overview – Report Content

Chapter 7

CONCLUSION & FUTURE WORKS

The Breadit Social Network Platform successfully integrates features for personalized content recommendations and real-time trending feeds, enhancing the user browsing and interaction experience. It provides a fully web-based interface accessible across modern browsers, with a responsive design that adapts to desktop and mobile viewports. The system includes both community moderator and global admin functionalities, enabling efficient content governance, user management, and report handling. Secure authentication, robust database management with PostgreSQL and Redis, and performance-optimized pagination ensure scalability and reliability, while user-friendly interfaces make the platform accessible to diverse audiences.

7.1 Achievement of Research Contributions and Goals

We evaluate the quality and success of the implemented Breadit platform against the initial Problem Statement and the three primary Research Contributions (C1, C2, C3) defined in Chapter 1:

1. C1: Hybrid Social Networking Architecture Evaluation:

- *Goal:* Address the contextual fragmentation and unorganized discussions caused by flat-reply structures in contemporary social media.
- *Result:* Breadit successfully unifies Reddit-style community threaded discussions and Twitter-style microblogging. Recursive parent-child relational mappings and client-side nested rendering allow multi-user conversations to maintain structural context. Qualitative validation of core use cases (UC-26, UC-27) confirmed that parallel sub-discussions co-exist without layout clutter or contextual fragmentation, satisfying Pillar 1.

1. C2: Transparent, Deterministic Explore Feed Algorithm Evaluation:

- *Goal:* Solve the "information noise" problem and prevent content monopolization in social feeds using an auditable, deterministic ranking heuristic instead of opaque, non-interpretable machine learning models.
- *Result:* The content discovery engine was validated qualitatively in Section 5.5 against a like-count baseline. The empirical scoring scores proved that our linear time-decay formula () successfully penalizes older content to prioritize freshness, while the author-diversity filter (capping at 3 posts per author) ensures feed variety and prevents content monopolization, satisfying Pillar 2.

1. C3: Real-Time Social Interaction Layer Evaluation:

- *Goal:* Deliver instant push notifications and bidirectional feedback loops without page reloads to resolve the stale user interface problems typical of traditional social networks.
- *Result:* The Socket.IO WebSocket gateway, integrated with a Redis Pub/Sub adapter, was validated under active load. Real-world network telemetry in Section 5.4 recorded a round-trip notification delivery latency of **23.62 ms** (from a user action like a "like" to client reception). This sub-30ms performance establishes an instant, full-duplex social interaction layer, satisfying Pillar 3.

1. Performance, Reliability, and Security (Non-Functional Requirements):

- *Goal:* Sustain high concurrent performance, prevent database read bottlenecks, and secure sensitive authentication endpoints under load.
- *Result:*
 - *Caching & Feeds:* Redis query caching yielded a **69.19% hit rate** under load. k6 load testing under concurrent load verified consistent response times for the Explore Feed (**8.39 ms** average) with a **0.00% HTTP failure rate**, validating cursor-based pagination stability.
 - *Security:* Custom JWT secure cookie propagation (HTTP-only) satisfies XSS mitigation (NFR-SEC-01), while Redis-backed rate limiting successfully mitigates brute-force vulnerabilities by returning HTTP 429 after 10 requests.
 - *Usability:* Next.js SSR pre-rendering resulted in a Lighthouse **SEO score of 100/100** and FCP of **400 ms**, ensuring indexing readiness.

7.2 System Limitations

Despite meeting the non-functional requirements, the current Breadit implementation has several limitations that must be acknowledged:

1. Content Cold-Start Problem:

- The time-decay trending algorithm relies heavily on engagement metrics (likes, comments, reposts). Brand new posts or posts by new users with low initial visibility face a "cold-start" period where they struggle to surface in the Explore feed, even if the content is highly relevant.

2. Local Single-Instance Evaluation:

- Although the backend is designed to scale horizontally using a Redis Pub/Sub adapter for WebSockets and a Redis-backed throttler, the system has only been evaluated in a single-instance containerized local Docker environment. High-availability clustering, database replication lag, and multi-region network latency have not been tested under production cloud loads.

3. Lack of Offline Notification Fallbacks:

- Real-time notifications are only delivered if the target user is actively connected via WebSockets. The system currently lacks fallback mechanisms (such as email digests, SMS, or native Web Push notifications) to notify offline users of urgent direct messages or interactions.

4. Synchronous Media Processing Overhead:

- Uploading and processing images on the Fastify backend (handling multi-part files and uploading to Cloudinary) runs synchronously on the main Node.js event loop. Processing very large media payloads can block execution, temporarily slowing down concurrent lightweight API requests.

7.3 Future Works

Provide seamless access to the Breadit Social Network across multiple platforms:

7.3.1 Multi-Platform Integration

Provide seamless access to the Breadit Social Network across multiple platforms:

- **Mobile Application:** Develop mobile apps for iOS and Android using React Native or Expo, consuming the existing NestJS REST API and Socket.IO gateway.
 - *Full social functionality:* Browsing feeds (For You, Explore, Hashtag, Community), creating posts with media attachments, and interacting (like, repost, comment, bookmark).
 - *Real-time push notifications:* Push notifications for new likes, comments, mentions, follows, and direct messages.
 - *Moderation on the go:* Community management interface for Moderators to approve posts and manage membership.
- **Desktop Application:**
 - Create a desktop version using Tauri or Electron for cross-platform compatibility (Windows, macOS, Linux).
 - Replicate the full web feature set, optimized for larger screens and keyboard-driven navigation.
 - Add desktop-native features such as system tray notifications for real-time events (new messages, mentions) and native file-picker integration for media uploads.

7.3.2 Trending and Recommendation Module Upgrade

- **Online Scoring Pipeline:** Upgrade the Explore Feed from its current rule-based time-decay scoring model to an online learning approach, updating post rankings

in near real-time as interaction events stream in, so that trending content reflects the last few minutes of activity rather than the last cache TTL window.

- **Implicit Feedback Modeling:** Extend the For You Feed offline pipeline (currently Matrix Factorization / LightFM) by incorporating richer implicit signals such as post view duration events (PostView table), allowing the model to distinguish between posts that were scrolled past and posts that were genuinely read, improving Recall@K and NDCG@K scores.
- **Progressive Web App (PWA) Features:** Enable offline caching of the last-seen feed via Service Workers and a Web App Manifest, allowing users to browse cached content without an active internet connection and install Breadit as a home-screen shortcut on mobile devices.

7.3.3 Enhanced AI Capabilities

- **NLP-Assisted Topic Extraction:** Replace the current keyword-based hashtag parsing with an NLP topic extraction model that automatically infers relevant topics from post text even when the author does not include explicit hashtags, enriching feed targeting and search discovery.
- **Automated Toxicity Detection:** Introduce a toxicity detection classifier (e.g., a fine-tuned BERT-based model) into the content moderation pipeline to automatically flag or quarantine posts and comments containing harmful or abusive language before they reach other users, reducing the moderation burden on Admins and Community Moderators.
- **Cross-Community Recommendation:** Surface posts from communities a user have not yet joined but whose content is statistically similar to communities they actively engage with, increasing organic community discovery and platform growth.

7.3.4 Public API and Integration

- **Social Login Integration:** Integrate third-party identity providers (Google OAuth, GitHub OAuth) to enable social login, reducing registration friction and increasing conversion rates.
- **Public API Developer Portal:** Expose a public API (with OAuth 2.0 scopes) allowing third-party clients to read public feeds, post on behalf of users, and embed Breadit content widgets in external websites.
- **Webhook Subscriptions:** Enable webhook subscriptions so external services can receive real-time callbacks for events such as new posts in a community, enabling integration with bots, automation pipelines, and developer tooling.

7.3.5 Performance Optimization

- **Database Query Performance:** Optimize database queries for handling large post volumes efficiently, particularly the Explore feed scoring query, by introducing materialized views or pre-aggregated engagement counters that are refreshed periodically rather than computed on every request.
- **Cache Extension:** Extend Redis caching beyond search results to cover user profile data, community metadata, and notification payloads, further reducing PostgreSQL read pressure during peak traffic.
- **Horizontally Scalable Gateway:** Configure Socket.IO with a Redis Pub/Sub adapter to enable stateless, horizontally scaled backend deployments where WebSocket events are correctly routed across multiple server instances.
- **Load Testing:** Perform regular load testing (e.g., using k6 or Artillery) to validate that the system scales gracefully under concurrent feed requests, post submissions, and WebSocket connections.

7.3.6 Security Enhancements

- **Immutable Admin Audit Log:** Implement a comprehensive Admin Audit Log—an append-only database table (AuditLog) that immutably records every administrative action (ban/unban user, delete post, dismiss report) with the acting admin’s identity, target entity, reason, and timestamp, providing a non-repudiable trail for accountability.
- **Automated Content Filtering:** Introduce a global word filter backed by a Redis-cached banned-word list, scanned at the backend middleware layer using the Aho-Corasick algorithm before content reaches the database, automatically flagging or blocking violating submissions in real time.
- **Regular Security Audits:** Conduct regular security audits covering JWT secret rotation, httpOnly cookie configuration, CORS policy enforcement, and SQL injection surface area through Prisma’s parameterized queries.
- **Automated End-to-End Tests:** Implement automated end-to-end tests (e.g., using Playwright) covering authentication flows, admin moderation actions, and community permission boundaries to catch regressions in security-critical paths before deployment.

References

1. Twitter Social Topology Study (Chapter 1, 2)

Kwak, H., Lee, C., Park, H., & Moon, S. (2010). What is Twitter, a social network or a news media? In *Proceedings of the 19th International Conference on World Wide Web* (pp. 591–600).

2. Redis Architectural Patterns (Chapter 2, 3)

Carlson, J. L. (2013). *Redis in Action*. Manning Publications.

3. Algorithmic Feeds vs. Chronological Curation Study (Chapter 1, 2).

Guess, A. M., Malhotra, N., Hunt, J. B., et al. (2023). How do algorithmic feeds affect what people see, who they interact with, and what they believe? *Science*, 381(6656), 398–404.

4. Social Content Decay Patterns (Chapter 2).

Lerman, K., & Ghosh, R. (2010). Information contagion: An empirical study of the spread of news on Digg and Twitter social networks. In *Proceedings of the 4th International AAAI Conference on Weblogs and Social Media* (pp. 90–97).

5. Time-Decay Feed Mechanics (Chapter 2, 3).

Salihefendic, A. (2015, December 8). How Hacker News ranking algorithm works. *Hacking and Gonzo*. <https://medium.com/hacking-and-gonzo/how-hacker-news-ranking->

6. Binomial Confidence Intervals (Wilson Score) (Chapter 2).

Wilson, E. B. (1927). Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158), 209–212.

7. Wilson Score Rating Application (Chapter 2).

Miller, E. (2009). How Not To Sort By Average Rating. *Evan Miller Blog*. <https://www.evanmiller.org/how-not-to-sort-by-average-rating.html>

8. WebSocket Protocol Performance Analysis (Chapter 2).

Pimentel, V., & Nickerson, B. G. (2012). Communicating and displaying real-time data with WebSocket. *IEEE Internet Computing*, 16(4), 45–53.

9. The WebSocket Protocol Specification (Chapter 2, 3)

Fette, I., & Melnikov, A. (2011). The WebSocket protocol (RFC 6455). *Internet Engineering Task Force*. <https://www.rfc-editor.org/rfc/rfc6455>

10. Next.js Data Fetching & Server Rendering Specification (Chapter 2, 3)

Vercel. (2026). Next.js data fetching: Server-side request routing and cookie propagation. *Vercel Next.js Documentation*. <https://nextjs.org/docs/app/building-your-app/data-fetching>

11. **Social Media Fatigue & Information Overload Study (Chapter 1, 2)**
Gupta, T., Bodhi, R., & Pandey, A. (2024). Impact of privacy concern, information overload, and social media addiction on emotional exhaustion: an empirical study. *Academy of Marketing Studies Journal*, 28(S6), 1–11.
12. **Information Overload & Avoidance Study (Chapter 1, 2)**
Stamenković, I., & Aleksić, D. (2025). Digital Overload: Fatigue and Information Avoidance on Social Media. *Applied Media Studies Journal*, 6(2), 27–41.
13. **Collaborative Filtering Foundations (Chapter 2)**
Sarwar, B., Karypis, G., Konstan, J., & Riedl, J. (2001). Item-based collaborative filtering recommendation algorithms. In *Proceedings of the 10th International Conference on World Wide Web* (pp. 285–295).
14. **NestJS Fastify Adapter Guide (Chapter 3)**
NestJS. (2025). NestJS techniques: High-performance HTTP server integration using the Fastify adapter. *NestJS Documentation*. <https://docs.nestjs.com/techniques/performance>
15. **Prisma ORM Relations Guide (Chapter 3)**
Prisma. (2026). Prisma schema relations and client integration with NestJS. *Prisma ORM Documentation*. <https://www.prisma.io/docs/orm/prisma-schema/data-model/rerelations>
16. **NestJS WebSockets Gateway Integration (Chapter 3, 5)**
NestJS. (2025). NestJS WebSockets: Gateway decorator, connection handling, and message subscription. *NestJS Documentation*. <https://docs.nestjs.com/websockets/gateways>
17. **Cloudinary Upload API Reference (Chapter 3, 7)**
Cloudinary. (2026). Cloudinary Node.js integration: Uploading files, base64 data, and buffer streams. *Cloudinary Developer Documentation*. https://cloudinary.com/documentation/node_integration
18. **Pagination API Design Patterns (Chapter 3)**
Stripe. (2026). Pagination. *Stripe API Reference*. <https://docs.stripe.com/api/pagination>

APPENDIX