Searches & Use Cases

Nº	Name	CloudLogging	Elasticsearch	Comments
		Searches		1
1	Find who deleted a folder (requires values)	json_payload.event_type="yandex.cloud.a udit.resourcemanager.DeleteFolder" and json_payload.details.folder_name="<назв ание каталога>"	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.resourcema nager.DeleteFolder and cloud.folder.name: <название каталога>	
2	Find who created/stopped /restarted/delet ed a virtual machine (requires values)	json_payload.details.instance_id="<<иде нтификатор виртуальной машины>>" and (json_payload.event_type="yandex.cloud. audit.compute.CreateInstance" or json_payload.event_type="yandex.cloud.a udit.compute.UpdateInstance" or json_payload.event_type="yandex.cloud.a udit.compute.DeleteInstance" or json_payload.event_type="yandex.cloud.a udit.compute.StartInstance" or json_payload.event_type="yandex.cloud.a udit.compute.StopInstance" or json_payload.event_type="yandex.cloud.a udit.compute.RestartInstance")	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.*I nstance and cloud.instance.name: testdasdas	
3	What actions did a particular user perform over a period of time (requires values)	<pre>json_payload.authentication.subject_nam e="mirtov8@yandex-team.ru" and json_payload.event_time<"2022-03-01" and json_payload.event_time<"2022-04- 01"</pre>	event.dataset: yandexcloud.audittrail and user.name: mirtov8@yandex- team.ru and event_time < 2022-07-15	

Nº	Name	CloudLogging	Elasticsearch	Comments
4	Search for events by objects of a specific folder (requires values)	json_payload.resource_metadata.path[1]. resource_type="resource-manager.folder" and json_payload.resource_metadata.path[1]. resource_name="<имя каталога>") or (json_payload.resource_metadata.path[2]. resource_type="resource- manager.folder" and json_payload.resource_metadata.path[2]. resource_name="<имя каталога>"	event.dataset:yandexcloud.aud ittrail and cloud.folder.name:"mirtov- scale"	
		Use cases	S	
		IAM		
1	Triggered when creating service account credentials	<pre>json_payload.event_type="yandex.cloud.a udit.iam.CreateAccessKey" or json_payload.event_type="yandex.cloud.a udit.iam.CreateKey" or json_payload.event_type="yandex.cloud.a udit.iam.CreateApiKey"</pre>	event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.iam.Creat eAccessKey or yandex.cloud.audit.iam.Create Key or andex.cloud.audit.iam.CreateA piKey)	
2	Trigger on any action under a privileged account with the role "resourcemanager.clouds. owner" and "organizationmanager.admin" " (can be a list) (requires values)	<pre>json_payload.authentication.subject_nam e="mirtov8@yandex-team.ru" or json_payload.authentication.subject_nam e="kirill@yandex-team.ru"</pre>	event.dataset: yandexcloud.audittrail and user.name: mirtov8@yandex- team.ru kirill8@yandex- team.ru	

Nº	Name	CloudLogging	<u>Elasticsearch</u>	Comments
	(requires values)			
3	Abnormal number of failed authorization attempts (requires values)		event.dataset: yandexcloud.audittrail and error.message: Permission denied	
4	Assignment of admin rights (for resources: folder, cloud)	<pre>json_payload.details.access_binding_del tas.access_binding.role_i="admin"</pre>	event.dataset: yandexcloud.audittrail and details.access_binding_deltas .access_binding.role_id: admin	
5	Assigning the vpc.public.admin role	<pre>json_payload.details.access_binding_del tas.access_binding.role_id="vpc.publicA dmin"</pre>	event.dataset: yandexcloud.audittrail and details.access_binding_deltas .access_binding.role_id: vpc.publicAdmin	
6	Calling the API using YC or terraform under a suspicious user or ip	<pre>json_payload.request_metadata.user_agen t:"YC" or json_payload.request_metadata.user_agen t:"Terraform"</pre>	event.dataset: yandexcloud.audittrail and (user_agent.original.keyword: *YC/* or user_agent.original.keyword: *Terraform*)	
7	coming soon A new certificate has been added to the federation			
8	coming soon			

Nº	Name	CloudLogging	Elasticsearch	Comments
	Changed federation settings			
9	new Any action using a cloud service account from a range of IP addresses outside the cloud	<pre>not json_payload.request_metadata.remote_ad dress:"51.250"</pre>	event.dataset: yandexcloud.audittrail and user.type: SERVICE_ACCOUNT and not source.ip: ("51.250.0.0/17" or "31.44.8.0/21" or "62.84.112.0/20" or "84.201.128.0/18" or "84.252.128.0/20" or "130.193.32.0/19" or "178.154.192.0/18" or "178.170.222.0/24" or "185.206.164.0/22" or "193.32.216.0/22" or "217.28.224.0/20") and source.ip: *	
		Compute		
10	Triggering on an event with the creation of a VM with a white IP address	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and json_payload.details.network_interfaces .primary_v4_address.one_to_one_nat.addr ess exists</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.Cr eateInstance and details.network_interfaces.pr imary_v4_address.one_to_one_n at.address: *	
11	Triggered to create "two-legged" virtual machines	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and json_payload.details.network_interfaces [1].index="1"</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.Cr eateInstance and</pre>	

Nº	Name	CloudLogging	Elasticsearch	Comments
			details.network_interfaces.in dex: 1	
12	Uploading an image to the cloud from a non-fixed S3 Bucket (requires values)	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateImage" and not json_payload.details.source_uri:"https: //storage.yandexcloud.net/action-log- 123"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.Cr eateImage and not cloud.image.source_uri: "https://storage.yandexcloud. net/action-log-123"	
13	Create VM with image_id from Marketplace	<pre>not json_payload.details.product_ids[0]=nul l</pre>	<pre>event.dataset: yandexcloud.audittrail and details.product_ids: *</pre>	
14	Adding a public IP address to an existing virtual machine	<pre>json_payload.event_type="yandex.cloud.a udit.compute.AddInstanceOneToOneNat"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.Ad dInstanceOneToOneNat	
15	VM creation/modific ation events - enabling the serial port	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and json_payload.details.metadata_serial_po rt_enable="1"</pre>	event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: yandex.cloud.audit.compute.Cr eateInstance and details.metadata_serial_port_ enable: 1	
16	new Modifying VM - Adding Access to Serial Console	<pre>json_payload.event_type="yandex.cloud.a udit.compute.UpdateInstance" or json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and json_payload.details.metadata_serial_po rt_enable="1"</pre>	event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: (yandex.cloud.audit.compute.C reateInstance or	

Nº	Name	CloudLogging	Elasticsearch	Comments
			yandex.cloud.audit.compute.Up dateInstance) and details.metadata_serial_port_enable: 1	
17	new VM custom metadata value suspected to contain sensitive data	<pre>(json_payload.event_type="yandex.cloud. audit.compute.CreateInstance" or json_payload.event_type="yandex.cloud.a udit.compute.UpdateInstance") and json_payload.details.metadata_keys[0]: secret</pre>	event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.compute.U pdateInstance or yandex.cloud.audit.compute.Cr eateInstance) and details.metadata_keys: secret key password pass token oauth aws_access_key_id and event.outcome : success	
	Creating a VM without SG	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and not json_payload.details.network_interfaces .security_group_ids EXISTS</pre>	event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: yandex.cloud.audit.compute.Cr eateInstance and not details.network_interfaces.se curity_group_ids: *	
	1	VPC		
18	Creating too wide (insecure) ACL Security Group for ipv4, tcp	<pre>json_payload.event_type="yandex.cloud.a udit.network.CreateSecurityGroup" or json_payload.event_type="yandex.cloud.a udit.network.UpdateSecurityGroup" and json_payload.details.rules[0].direction ="INGRESS" and json_payload.details.rules[0].cidr_bloc ks.v4_cidr_blocks[0]="0.0.0.0/0"</pre>	event.dataset: yandexcloud.audittrail and (event.action: yandex.cloud.audit.network.Cr eateSecurityGroup or yandex.cloud.audit.network.Up dateSecurityGroup) and details.rules.direction: INGRESS and	

Nº	Name	CloudLogging	Elasticsearch	Comments
			details.rules.cidr_blocks.v4_ cidr_blocks: *0.0.0.0*	
19	Creating a public address without a DDoS protection checkbox	<pre>json_payload.event_type="yandex.cloud.a udit.compute.CreateInstance" and not json_payload.details.external_ipv4_addr ess.requirements.ddos_protection_provid er exists</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.network.Cr eateAddress and not details.external_ipv4_address .requirements.ddos_protection _provider: qrator	
20	new Creating / applying a security group by an account not from the list of allowed (requires values)	<pre>(json_payload.event_type="yandex.cloud. audit.network.CreateSecurityGroup" or json_payload.event_type="yandex.cloud.a udit.network.UpdateSecurityGroup") and not json_payload.authentication.subject_nam e="mirtov8@yandex-team.ru"</pre>	event.dataset: yandexcloud.audittrail and (event.action: yandex.cloud.audit.network.Cr eateSecurityGroup or yandex.cloud.audit.network.Up dateSecurityGroup) and not user.name: mirtov8@yandex- team.ru kirill@yandex-team.ru	
21	Any action with Security Group objects	<pre>json_payload.event_type="yandex.cloud.a udit.network.CreateSecurityGroup" or json_payload.event_type="yandex.cloud.a udit.network.UpdateSecurityGroup"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.network.*Se curityGroup	
		ObjectStorage		
22	Подозрительны е дейсвия с хранилищем логов AuditTrails (S3 Bucket)	<pre>json_payload.event_type="yandex.cloud.a udit.storage.BucketAclUpdate" or json_payload.event_type="yandex.cloud.a udit.storage.BucketPolicyUpdate"</pre>	event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.storage.B ucketAclUpdate or yandex.cloud.audit.storage.Bu cketPolicyUpdate)	

Nº	Name	CloudLogging	Elasticsearch	Comments
23	new Suspicious activities with the AuditTrails log storage (S3 Bucket)	<pre>json_payload.event_type="yandex.cloud.a udit.storage.BucketUpdate" and (json_payload.details.objects_access: "true" or json_payload.details.settings_read_acce ss: "true" or json_payload.details.list_access: "true")</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.storage.Bu cketUpdate and (details.objects_access: true or details.settings_read_access: true or details.list_access: true) event.dataset:	
24	new Object storage bucket (S3) became public when created/modifie d via ACL	<pre>json_payload.event_type="yandex.cloud.a udit.storage.BucketAclUpdate" and json_payload.details.acl.grants.grant_t ype: "ALL_USERS"</pre>	yandexcloud.audittrail and event.action: yandex.cloud.audit.storage.Bu cketAclUpdate and details.acl.grants.grant_type : "ALL_USERS"	
		Lockbox/KN		
25	Triggered by changing access rights to KMS symmetric encryption keys	<pre>json_payload.event_type="yandex.cloud.a udit.kms.UpdateSymmetricKeyAccessBindin gs" or json_payload.event_type="yandex.cloud.a udit.kms.CreateSymmetricKeyAccessBindin gs"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit. kms. *SymmetricKeyAccessBindings	
26	Removing a KMS key	<pre>json_payload.event_type="yandex.cloud.a udit.kms.DeleteSymmetricKey"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.kms.Delete SymmetricKey	

Nº	Name	CloudLogging	Elasticsearch	Comments
27	Assigning/Updati ng LockBox Secret Rights	<pre>json_payload.event_type="yandex.cloud.a udit.lockbox.UpdateSecretAccessBindings"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.lockbox.Up dateSecretAccessBindings	
28	new Assigning a person with access to a lockbox service account secrets on the VM (requires values)	<pre>json_payload.event_type="yandex.cloud.a udit.compute.UpdateInstance" and json_payload.details.service_account_id : "ajeg2ar8m8o25u63dj9f"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.Up dateInstance and details.service_account_id: ajeg2ar8m8o25u63dj9f	
29	new Reading a secret from Lockbox from an IP address different from the cloud address range (requires values)	<pre>json_payload.event_type="yandex.cloud.a udit.lockbox.GetPayload" and not json_payload.request_metadata.remote_ad dress:"51.250"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.lockbox.Ge tPayload and not source.ip: ("51.250.0.0/17" or "31.44.8.0/21" or "62.84.112.0/20" or "84.201.128.0/18" or "84.252.128.0/20" or "130.193.32.0/19" or "178.154.192.0/18" or "178.170.222.0/24" or "185.206.164.0/22" or "193.32.216.0/22" or "217.28.224.0/20")	

Nº	Name	CloudLogging	Elasticsearch	Comments
30	new Reading a secret from Lockbox using an account that is different from the target (requires values)	<pre>json_payload.event_type="yandex.cloud.a udit.lockbox.GetPayload" and not json_payload.authentication.subject_id: "ajesnkfkc77lbh50isvg" and json_payload.details.secret_id="e6q7q5m sguqg22ji78e0"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.lockbox.Ge tPayload and not user.id: ajeg2ar8m8o25u63dj9f and details.secret_name: secret1	
		MDB		
31	new Creating an MDB cluster by a cloud user not from the list of administrators (requires values)	<pre>json_payload.event_type: "yandex.cloud.audit.mdb." and not json_payload.authentication.subject_nam e: "test"</pre>	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.mdb.*.Crea teCluster and not user.name: mirtov8@yandex-team.ru kirill@yandex-team.ru	
32	new Creating/Changi ng an MDB User	<pre>json_payload.event_type: "CreateUser" or json_payload.event_type: "UpdateUser"</pre>	event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.mdb.*.Upd ateUser or yandex.cloud.audit.mdb.*.Crea teUser)	
33	new Deleting an MDB Cluster	<pre>json_payload.event_type: "DeleteCluster"</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.mdb.*.Dele teCluster</pre>	
34	new	<pre>(json_payload.event_type: "DeleteCluster" or</pre>	event.dataset: yandexcloud.audittrail and	

Nº	Name	CloudLogging	Elasticsearch	Comments
	Administrative actions with MDB from ip addresses that are different from the trusted range (requires values)	<pre>json_payload.event_type: "CreateCluster") and not json_payload.request_metadata.remote_ad dress: "51.250"</pre>	event.action: (yandex.cloud.audit.mdb.*.Upd ateUser or yandex.cloud.audit.mdb.*.Crea teUser or yandex.cloud.audit.mdb.*.Crea teCluster or yandex.cloud.audit.mdb.*.Upda teCluster) and source.ip: ("2a00:1fa0:474:9876:4cac:6c4 3:12aa:2bd2" or "2a00:1fa0:474:9876:4cac:6c43 :12aa:2bd1")	
35	coming soon Enabling a dangerous setting when creating a cluster	-доступ из datalens -публичный доступ -доступ из консоли управления -доступ из serverless		
36	coming soon Enabling a dangerous setting when changing a cluster	-доступ из datalens -публичный доступ -доступ из консоли управления -доступ из serverless		
37	coming soon Not enabled / unchecked "Protection from deletion" when			

Nº	Name			Comments
		CloudLogging	<u>Elasticsearch</u>	
	creating/changin			
	g	* 1		
38	coming soon	-настройки log_statements and log_connections		
	Changing			
	settings affecting			
	the collection of			
	audit logs from			
	MDB when			
	creating /			
	changing			
39	coming soon			
	Issuing privileged			
	GRANT			
	mdb_admin to a			
	user			
40	coming soon			
40	Creating/Modifyi			
	ng a Cluster			
	without a			
	Security Group			
	Installed			
The		are not part of Audit Trails but are pative bee	audit logs, and currently they cannot be analy	zed in
	dLogging	are not part of Addit Trails, but are flative kos	addit logs, and currently they calliot be allaly	ZCU III
CIUU	uluggiiig	Kubernetes (for k8s events, you r	and to get up a galution)	

General

Nº	Name	CloudLogging	<u>Elasticsearch</u>	Comments
1	Access denied events - unauthorized		event.dataset: yandexcloud.k8s_audit_logs and responseStatus.reason: Forbidden and not user.name: (system*node* or *gatekeeper* or *kyverno* or *proxy* or *scheduler* or *anonymous* or *csi* or *controller*)	
2	Assigning a cluster-admin or admin role (clusterrolebinding or rolebinding)		event.dataset: yandexcloud.k8s_audit_logs and requestObject.roleRef.name.keyword:(clus ter-admin or admin) and objectRef.resource.keyword: (clusterrolebindings or rolebindings) and verb: create and not responseObject.reason: AlreadyExists	
3	Successful connection to the cluster from an external IP address		event.dataset : yandexcloud.k8s_audit_logs and source.ip : * and not responseStatus.status : Failure	
4	NetworkPolicies: create, delete, change		event.dataset: yandexcloud.k8s_audit_logs and requestObject.kind.keyword: (NetworkPolicy or CiliumNetworkPolicy or DeleteOptions) and verb: (create or update or delete) and objectRef.resource: networkpolicies	
5	Exec inside the container (shell		event.dataset : yandexcloud.k8s_audit_logs and objectRef.subresource.keyword: exec	

Nº	Name	CloudLogging	Elasticsearch	Comments
	inside the container)			
6	Creating a pod with image NOT from Yandex container registry (not relevant for Clients using their own cr)		event.dataset: yandexcloud.k8s_audit_logs and not requestObject.status.containerStatuses.im age.keyword: *cr.yandex/* and requestObject.status.containerStatuses.con tainerID: *docker* and verb: patch and not requestObject.status.containerStatuses.im age.keyword: (*falco* or *openpolicyagent* or *kyverno* or *k8s.gcr.io*)	
7	Create pod in kube-system namespace		event.dataset: yandexcloud.k8s_audit_logs and objectRef.namespace.keyword: kube- system and verb: create and objectRef.resource.keyword: pods and objectRef.name: * and not objectRef.name : (*calico* or *dns* or *npd* or *proxy* or *metrics* or *csi* or *masq*)	
8	Calling k8s-api under a service account from an external ip address		event.dataset: yandexcloud.k8s_audit_logs and user.name: system\\:serviceaccount\\:* not source.ip: ("10.0.0.0/8 " or " 172.16.0.0/12" or " 192.168.0.0/16"	

Nº	Name	CloudLogging	Elasticsearch	Comments
9	Any Alert from Falco		event.dataset : yandexcloud.k8s_falco and not objectRef.namespace: falco	
10	Falco removed		event.dataset: yandexcloud.k8s_audit_logs and verb: delete and objectRef.namespace.keyword: falco and objectRef.resource.keyword: daemonsets	
	A Gatekeeper		T	Т
12	OPA Gatekeeper triggered - denied events (only in enforce mode) Removing a gatekeeper from a k8s cluster		event.dataset: yandexcloud.k8s_audit_logs and responseObject.status.keyword: Failure and responseObject.message:" admission webhook \\\"validation.gatekeeper.sh\\\" denied the request" and not objectRef.namespace: falco and not user.name: system\\\:serviceaccount\\\:kube- system\\\:daemon-set-controller event.dataset: yandexcloud.k8s_audit_logs and objectRef.name.keyword: gatekeeper- validating-webhook-configuration and verb	
13	Modifying/deleti ng a Constraint object		: delete event.dataset : yandexcloud.k8s_audit_logs and objectRef.apiGroup.keyword: constraints.gatekeeper.sh and (verb : delete or update) and not user.name :	
Kvv	erno		"system:serviceaccount:gatekeeper- system:gatekeeper-admin"	

Nº	Name	CloudLogging	Elasticsearch	Comments	
14	Kyverno triggered - denied events (only in enforce mode)		event.dataset: yandexcloud.k8s_audit_logs and responseObject.status.keyword: Failure and responseObject.message:" admission webhook \\\"validate.kyverno.svc\\\" denied the request" and not objectRef.namespace: falco and not user.name: system\\\:serviceaccount\\\:kubesystem\\\:daemon-set-controller		
15	Removing Kyverno from the k8s cluster		event.dataset: yandexcloud.k8s_audit_logs and objectRef.name.keyword: kyverno- resource-validating-webhook-cfg and verb: delete		
16	Changing/deletin g a Kyverno Policy object		event.dataset: yandexcloud.k8s_audit_logs and objectRef.apiGroup.keyword: kyverno.io and (verb: delete or update) and objectRef.resource.keyword: *policies		
Kyv	erno-report				
17	Kyvenro triggered: fail status of policy result (Yandexcloud:k8 s:kyverno- reporter-detect)		event.dataset : yandexcloud.k8s_kyverno and Status : fail		
Exte	External Secrets				

Nº	Name	CloudLogging	<u>Elasticsearch</u>	Comments
18	Changing / creating an external secrets object with an account other than ci / cd (this object goes to the lockbox and copies the secret from there)		event.dataset: yandexcloud.k8s_audit_logs and not user.name: "ajesnkfkc77lbh50isvg" and not user.name: "system:serviceaccount:external- secrets:external-secrets" and objectRef.name: "external-secret" and verb: (patch or create)	
19	Read secrets under user account		event.dataset: yandexcloud.k8s_audit_logs and objectRef.resource: "secrets" and verb: "get" and not user.name: ("system:serviceaccount:external-secrets:external-secrets" or "system:serviceaccount:kube-system:hubble-generate-certs" or "system:serviceaccount:kyverno:kyverno")	