




















Searches & Use Cases





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
Searches				
1	Find who deleted a folder (requires values)	<code>json_payload.event_type="yandex.cloud.audit.resourcemanager.DeleteFolder" and json_payload.details.folder_name"<название каталога>"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.resourcemanager.DeleteFolder and cloud.folder.name: <название каталога></code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$.event_type") = 'yandex.cloud.audit.resourcemanager.DeleteFolder' and JSON_VALUE(data, "\$.details.folder_name") = 'test' limit 100</code>
2	Find who created/stopped/restarted/deleted a virtual machine (requires values)	<code>json_payload.details.instance_id="<идентификатор виртуальной машины>" and (json_payload.event_type="yandex.cloud.audit.compute.CreateInstance" or json_payload.event_type="yandex.cloud.audit.compute.UpdateInstance" or json_payload.event_type="yandex.cloud.audit.compute.DeleteInstance" or</code>	<code>event.dataset: yandexcloud.audittrail and event.action : yandex.cloud.audit.compute.*Instance and cloud.instance.name: testdasdas</code>	<code>select * from bindings.`binding` where (JSON_VALUE(data, "\$.event_type") = 'yandex.cloud.audit.compute.DeleteInstance' or JSON_VALUE(data, "\$.event_type") =</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
		<pre>json_payload.event_type="yandex .cloud.audit.compute.StartInsta nce" or json_payload.event_type="yandex .cloud.audit.compute.StopInstan ce" or json_payload.event_type="yandex .cloud.audit.compute.RestartIns tance")</pre>		<pre>'yandex.cloud.audit.comp ute.CreateInstance') and JSON_VALUE(data, "\$.details.instance_id") = 'fhmpgh36fo3vclan2e99' limit 100 ;</pre>
3	What actions did a particular user perform over a period of time (requires values)	<pre>json_payload.authentication.sub ject_name="mirtov8@yandex- team.ru" and json_payload.event_time<"2022- 03-01" and json_payload.event_time<"2022- 04-01"</pre>	<pre>event.dataset: yandexcloud.audittrail and user.name : mirtov8@yandex-team.ru and event_time < 2022- 07-15</pre>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$.authentication.subjec t_name") = 'mirtov8@yandex-team.ru' and cast(JSON_VALUE(data, "\$event_time")as Timestamp) > Date("2022- 08-15") limit 10 ;</pre>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
4	Search for events by objects of a specific folder (requires values)	<code>json_payload.resource_metadata.path[1].resource_type="resource-manager.folder" and json_payload.resource_metadata.path[1].resource_name="<имя каталога>" or (json_payload.resource_metadata.path[2].resource_type="resource-manager.folder" and json_payload.resource_metadata.path[2].resource_name="<имя каталога>"</code>	<code>event.dataset:yandexcloud.audittrail and cloud.folder.name:"mirtov-scale"</code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$.resource_metadata.path[2].resource_name") = 'mirtov-scale' limit 100 ;</code>
Use cases				
IAM				
1	Triggered when creating service account credentials	<code>json_payload.event_type="yandex.cloud.audit.iam.CreateAccessKey" or json_payload.event_type="yandex.cloud.audit.iam.CreateKey" or json_payload.event_type="yandex.cloud.audit.iam.CreateApiKey"</code>	<code>event.dataset:yandexcloud.audittrail and event.action:(yandex.cloud.audit.iam.CreateAccessKey or yandex.cloud.audit.iam.CreateKey or yandex.cloud.audit.iam.CreateApiKey)</code>	<code>select * from bindings.`binding-yds` where JSON_VALUE(data, "\$.event_type") = 'yandex.cloud.audit.iam.CreateAccessKey' or JSON_VALUE(data, "\$.event_type") = 'yandex.cloud.audit.iam.CreateKey' or JSON_VALUE(data,</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<code>"\$.event_type") = 'yandex.cloud.audit.iam. CreateApiKey' limit 1 ;</code>
2	Trigger on any action under a privileged account with the role "resource-manager.clouds.owner" and "organization-manager.admin" (can be a list) (requires values)	<code>json_payload.authentication.subject_name="mirtov8@yandex-team.ru" or json_payload.authentication.subject_name="kirill@yandex-team.ru"</code>	<code>event.dataset: yandexcloud.audittrail and user.name : mirtov8@yandex-team.ru kirill18@yandex-team.ru</code>	-
3	Abnormal number of failed authorization attempts (requires values)	---	<code>event.dataset: yandexcloud.audittrail and error.message: Permission denied</code>	-
4	Assignment of admin rights (for resources: folder, cloud)	<code>json_payload.details.access_binding_deltas.access_binding.role_id="admin"</code>	<code>event.dataset: yandexcloud.audittrail and details.access_binding_</code>	<code>select * from bindings.`binding` where</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			<code>deltas.access_binding.role_id: admin</code>	<pre>JSON_VALUE(data, "\$details.access_binding_deltas.access_binding.role_id") = 'admin' limit 1 ;</pre>
5	Assigning the vpc.public.admin role	<code>json_payload.details.access_binding_deltas.access_binding.role_id="vpc.publicAdmin"</code>	<code>event.dataset: yandexcloud.audittrail and details.access_binding_deltas.access_binding.role_id: vpc.publicAdmin</code>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$details.access_binding_deltas.access_binding.role_id") = 'vpc.publicAdmin' limit 1 ;</pre>
6	Calling the API using YC or terraform under a suspicious user or ip	<code>json_payload.request_metadata.user_agent:"YC" or json_payload.request_metadata.user_agent:"Terraform"</code>	<code>event.dataset: yandexcloud.audittrail and (user_agent.original.keyword: *YC/* or user_agent.original.keyword: *Terraform*)</code>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$details.request_metadata.user_agent") = 'YC' or JSON_VALUE(data,</pre>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<code>\$.details.request_metadata.user_agent") = 'Terraform' limit 1 ;</code>
7	coming soon A new certificate has been added to the federation	---	---	
8	coming soon Changed federation settings	---	---	
9	new <i>Any action using a cloud service account from a range of IP addresses outside the cloud</i>	not <code>json_payload.request_metadata.remote_address:"51.250"...</code>	<code>event.dataset: yandexcloud.audittrail and user.type: SERVICE_ACCOUNT and not source.ip: ("51.250.0.0/17" or "31.44.8.0/21" or "62.84.112.0/20" or "84.201.128.0/18" or "84.252.128.0/20" or "130.193.32.0/19" or "178.154.192.0/18" or "178.170.222.0/24" or "185.206.164.0/22" or "193.32.216.0/22" or</code>	-

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			"217.28.224.0/20") and source.ip: *	
Compute				
10	Triggering on an event with the creation of a VM with a white IP address	<code>json_payload.event_type="yandex.cloud.audit.compute.CreateInstance" and json_payload.details.network_interfaces.primary_v4_address.one_to_one_nat.address exists</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.CreateInstance and details.network_interfaces.primary_v4_address. one_to_one_nat.address: *</code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.compute.CreateInstance' and JSON_EXISTS(data, "\$..details.network_interfaces.primary_v4_address. one_to_one_nat.address") limit 1 ;</code>
11	Triggered to create "two-legged" virtual machines	<code>json_payload.event_type="yandex.cloud.audit.compute.CreateInstance" and json_payload.details.network_interfaces[1].index="1"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.CreateInstance and details.network_interfaces.index: 1</code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.compute.CreateInstance' and JSON_VALUE(data,</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<code>\$.details.network_interfaces[1].index") = '1'</code> <code>limit 1</code> <code>;</code>
12	Uploading an image to the cloud from a non-fixed S3 Bucket (requires values)	<code>json_payload.event_type="yandex.cloud.audit.compute.CreateImage" and not</code> <code>json_payload.details.source_uri:"https://storage.yandexcloud.net/action-log-123"</code>	<code>event.dataset:</code> <code>yandexcloud.audittrail</code> <code>and event.action:</code> <code>yandex.cloud.audit.compute.CreateImage and not</code> <code>cloud.image.source_uri:</code> <code>"https://storage.yandexcloud.net/action-log-123"</code>	<code>select * from</code> <code>bindings.`binding`</code> <code>where</code> <code>JSON_VALUE(data,</code> <code>"\$.event_type") =</code> <code>'yandex.cloud.audit.compute.CreateImage' and</code> <code>JSON_VALUE(data,</code> <code>"\$.details.source_uri")</code> <code>!=</code> <code>'https://storage.yandexcloud.net/action-log-123'</code> <code>limit 1</code> <code>;</code>
13	Create VM with image_id from Marketplace	<code>not</code> <code>json_payload.details.product_ids[0]=null</code>	<code>event.dataset:</code> <code>yandexcloud.audittrail</code> <code>and</code> <code>details.product_ids: *</code>	<code>select * from</code> <code>bindings.`binding`</code> <code>where</code> <code>JSON_VALUE(data,</code> <code>"\$.event_type") =</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				'yandex.cloud.audit.compute.CreateInstance' and JSON_VALUE(data, "\$\$.details.product_ids[0]") != 'null' limit 1 ;
14	Adding a public IP address to an existing virtual machine	json_payload.event_type="yandex.cloud.audit.compute.AddInstanceOneToOneNat"	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.AddInstanceOneToOneNat	select * from bindings.`binding` where JSON_VALUE(data, "\$\$.event_type") = 'yandex.cloud.audit.compute.AddInstanceOneToOneNat' limit 1 ;
15	VM creation/modification events - enabling the serial port	json_payload.event_type="yandex.cloud.audit.compute.CreateInstance" and json_payload.details.metadata_serial_port_enable="1"	event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: yandex.cloud.audit.compute.CreateInstance and details.metadata_serial_port_enable: 1	select * from bindings.`binding` where JSON_VALUE(data, "\$\$.event_type") = 'yandex.cloud.audit.compute.CreateInstance' and JSON_VALUE(data,





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<pre> \$.details.metadata_serial_port_enable") = '1' limit 1 ; </pre>
16	new Modifying VM - Adding Access to Serial Console	<pre> json_payload.event_type="yandex.cloud.audit.compute.UpdateInstance" or json_payload.event_type="yandex.cloud.audit.compute.CreateInstance" and json_payload.details.metadata_serial_port_enable="1" </pre>	<pre> event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: (yandex.cloud.audit.compute.CreateInstance or yandex.cloud.audit.compute.UpdateInstance) and details.metadata_serial_port_enable: 1 </pre>	<pre> select * from bindings.`binding` where JSON_VALUE(data, "\$.event_type") = 'yandex.cloud.audit.compute.UpdateInstance' and JSON_VALUE(data, "\$.details.metadata_serial_port_enable") = '1' limit 1 ; </pre>
17	new VM custom metadata value suspected to contain sensitive data	<pre> (json_payload.event_type="yandexcloud.audit.compute.CreateInstance" or json_payload.event_type="yandex.cloud.audit.compute.UpdateInstance") and json_payload.details.metadata_keys[0]: secret </pre>	<pre> event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.compute.UpdateInstance or yandex.cloud.audit.compute.CreateInstance) and details.metadata_keys: secret key password pass token oauth </pre>	-



No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			aws_access_key_id and event.outcome : success	
18	Creating a VM without SG	<code>json_payload.event_type="yandex .cloud.audit.compute.CreateInstance" and not json_payload.details.network_in terfaces.security_group_ids EXISTS</code>	<code>event.dataset: yandexcloud.audittrail and event.outcome : success and event.action: yandex.cloud.audit.comp ute.CreateInstance and not details.network_interfa ces.security_group_ids: *</code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.comp ute.CreateInstance' and JSON_EXISTS(data, "\$..details.network_inter faces[0].security_group_ ids") = False limit 4 ;</code>
VPC				
19	Creating too wide (insecure) ACL Security Group	<code>json_payload.event_type="yandex .cloud.audit.network.CreateSecu rityGroup" or json_payload.event_type="yandex .cloud.audit.network.UpdateSecu rityGroup" and json_payload.details.rules[0].d irection="INGRESS" and json_payload.details.rules[0].c idr_blocks.v4_cidr_blocks[0]="0 .0.0.0/0"</code>	<code>event.dataset: yandexcloud.audittrail and (event.action: yandex.cloud.audit.netw ork.CreateSecurityGroup or yandex.cloud.audit.netw ork.UpdateSecurityGroup) and details.rules.direction : INGRESS and details.rules.cidr_bloc</code>	<code>select * from bindings.`binding` where (JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.netw ork.CreateSecurityGroup' or JSON_VALUE(data, "\$..event_type") =</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			ks.v4_cidr_blocks: *0.0.0.0*	'yandex.cloud.audit.network.UpdateSecurityGroup') and (JSON_VALUE(data, "\$\$.details.rules[0].direction") = 'INGRESS' and JSON_VALUE(data, "\$\$.details.rules[0].cidr_blocks.v4_cidr_blocks[0]]") = '0.0.0.0/0') limit 1 ;
20	Creating a public address without a DDoS protection checkbox	json_payload.event_type="yandex.cloud.audit.network.CreateAddress" and not json_payload.details.external_ipv4_address.requirements.ddos_protection_provider exists	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.network.CreateAddress and not details.external_ipv4_address.requirements.ddos_protection_provider:qrator	select * from bindings.`binding` where JSON_VALUE(data, "\$\$.event_type") = 'yandex.cloud.audit.network.CreateAddress' and JSON_EXISTS(data, "\$\$.details.external_ipv4_address.requirements.ddos_protection_provider") = False limit 2





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				;
21	new Creating / applying a security group by an account not from the list of allowed (requires values)	<pre>(json_payload.event_type="yandex.cloud.audit.network.CreateSecurityGroup" or json_payload.event_type="yandex.cloud.audit.network.UpdateSecurityGroup") and not json_payload.authentication.subject_name="mirtov8@yandex-team.ru"</pre>	<pre>event.dataset: yandexcloud.audittrail and (event.action: yandex.cloud.audit.network.CreateSecurityGroup or yandex.cloud.audit.network.UpdateSecurityGroup) and not user.name: mirtov8@yandex-team.ru kirill@yandex-team.ru</pre>	-
22	Any action with Security Group objects	<pre>json_payload.event_type="yandex.cloud.audit.network.CreateSecurityGroup" or json_payload.event_type="yandex.cloud.audit.network.UpdateSecurityGroup"</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.network.*SecurityGroup</pre>	<pre>select * from bindings.`binding` where (JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.network.CreateSecurityGroup' or JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.network.UpdateSecurityGroup') limit 5 ;</pre>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
ObjectStorage(S3)				
23	Suspicious activities with S3 Bucket	<code>json_payload.event_type="yandex.cloud.audit.storage.BucketAclUpdate" or json_payload.event_type="yandex.cloud.audit.storage.BucketPolicyUpdate"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.storage.BucketAclUpdate or yandex.cloud.audit.storage.BucketPolicyUpdate)</code>	<pre>select * from bindings.`binding` where (JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.storage.BucketAclUpdate' or JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.storage.BucketPolicyUpdate') limit 5 ;</pre>
24	new Bucket become public	<code>json_payload.event_type="yandex.cloud.audit.storage.BucketUpdate" and (json_payload.details.objects_access: "true" or json_payload.details.settings_read_access: "true" or json_payload.details.list_access: "true")</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.storage.BucketUpdate and (details.objects_access: true or details.settings_read_access: true or details.list_access: true)</code>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.storage.BucketUpdate' and (JSON_VALUE(data, "\$..details.objects_access</pre>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<pre>s") = 'true' or JSON_VALUE(data, "\$details.settings_read_access") = 'true' or JSON_VALUE(data, "\$details.list_access") = 'true') limit 5 ;</pre>
25	new Object storage bucket (S3) became public when created/modified via ACL	<pre>json_payload.event_type="yandex .cloud.audit.storage.BucketAcLU pdate" and json_payload.details.acl.grants .grant_type: "ALL_USERS"</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.stor age.BucketAcUpdate and details.acl.grants.gran t_type: "ALL_USERS"</pre>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$event_type") = 'yandex.cloud.audit.stor age.BucketUpdate' and JSON_VALUE(data, "\$details.acl.grants.gr ant_type") = 'ALL_USERS' limit 5 ;</pre>
Lockbox/KMS				
26	Triggered by changing access rights to KMS	<pre>json_payload.event_type="yandex .cloud.audit.kms.UpdateSymmetri cKeyAccessBindings" or</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action:</pre>	<pre>select * from bindings.`binding`</pre>




No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
	symmetric encryption keys	<code>json_payload.event_type="yandex.cloud.audit.kms.CreateSymmetricKeyAccessBindings"</code>	<code>yandex.cloud.audit.kms.*SymmetricKeyAccessBindings</code>	<pre>where JSON_VALUE(data, "\$event_type") = 'yandex.cloud.audit.kms. UpdateSymmetricKeyAccess Bindings' or JSON_VALUE(data, "\$event_type") = 'yandex.cloud.audit.kms. CreateSymmetricKeyAccess Bindings' limit 5 ;</pre>
27	Removing a KMS key	<code>json_payload.event_type="yandex.cloud.audit.kms.DeleteSymmetricKey"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.kms. DeleteSymmetricKey</code>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$event_type") = 'yandex.cloud.audit.kms. DeleteSymmetricKey' limit 5 ;</pre>
28	Assigning/Updating LockBox Secret Rights	<code>json_payload.event_type="yandex.cloud.audit.lockbox.UpdateSecretAccessBindings"</code>	<code>event.dataset: yandexcloud.audittrail and event.action:</code>	-





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			yandex.cloud.audit.lockbox.UpdateSecretAccessB indings	
29	new Assigning a person with access to a lockbox service account secrets on the VM (requires values)	json_payload.event_type="yandex.cloud.audit.compute.UpdateInstance" and json_payload.details.service_account_id: "ajeg2ar8m8o25u63dj9f"	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.compute.UpdateInstance and details.service_account_id: ajeg2ar8m8o25u63dj9f	-
30	new Reading a secret from Lockbox from an IP address different from the cloud address range (requires values)	json_payload.event_type="yandex.cloud.audit.lockbox.GetPayload" and not json_payload.request_metadata.remote_address:"51.250"...	event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.lockbox.GetPayload and not source.ip: ("51.250.0.0/17" or "31.44.8.0/21" or "62.84.112.0/20" or "84.201.128.0/18" or "84.252.128.0/20" or "130.193.32.0/19" or "178.154.192.0/18" or "178.170.222.0/24" or "185.206.164.0/22" or	-





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			"193.32.216.0/22" or "217.28.224.0/20")	
31	new Reading a secret from Lockbox using an account that is different from the target (requires values)	<code>json_payload.event_type="yandex.cloud.audit.lockbox.GetPayload" and not json_payload.authentication.subject_id: "ajesnkfk77lbh50isvg" and json_payload.details.secret_id="e6q7q5msguqg22ji78e0"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.lockbox.GetPayload and not user.id: ajeg2ar8m8o25u63dj9f and details.secret_name: secret1</code>	-
MDB				
32	new Creating an MDB cluster by a cloud user not from the list of administrators (requires values)	<code>json_payload.event_type: "yandex.cloud.audit.mdb." and not json_payload.authentication.subject_name: "test"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.mdb. *.CreateCluster and not user.name : mirtov8@yandex-team.ru kirill@yandex-team.ru</code>	-
33	new Creating/Changing an MDB User	<code>json_payload.event_type: "CreateUser" or json_payload.event_type: "UpdateUser"</code>	<code>event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.mdb. *.UpdateUser or yandex.cloud.audit.mdb. *.CreateUser)</code>	<code>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.mdb.</code>





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
				<pre>postgresql.CreateUser' or JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.mdb. postgresql.UpdateUser' limit 5 ;</pre>
34	new Deleting an MDB Cluster	<pre>json_payload.event_type: "DeleteCluster"</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: yandex.cloud.audit.mdb. *.DeleteCluster</pre>	<pre>select * from bindings.`binding` where JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.mdb. postgresql.DeleteCluster ' or JSON_VALUE(data, "\$..event_type") = 'yandex.cloud.audit.mdb. postgresql.UpdateUser' limit 5 ;</pre>
35	new Administrative actions with MDB from ip	<pre>(json_payload.event_type: "DeleteCluster" or json_payload.event_type: "CreateCluster") and not</pre>	<pre>event.dataset: yandexcloud.audittrail and event.action: (yandex.cloud.audit.mdb *.UpdateUser or</pre>	-





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
	addresses that are different from the trusted range (requires values)	<code>json_payload.request_metadata.remote_address: "51.250"</code>	<code>yandex.cloud.audit.mdb.*.CreateUser or yandex.cloud.audit.mdb.*.CreateCluster or yandex.cloud.audit.mdb.*.UpdateCluster) and source.ip : ("2a00:1fa0:474:9876:4cac:6c43:12aa:2bd2" or "2a00:1fa0:474:9876:4cac:6c43:12aa:2bd1")</code>	
36	coming soon Enabling a dangerous setting when creating a cluster	-доступ из datalens -публичный доступ -доступ из консоли управления -доступ из serverless	---	
37	coming soon Enabling a dangerous setting when changing a cluster	-доступ из datalens -публичный доступ -доступ из консоли управления -доступ из serverless	---	
38	coming soon Not enabled / unchecked	--	---	





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
	"Protection from deletion" when creating/changing			
39	coming soon Changing settings affecting the collection of audit logs from MDB when creating / changing	-настройки log_statements and log_connections	---	
40	coming soon Issuing privileged GRANT mdb_admin to a user	---	---	
41	coming soon Creating/Modifying a Cluster without a Security Group Installed	---	---	





No	Name	CloudLogging 	Elasticsearch   Opensearch	Yandex Query  (S3 or YDS)
The following Use cases are not part of Audit Trails, but are native k8s audit logs, and currently they cannot be analyzed in CloudLogging				
Kubernetes (for k8s events, you need to set up a solution)				
General				
1	Access denied events - unauthorized	---	event.dataset : yandexcloud.k8s_audit_logs and responseStatus.reason : Forbidden and not user.name : (system*node* or *gatekeeper* or *kyverno* or *proxy* or *scheduler* or *anonymous* or *csi* or *controller*)	
2	Assigning a cluster-admin or admin role (clusterrolebinding or rolebinding)	---	event.dataset : yandexcloud.k8s_audit_logs and responseObject.roleRef.name.key word:(cluster-admin or admin) and objectRef.resource.keyword: (clusterrolebindings or rolebindings) and verb : create and not responseObject.reason : AlreadyExists	
3	Successful connection to the cluster from	---	event.dataset : yandexcloud.k8s_audit_logs and source.ip : * and not responseStatus.status : Failure	





No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
	an external IP address			
4	NetworkPolicies: create, delete, change	---	event.dataset : yandexcloud.k8s_audit_logs and requestObject.kind.keyword: (NetworkPolicy or CiliumNetworkPolicy or DeleteOptions) and verb : (create or update or delete) and objectRef.resource : networkpolicies	
5	Exec inside the container (shell inside the container)	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.subresource.keyword: exec	
6	Creating a pod with image NOT from Yandex container registry (not relevant for Clients using their own cr)	---	event.dataset : yandexcloud.k8s_audit_logs and not requestObject.status.containerStatuses.image.keyword: *cr.yandex/* and requestObject.status.containerStatuses.containerID : *docker* and verb : patch and not	

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			requestObject.status.containerStatuses.image.keyword: (*falco* or *openpolicyagent* or *kyverno* or *k8s.gcr.io*)	
7	Create pod in kube-system namespace	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.namespace.keyword: kube-system and verb : create and objectRef.resource.keyword: pods and objectRef.name : * and not objectRef.name : (*calico* or *dns* or *npd* or *proxy* or *metrics* or *csi* or *masq*)	
8	Calling k8s-api under a service account from an external ip address	---	event.dataset : yandexcloud.k8s_audit_logs and user.name : system\\:\\:serviceaccount\\:\\:* not source.ip: ("10.0.0.0/8 " or " 172.16.0.0/12" or " 192.168.0.0/16"	
Falco				
9	Any Alert from Falco	---	event.dataset : yandexcloud.k8s_falco and not objectRef.namespace: falco	
10	Falco removed	---	event.dataset : yandexcloud.k8s_audit_logs and	

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			verb : delete and objectRef.namespace.keyword: falco and objectRef.resource.keyword : daemonsets	
OPA Gatekeeper				
11	OPA Gatekeeper triggered - denied events (only in enforce mode)	---	event.dataset : yandexcloud.k8s_audit_logs and responseObject.status.keyword: Failure and responseObject.message :" admission webhook \\\\"validation.gatekeeper.sh\\"" denied the request" and not objectRef.namespace : falco and not user.name : system\\\:serviceaccount\\\:kube -system\\\:daemon-set-controller	
12	Removing a gatekeeper from a k8s cluster	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.name.keyword: gatekeeper-validating-webhook- configuration and verb : delete	

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
13	Modifying/deleting a Constraint object	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.apiGroup.keyword: constraints.gatekeeper.sh and (verb : delete or update) and not user.name : "system:serviceaccount:gatekeeper-system:gatekeeper-admin"	
Kyverno				
14	Kyverno triggered - denied events (only in enforce mode)	---	event.dataset : yandexcloud.k8s_audit_logs and responseObject.status.keyword: Failure and responseObject.message : " admission webhook \\\\\\"validate.kyverno.svc\\\\\\" denied the request" and not objectRef.namespace : falco and not user.name : system\\\\\\:serviceaccount\\\\\\:kube- system\\\\\\:daemon-set-controller	
15	Removing Kyverno from the k8s cluster	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.name.keyword:	

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
			kyverno-resource-validating-webhook-cfg and verb : delete	
16	Changing/deleting a Kyverno Policy object	---	event.dataset : yandexcloud.k8s_audit_logs and objectRef.apiGroup.keyword: kyverno.io and (verb : delete or update) and objectRef.resource.keyword: *policies	
Kyverno-report				
17	Kyverno triggered: fail status of policy result (Yandexcloud:k8s:kyverno-reporter-detect)	---	event.dataset : yandexcloud.k8s_kyverno and Status : fail	
External Secrets				
18	Changing / creating an external secrets object with an account other than ci / cd (this		event.dataset : yandexcloud.k8s_audit_logs and not user.name: "ajesnkfk77lbh50isvg" and not user.name: "system:serviceaccount:external-	

No	Name	CloudLogging 	Elasticsearch  Opensearch 	Yandex Query  (S3 or YDS)
	object goes to the lockbox and copies the secret from there)		secrets:external-secrets" and objectRef.name: "external-secret" and verb: (patch or create)	
19	Read secrets under user account		event.dataset : yandexcloud.k8s_audit_logs and objectRef.resource: "secrets" and verb: "get" and not user.name: ("system:serviceaccount:external-secrets:external-secrets" or "system:serviceaccount:kube-system:hubble-generate-certs" or "system:serviceaccount:kyverno:kyverno")	