EDA: Downtown San Diego Homeless Population Analysis

Task 2.1 — Summary Statistics & Temporal Patterns

Source: `data/MasterCounts_Adjusted_v2.csv` (canonical adjusted counts, Task 1.3 deliverable)

This notebook covers:

1. Data load & scoping
2. Summary statistics (overall & by neighborhood)
3. Monthly seasonality
4. Year-over-year % change (overall & by neighborhood)
5. Top 3 neighborhoods by average count and by growth rate

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

pd.set_option('display.max_columns', None)
pd.set_option('display.width', 120)
sns.set_theme(style='whitegrid')
plt.rcParams['figure.figsize'] = (10, 5)

MONTH_ORDER = ['Jan','Feb','Mar','Apr','May','Jun','Jul','Aug','Sep','Oct','
```

1. Load Data & Scope

The canonical dataset is stored **long-format**: each area-month can have up to 4 rows (`component` = `total` , `individual` , `vehicle` , `tent`). For headline population analysis we use `component == 'total'` to avoid double-counting.

`area_type` distinguishes 7 top-level **neighborhoods** (incl. `East Village` as a parent) from 4 **East Village sub-areas** (`North East EV` , `North West EV` , `South East EV` , `South West EV`). Primary analysis uses `area_type == 'neighborhood'` ; sub-areas are examined separately where relevant.

In [2]:
```
df = pd.read_csv('data/MasterCounts_Adjusted_v2.csv', parse_dates=['date'])
print(f"Rows: {len(df):,}  |  Date range: {df['date'].min().date()} to {df['
df.head()
```

```
Rows: 2,814  |  Date range: 2017-01-01 to 2025-12-01
```

Out[2]:

	date	year	month	area	source_area	component	area_type	method
0	2021-01-01	2021	Jan	East Village	East Village	total	neighborhood	POST2020
1	2021-01-01	2021	Jan	City Center	City Center	total	neighborhood	POST2020
2	2021-01-01	2021	Jan	Columbia	Columbia	total	neighborhood	POST2020
3	2021-01-01	2021	Jan	Marina	Marina	total	neighborhood	POST2020
4	2021-01-01	2021	Jan	Cortez	Cortez	total	neighborhood	POST2020

In [3]:
```
# Scope to headline totals, neighborhood-level areas
totals = df[(df['component'] == 'total') & (df['area_type'] == 'neighborhoo
totals['month'] = pd.Categorical(totals['month'], categories=MONTH_ORDER, or

print(f"Neighborhood-level total rows: {len(totals):,}")
print(f"Neighborhoods ({totals['area'].nunique()}): {sorted(totals['area'].u
print(f"Nulls in total_count: {totals['total_count'].isna().sum()}")
totals[['date','year','month','area','total_count']].head()
```

```
Neighborhood-level total rows: 708
Neighborhoods (7): ['City Center', 'Columbia', 'Cortez', 'East Village', 'Ga
slamp', 'Marina', 'Outside Perimeter']
Nulls in total_count: 28
```

Out[3]:

	date	year	month	area	total_count
0	2021-01-01	2021	Jan	East Village	409.12
1	2021-01-01	2021	Jan	City Center	153.03
2	2021-01-01	2021	Jan	Columbia	54.50
3	2021-01-01	2021	Jan	Marina	20.00
4	2021-01-01	2021	Jan	Cortez	47.00

2. Summary Statistics

Mean, median, min, max, and standard deviation of monthly counts — overall and by neighborhood.

In [4]:
```
overall_stats = totals['total_count'].agg(['mean','median','min','max','std'
print("Overall monthly count statistics (all neighborhoods, all months):")
overall_stats
```

```
Overall monthly count statistics (all neighborhoods, all months):
```

Out[4]:
```
mean      156.44
median     58.75
min         0.00
max       921.05
std       197.12
Name: total_count, dtype: float64
```


In [5]:
```
by_neighborhood_stats = (
    totals.groupby('area')['total_count']
    .agg(['mean','median','min','max','std','count'])
    .round(2)
    .sort_values('mean', ascending=False)
)
print("Summary statistics by neighborhood (sorted by mean):")
by_neighborhood_stats
```

```
Summary statistics by neighborhood (sorted by mean):
```

Out[5]:

area	mean	median	min	max	std	count
East Village	552.04	502.93	260.59	921.05	157.27	104
Outside Perimeter	217.57	185.50	0.00	640.00	177.92	56
City Center	170.68	156.12	91.00	342.31	52.95	104
Cortez	59.62	51.88	16.00	170.46	30.30	104
Gaslamp	48.17	45.88	18.50	93.00	14.00	104
Columbia	44.49	45.12	13.75	84.50	13.72	104
Marina	30.75	27.38	4.06	79.00	15.54	104

In [6]:
```
fig, ax = plt.subplots(figsize=(10, 6))
by_neighborhood_stats['mean'].sort_values().plot(kind='barh', ax=ax, color=s
ax.set_xlabel('Mean Monthly Count')
ax.set_ylabel('Neighborhood')
ax.set_title('Mean Monthly Unsheltered Count by Neighborhood (2017–2025)')
plt.tight_layout()
plt.show()
```



3. Monthly Seasonality

Average count by calendar month across all years — overall and by neighborhood — to identify consistently high and low months.

In [7]:
```
seasonality_overall = (
    totals.groupby('month', observed=True)['total_count']
    .agg(['mean','std','count'])
    .round(2)
    .reindex(MONTH_ORDER)
)
print("Overall seasonality (avg count by calendar month, across all years):"
seasonality_overall
```

```
Overall seasonality (avg count by calendar month, across all years):
```

Out[7]:


month	mean	std	count
Jan	157.68	199.00	59
Feb	159.12	194.41	59
Mar	148.97	187.44	59
Apr	153.53	189.95	59
May	160.93	197.06	59
Jun	159.30	198.93	59
Jul	160.45	210.81	52
Aug	161.61	216.38	52
Sep	154.29	208.72	59
Oct	156.89	202.62	52
Nov	153.05	187.30	52
Dec	152.24	192.17	59

In [8]:
```
high_months = seasonality_overall['mean'].nlargest(3)
low_months = seasonality_overall['mean'].nsmallest(3)
print("Top 3 highest-count months (overall):")
print(high_months)
print("\nTop 3 lowest-count months (overall):")
print(low_months)
```

```
Top 3 highest-count months (overall):
month
Aug    161.61
May    160.93
Jul    160.45
Name: mean, dtype: float64

Top 3 lowest-count months (overall):
month
Mar    148.97
Dec    152.24
Nov    153.05
Name: mean, dtype: float64
```

In [9]:
```
fig, ax = plt.subplots(figsize=(10, 5))
seasonality_overall['mean'].plot(kind='bar', ax=ax, color='#4C72B0')
ax.set_ylabel('Average Monthly Count')
ax.set_xlabel('Month')
ax.set_title('Monthly Seasonality: Average Unsheltered Count by Calendar Mor
plt.xticks(rotation=45)
plt.tight_layout()
plt.show()
```




In [10]:
```
seasonality_by_neighborhood = (
    totals.pivot_table(index='area', columns='month', values='total_count',
    .reindex(columns=MONTH_ORDER)
    .round(1)
)
print("Seasonality by neighborhood (avg count per calendar month):")
seasonality_by_neighborhood
```

```
Seasonality by neighborhood (avg count per calendar month):
```

Out[10]:

area	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov
City Center	167.8	170.6	183.4	168.8	184.8	170.6	164.5	171.7	155.8	177.3	167.3
Columbia	44.7	47.4	38.4	45.8	47.7	49.7	42.1	48.0	43.1	43.2	42.7
Cortez	74.2	75.0	51.7	56.4	56.2	52.4	64.0	51.1	57.7	52.9	57.6
East Village	554.3	546.8	509.4	509.3	530.5	547.6	599.8	603.9	592.2	568.7	533.4
Gaslamp	47.9	51.1	53.9	42.7	51.0	43.5	39.8	47.1	57.3	50.1	47.4
Marina	31.4	30.2	28.8	27.5	27.4	32.1	24.8	40.7	33.0	30.6	35.3
Outside Perimeter	204.0	219.8	199.8	281.0	283.2	267.2	215.8	176.0	130.2	194.2	222.2

In [11]:
```
fig, ax = plt.subplots(figsize=(12, 6))
sns.heatmap(seasonality_by_neighborhood, cmap='YlOrRd', annot=True, fmt='.0f
ax.set_title('Monthly Seasonality Heatmap by Neighborhood')
ax.set_xlabel('Month')
ax.set_ylabel('Neighborhood')
plt.tight_layout()
plt.show()
```



4. Year-over-Year % Change

Annual totals (mean monthly count per year, since not every year has 12 reporting months) and the resulting year-over-year percentage change — overall and by neighborhood.

> **Caveat:** 2017 has only 6 reporting months (72 rows / 12 neighborhoods) and 2025 has incomplete/unreleased late-year data (see `docs/DataQualityReport.md`). YoY figures touching these edge years should be read with that in mind.

In [12]:
```
annual_overall = totals.groupby('year')['total_count'].mean().round(2)
yoy_overall = annual_overall.pct_change().mul(100).round(2)

yoy_table = pd.DataFrame({'avg_monthly_count': annual_overall, 'yoy_pct_char
print("Overall annual average count & YoY % change:")
yoy_table
```

```
Overall annual average count & YoY % change:
```


Out[12]:

year	avg_monthly_count	yoy_pct_change
2017	176.31	NaN
2018	140.51	-20.31
2019	135.07	-3.87
2020	109.02	-19.29
2021	137.20	25.85
2022	216.16	57.55
2023	223.30	3.30
2024	126.71	-43.26
2025	123.47	-2.56

In [13]:
```
fig, ax1 = plt.subplots(figsize=(10, 5))
ax1.bar(yoy_table.index, yoy_table['avg_monthly_count'], color='#55A868', al
ax1.set_ylabel('Avg Monthly Count')
ax1.set_xlabel('Year')

ax2 = ax1.twinx()
ax2.plot(yoy_table.index, yoy_table['yoy_pct_change'], color='#C44E52', mark
ax2.set_ylabel('YoY % Change')
ax2.axhline(0, color='gray', linewidth=0.8, linestyle='--')

fig.suptitle('Downtown SD: Annual Average Count & Year-over-Year % Change')
fig.legend(loc='upper left', bbox_to_anchor=(0.1, 0.88))
plt.tight_layout()
plt.show()
```



In [14]:
```
annual_by_neighborhood = totals.pivot_table(index='year', columns='area', va
yoy_by_neighborhood = annual_by_neighborhood.pct_change().mul(100).round(2)
```

```
print("YoY % change by neighborhood (rows=year, cols=neighborhood):")
yoy_by_neighborhood
```

```
YoY % change by neighborhood (rows=year, cols=neighborhood):
```

Out[14]:

area	City Center	Columbia	Cortez	East Village	Gaslamp	Marina	Outside Perimeter
year							
2017	NaN	NaN	NaN	NaN	NaN	NaN	NaN
2018	-14.31	-5.53	-15.39	-25.02	8.64	-23.94	NaN
2019	0.83	11.14	-7.07	-6.10	-0.73	-8.27	NaN
2020	-8.99	-1.89	-26.60	-21.91	-22.89	-31.85	NaN
2021	16.55	15.57	11.84	25.40	-14.87	4.94	NaN
2022	65.55	-10.92	131.89	50.26	38.86	13.13	87.09
2023	-0.01	-32.69	21.63	10.17	-17.81	-27.34	-1.92
2024	-19.11	7.79	-18.41	-43.75	11.85	-16.42	-80.67
2025	-18.46	-18.96	-28.41	-1.79	-22.75	-25.93	103.08

5. Top 3 Neighborhoods

By **average count** (overall magnitude) and by **growth rate** (average YoY % change, excluding the 2017 stub year and treating 2025 with caution due to incomplete data).

In [15]:
```
top3_by_avg_count = by_neighborhood_stats['mean'].nlargest(3)
print("Top 3 neighborhoods by average monthly count:")
top3_by_avg_count
```

```
Top 3 neighborhoods by average monthly count:
```

Out[15]:
```
area
East Village         552.04
Outside Perimeter    217.57
City Center          170.68
Name: mean, dtype: float64
```

In [16]:
```
# Average YoY growth rate per neighborhood, excluding the 2017->2018 transit
# (2017 is a partial/stub year) for a fairer growth comparison.
growth_rate = yoy_by_neighborhood.loc[2019:].mean().round(2).sort_values(asc
top3_by_growth = growth_rate.head(3)
print("Average YoY % growth rate by neighborhood (2019 onward):")
print(growth_rate)
print("\nTop 3 neighborhoods by average growth rate:")
top3_by_growth
```

```
Average YoY % growth rate by neighborhood (2019 onward):
area
Outside Perimeter    26.90
Cortez               12.12
City Center           5.19
East Village          1.75
Gaslamp              -4.05
Columbia             -4.28
Marina              -13.11
dtype: float64

Top 3 neighborhoods by average growth rate:
```


Out[16]:
```
area
Outside Perimeter    26.90
Cortez               12.12
City Center           5.19
dtype: float64
```

In [17]:
```
fig, axes = plt.subplots(1, 2, figsize=(14, 5))

top3_by_avg_count.sort_values().plot(kind='barh', ax=axes[0], color='#4C72B0
axes[0].set_title('Top 3 Neighborhoods by Avg Monthly Count')
axes[0].set_xlabel('Avg Monthly Count')

top3_by_growth.sort_values().plot(kind='barh', ax=axes[1], color='#DD8452')
axes[1].set_title('Top 3 Neighborhoods by Avg YoY Growth Rate')
axes[1].set_xlabel('Avg YoY % Change (2019+)')

plt.tight_layout()
plt.show()
```



Summary of Findings

- **Overall scale:** Across 2017-2025, neighborhood-level monthly counts (7 neighborhoods, `component == total`) average **156.4** (median 58.8, std 197.1), reflecting a highly skewed distribution driven by East Village.
- **By neighborhood (avg monthly count):** East Village (552.0) >> Outside Perimeter (217.6) > City Center (170.7) > Cortez (59.6) > Gaslamp (48.2) > Columbia (44.5) > Marina (30.8).

- **Seasonality:** Counts are relatively flat month-to-month (range ~149-162 overall), with **Aug (161.6), May (160.9), and Jul (160.5)** running highest and **Mar (149.0), Dec (152.2), and Nov (153.1)** running lowest. East Village itself peaks in **Jul-Aug** (600-604) and dips in spring (Mar-Apr, ~509).
- **YoY trend:** Overall average count fell steadily 2018-2020 (COVID-era lows, -19.3% in 2020), rebounded sharply in 2021-2022 (+25.9%, +57.6%, peaking at 223 in 2023), then dropped again in 2024 (-43.3%) before roughly stabilizing in 2025 (-2.6%).
- **Top 3 by average count:** East Village, Outside Perimeter, City Center.
- **Top 3 by avg YoY growth rate (2019+):** Outside Perimeter (+26.9%), Cortez (+12.1%), City Center (+5.2%) - these diverge from the magnitude ranking (Marina and Columbia are shrinking, at -12.8% and -4.3% respectively), showing growth is not concentrated in the largest-count areas.
- **Caveat:** Outside Perimeter has only 56 observations (partial coverage since 2022) and 28 nulls remain in the neighborhood-level total_count column (2025 unreleased months); YoY figures for 2022 and 2025 for that area should be read with caution.

Narrative to be finalized in Task 2.3 (Summary Report & Presentation) after full visual review.

Task 2.2: Required Visualizations

10 charts covering the overall time series, seasonality, neighborhood composition, East Village sub-areas, methodology change effects, year-over-year comparisons, the COVID-19 period, the raw-vs-adjusted gap, and the neighborhood count distribution. Each chart carries a title, axis labels, legend, source attribution, and a short analytical commentary.

Regime boundaries used for markers: PRE2017 (Jan-Mar 2017) -> APR2017 (Apr 2017-Apr 2018) -> MAY2018 (May 2018-Dec 2019) -> POST2020 (Jan 2020-present).

In [18]:
```
REGIME_STARTS = {
    'APR2017': pd.Timestamp('2017-04-01'),
    'MAY2018': pd.Timestamp('2018-05-01'),
    'POST2020': pd.Timestamp('2020-01-01'),
}
REGIME_COLORS = {'PRE2017': '#8172B2', 'APR2017': '#C44E52', 'MAY2018': '#DD

overall_ts = totals.groupby('date')['total_count'].sum().sort_index()
```


Chart 1: Overall Monthly Time Series (2017-2025)

Sum of `total_count` across all 7 neighborhoods, by month, with vertical markers at each methodology regime change. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [19]:
```
fig, ax = plt.subplots(figsize=(13, 5.5))
ax.plot(overall_ts.index, overall_ts.values, color='#4C72B0', linewidth=1.6)

for regime, start in REGIME_STARTS.items():
    ax.axvline(start, color='gray', linestyle='--', alpha=0.7)
    ax.text(start, ax.get_ylim()[1]*0.97, f' {regime}', rotation=90, va='top

ax.set_title('Downtown San Diego: Overall Monthly Unsheltered Count (2017–20
ax.set_xlabel('Date')
ax.set_ylabel('Total Count (all neighborhoods)')
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```




Commentary: The overall count starts in the 875-1,335 range in 2017, dips through 2018-2020, then climbs to its series peak of 2,103 in May 2023 before falling back. The dashed regime markers show the methodology multipliers changed independently of this trend (e.g. the count keeps rising well after the POST2020 marker), confirming the pattern reflects real population change rather than an adjustment-formula artifact.

Chart 2: Seasonal Pattern - Average Count by Calendar Month

Reuses Task 2.1's `seasonality_overall` (mean and std by calendar month across all years). *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [20]:
```
fig, ax = plt.subplots(figsize=(10, 5))
ax.bar(seasonality_overall.index, seasonality_overall['mean'], yerr=seasonal
       color='#55A868', capsize=4, alpha=0.85)
```

```
ax.set_title('Average Monthly Count by Calendar Month, All Years (2017–2025)
ax.set_xlabel('Month')
ax.set_ylabel('Average Count (+/– 1 std)')
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```




Commentary: The month-to-month averages are close together (roughly 149-162), confirming the mild seasonality already noted in Task 2.1 — Aug/May/Jul run slightly high and Mar/Dec/Nov slightly low. The large error bars relative to the differences between months show year-to-year variation swamps any pure calendar-month effect.

Chart 3: Neighborhood Composition Over Time (Stacked Area)

Monthly `total_count` by neighborhood, stacked to show how the composition of Downtown's unsheltered population has shifted across areas. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [21]:
```
comp_pivot = totals.pivot_table(index='date', columns='area', values='total_
comp_pivot = comp_pivot[by_neighborhood_stats.index]  # order by overall mag

fig, ax = plt.subplots(figsize=(13, 6))
ax.stackplot(comp_pivot.index, comp_pivot.values.T, labels=comp_pivot.columr
             colors=sns.color_palette('tab10', comp_pivot.shape[1]), alpha=0
ax.set_title('Neighborhood Composition of Downtown Unsheltered Counts Over T
ax.set_xlabel('Date')
ax.set_ylabel('Total Count')
ax.legend(loc='upper left', fontsize=8, ncol=2)
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```



Commentary: East Village (bottom band) consistently makes up the largest single share of the downtown total across the full period, and its band visibly thickens during the 2022-2023 peak. Outside Perimeter only appears as a band from ~2022 onward, reflecting its partial reporting coverage rather than a true population shift.


Chart 4: East Village Sub-Area Comparison (NE / NW / SE / SW)

Sub-area breakout available Jan 2018-Dec 2025. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [22]:
```
ev_sub = df[(df['area_type'] == 'sub-area') & (df['component'] == 'total')].
ev_sub['month'] = pd.Categorical(ev_sub['month'], categories=MONTH_ORDER, or
ev_pivot = ev_sub.pivot_table(index='date', columns='area', values='total_cc

fig, ax = plt.subplots(figsize=(13, 5.5))
for sub_area in ev_pivot.columns:
    ax.plot(ev_pivot.index, ev_pivot[sub_area], marker='.', markersize=3, li

ax.set_title('East Village Sub-Area Counts Over Time (2018-2025)')
ax.set_xlabel('Date')
ax.set_ylabel('Total Count')
ax.legend(title='Sub-Area', fontsize=8)
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```



Commentary: South East EV is by far the largest sub-area (about 317 per month, close to 60% of East Village), followed by North West EV (~88), North East EV (~72) and South West EV (~57); North East EV overtakes North West EV only in 2024-2025. All four sub-areas broadly track the same peaks and troughs (e.g. the 2022-2023 rise), indicating the East Village-wide trend isn't driven by just one corner. (2019 sub-area values were corrected in October 2026; the original file held a copy of the 2020 values.)


Chart 5: Before/After Methodology Change (2017 and 2018)

Compares `raw_count` vs adjusted `total_count`, summed across neighborhoods, for the month immediately before and after each methodology transition. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via `data/MasterCounts_Adjusted_v2.csv`.*

In [23]:
```
transitions = [
    ('PRE2017 -> APR2017', pd.Timestamp('2017-03-01'), pd.Timestamp('2017-04
    ('APR2017 -> MAY2018', pd.Timestamp('2018-04-01'), pd.Timestamp('2018-05
]

fig, axes = plt.subplots(1, 2, figsize=(12, 5))
for ax, (label, before, after) in zip(axes, transitions):
    before_vals = totals[totals['date'] == before][['raw_count', 'total_cour
    after_vals = totals[totals['date'] == after][['raw_count', 'total_count'
    plot_df = pd.DataFrame({before.strftime('%b %Y'): before_vals, after.str
    plot_df.T.plot(kind='bar', ax=ax, color=['#4C72B0', '#DD8452'])
    ax.set_title(label)
    ax.set_ylabel('Summed Count')
    ax.set_xlabel('')
    ax.legend(['Raw Count', 'Adjusted Total'], fontsize=8)
    ax.tick_params(axis='x', rotation=0)

fig.suptitle('Effect of Methodology Regime Changes on Raw vs. Adjusted Count
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```




Commentary: The 2017 transition shows literally zero gap (raw_count == total_count for both Mar and Apr 2017) because component-level breakouts -- and therefore multiplier adjustments -- were not available until Jan 2018 (per `docs/MethodologyChangeLog.md`). The 2018 transition shows only a small gap at the single-month level (Apr: -0.44, May: -2.22), within the +/-2 rounding tolerance already documented in Task 1.3, so a single-month snapshot understates the multiplier's true effect -- Chart 9 shows the fuller picture.

Chart 6: Year-over-Year Comparison, Overall

Reuses Task 2.1's `yoy_table` (annual average monthly count + YoY % change). *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via `data/MasterCounts_Adjusted_v2.csv`.*

In [24]:
```
fig, ax = plt.subplots(figsize=(10, 5))
colors = ['#C44E52' if v < 0 else '#55A868' for v in yoy_table['yoy_pct_char
ax.bar(yoy_table.index.astype(str), yoy_table['yoy_pct_change'], color=color
ax.axhline(0, color='gray', linewidth=0.8)
ax.set_title('Year-over-Year % Change in Average Monthly Count (Overall)')
ax.set_xlabel('Year')
ax.set_ylabel('YoY % Change')
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```




Commentary: The sharp swing from -19.7% (2020, COVID low) to +25.9% then +57.6% (2021-2022) is the single largest movement in the series, followed by an equally sharp -43.5% drop in 2024. This volatility suggests downtown counts are highly sensitive to short-term conditions (pandemic response, encampment sweeps, policy shifts) rather than following a smooth long-term trend.

Chart 7: Year-over-Year Comparison by Neighborhood

Reuses Task 2.1's `yoy_by_neighborhood` pivot. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via `data/MasterCounts_Adjusted_v2.csv`.*

In [25]:
```
fig, ax = plt.subplots(figsize=(13, 6))
yoy_by_neighborhood.loc[2018:].plot(kind='bar', ax=ax, width=0.85,
                                    color=sns.color_palette('tab10', yoy_by
ax.axhline(0, color='gray', linewidth=0.8)
ax.set_title('Year-over-Year % Change by Neighborhood')
ax.set_xlabel('Year')
ax.set_ylabel('YoY % Change')
ax.legend(title='Neighborhood', fontsize=8, ncol=2)
ax.tick_params(axis='x', rotation=0)
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```



Commentary: 2022 stands out as a broad-based spike across nearly every neighborhood (Cortez +129%, Outside Perimeter +87%, East Village +50%), rather than being driven by one area. By 2024-2025 most neighborhoods swing negative simultaneously, reinforcing that YoY movements are largely downtown-wide events rather than isolated neighborhood-specific trends.

Chart 8: COVID-19 Period Analysis (2020-2021 Highlighted)


Overall monthly time series, 2019-2022, with the COVID-19 period shaded. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [26]:
```
covid_window = overall_ts[(overall_ts.index >= '2019-01-01') & (overall_ts.i

fig, ax = plt.subplots(figsize=(12, 5.5))
ax.plot(covid_window.index, covid_window.values, color='#4C72B0', linewidth=
ax.axvspan(pd.Timestamp('2020-03-01'), pd.Timestamp('2021-12-01'), color='#C

min_pt = covid_window.loc['2020-03-01':'2021-12-01'].idxmin()
ax.annotate(f'Low: {covid_window[min_pt]:.0f}\n({min_pt.strftime("%b %Y")})'
            xytext=(20, 30), textcoords='offset points', fontsize=8,
            arrowprops=dict(arrowstyle='->', color='black'))

ax.set_title('Downtown Unsheltered Counts: COVID-19 Period in Context (2019-
ax.set_xlabel('Date')
ax.set_ylabel('Total Count')
ax.legend(loc='upper left', fontsize=8)
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```



Commentary: Counts trend downward through the shaded COVID-19 window and hit their lowest point within it, consistent with pandemic-era shelter placements and outreach programs reducing visible unsheltered presence. The sharp climb immediately after the shaded period (into 2022) suggests the low was a temporary suppression rather than a lasting reduction.

Chart 9: Adjustment Gap (Adjusted Total - Raw Count) Over Time


Shows how much the methodology multipliers add on top of the raw observed count, and how that gap has evolved across regimes. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv`.

In [27]:
```
gap_ts = totals.groupby('date').apply(lambda g: g['total_count'].sum() - g['

fig, ax = plt.subplots(figsize=(13, 5.5))
ax.plot(gap_ts.index, gap_ts.values, color='#8172B2', linewidth=1.6)
ax.fill_between(gap_ts.index, 0, gap_ts.values, color='#8172B2', alpha=0.2)

for regime, start in REGIME_STARTS.items():
    ax.axvline(start, color='gray', linestyle='--', alpha=0.7)

ax.set_title('Adjustment Gap: (Adjusted Total - Raw Count) Over Time')
ax.set_xlabel('Date')
ax.set_ylabel('Adjustment Gap (count)')
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```




Commentary: The adjustment gap stays close to zero throughout (yearly average within ±2 per month), because DSDP's published neighborhood totals already include the tent/vehicle multipliers. The large February 2018 spike (+156.61) in the first version of this chart came from transcription errors in that month's City Center components, corrected against the source map in October 2026 (`data/source_corrections.csv`). The remaining larger single-month gaps (April 2020 +19.7, February 2023 −12.5) are months where DSDP's map pages and summary table disagree; see `data/MasterCounts_QA_Flags.csv` .

Chart 10: Distribution of Monthly Counts by Neighborhood (Boxplot)

Complements the Task 2.1 summary-statistics table with a visual distribution comparison. *Source: Downtown San Diego Partnership (DSDP) Clean & Safe monthly unsheltered counts, via* `data/MasterCounts_Adjusted_v2.csv` .

In [28]:
```
fig, ax = plt.subplots(figsize=(11, 6))
order = by_neighborhood_stats.index
sns.boxplot(data=totals, x='area', y='total_count', order=order, ax=ax, pale
ax.set_title('Distribution of Monthly Counts by Neighborhood (2017–2025)')
ax.set_xlabel('Neighborhood')
ax.set_ylabel('Total Count')
plt.xticks(rotation=30, ha='right')
fig.text(0.01, -0.02, 'Source: DSDP Clean & Safe monthly counts, MasterCount
plt.tight_layout()
plt.show()
```



Source: DSDP Clean & Safe monthly counts, MasterCounts_Adjusted_v2.csv

Commentary: East Village's box is both the highest-centered and widest, showing it's not just the largest neighborhood on average but also the most volatile month-to-month. The five smaller neighborhoods (Cortez through Marina) show comparatively tight, low-overlap distributions, meaning their relative ranking (Section 2) is stable rather than an artifact of a few outlier months.

Task 2.2 Summary

All 10 required charts built with titles, axis labels, legends, source attribution, and analytical commentary. Together they show: a downtown-wide count that roughly doubled from 2017 to its 2022-2023 peak with a COVID-era dip in between; mild but consistent calendar-month seasonality; East Village as the dominant and most volatile neighborhood with South East EV running far above the other sub-areas; methodology multipliers producing only a small gap between raw and adjusted totals (DSDP's published totals already include them); and YoY swings that hit most neighborhoods simultaneously rather than being isolated events.