

# The State of Linked Data

## An Extensible Framework to Asses and Build Dataset Profiles

Ahmad Assaf<sup>1,2</sup>, Aline Senart<sup>2</sup> and Raphaël Troncy<sup>1</sup>

<sup>1</sup> EURECOM, Sophia Antipolis, France. <firstName.lastName@eurecom.fr>

<sup>2</sup> SAP Labs France. <firstName.lastName@sap.com>

**Abstract.** Linked Open Data (LOD) has emerged as one of the largest collection of interlinked datasets on the web. Benefiting from this mine of data requires the existence of descriptive information about each dataset in the accompanying metadata. Such meta information is currently very limited to few Data Portals where they are provided manually thus giving little or bad quality insights. To address this issue, we propose a scalable automatic approach for extracting and generating descriptive linked dataset meta information. This approach apply several techniques to check the validity of the attached metadata of a certain dataset as well as a whole Data Portal. Using our framework on prominent Data Portals shows that the general state of the Linked Open Data needs attention as most of datasets suffer from ad quality metadata and lack additional informative metrics.

**Keywords:** Linked Data, Dataset Profile, Metadata, Data Quality

## 1 Introduction

In the last few years the Semantic Web gained a momentum supported by the introduction of many related initiatives like the Linked Open Data (LOD)[5]. From 12 datasets cataloged in 2007, the Linked Open Data has grown to almost 1000 datasets containing almost 82 billion triples<sup>3</sup>. Data is being published by both public and private sectors and covers a diverse set of domains from life sciences to military.

The Linked Open Data is a gold mine for organizations and individuals who are trying to leverage external data sources in order to produce more informed business decisions [11]. This success lies in the cooperation between data publishers and consumers. Users are empowered to find, share and combine information in their applications easily. However, the heterogeneous nature of data sources reflects directly on the data quality as these sources often contain inconsistent as well as misinterpreted and incomplete information and meta information. Accompanied with the significant variation of size, used languages and freshness, finding useful datasets without prior knowledge is increasingly complicated. This

---

<sup>3</sup> <http://datahub.io/dataset?tags=lod>

can be clearly noticed in the LOD Cloud <sup>4</sup> as few datasets like DBPedia[6], Freebase[10] and YAGO[34] are favored over hidden gems that may include domain specific knowledge more suitable for the tasks on hand.

The main entry point for discovering and identifying needed datasets is through public Data Portals like DataHub<sup>5</sup> and Europe’s Public Data<sup>6</sup> or private ones like Quandl<sup>7</sup> and Engima<sup>8</sup>. Private portals harness manually curated data from various sources and expose them to users either freely or through paid plans. The data available is of higher quality but lesser quantity compared to what is available in public portals. Similarly in some public Data Portals, administrators manually review datasets information and attach suitable meta information. This information is mainly in form of predefined tags such as *media*, *geography*, *life sciences*, etc. for organization and clustering purposes. The increasing number of available datasets makes the review and curation process unsustainable even when outsourced to communities. Furthermore, the diversity of those datasets makes it hard to classify them with a fixed number of predefined tags that can be subjectively assigned without capturing the essence and breadth of the dataset[29].

*Data profiling* is the process of creating descriptive dataset metadata. It is a cardinal activity when facing an unfamiliar dataset[31]. It helps in assessing the importance of the dataset, improve users’ ability to search and reuse part of the dataset and detect irregularities to improve its quality. Data profiling includes several tasks:

- **Metadata profiling:** Provide several information about the dataset. This can include general information (dataset description, release and update dates, etc.), legal information (license information, openness, etc.), practical information (access points, data dumps, etc.) and so on.
- **Statistical profiling:** Provides statistical information about data types and patterns in the dataset. i.e. properties distribution, number of entities and RDF triples, etc.
- **Topical profiling:** Provides descriptive and reliable knowledge on the dataset’s content and structure. This can be in form of tags and categories used to facilitate search and reuse of existing datasets.

In this work, we address the above mentioned challenges of automatic assessment and generation of descriptive datasets profiles. This paper proposes an extensible framework consisting of a processing pipeline that combines techniques for Data Portals identification, datasets crawling and a set of pluggable modules combining several profiling tasks. The framework assesses the provided dataset metadata against an aggregated standard set of information. Metadata fields are automatically corrected when possible i.e. missing license link. Moreover, a report is created with issues that cannot be automatically fixed and is

<sup>4</sup> <http://lod-cloud.net>

<sup>5</sup> <http://datahub.io>

<sup>6</sup> <http://publicdata.eu>

<sup>7</sup> <https://quandl.com/>

<sup>8</sup> <http://enigma.io/>

sent to the dataset’s maintainer via e-mail. There exist various statistical and topical profiling tools for both relational and Linked Data. The architecture of the framework allows to easily add several profiling tasks. For this paper, we will focus on Linked Data profiling tools as we will present our findings on the overall state of Linked Data in some of the prominent Data Portals.

The remainder of the paper is structured as follows. Section 2 reviews related literature. Section 3 describes the framework’s architecture to assess and generate dataset profiles. Section 4 shows the results of running this tool on some of the most prominent Data Portals and their discussion. Finally, Section 5 presents the conclusion and future work.

## 2 Related Work

There exist a considerable amount of tools that tackle specific profiling tasks. However, to the best of our knowledge this is the first effort towards extensible automatic assessment and generation of descriptive dataset profiles. For this paper, we will focus on Linked Data profiling tasks. However, one of the advantages of this framework is the ability to easily configure additional profiling tasks accommodating different data types i.e. relational.

Data Catalog Vocabulary (DCAT)[19] and the Vocabulary of Interlinked Datasets (VoID)[15] are concerned with metadata about RDF datasets. Quality Assessment of Data Sources (Flemming’s Data Quality Assessment Tool)<sup>9</sup> provides basic metadata assessment as it calculates data quality scores based on manual user input. The user should assign weights to the predefined quality metrics and answer a series of questions regarding the dataset. These include, for example, the use of obsolete classes and properties by defining the number of described entities that are assigned disjoint classes, the usage of stable URIs and whether the publisher provides a mailing list for the dataset. The ODI certificate<sup>10</sup> provides a description of the published data quality in plain English. It aspires to act as a mark of approval that helps publishers understand how to publish good open data and users how to use it. It gives publishers the ability to provide assurance and support on their data while encouraging further improvements through an ascending scale. ODI comes as an online and free questionnaire for data publishers focusing on certain characteristics about their data. In [8] authors generate VoID descriptions limited to a subset of properties that can be automatically deduced from resources within the dataset. However, it still provides data consumers with interesting insights.

Calculating datasets statistical information is vital to applications dealing with query optimization and answering, data cleansing, schema induction and data mining[25][21][29]. Semantic sitemaps[14] and RDFStats[30] where one of the first to deal with RDF data statistics and summaries. ExpLOD[26] creates statistics on the interlinking between datasets based on `owl:sameAs` links. In [31] the author introduces a tool that induces the actual schema of the data

<sup>9</sup> <http://linkeddata.informatik.hu-berlin.de/LDSrcAss/datenquelle.php>

<sup>10</sup> <https://certificates.theodi.org/>

and gather corresponding statistics accordingly. LODStats [3] is a stream-based approach that calculates more general dataset statistics. ProLOD++[1] is a Web-based tool that allows LOD analysis via automatically computed hierarchical clustering[9]. Aether[32] generates VoID statistical descriptions of RDF datasets. It also provides a Web interface to view and compare VoID descriptions. LODOP[4] is a MapReduce framework to compute, optimize and benchmark dataset profiles. The main target for this framework is to optimize the runtime costs for Linked Data profiling. In [28] authors calculate certain statistical information for the purpose of observing the dynamic changes in datasets.

Topical and categorical information facilitates dataset search and reuse. Topical profiling focuses on content-wise analysis at the instances and ontological levels. GERBIL [36] is a general entity annotation framework that provides machine processable output allowing efficient querying. In addition, there exist several entity annotation tools and frameworks [13] but none of those systems are designed specifically for dataset annotation. In [23] authors created a semantic portal to manually annotate and publish metadata about both LOD and non-RDF datasets. In [29] authors automatically assigned Freebase domains to extracted instance labels of some of the LOD Cloud datasets. The goal was provide automatic domain identification, thus enabling improving datasets clustering and categorization. In [7] the authors extracted dataset topics by exploiting the graph structure and ontological information, thus removing the dependency on textual labels. In [20] authors generate VoID and VoL<sup>11</sup> descriptions via a processing pipeline that extracts dataset topic models ranked on graphical models of selected DBpedia categories.

Semantic search engines like Sindice[17], Swoogle[18] and Watson[16] help in entities lookup but are not designed specifically for dataset search. In [33], authors utilized the sig.ma index[35] to identify appropriate data sources for interlinking.

There exist several approaches to create LOD indexes. In [2] authors used VoID descriptions to optimize query processing by determining relevant queryable datasets. In [24] authors created an approximate index structure (QTree) and an algorithm for answering conjunctive queries over Linked Data. SchemEX[27] is a stream-based approach leveraging type and property information of RDF instances to create schema-level indexes.

## References

1. Z. Abedjan, T. Gruetze, A. Jentzsch, and F. Naumann. Profiling and mining rdf data with proloD++. In *Data Engineering (ICDE), 2014 IEEE 30th International Conference on*, pages 1198–1201, March 2014.
2. K. Alexander, R. Cyganiak, M. Hausenblas, and J. Zhao. Describing linked datasets - on the design and usage of void, the 'vocabulary of interlinked datasets'. In *WWW 2009 Workshop: Linked Data on the Web (LDOW2009)*, Madrid, Spain.

<sup>11</sup> <http://data.linkededucation.org/vol>

3. S. Auer, J. Demter, M. Martin, and J. Lehmann. Lodstats — an extensible framework for high-performance dataset analytics. In *Proceedings of the 18th International Conference on Knowledge Engineering and Knowledge Management, EKAW'12*, pages 353–362, 2012.
4. A. J. Benedikt Forchhammer and F. Naumann. Lodop - multi-query optimization for linked data profiling queries. In *In Proceedings of the International Workshop on Dataset PROFiling and fEderated Search for Linked Data (PROFILES) in conjunction with ESWC.*, Heraklion, Greece, 0 2014.
5. C. Bizer, T. Heath, and T. Berners-Lee. Linked Data - The Story So Far. *International Journal on Semantic Web and Information Systems*, 5(3):1–22, 2009.
6. C. Bizer, J. Lehmann, G. Kobilarov, S. Auer, C. Becker, R. Cyganiak, and S. Hellmann. Dbpedia - a crystallization point for the web of data. *Web Semant.*, 7(3):154–165, Sept. 2009.
7. C. Böhm, G. Kasneci, and F. Naumann. Latent topics in graph-structured data. In *Proceedings of the 21st ACM International Conference on Information and Knowledge Management, CIKM '12*, pages 2663–2666, 2012.
8. C. Böhm, J. Lorey, and F. Naumann. Creating void descriptions for web-scale data. *Web Semant.*, 9(3):339–345, Sept. 2011.
9. C. Böhm, F. Naumann, Z. Abedjan, D. Fenz, T. Grutze, D. Hefenbrock, M. Pohl, and D. Sonnabend. Profiling linked open data with prolod. In *Data Engineering Workshops (ICDEW), 2010 IEEE 26th International Conference on*, pages 175–178, March 2010.
10. K. Bollacker, C. Evans, P. Paritosh, T. Sturge, and J. Taylor. Freebase: A collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD International Conference on Management of Data, SIGMOD '08*, pages 1247–1250, 2008.
11. D. Boyd and K. Crawford. Six provocations for big data. *A Decade in Internet Time: Symposium on the Dynamics of the Internet and Society*, pages 1–17, 2011.
12. M. Brümmer, C. Baron, I. Ermilov, M. Freudenberg, D. Kontokostas, and S. Hellmann. DataID: Towards semantically rich metadata for complex datasets. In *Proceedings of the 10th International Conference on Semantic Systems*, 2014.
13. M. Cornolti, P. Ferragina, and M. Ciaramita. A framework for benchmarking entity-annotation systems. In *Proceedings of the 22Nd International Conference on World Wide Web, WWW '13*, pages 249–260, 2013.
14. R. Cyganiak, H. Stenzhorn, R. Delbru, S. Decker, and G. Tummarello. Semantic sitemaps: Efficient and flexible access to datasets on the semantic web. In *Proceedings of the 5th European Semantic Web Conference on The Semantic Web: Research and Applications, ESWC'08*, pages 690–704, 2008.
15. R. Cyganiak, J. Zhao, M. Hausenblas, and K. Alexander. Describing linked datasets with the VoID vocabulary. W3C note, W3C, Mar. 2011. <http://www.w3.org/TR/2011/NOTE-void-20110303/>.
16. M. d'Aquin and E. Motta. Watson, more than a semantic web search engine. *Semant. web*, 2(1), Jan. 2011.
17. R. Delbru, N. Toupikov, and M. Catasta. Hierarchical link analysis for ranking web data. *The Semantic Web: Research and Applications*, 2010.
18. L. Ding, T. Finin, A. Joshi, R. Pan, and R. Cost. Swoogle: A semantic web search and metadata engine. *CIKM04*, 2004.
19. J. Erickson and F. Maali. Data catalog vocabulary (DCAT). W3C recommendation, W3C, Jan. 2014. <http://www.w3.org/TR/2014/REC-vocab-dcat-20140116/>.

20. B. Fetahu, S. Dietze, B. Pereira Nunes, M. Antonio Casanova, D. Taibi, and W. Nejdl. A scalable approach for efficiently generating structured dataset topic profiles. In *The Semantic Web: Trends and Challenges*, volume 8465 of *Lecture Notes in Computer Science*. Springer International Publishing, 2014.
21. M. Frosterus, E. Hyvönen, and J. Laitio. Creating and publishing semantic meta-data about linked and open datasets. In D. Wood, editor, *Linking Government Data*, pages 95–112. Springer New York, 2011.
22. M. Frosterus, E. Hyvönen, and J. Laitio. Datafinland - a semantic portal for open and linked datasets. In *ESWC (2)'11*, pages 243–254, 2011.
23. M. Frosterus, E. Hyvönen, and J. Laitio. Datafinland—a semantic portal for open and linked datasets. In *The Semantic Web: Research and Applications*, volume 6644 of *Lecture Notes in Computer Science*, pages 243–254. Springer Berlin Heidelberg, 2011.
24. A. Harth, K. Hose, M. Karnstedt, A. Polleres, K.-U. Sattler, and J. Umbrich. Data summaries for on-demand queries over linked data. In *Proceedings of the 19th International Conference on World Wide Web, WWW '10*, pages 411–420, 2010.
25. A. Jentzsch. Profiling the web of data. In *The 2014 International Semantic Web Conference, Doctoral Consortium*, 2014.
26. S. Khatchadourian and M. P. Consens. Explod: Summary-based exploration of interlinking and rdf usage in the linked open data cloud. In *Proceedings of the 7th International Conference on The Semantic Web: Research and Applications - Volume Part II, ESWC'10*, pages 272–287, 2010.
27. M. Konrath, T. Gottron, S. Staab, and A. Scherp. Schemex - efficient construction of a data catalogue by stream-based indexing of linked data. *Web Semant.*, 16:52–58, Nov. 2012.
28. T. Käfer, A. Abdelrahman, J. Umbrich, P. O'Byrne, and A. Hogan. Observing linked data dynamics. In *The Semantic Web: Semantics and Big Data*, volume 7882 of *Lecture Notes in Computer Science*, pages 213–227. 2013.
29. S. Lalithsena, P. Hitzler, A. Sheth, and P. Jain. Automatic domain identification for linked open data. In *Web Intelligence (WI) and Intelligent Agent Technologies (IAT), 2013 IEEE/WIC/ACM International Joint Conferences on*, volume 1, pages 205–212, Nov 2013.
30. A. Langegger and W. Woss. Rdfstats - an extensible rdf statistics generator and library. In *Proceedings of the 2009 20th International Workshop on Database and Expert Systems Application, DEXA '09*, pages 79–83, 2009.
31. H. Li. Data profiling for semantic web data. In F. Wang, J. Lei, Z. Gong, and X. Luo, editors, *Web Information Systems and Mining*, volume 7529 of *Lecture Notes in Computer Science*, pages 472–479. Springer Berlin Heidelberg, 2012.
32. E. Mäkelä. Aether – generating and viewing extended void statistical descriptions of rdf datasets. In *Proceedings of the ESWC 2014 demo track, Springer-Verlag*, 2014.
33. A. Nikolov, M. d'Aquin, and E. Motta. What should i link to? identifying relevant sources and classes for data linking. In *The Semantic Web*, volume 7185 of *Lecture Notes in Computer Science*. Springer Berlin Heidelberg, 2012.
34. F. M. Suchanek, G. Kasneci, and G. Weikum. Yago: A core of semantic knowledge. In *Proceedings of the 16th International Conference on World Wide Web, WWW '07*, pages 697–706, 2007.
35. G. Tummarello, S. Danielczyk, R. Cyganiak, R. Delbru, M. Catasta, E. P. Federale, and S. Decker. Sig.ma: Live views on the web of data. In *In Proc. WWW-2010*, pages 1301–1304. ACM Press, 2010.

36. R. Usbeck, M. Röder, A.-C. Ngonga-Ngomo, C. Baron, A. Both, M. Brümmer, D. Ceccarelli, M. Cornolti, D. Cherix, B. Eickmann, P. Ferragina, C. Lemke, A. Moro, R. Navigli, F. Piccinno, G. Rizzo, H. Sack, R. Speck, R. Troncy, J. Waitelonis, and L. Wesemann. GERBIL – general entity annotation benchmark framework. In *Submitted to the 24th WWW conference*, 2015.