Order file

The order file sends Capacity the orders you want shipped. Each line is one order line, with the order details repeated on every line of the order.

Direction	You to Capacity
Folder	`IN` in your folder on `ftp01.capacityllc.com`
When	Every 5 minutes from 00:48 to 23:18, Sunday to Friday; every 10 minutes on Saturday, US Eastern
After processing	Capacity moves the file to an archive and adds a batch number to the front of its name

The flat file rules apply to every layout on this page.

Required rules

- **Header row, then one line per order line.** Capacity reads columns by position, so every line has every column of your layout, in order, even when a value is empty.
- **`EndOfLine` is always `EOL`.** It is the last column of versions 3.0, 4.0 and 4.1.
- **One `PickTicketID` per order.** All lines of an order share the same `PickTicketID`, and the order-level columns (ship-to, ship method, dates and amounts) must be identical on every line of the order.
- **Unique order numbers.** Use a new `PickTicketID` for every order. If Capacity receives a `PickTicketID` it already has, it holds the new order as a duplicate for review.
- **Your owner code.** `ClientCode` must be your two-character owner code on every line. A file with another owner code is rejected.
- **A ship-to name.** Send `ShipBusinessName`, `ShipName` or both. Release lines take the name from the EDI purchase order.
- **Known SKUs.** Every `ItemProductID` must already exist in Capacity, as a Capacity SKU or an alternate SKU. Send new products first.
- **Whole-number quantities.** Quantities are whole numbers of units, digits only, with no thousands separator.
- **Dates.** Use `MM/DD/YYYY`, US Eastern. `YYYY-MM-DD` is also accepted.

Ship methods

`ShipMethod` must match one of the ship methods set up for your account, character for character. Capacity gives you the list during onboarding and adds methods on request. Email itedi@capacityllc.com to ask for a new one.

An order with an empty or unknown `ShipMethod` is still imported. Capacity holds it until the ship method is corrected, then releases it to the warehouse. Send a ship method from your list to avoid the delay.

The ship confirmation reports the carrier service actually used, under Capacity's own service name. See the ship confirmation file.

Quantities

- `ItemOrderQuantity` is the quantity your customer ordered.
- `ItemShipQuantity` is the quantity to ship. Leave it empty to ship the ordered quantity.
- When you send `ItemShipQuantity`, Capacity ships that quantity, even when it is lower than the ordered quantity. A value of `0` creates a line with nothing to ship.

Releasing an EDI purchase order

Some retailers send their purchase orders to Capacity by EDI (an X12 850) on your behalf. Capacity holds each of these orders until you release it, so that you decide what ships and when.

To release one, add a line to an order file for each product to ship:

1. Set `ReleaseFlag` to `Y`.
2. Set `CapacityImportID` to Capacity's import number for the EDI order. Capacity gives you this number.
3. Repeat the `PONumber`, `RetailerCode` and `StoreNumber` of the EDI order.
4. Give the order your own `PickTicketID`, and set `ClientCode`, `ItemProductID`, `ItemOrderQuantity` and `ItemShipQuantity`.
5. Leave the ship-to columns and `ShipMethod` empty. Capacity uses the address and routing of the EDI order.

The third line of each sample file below is a release line.

If an order cannot be imported

Each order in a file is imported on its own. If Capacity asks you to resend an order, send only that order in a new file, not the whole file again.

Versions

VERSION	COLUMNS	DELIMITER	QUOTING
4.1	67	Tab	Optional
4.0	67, the same as 4.1	Tab	Optional
3.0	61: version 4.1 without `ItemProductDesc`, the cash-on-delivery columns and `SaturdayDelivery`	Tab	Not supported
Comma-delimited	19	Comma	Optional

New clients use version 4.1. The other versions are kept for existing clients. Versions 4.1 and 4.0 and the comma-delimited layout accept values wrapped in double quotes. In version 3.0, a double quote is read as part of the value.

The comma-delimited layout has no owner code column: Capacity takes your owner code from your account. It also uses the date the file is processed as the order date.

Layout

File name	`Any unique name, for example orders-20261110-153000.txt`
Delimiter	Tab
Header row	Yes, first line, with the column names below in this order

Columns	67
Quoting	Optional. A value may be wrapped in double quotes; a quote inside it is written twice ("").

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
1	`PickTicketID`	Char	50	Yes	Your order number. It identifies the order in Capacity and comes back in the ship confirmation. Use a new value for every order; every line of the order repeats it.
2	`MasterOrderID`	Char	50	No	Your master or parent order number, if you split one customer order into several. Returned in the ship confirmation.
3	`ReleaseFlag`	Char `Y/N`	1	No	Y to release an EDI purchase order that Capacity is holding for you. N or empty for a new order.
4	`Reship850Flag`	Char `Y/N`	1	No	Reserved for EDI purchase order releases. Send N or leave empty unless Capacity tells you otherwise.
5	`OrderType`	Char	10	No	Your order type code, as set up with Capacity. Empty or unknown values are imported as a regular order.
6	`SpecialProcessingFlag`	Char `Y/N`	1	No	Y when the order needs the special handling agreed with Capacity during onboarding.
7	`CapacityImportID`	Integer	20	Conditional	Release lines only: Capacity's import number of the EDI purchase order you are releasing. Capacity gives you this number. Empty on new orders.
8	`PONumber`	Char	50	No	Customer purchase order number. When empty, Capacity uses PickTicketID. On release lines, the purchase order number of the EDI order.
9	`RetailerCode`	Char	3	No	Retailer code agreed with Capacity, for example WEB for your own web store. Empty or unknown codes are treated as WEB. On release lines, the retailer of the EDI order.
10	`StoreNumber`	Char	50	No	Customer store number. On release lines, the store of the EDI order.
11	`ShipToLocation`	Char	50	No	Retailer store or distribution center code. When ShipCity, ShipState and ShipZip are all empty, Capacity takes the address from the retailer location with this code.
12	`ClientCode`	Char	2	Yes	Your two-character owner code, for example ZZ. It must match your account; a file with another owner code is rejected.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
13	`DropshipID`	Integer	5	No	Reserved. Leave empty.
14	`ExternalCustomerID`	Char	50	No	Your customer number for the buyer.
15	`ShipBusinessName`	Char	128	Conditional	Ship-to company name. Send ShipBusinessName, ShipName or both: at least one is required. Not needed on release lines, which use the address on the EDI purchase order.
16	`ShipName`	Char	128	Conditional	Ship-to person or attention name. Required when ShipBusinessName is empty. Not needed on release lines, which use the address on the EDI purchase order.
17	`ShipAddress1`	Char	128	Conditional	First ship-to address line. Required unless ShipToLocation supplies the address. Carriers print 30 to 35 characters, so keep it short. Not needed on release lines, which use the address on the EDI purchase order.
18	`ShipAddress2`	Char	128	No	Second ship-to address line.
19	`ShipCity`	Char	128	Conditional	Ship-to city. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.
20	`ShipState`	Char	50	Conditional	Ship-to state or province. Use the 2-character code; for the US, Canada and Australia the full name is also accepted. Required unless ShipToLocation supplies the address. An unrecognised state holds the order for review. Not needed on release lines, which use the address on the EDI purchase order.
21	`ShipZip`	Char	20	Conditional	Ship-to ZIP or postal code, for example 08817 or 08817-1234. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.
22	`ShipCountry`	Char	50	No	Ship-to country: ISO 2-character code (for example US) or country name. When empty, Capacity derives the country from ShipState.
23	`ShipPhone`	Char	50	No	Ship-to phone number. Recommended for international shipments.
24	`ShipEmail`	Char	50	No	Ship-to email address, used for carrier delivery notices.
25	`ShipResidentialFlag`	Char `Y/N`	1	No	Y for a residential address, N or empty for a business address. A ship method that is residential-only or commercial-only overrides this flag.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
26	`ShipMethod`	Char	100	Conditional	Carrier service, exactly as it appears in the list of ship methods Capacity sets up for your account. Required on new orders; not used on release lines. An empty or unknown value holds the order until Capacity corrects the ship method.
27	`ThirdPartyAccount`	Char	50	No	Carrier account to bill for shipping (third-party billing). The account must be set up with Capacity first.
28	`SignatureRequired`	Char `Y/N`	1	No	Y when the carrier must collect a signature on delivery.
29	`ShipComment`	Char	1000	No	Shipping or packing instructions. Line breaks are removed.
30	`GiftWrapFlag`	Char `Y/N`	1	No	Y to mark the order as a gift.
31	`GiftFrom`	Char	50	No	Gift sender name, printed on the gift message.
32	`GiftTo`	Char	50	No	Gift recipient name, printed on the gift message.
33	`GiftMessage`	Char	1000	No	Gift message text.
34	`BillBusinessName`	Char	128	No	Bill-to company name.
35	`BillName`	Char	128	No	Bill-to person name.
36	`BillAddress1`	Char	128	No	First bill-to address line.
37	`BillAddress2`	Char	128	No	Second bill-to address line.
38	`BillCity`	Char	50	No	Bill-to city.
39	`BillState`	Char	50	No	Bill-to state or province: 2-character code or name.
40	`BillZip`	Char	20	No	Bill-to ZIP or postal code.
41	`BillCountry`	Char	50	No	Bill-to country: ISO 2-character code or country name.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
42	`BillPhone`	Char	50	No	Bill-to phone number.
43	`PaymentTerms`	Char	50	No	Payment terms, printed on the packing slip where your packing slip shows them.
44	`OrderDate`	Date `MM/DD/YYYY`	10	No	Date the customer placed the order. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
45	`RequestedShipDate`	Date `MM/DD/YYYY`	10	No	Do not ship before this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
46	`CancelDate`	Date `MM/DD/YYYY`	10	No	Ship no later than this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
47	`RequestedDeliveryDate`	Date `MM/DD/YYYY`	10	No	Date the customer asked for delivery. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
48	`DeliveryByDate`	Date `MM/DD/YYYY`	10	No	Do not deliver after this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
49	`ShippingAmount`	Decimal `Decimal(9,2)`	12	No	Shipping and handling you charged your customer. Returned as TotalChargeAmount in the ship confirmation.
50	`ShippingTaxRate`	Decimal `Decimal(5,2)`	6	No	Tax rate on shipping, as a percentage from 0.00 to 100.00.
51	`OrderDiscountRate`	Decimal `Decimal(5,2)`	6	No	Order discount, as a percentage from 0.00 to 100.00.
52	`OrderDiscountAmount`	Decimal `Decimal(9,2)`	12	No	Order discount, as an amount.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
53	`ItemLineNumber`	Integer	10	No	Your line number. For your reference; the ship confirmation reports Capacity's own line numbers.
54	`ItemProductID`	Char	28	Yes	The Capacity SKU or its alternate SKU. It must already exist in Capacity; an unknown SKU holds the order for review.
55	`ItemUnitAmount`	Decimal `Decimal(9,2)`	12	No	Unit price charged to your customer. Used for packing slips and order totals.
56	`ItemDiscountRate`	Decimal `Decimal(5,2)`	6	No	Line discount, as a percentage from 0.00 to 100.00.
57	`ItemTaxRate`	Decimal `Decimal(5,2)`	6	No	Line tax rate, as a percentage from 0.00 to 100.00.
58	`ItemOrderQuantity`	Integer	10	Yes	Quantity ordered, in units. A whole number of 0 or more, digits only.
59	`ItemShipQuantity`	Integer	10	No	Quantity to ship, in units. Leave empty to ship ItemOrderQuantity. When you send a value, Capacity ships that quantity, so 0 creates a line with nothing to ship. On release lines, the quantity to release.
60	`BuyerItemNumber`	Char	50	No	Your customer's item number for the product.
61	`ItemProductDesc`	Char	50	No	Product description for the packing slip.
62	`CODFlag`	Char `Y/N`	1	No	Y for a cash-on-delivery shipment.
63	`CODAmount`	Decimal `Decimal(9,2)`	12	Conditional	Amount the carrier collects. Required, and greater than 0, when CODFlag is Y.
64	`CODAddShipCharges`	Char `Y/N`	1	No	Y to add the shipping charges to the collected amount.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
65	`CODCashierCheck`	Char `Y/N`	1	No	Y when the carrier must collect a cashier's check or money order only.
66	`SaturdayDelivery`	Char `Y/N`	1	No	Y to request Saturday delivery, where the carrier service offers it.
67	`EndOfLine`	Char	3	Yes	Always the text EOL. Marks the end of the line. • `EOL` End of line

OrderFile-4.1-sample.txt

```
PickTicketID→MasterOrderID→ReleaseFlag→Reship850Flag→OrderType→SpecialProcessingFlag→CapacityImportID→PONumber→RetailerCode→StoreNumber→ShipToLocation→ClientCode→DropshipID→ExternalCustomerID→ShipBusinessName→ShipName→ShipAddress1→ShipAddress2→ShipCity→ShipState→ShipZip→ShipCountry→ShipPhone→ShipEmail→ShipResidentialFlag→ShipMethod→ThirdPartyAccount→SignatureRequired→ShipComment→GiftWrapFlag→GiftFrom→GiftTo→GiftMessage→BillBusinessName→BillName→BillAddress1→BillAddress2→BillCity→BillState→BillZip→BillCountry→BillPhone→PaymentTerms→OrderDate→RequestedShipDate→CancelDate→RequestedDeliveryDate→DeliveryByDate→ShippingAmount→ShippingTaxRate→OrderDiscountRate→OrderDiscountAmount→ItemLineNumber→ItemProductID→ItemUnitAmount→ItemDiscountRate→ItemTaxRate→ItemOrderQuantity→ItemShipQuantity→BuyerItemNumber→ItemProductDesc→CODFlag→CODAmount→CODAddShipCharges→CODCashierCheck→SaturdayDelivery→EndOfLine
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→1→SKU-EXAMPLE-1→20.00→→6.63→2→→→Example face cream 50 ml→N→→N→N→N→EOL
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→2→SKU-EXAMPLE-2→12.50→→6.63→1→→→Example lip balm→N→→N→N→N→EOL
PT-0001002→→Y→N→→N→50954801→PO-0001002→RTL→0001→→ZZ→→→→→
```

This version is kept for clients that already use it. New clients use version 4.1.

File name	`Any unique name, for example orders-20261110-153000.txt`
Delimiter	Tab
Header row	Yes, first line, with the column names below in this order
Columns	67
Quoting	Optional. A value may be wrapped in double quotes; a quote inside it is written twice ("").

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
1	`PickTicketID`	Char	50	Yes	Your order number. It identifies the order in Capacity and comes back in the ship confirmation. Use a new value for every order; every line of the order repeats it.
2	`MasterOrderID`	Char	50	No	Your master or parent order number, if you split one customer order into several. Returned in the ship confirmation.
3	`ReleaseFlag`	Char `Y/N`	1	No	Y to release an EDI purchase order that Capacity is holding for you. N or empty for a new order.
4	`Reship850Flag`	Char `Y/N`	1	No	Reserved for EDI purchase order releases. Send N or leave empty unless Capacity tells you otherwise.
5	`OrderType`	Char	10	No	Your order type code, as set up with Capacity. Empty or unknown values are imported as a regular order.
6	`SpecialProcessingFlag`	Char `Y/N`	1	No	Y when the order needs the special handling agreed with Capacity during onboarding.
7	`CapacityImportID`	Integer	20	Conditional	Release lines only: Capacity's import number of the EDI purchase order you are releasing. Capacity gives you this number. Empty on new orders.
8	`PONumber`	Char	50	No	Customer purchase order number. When empty, Capacity uses PickTicketID. On release lines, the purchase order number of the EDI order.
9	`RetailerCode`	Char	3	No	Retailer code agreed with Capacity, for example WEB for your own web store. Empty or unknown codes are treated as WEB. On release lines, the retailer of the EDI order.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
10	`StoreNumber`	Char	50	No	Customer store number. On release lines, the store of the EDI order.
11	`ShipToLocation`	Char	50	No	Retailer store or distribution center code. When ShipCity, ShipState and ShipZip are all empty, Capacity takes the address from the retailer location with this code.
12	`ClientCode`	Char	2	Yes	Your two-character owner code, for example ZZ. It must match your account; a file with another owner code is rejected.
13	`DropshipID`	Integer	5	No	Reserved. Leave empty.
14	`ExternalCustomerID`	Char	50	No	Your customer number for the buyer.
15	`ShipBusinessName`	Char	128	Conditional	Ship-to company name. Send ShipBusinessName, ShipName or both: at least one is required. Not needed on release lines, which use the address on the EDI purchase order.
16	`ShipName`	Char	128	Conditional	Ship-to person or attention name. Required when ShipBusinessName is empty. Not needed on release lines, which use the address on the EDI purchase order.
17	`ShipAddress1`	Char	128	Conditional	First ship-to address line. Required unless ShipToLocation supplies the address. Carriers print 30 to 35 characters, so keep it short. Not needed on release lines, which use the address on the EDI purchase order.
18	`ShipAddress2`	Char	128	No	Second ship-to address line.
19	`ShipCity`	Char	128	Conditional	Ship-to city. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.
20	`ShipState`	Char	50	Conditional	Ship-to state or province. Use the 2-character code; for the US, Canada and Australia the full name is also accepted. Required unless ShipToLocation supplies the address. An unrecognised state holds the order for review. Not needed on release lines, which use the address on the EDI purchase order.
21	`ShipZip`	Char	20	Conditional	Ship-to ZIP or postal code, for example 08817 or 08817-1234. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.
22	`ShipCountry`	Char	50	No	Ship-to country: ISO 2-character code (for example US) or country name. When empty, Capacity derives the country from ShipState.
23	`ShipPhone`	Char	50	No	Ship-to phone number. Recommended for international shipments.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
24	`ShipEmail`	Char	50	No	Ship-to email address, used for carrier delivery notices.
25	`ShipResidentialFlag`	Char `Y/N`	1	No	Y for a residential address, N or empty for a business address. A ship method that is residential-only or commercial-only overrides this flag.
26	`ShipMethod`	Char	100	Conditional	Carrier service, exactly as it appears in the list of ship methods Capacity sets up for your account. Required on new orders; not used on release lines. An empty or unknown value holds the order until Capacity corrects the ship method.
27	`ThirdPartyAccount`	Char	50	No	Carrier account to bill for shipping (third-party billing). The account must be set up with Capacity first.
28	`SignatureRequired`	Char `Y/N`	1	No	Y when the carrier must collect a signature on delivery.
29	`ShipComment`	Char	1000	No	Shipping or packing instructions. Line breaks are removed.
30	`GiftWrapFlag`	Char `Y/N`	1	No	Y to mark the order as a gift.
31	`GiftFrom`	Char	50	No	Gift sender name, printed on the gift message.
32	`GiftTo`	Char	50	No	Gift recipient name, printed on the gift message.
33	`GiftMessage`	Char	1000	No	Gift message text.
34	`BillBusinessName`	Char	128	No	Bill-to company name.
35	`BillName`	Char	128	No	Bill-to person name.
36	`BillAddress1`	Char	128	No	First bill-to address line.
37	`BillAddress2`	Char	128	No	Second bill-to address line.
38	`BillCity`	Char	50	No	Bill-to city.
39	`BillState`	Char	50	No	Bill-to state or province: 2-character code or name.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
40	`BillZip`	Char	20	No	Bill-to ZIP or postal code.
41	`BillCountry`	Char	50	No	Bill-to country: ISO 2-character code or country name.
42	`BillPhone`	Char	50	No	Bill-to phone number.
43	`PaymentTerms`	Char	50	No	Payment terms, printed on the packing slip where your packing slip shows them.
44	`OrderDate`	Date `MM/DD/YYYY`	10	No	Date the customer placed the order. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
45	`RequestedShipDate`	Date `MM/DD/YYYY`	10	No	Do not ship before this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
46	`CancelDate`	Date `MM/DD/YYYY`	10	No	Ship no later than this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
47	`RequestedDeliveryDate`	Date `MM/DD/YYYY`	10	No	Date the customer asked for delivery. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
48	`DeliveryByDate`	Date `MM/DD/YYYY`	10	No	Do not deliver after this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
49	`ShippingAmount`	Decimal `Decimal(9,2)`	12	No	Shipping and handling you charged your customer. Returned as TotalChargeAmount in the ship confirmation.
50	`ShippingTaxRate`	Decimal `Decimal(5,2)`	6	No	Tax rate on shipping, as a percentage from 0.00 to 100.00.
51	`OrderDiscountRate`	Decimal `Decimal(5,2)`	6	No	Order discount, as a percentage from 0.00 to 100.00.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
52	`OrderDiscountAmount`	Decimal `Decimal(9,2)`	12	No	Order discount, as an amount.
53	`ItemLineNumber`	Integer	10	No	Your line number. For your reference; the ship confirmation reports Capacity's own line numbers.
54	`ItemProductID`	Char	28	Yes	The Capacity SKU or its alternate SKU. It must already exist in Capacity; an unknown SKU holds the order for review.
55	`ItemUnitAmount`	Decimal `Decimal(9,2)`	12	No	Unit price charged to your customer. Used for packing slips and order totals.
56	`ItemDiscountRate`	Decimal `Decimal(5,2)`	6	No	Line discount, as a percentage from 0.00 to 100.00.
57	`ItemTaxRate`	Decimal `Decimal(5,2)`	6	No	Line tax rate, as a percentage from 0.00 to 100.00.
58	`ItemOrderQuantity`	Integer	10	Yes	Quantity ordered, in units. A whole number of 0 or more, digits only.
59	`ItemShipQuantity`	Integer	10	No	Quantity to ship, in units. Leave empty to ship ItemOrderQuantity. When you send a value, Capacity ships that quantity, so 0 creates a line with nothing to ship. On release lines, the quantity to release.
60	`BuyerItemNumber`	Char	50	No	Your customer's item number for the product.
61	`ItemProductDesc`	Char	50	No	Product description for the packing slip.
62	`CODFlag`	Char `Y/N`	1	No	Y for a cash-on-delivery shipment.
63	`CODAmount`	Decimal `Decimal(9,2)`	12	Conditional	Amount the carrier collects. Required, and greater than 0, when CODFlag is Y.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
64	`CODAddShipCharges`	Char `Y/N`	1	No	Y to add the shipping charges to the collected amount.
65	`CODCashierCheck`	Char `Y/N`	1	No	Y when the carrier must collect a cashier's check or money order only.
66	`SaturdayDelivery`	Char `Y/N`	1	No	Y to request Saturday delivery, where the carrier service offers it.
67	`EndOfLine`	Char	3	Yes	Always the text EOL. Marks the end of the line. • `EOL` End of line

OrderFile-4.0-sample.txt

```
PickTicketID→MasterOrderID→ReleaseFlag→Reship850Flag→OrderType→SpecialProcessingFlag→CapacityImportID→PONumber→RetailerCode→StoreNumber→ShipToLocation→ClientCode→DropshipID→ExternalCustomerID→ShipBusinessName→ShipName→ShipAddress1→ShipAddress2→ShipCity→ShipState→ShipZip→ShipCountry→ShipPhone→ShipEmail→ShipResidentialFlag→ShipMethod→ThirdPartyAccount→SignatureRequired→ShipComment→GiftWrapFlag→GiftFrom→GiftTo→GiftMessage→BillBusinessName→BillName→BillAddress1→BillAddress2→BillCity→BillState→BillZip→BillCountry→BillPhone→PaymentTerms→OrderDate→RequestedShipDate→CancelDate→RequestedDeliveryDate→DeliveryByDate→ShippingAmount→ShippingTaxRate→OrderDiscountRate→OrderDiscountAmount→ItemLineNumber→ItemProductID→ItemUnitAmount→ItemDiscountRate→ItemTaxRate→ItemOrderQuantity→ItemShipQuantity→BuyerItemNumber→ItemProductDesc→CODFlag→CODAmount→CODAddShipCharges→CODCashierCheck→SaturdayDelivery→EndOfLine
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→1→SKU-EXAMPLE-1→20.00→→6.63→2→→→Example face cream 50 ml→N→→N→N→N→EOL
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→2→SKU-EXAMPLE-2→12.50→→6.63→1→→→Example lip balm→N→→N→N→N→EOL
PT-0001002→→Y→N→→N→50954801→PO-0001002→RTL→0001→→ZZ→→→→→
```

EXISTING CLIENTS ONLY

This version is kept for clients that already use it. New clients use version 4.1.

File name	`Any unique name, for example orders-20261110-153000.txt`
Delimiter	Tab
Header row	Yes, first line, with the column names below in this order
Columns	61
Quoting	Not supported. Values must not contain tabs, line breaks or double quotes.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
1	`PickTicketID`	Char	50	Yes	Your order number. It identifies the order in Capacity and comes back in the ship confirmation. Use a new value for every order; every line of the order repeats it.
2	`MasterOrderID`	Char	50	No	Your master or parent order number, if you split one customer order into several. Returned in the ship confirmation.
3	`ReleaseFlag`	Char `Y/N`	1	No	Y to release an EDI purchase order that Capacity is holding for you. N or empty for a new order.
4	`Reship850Flag`	Char `Y/N`	1	No	Reserved for EDI purchase order releases. Send N or leave empty unless Capacity tells you otherwise.
5	`OrderType`	Char	10	No	Your order type code, as set up with Capacity. Empty or unknown values are imported as a regular order.
6	`SpecialProcessingFlag`	Char `Y/N`	1	No	Y when the order needs the special handling agreed with Capacity during onboarding.
7	`CapacityImportID`	Integer	20	Conditional	Release lines only: Capacity's import number of the EDI purchase order you are releasing. Capacity gives you this number. Empty on new orders.
8	`PONumber`	Char	50	No	Customer purchase order number. When empty, Capacity uses PickTicketID. On release lines, the purchase order number of the EDI order.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
9	`RetailerCode`	Char	3	No	Retailer code agreed with Capacity, for example WEB for your own web store. Empty or unknown codes are treated as WEB. On release lines, the retailer of the EDI order.
10	`StoreNumber`	Char	50	No	Customer store number. On release lines, the store of the EDI order.
11	`ShipToLocation`	Char	50	No	Retailer store or distribution center code. When ShipCity, ShipState and ShipZip are all empty, Capacity takes the address from the retailer location with this code.
12	`ClientCode`	Char	2	Yes	Your two-character owner code, for example ZZ. It must match your account; a file with another owner code is rejected.
13	`DropshipID`	Integer	5	No	Reserved. Leave empty.
14	`ExternalCustomerID`	Char	50	No	Your customer number for the buyer.
15	`ShipBusinessName`	Char	128	Conditional	Ship-to company name. Send ShipBusinessName, ShipName or both: at least one is required. Not needed on release lines, which use the address on the EDI purchase order.
16	`ShipName`	Char	128	Conditional	Ship-to person or attention name. Required when ShipBusinessName is empty. Not needed on release lines, which use the address on the EDI purchase order.
17	`ShipAddress1`	Char	128	Conditional	First ship-to address line. Required unless ShipToLocation supplies the address. Carriers print 30 to 35 characters, so keep it short. Not needed on release lines, which use the address on the EDI purchase order.
18	`ShipAddress2`	Char	128	No	Second ship-to address line.
19	`ShipCity`	Char	128	Conditional	Ship-to city. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.
20	`ShipState`	Char	50	Conditional	Ship-to state or province. Use the 2-character code; for the US, Canada and Australia the full name is also accepted. Required unless ShipToLocation supplies the address. An unrecognised state holds the order for review. Not needed on release lines, which use the address on the EDI purchase order.
21	`ShipZip`	Char	20	Conditional	Ship-to ZIP or postal code, for example 08817 or 08817-1234. Required unless ShipToLocation supplies the address. Not needed on release lines, which use the address on the EDI purchase order.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
22	`ShipCountry`	Char	50	No	Ship-to country: ISO 2-character code (for example US) or country name. When empty, Capacity derives the country from ShipState.
23	`ShipPhone`	Char	50	No	Ship-to phone number. Recommended for international shipments.
24	`ShipEmail`	Char	50	No	Ship-to email address, used for carrier delivery notices.
25	`ShipResidentialFlag`	Char `Y/N`	1	No	Y for a residential address, N or empty for a business address. A ship method that is residential-only or commercial-only overrides this flag.
26	`ShipMethod`	Char	100	Conditional	Carrier service, exactly as it appears in the list of ship methods Capacity sets up for your account. Required on new orders; not used on release lines. An empty or unknown value holds the order until Capacity corrects the ship method.
27	`ThirdPartyAccount`	Char	50	No	Carrier account to bill for shipping (third-party billing). The account must be set up with Capacity first.
28	`SignatureRequired`	Char `Y/N`	1	No	Y when the carrier must collect a signature on delivery.
29	`ShipComment`	Char	1000	No	Shipping or packing instructions. Line breaks are removed.
30	`GiftWrapFlag`	Char `Y/N`	1	No	Y to mark the order as a gift.
31	`GiftFrom`	Char	50	No	Gift sender name, printed on the gift message.
32	`GiftTo`	Char	50	No	Gift recipient name, printed on the gift message.
33	`GiftMessage`	Char	1000	No	Gift message text.
34	`BillBusinessName`	Char	128	No	Bill-to company name.
35	`BillName`	Char	128	No	Bill-to person name.
36	`BillAddress1`	Char	128	No	First bill-to address line.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
37	`BillAddress2`	Char	128	No	Second bill-to address line.
38	`BillCity`	Char	50	No	Bill-to city.
39	`BillState`	Char	50	No	Bill-to state or province: 2-character code or name.
40	`BillZip`	Char	20	No	Bill-to ZIP or postal code.
41	`BillCountry`	Char	50	No	Bill-to country: ISO 2-character code or country name.
42	`BillPhone`	Char	50	No	Bill-to phone number.
43	`PaymentTerms`	Char	50	No	Payment terms, printed on the packing slip where your packing slip shows them.
44	`OrderDate`	Date `MM/DD/YYYY`	10	No	Date the customer placed the order. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
45	`RequestedShipDate`	Date `MM/DD/YYYY`	10	No	Do not ship before this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
46	`CancelDate`	Date `MM/DD/YYYY`	10	No	Ship no later than this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
47	`RequestedDeliveryDate`	Date `MM/DD/YYYY`	10	No	Date the customer asked for delivery. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
48	`DeliveryByDate`	Date `MM/DD/YYYY`	10	No	Do not deliver after this date. MM/DD/YYYY (YYYY-MM-DD is also accepted). A date Capacity cannot read is left off the order.
49	`ShippingAmount`	Decimal `Decimal(9,2)`	12	No	Shipping and handling you charged your customer. Returned as TotalChargeAmount in the ship confirmation.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
50	`ShippingTaxRate`	Decimal `Decimal(5,2)`	6	No	Tax rate on shipping, as a percentage from 0.00 to 100.00.
51	`OrderDiscountRate`	Decimal `Decimal(5,2)`	6	No	Order discount, as a percentage from 0.00 to 100.00.
52	`OrderDiscountAmount`	Decimal `Decimal(9,2)`	12	No	Order discount, as an amount.
53	`ItemLineNumber`	Integer	10	No	Your line number. For your reference; the ship confirmation reports Capacity's own line numbers.
54	`ItemProductID`	Char	28	Yes	The Capacity SKU or its alternate SKU. It must already exist in Capacity; an unknown SKU holds the order for review.
55	`ItemUnitAmount`	Decimal `Decimal(9,2)`	12	No	Unit price charged to your customer. Used for packing slips and order totals.
56	`ItemDiscountRate`	Decimal `Decimal(5,2)`	6	No	Line discount, as a percentage from 0.00 to 100.00.
57	`ItemTaxRate`	Decimal `Decimal(5,2)`	6	No	Line tax rate, as a percentage from 0.00 to 100.00.
58	`ItemOrderQuantity`	Integer	10	Yes	Quantity ordered, in units. A whole number of 0 or more, digits only.
59	`ItemShipQuantity`	Integer	10	No	Quantity to ship, in units. Leave empty to ship ItemOrderQuantity. When you send a value, Capacity ships that quantity, so 0 creates a line with nothing to ship. On release lines, the quantity to release.
60	`BuyerItemNumber`	Char	50	No	Your customer's item number for the product.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
61	`EndOfLine`	Char	3	Yes	Always the text EOL. Marks the end of the line. • `EOL` End of line

OrderFile-3.0-sample.txt

```
PickTicketID→MasterOrderID→ReleaseFlag→Reship850Flag→OrderType→SpecialProcessingFlag→CapacityImportID→PONumbe
r→RetailerCode→StoreNumber→ShipToLocation→ClientCode→DropshipID→ExternalCustomerID→ShipBusinessName→ShipName→
ShipAddress1→ShipAddress2→ShipCity→ShipState→ShipZip→ShipCountry→ShipPhone→ShipEmail→ShipResidentialFlag→Ship
Method→ThirdPartyAccount→SignatureRequired→ShipComment→GiftWrapFlag→GiftFrom→GiftTo→GiftMessage→BillBusinessN
ame→BillName→BillAddress1→BillAddress2→BillCity→BillState→BillZip→BillCountry→BillPhone→PaymentTerms→OrderDat
e→RequestedShipDate→CancelDate→RequestedDeliveryDate→DeliveryByDate→ShippingAmount→ShippingTaxRate→OrderDisco
untRate→OrderDiscountAmount→ItemLineNumber→ItemProductID→ItemUnitAmount→ItemDiscountRate→ItemTaxRate→ItemOrde
rQuantity→ItemShipQuantity→BuyerItemNumber→EndOfLine
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817
→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→
US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→1→SKU-EXAMPLE-1→20.00→→6.63→2→→→EOL
PT-0001001→→N→N→→N→→PO-0001001→WEB→→→ZZ→→CUST-0001→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817
→US→555-0100→jordan@example.com→Y→GROUND→→N→→N→→→→→Jordan Example→100 Example Street→Suite 2→Edison→NJ→08817→
US→555-0100→→11/10/2026→11/11/2026→11/20/2026→→→5.95→6.63→→0.00→2→SKU-EXAMPLE-2→12.50→→6.63→1→→→EOL
PT-0001002→→Y→N→→N→50954801→PO-0001002→RTL→0001→→ZZ→→→→→
```

Columns	19
Quoting	Optional. A value may be wrapped in double quotes; a quote inside it is written twice ("").

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
1	`DETAILID`	Integer	10	No	Your line number. For your reference.
2	`SHIPID`	Integer	10	Yes	Your shipment number, digits only. Capacity uses it as the order's PickTicketID; every line of the order repeats it.
3	`PONUMBER`	Char	50	No	Customer purchase order number. When empty, Capacity uses SHIPID.
4	`COMPANY`	Char	128	Conditional	Ship-to and bill-to company name. Send COMPANY, ATTN or both: at least one is required.
5	`ADDRESS`	Char	128	Yes	First ship-to address line, also used as the bill-to address.
6	`ADDRESS2`	Char	128	No	Second ship-to address line.
7	`CITY`	Char	128	Yes	Ship-to city.
8	`STATE`	Char	50	Yes	Ship-to state or province. Use the 2-character code; for the US, Canada and Australia the full name is also accepted.
9	`ZIP`	Char	20	Yes	Ship-to ZIP or postal code.
10	`COUNTRY`	Char	50	No	Ship-to country: ISO 2-character code or country name. When empty, Capacity derives the country from STATE.
11	`ATTN`	Char	128	Conditional	Ship-to person or attention name. Required when COMPANY is empty.
12	`PHONE`	Char	50	No	Ship-to phone number.
13	`QTY`	Integer	10	Yes	Quantity to ship, in units. A whole number, digits only.
14	`PARTNUM`	Char	28	Yes	The Capacity SKU or its alternate SKU. It must already exist in Capacity.
15	`PRODUCTDESCRIPTION`	Char	50	No	Product description for the packing slip.

#	COLUMN	TYPE	MAX LENGTH	REQUIRED	DESCRIPTION
16	`DATE_SHIP_NEEDED`	Date `MM/DD/YYYY`	10	No	Requested ship date.
17	`SHIPMETHOD`	Char	100	Yes	Carrier service, exactly as it appears in the list of ship methods Capacity sets up for your account. An unknown value holds the order until Capacity corrects the ship method.
18	`ORDER_TYPE`	Char	10	No	Your order type code, as set up with Capacity. Empty or unknown values are imported as a regular order.
19	`DIVISION`	Char	50	No	Your division. For your reference; Capacity does not use it.

OrderFile-comma-sample.txt

```
DETAILID,SHIPID,PONUMBER,COMPANY,ADDRESS,ADDRESS2,CITY,STATE,ZIP,COUNTRY,ATTN,PHONE,QTY,PARTNUM,PRODUCTDESCRIPTION,DATE_SHIP_NEEDED,SHIPMETHOD,ORDER_TYPE,DIVISION
1,1001,PO-0001001,Example Company,100 Example Street,,Edison,NJ,08817,US,Jordan Example,555-0100,2,SKU-EXAMPLE-1,Example face cream 50 ml,11/12/2026,GROUND,,
2,1001,PO-0001001,Example Company,100 Example Street,,Edison,NJ,08817,US,Jordan Example,555-0100,1,SKU-EXAMPLE-2,Example lip balm,11/12/2026,GROUND,,
```