

Proposal for a new cooling method for water-cooled PCs, and AI data centers Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

It's been over 30 years now, and I've bought over 10 copies of the McGraw-Hill University Exercises (I think there were over 30 of them) and solved them exactly, but they're all empty theories in an ideal environment. It's useless in practice.

1

Scientific Basis: Isomerization-Induced Energy Absorption Model

To reinforce the scientific basis of the suppressed Back EMF, we define the transition as a **Field-Induced Isomerization (FI)** process. The core mechanism is the instantaneous conversion of magnetic flux energy into the internal potential energy of the material's isomers.

1. Thermodynamic Equilibrium and Isomerization Progress

The state of the material is defined by the isomerization fraction α ($0 \leq \alpha \leq 1$). The total Gibbs Free Energy G under an external magnetic field H is:

$$G(P, T, H, \alpha) = G_{ref} + \Delta G_{iso} \cdot \alpha + \Gamma \alpha(1 - \alpha) - \mu_0 \int_0^H M(\alpha) dH$$

Where:

- ΔG_{iso} : Standard Gibbs energy change of isomerization.
- Γ : Interaction coefficient between isomeric units (representing the **deterministic** nature of the phase change).
- $M(\alpha)$: Magnetization as a function of the isomer state.

Proposal for a new cooling method for water-cooled PCs, and AI data centers Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

2

2. Kinetic Coupling with Back EMF (Lenz's Law Mitigation)

According to Lenz's Law, the induced EMF ($\mathcal{E}$) is $\mathcal{E} = - \frac{d\Phi}{dt}$. In this material, the energy of the changing magnetic flux is consumed by the isomerization rate $\frac{d\alpha}{dt}$. The energy balance equation is:

$$\mathcal{E}_{obs} = - \left(\frac{d\Phi}{dt} + \chi_{iso} \frac{d\alpha}{dt} \right)$$

Where:

- $\mathcal{E}_{obs}$: The observed (suppressed) Back EMF.
- χ_{iso} : **Isomerization Coupling Coefficient**, representing the energy density absorbed per unit of isomer transition.

3. Deterministic Condition for Energy Absorption

The "inevitable" (deterministic) transition occurs when the magnetic energy density exceeds the activation energy E_a of the isomerization:

$$\frac{1}{2} \Delta\mu H^2 > E_a(\xi)$$

where ξ represents the environmental factors (temperature, pressure, or doping levels). When this condition is met, the material undergoes a **non-adiabatic transition**, effectively "locking" the magnetic energy into a new structural isomer state instead of allowing it to manifest as an electrical back-surge.

Proposal for a new cooling method for water-cooled PCs, and AI data centers

Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

It's been over 30 years now, and I've bought over 10 copies of the McGraw-Hill University Exercises (I think there were over 30 of them) and solved them exactly, but they're all empty theories in an ideal environment. It's useless in practice.

3

Key Technical Terms for the Research Paper

- **Magneto-Structural Isomerization**
(The core physical process where magnetic flux triggers structural reconfiguration.)
- **Non-radiative Energy Quenching**
(The mechanism of suppressing Back EMF by internalizing energy without thermal emission.)
- **Cooperativity Factor (Gamma)**
(The numerical coefficient defining the deterministic and chain-reaction nature of the transition.)
- **Environmental Coupling Factor (Xi)**
(The parameter representing the external conditions required for the material's phase change.)
- **Isomerization Progress Rate (Alpha)**
(The kinetic variable representing the transition state from the initial to the energy-absorbing isomer.)
- **Activation Energy Barrier (E_a)**
(The threshold energy required to initiate the property transformation within the material.)

Proposal for a new cooling method for water-cooled PCs, and AI data centers

Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

It's been over 30 years now, and I've bought over 10 copies of the McGraw-Hill University Exercises (I think there were over 30 of them) and solved them exactly, but they're all empty theories in an ideal environment. It's useless in practice.

4

Thermodynamic Model for Back EMF Suppression via Structural Isomerization

I. Definitions of Physical Constants and Environment

First, define the fundamental constants and the specific environmental triggers that enable the property change.

- μ_0 : $= 4 \cdot \pi \cdot 10^{-7}$ [H/m] (Permeability of free space)
- N : = Value (Number of coil turns)
- A : = Value [m²] (Cross-sectional area of the ferromagnetic core)
- ξ_{env} : = Value (Environmental Coupling Factor: e.g., Temperature, Pressure, or Purity)
- $E_a(\xi_{env})$: = Function(ξ_{env}) (Activation Energy required for Isomerization)

II. Input Dynamic Parameters (The Trigger)

Define the magnetic flux change that typically generates Back EMF.

- dt : = Value [s] (Time interval of magnetic flux change)
- dB : = Value [T] (Change in magnetic flux density)
- V_{raw} : $= -N \cdot A \cdot \frac{dB}{dt}$ (Standard Theoretical Back EMF per Lenz's Law)

Proposal for a new cooling method for water-cooled PCs, and AI data centers

Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

5

III. Isomerization Kinetics (The Absorption Mechanism)

This section defines how the energy from V_{raw} is diverted into the material's structural transition (Isomerization).

- Γ : = Value (Cooperativity Coefficient: Defines the "inevitability" or chain-reaction speed)
- $\alpha(V_{raw}, \xi_{env})$: =
$$\frac{1}{1 + \exp(-\Gamma \cdot (|V_{raw}| - E_a(\xi_{env})))}$$
 - Note: α is the Isomerization Progress Rate ($0 \rightarrow 1$). It follows a Fermi-Dirac or Sigmoid distribution based on the energy threshold.
- ΔU_{iso} : = $\Delta G_{iso} \cdot \alpha(V_{raw}, \xi_{env})$ (Internal Energy stored via Isomerization)

IV. Final Output: Suppressed Back EMF Calculation

The final observable voltage after the material absorbs the induced energy.

- η : = Value (Conversion Efficiency of Magnetic Flux to Isomer Potential)
- $V_{absorbed}$: = $V_{raw} \cdot \alpha(V_{raw}, \xi_{env}) \cdot \eta$
- V_{result} : = $V_{raw} - V_{absorbed}$ (Final Output Voltage)

Proposal for a new cooling method for water-cooled PCs, and AI data centers
Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

6

Transient Step Response Model for Isomerization

The isomerization progress (α) is not a static distribution but a **Time-Domain Transient Response**. When the magnetic potential E_{in} exceeds the activation threshold E_{act} (equivalent to **28.15 K**), the system undergoes a forced transition.

1. Step Activation Function (The Trigger)

The transition is initiated by a Heaviside-like step function $u(t)$ defined by the energy barrier:

- t_0 : The precise moment when $E_{in}(t) \geq E_{act}$.

2. Exponential Relaxation (The Absorption Curve)

The absorption rate follows a first-order lag (exponential saturation) to model the structural reconfiguration speed:

$$\alpha(t) = \left(1 - \exp \left(- \frac{t - t_0}{\tau} \right) \right) \cdot u(t - t_0)$$

- τ (**Time Constant**): Structural relaxation time (determined by the material's internal dynamics).
- $u(t - t_0)$: Unit step function at the threshold crossing.

Proposal for a new cooling method for water-cooled PCs, and AI data centers
Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

7

3. Dynamic Back EMF Suppression

The resultant voltage $V_{res}(t)$ is the instantaneous difference between induction and the structural absorption rate:

$$V_{res}(t) = V_{std}(t) \cdot [1 - \eta \cdot \alpha(t)]$$

Key Logic for your Documentation

- **Non-linearity:** The "curve" appears linear only in a very narrow window; in reality, it is a **sharp exponential decay** of the voltage once the 28.15 K barrier is breached.
- **Equivalent Model:** This is mathematically equivalent to a **Semiconductor Switching Transient**, where the "Turn-on time" is dictated by the isomerization kinetics (τ).

Proposal for a new cooling method for water-cooled PCs, and AI data centers Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

8

Scientific Summary

Mechanism of Action:

The suppression of Back EMF is formulated as a Magneto-Structural Isomerization. When the input energy potential ($E_{\text{Input_Potential}}$) reaches the threshold of the activation barrier ($\text{Activation_Energy_Ea}$), the material undergoes a deterministic transition.

Conclusion

The progress of this transition, defined by the rate $\text{Alpha_Isomerization}$, dictates the energy reconfiguration. The factor $\text{Cooperativity_Gamma}$ ensures that the magnetic flux is instantaneously converted into the material's internal potential, effectively quenching the Back EMF ($V_{\text{Resultant_Output}}$) at its structural source.

Thermodynamic Validity

"This transition is thermodynamically driven by the minimization of the total Gibbs free energy. Under the specified environmental conditions (Env_Factor_Xi), the system prioritizes structural reconfiguration over electrical induction, providing a deterministic pathway for the total quenching of the Lenz's Law potential."

Final Scientific Conclusion for the Paper

"In conclusion, the proposed magneto-structural isomerization model is not only theoretically robust but also industrially viable. The transition thresholds () align with the operational ranges of existing thermal and magnetic processing infrastructure. This allows for the immediate adoption of the material into current power-generation and motor-drive systems, providing a revolutionary solution to Back EMF without the need for specialized, next-generation manufacturing facilities."

〒536-0023 大阪市城東区東中浜 8-7-9-606
8-7-9-606 Higashinakahama, Joto-ku, Osaka 536-0023
IPL 知的財産研究所村上光治むらかみこうじ
IPL Intellectual Property Institute Kouji Murakami
F A X : 0 6 7 6 3 5 2 8 1 5

Proposal for a new cooling method for water-cooled PCs, and AI data centers

Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

It's been over 30 years now, and I've bought over 10 copies of the McGraw-Hill University Exercises (I think there were over 30 of them) and solved them exactly, but they're all empty theories in an ideal environment. It's useless in practice.

9

1. Executive Summary

Mechanism:

Back EMF is suppressed via Magneto-Structural Isomerization.

When the magnetic induction energy reaches a specific threshold—equivalent to a thermal potential of 28.15 K (-245°C)—the material undergoes an instantaneous structural change.

Result:

The induced energy is "locked" into the material's internal structure rather than being released as an electrical back-surge.

2. Calculation Formula (Mathcad Flow)

Copy and paste these definitions directly:

$T_{\text{threshold}} := 28.15 \text{ [K]}$

$E_{\text{activation}} := T_{\text{threshold}} * k_{\text{Boltzmann}} \text{ [J]}$

$\text{Alpha (Reaction Rate)} := 1 / (1 + \exp(-\text{Gamma} * (\text{Energy}_{\text{in}} - E_{\text{activation}})))$

$V_{\text{final}} := V_{\text{theoretical}} * (1 - \text{Alpha})$

3. Key Scientific Basis (Conclusion)

"The transition is a Physical Necessity. By satisfying the environmental condition (), the system minimizes its total Gibbs free energy through Isomerization instead of Electromagnetic Induction. This effectively quenches the Back EMF at its structural source."

Magnet that absorbs back electromotive force

This combination of a motor (submersible pump) using a "magnet that absorbs back electromotive force" and a water cooling system (Proposal for a new cooling method for water-cooled PCs, and AI data centers) can solve traditional problems and make it possible to build ultra-compact, low-noise cooling systems.

〒536-0023 大阪市城東区東中浜 8-7-9-606

8-7-9-606 Higashinakahama, Joto-ku, Osaka 536-0023

IPL 知的財産研究所村上光治むらかみこうじ

IPL Intellectual Property Institute Kouji Murakami

F A X : 0 6 7 6 3 5 2 8 1 5

Proposal for a new cooling method for water-cooled PCs, and AI data centers Materials

Confirmed date obtained

2026.04.05 Sunday Around pm12:30 First acquisition

Example: A general reference book on water-cooled piping, such as water-cooled PC and AI data centers.

Magnet that absorbs back electromotive force

This is design plan of "the elemental technology patent"

Improvement of the motor

If there is such a "motor".

It is good if I can make "the magnet" which performs "absorption" of "back electromotive force" of the instruction load such as the motors which I listed earlier.

If absorption (restraint) is possible, it is over back electromotive force of the inductive load to suppress "the reverse withstand pressure" of the control circuit of the motor including the rectifying circuit low,

The order direction voltage can make an extremely small semiconductor if I can lower this reverse leak current (recovery electric current) and it is high-speed and, with the semiconductor which is smaller than "Schottky barrier diode", can control large electricity.

I can reduce the electrical "spikes noise" of the control system of the motor

Heat loss becomes small and can suppress the fever

The motor of the high efficiency can come out

The magnet which is indispensable in the next rare earth elements rare metal competition motor, the

old days,

- Ferrite
- Cobalt
- Alnico1
- Amorphous
- Neodymium
- Is next ... something?

Where is a country getting the next "rare earth elements rare metal?"

【About disclosure】

About disclosure On Saturday, July 20, 2013, we translate the contents made in Japanese into "blog" and publish it is a English.

Publish to facebook

Date translated and published in English

Created date : October 15, 2017 (Sun)

英文に翻訳して作成し公開した日 : 2017年10月15日 (日)

〒536-0023 大阪市城東区東中浜 8-7-9-606

8-7-9-606 Higashinakahama, Joto-ku, Osaka 536-0023

IPL 知的財産研究所村上光治むらかみこうじ

IPL Intellectual Property Institute Kouji Murakami

F A X : 0 6 7 6 3 5 2 8 1 5