INGENIC

RD_T30_KOALA_D

Schematic Revision 1.1

Title	Page
COVER SHEET	1
SYSTEM ARCHITECTURE	2
POWER_SUPPLY	3
T30_POWER	4
T30_IO/NOR FLASH/EEPROM	5
DVP_CONNECTOR/SD_CARD	6
ETH/USB/AUDIO	7
RST/BOOT/LDR/DEBUG/JTAG	8
REVISION HISTORY	9

INGENIC SEMICONDUCTOR CO.,LTD

Title: RD_T30_KOALA_D

Size: A3 | Page Name: COVER SHEET | Rev: 1.1

Date: Wednesday, April 17, 2019 | Sheet 1 of 9





INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: SYSTEM ARCHITECTURE	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 2 of 9	

POWER SUPPLY

12V DC-IN



5V/2A



Note: Compatible with DIO6912

VOUT=(1+200K/27K)*0.6=5.044V

1.8V/300mA



Indicitor LED



3.3V/1A



Note: Compatible with DIO6001/ETA3486

VOUT=(1+150K/33.2K)*0.6=3.311V

VCC_DDR/1A



Note: Compatible with DIO6001/ETA3486

VCC_DDR=(1+200K/100K)*0.6=1.8V(R5=200K/1%) FOR T30X/L/N

VCC_DDR=(1+150K/100K)*0.6=1.5V(R5=150K/1%) FOR T30Z

VCC_DDR=(1+150K/120K)*0.6=1.35V(R5=150K/1%) FOR T30A √

1.0V/1A



Note: Compatible with DIO6001/ETA3486

VOUT=(1+68K/100K)*0.6=1.0V



Mechanical Hole

INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: POWER_SUPPLY	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 3 of 9	

T30-POWER



INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: T30_POWER	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 4 of 9	

T30_IO/NOR FLASH/EEPROM









INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: T30_IO/NOR FLASH/EEPROM	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 5 of 9	

DVP_CONNECTOR/SD_CARD





INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: DVP_CONNECTOR/SD_CARD	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 6 of 9	

ETH_RMII/USB/AUDIO









INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: ETH/USB/AUDIO	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 7 of 9	

RST/BOOT/LDR/DEBUG/JTAG

DEBUG



JTAG



BOOT CONFIGURATION



BOOT_SEL1	BOOT_SEL0	BOOT FROM
0	0	SD card : MSC0
0	1	SFC : SPI0/SSI_CE0

LDR



RESET CIRCUITS



INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: RST/BOOT/LDR/DEBUG/JTAG	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 8 of 9	

Date	Revision	Change
Nov 09 2017	Rev1.0	1. First Revision
Apr 16 2019	Rev1.1	1. Optimize DDR Voltage Comments 2. Add DCDC notes 3. Change 3.3V(LDR pull-up resistor power) to 1.8V

INGENIC SEMICONDUCTOR CO.,LTD		
Title: RD_T30_KOALA_D		
Size: A3	Page Name: REVISION HISTORY	Rev: 1.1
Date: Wednesday, April 17, 2019	Sheet 9 of 9	