CHERRY



MX2A BLACK

DATASHEET

CHERRY MX2A BLACK

THE LINEAR SWITCHING CHARACTERISTIC COMBINED WITH AN INCREASED SPRING FORCE TRIGGERS DIRECTLY. THANKS TO A STRONGER SPIRAL SPRING, THE TRIED AND TRUE CHERRY MX BLACK SMOOTHLY MOVES THE KEYS BACK TO THE STARTING POSITION AND GRANTS THE NECESSARY STAYING POWER FOR LONG WRITING AND GAMING SESSIONS.

POWERFUL AND DIRECT

Original CHERRY MX is the world´s leading precision technology for mechanical key switches. The CHERRY Gold Crosspoint contact concept and the unprecedented production quality "Made in Germany" are unique. The MX2A series introduces a new level typing experience, setting a new standard for mechanical key switches.

TECHNICAL DATA

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	no
Warranty	2 years warranty
Stem color	Black
Cover colour	Black
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms
Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm

Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

PRODUCT VARIANTS

PART NUMBER	RGB
MX2A-11DN	no
MX2A_11NA	yes
MX2A_11NB	yes
MX2A-11NN	no
MX2A-11NW	no

MX2A BLACK [MX2A-11DN]



RGB: no

Part number	MX2A-11DN
EAN	4025112121371

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	no
Warranty	2 years warranty
Stem color	Black
Cover colour	Black
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms

Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm
Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

MX2A BLACK [MX2A_11NA]



RGB: yes

Part number	MX2A_11NA
EAN	4025112121371

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	yes
Warranty	2 years warranty
Stem color	Black
Cover colour	transparent
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms

Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm
Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

MX2A BLACK [MX2A_11NB]



RGB: yes

Part number	MX2A_11NB
EAN	4025112119200

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	yes
Warranty	2 years warranty
Stem color	Black
Cover colour	transparent
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms

Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm
Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

MX2A BLACK [MX2A-11NN]



RGB: no

Part number	MX2A-11NN
EAN	4025112108402

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	no
Warranty	2 years warranty
Stem color	Black
Cover colour	Black
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms

Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm
Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

MX2A BLACK [MX2A-11NW]



RGB: no

Part number	MX2A-11NW
EAN	4025112108419

SWITCH

Switch serie	MX Standard
IP protection class	40
RGB	no
Warranty	2 years warranty
Stem color	Black
Cover colour	Black
Bottom housing colour	Black
Actuator travel	4 mm
Pre-Travel	2 mm
Actuation characteristic	linear
Actuation force	60 cN
Initial force	30 cN
Final force	110 cN
Contact force	32 cN
Contact resistance	200 mΩ
Bounce time	5 ms

Operating temperature range min.	10 °C
Operating temperature range max.	70 °C
Storage temperature range min.	10 °C
Storage temperature range max.	70 °C
Total Height	18.5 mm
Width	15.63 mm
Depth	15.63 mm
Hotswap	no

PRODUCT INFORMATION

Dimensions and weight (without packaging)	1.6 g
Dimensions and weight (including packaging)	1.6 g

© Cherry Europe GmbH

Cherrystraße 2 · 91275 Auerbach/OPf. · Germany

cherry-world.com · cherry.de

Sales Support · Technischer Support · eHealth Support

+49 9643 - 2061 - 100

www.cherry.de/de-de/kontakt

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products.