N-K30

Finger	RFID	Inbuilt Battery	LAN	USB	Access Control

Time Attendance and Access Control

Storage Capacity

Finger Capacity	2000
Card Capacity	2000
Max User	2000
Password	2000
Log Capacity	1,50,000

Fetures

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

N-K30
"The Convenient biometric Finger verification ."

www.biomaxsecurity.com

Communication Interface

Communication	TCP/IP, USB

Biometric

Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)

Accepts moist and rough Finger

Accepts Color & Mahendi Finger

Compact & lightweight design

Unaffected by High Temperatures 0° ~ 50°

Audio/Visual

LCD	2.4" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software
Desktop, Web, Cloud

Time Attendance

Access Control

Employee Self Service

Mobile App

Access control

Relay	YES
Support Exit Reader	Remote, Push Button, No Touch

Power & Enviroment

Inbuilt Battery Backup	YES
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	160 x 150 x 65 mm