N-X990
Most Versatile Model

Finger	RFID	Inbuilt Battery	WiFi	LAN	USB	4G GPRS (Optional)	Access Control

Time Attendance and Access Control System

Storage Capacity

Finger Capacity	10,000 (20,000 Optional)
Card Capacity	10,000 (20,000 Optional)
Max User	10,000 (20,000 Optional)
Password	10,000 (20,000 Optional)
Log Capacity	2,00,000

Fetures

High-Speed and Accurate Fingerprint Identification
Fingerprint, Card, Password authentication
output relay for door open.
Good adaptation for dry, moist and rough fingerprints.
Supremely low Electric energy consumption.
Highly reliable and durable.
Comprehensive software development kit(SDK) is available for development and integration.

N-X990
"With Impressive features leveled up to meet your demands."

Communication Interface

Communication	WIFI, TCP/IP, USB, RS232/485

Biometric

Push Data	YES
4G GPRS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	1 GHz
Verification Time	<=1 second
Printer	YES
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)

Audio/Visual

LCD	3" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand input/output	YES
Relay	YES
Support Exit Reader	N-FR12, Wiegand Reader,
	Remote, Push Button, No Touch

Power & Enviroment

Inbuilt Battery Backup	YES
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	160 x 210 x 40 mm

Accepts moist and rough Finger

Accepts Color & Mahendi Finger

WiFi, TCP/IP, RS232/485, USB

Unaffected by High Temperatures 0° ~ 50°

Software
Desktop, Web, Cloud

Time Attendance

Access Control

Employee Self Service

Mobile App