Caprock DRILL BITS

7-5/8” CR613-SR(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	1/2”
Cutter Count (Total, Gage)	37,6
Blade Count	6
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	9.78
Max. TFA (Sq. Inches)	1.49

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	17,399

Nominal Dimensions:

Overall Length (Inches)	13.55
Make Up Length (Inches)	9.42
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	95

Standard Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

613-SR(K) Nomenclature Explained:

- 6 = Number of blades
- 13 = Primary Cutter Size (13mm)
- SR = Single Row of Cutters
- K = Bullets

3446 S. Main | Pearland, Texas 77581 | (866) 470-4202

Caprock DRILL BITS

7-5/8” CR613-SR(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	1/2”
Cutter Count (Total, Gage)	37,6
Blade Count	6
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	9.78
Max. TFA (Sq. Inches)	1.49

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	17,399

Nominal Dimensions:

Overall Length (Inches)	13.55
Make Up Length (Inches)	9.42
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	95

Standard Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

613-SR(K) Nomenclature Explained:

- 6 = Number of blades
- 13 = Primary Cutter Size (13mm)
- SR = Single Row of Cutters
- K = Bullets

3446 S. Main | Pearland, Texas 77581 | (866) 470-4202

Caprock DRILL BITS

7-5/8” CR613-SR(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	1/2”
Cutter Count (Total, Gage)	37,6
Blade Count	6
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	9.78
Max. TFA (Sq. Inches)	1.49

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	17,399

Nominal Dimensions:

Overall Length (Inches)	13.55
Make Up Length (Inches)	9.42
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	95

Standard Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

613-SR(K) Nomenclature Explained:

- 6 = Number of blades
- 13 = Primary Cutter Size (13mm)
- SR = Single Row of Cutters
- K = Bullets

3446 S. Main | Pearland, Texas 77581 | (866) 470-4202