9-7/8” CR619-SR

Drill Bit Specifications:

Cutter Size (Primary, Sec)	3/4” , 5/8”
Cutter Count (Total, Gage, Back Ream)	32 , 7
Blade Count	6
Gage Length (Inches)	3.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	17.60
Max. TFA (Sq. Inches)	1.49

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	50
Make-up Torque (ft/lbs)	40,563

Nominal Dimensions:

Overall Length (Inches)	*16.00
Make Up Length (Inches)	*11.12
Bit Breaker	SKB-21011
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	*165

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs. to approximate weight).

Taylor-Made Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

619-SR Nomenclature Explained:

- 6 = Number of Blades
- 19 = Primary Cutter Size (19mm)
- SR = Single Row

3446 S. Main
Pearland, TX 77581
1-866-470-4202