17-1/2” CR616-SR9

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage)	82,14
Blade Count	6
Gage Length (Inches)	3.5
Nozzle Count (Primary, Sec.)	9
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	83.9
Max. TFA (Sq. Inches)	3.34

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	66
Make-up Torque (ft/lbs)	40,500

Nominal Dimensions:

Overall Length (Inches)	20.25
Make Up Length (Inches)	15.375
Bit Breaker	SKB-21036
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	420

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs to approximate weight).

Standard Features:

- Large open face volume assists cuttings removal
- Nine nozzles optimize blade cleaning and cuttings removal
- Premium grade cutters maximize ROP and Life

616-SR9 Nomenclature Explained:

- 6 = Number of blades
- 16 = Primary Cutter Size (16mm)
- SR = Single Row of Cutters
- 9 = Number of Nozzles

**Interchangeable nozzles.*

3446 S. Main
Pearland, TX 77581
1-866-470-4202