6-1/8” 413-SR(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec.)	1/2”
Cutter Count (Total, Gage)	23,7
Blade Count	4
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	4
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	7.80
Max. TFA (Sq. Inches)	0.99

Operating Parameters:

Max. Hydraulic Flow Rate (GPM)	345
Max. Weight on Bit (1,000 Lbs.)	20
Make-up Torque (ft/lbs)	7611

Nominal Dimensions:

Overall Length (Inches)	10.95
Make Up Length (Inches)	7.20
Bit Breaker	SKB-21012
Connection	Ø3-1/2" API Reg.
Approx. Weight (Lbs.)	45

Standard Features:

- Large open face volume assists cuttings removal
- Four nozzles optimize blade cleaning and cuttings removal
- Premium grade cutters maximize ROP and Life

413-SR(K) Nomenclature Explained:

- 4 = Number of Blades
- 13 = Primary Cutter Size (13mm)
- SR = Single Row Cutters
- K = Bullets

3446 S. Main
Pearland, TX 77581

1-866-470-4202