8-3/4” 516-SR

Drill Bit Specifications:

Cutter Size	5/8" , 1/2”
Cutter Count (Total, Gage)	32, 6
Blade Count	5
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	5
Nozzle Size (Primary, Sec.)	60
JSA (Sq. Inches)	20.41
Max. TFA (Sq. Inches)	1.86

Operating Parameters:

Max Hydraulic Flow Rate (GPM)	578
Max. Weight on Bit (1,000 Lbs.)	32
Make-up Torque (ft/lbs)	16,488

Nominal Dimensions:

Overall Length (Inches)	13.71
Make Up Length (Inches)	9.65
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	85

Standard Features:

- Large open face volume assists cuttings removal
- Five nozzles optimize blade cleaning and cuttings removal
- Premium grade cutters maximize ROP and life
- PDC inserts for increased gage protection

516-SR Nomenclature Explained:

- 5 = Number of blades
- 16 = Primary Cutter Size (16mm)
- SR = Single Row of Cutters
- 5 = Number of nozzles*

**Interchangeable nozzles.*

3446 S. Main
Pearland, TX 77581

1-866-470-4202