6-3/4” CR613-XR(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	1/2”,7/16”
Cutter Count (Total,Gage,Back Ream)	54,12,6
Blade Count	6
Gage Length (Inches)	1.50
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	55
JSA (Sq. Inches)	12.20
Max. TFA (Sq. Inches)	1.18

Operating Parameters:

Max. Hydraulic Flow Rate (GPM)	306
Max. Weight on Bit (1,000 Lbs.)	28
Make-up Torque (ft/lbs)	8,913

Nominal Dimensions:

Overall Length (Inches)	10.65
Make Up Length (Inches)	6.90
Bit Breaker	SKB-21012
Connection	Ø3-1/2" API Reg.
Approx. Weight (Lbs.)	45

Tailor-Made Features:

- Premium grade cutters maximize ROP and Bit Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

613-XR(BR) Nomenclature Explained:

- 6 = Number of Blades
- 13 = Primary Cutter Size (13mm)
- XR = Backup Cutters
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202