12-1/4” CR516-XR8(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage, Back Ream)	83,7,5
Blade Count	5
Gage Length (Inches)	6.00
Nozzle Count (Primary, Sec.)	8
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	42.33
Max. TFA (Sq. Inches)	2.97

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	40,563

Nominal Dimensions:

Overall Length (Inches)	*22.86
Make Up Length (Inches)	*17.99
Bit Breaker	SKB-21011
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	*285

*Long tool joint available upon request (adds 6” to fishing neck, makeup and overall length, and 64 lbs to approximate weight).

Tailor-Made Features:

- Premium grade cutters maximize ROP and Life
- Customized step gauge design
- Eight nozzles optimize blade cleaning and cuttings removal
- Large open face volume assists cuttings removal
- PDC inserts for increased gage protection

516-XR8(K)(BR) Nomenclature Explained:

- 5 = Number of blades
- 16 = Primary Cutter Size (16mm)
- XR = Backup Cutters
- 8 = Number of Nozzles
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202