6-3/4” CR516-XR(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total,Gage,Back Ream)	39,5,5
Blade Count	5
Gage Length (Inches)	4.00
Nozzle Count (Primary, Sec.)	5
Nozzle Series (Primary, Sec.)	55
JSA (Sq. Inches)	9.64
Max. TFA (Sq. Inches)	0.98

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	28
Make-up Torque (ft/lbs)	7,611

Nominal Dimensions:

Overall Length (Inches)	13.26
Make Up Length (Inches)	9.50
Bit Breaker	SKB-21012
Connection	Ø3-1/2" API Reg.
Approx. Weight (Lbs.)	65

Tailor-Made Features:

- Premium grade cutters maximize ROP and Life
- Customized gauge design featuring 4” total gauge length - 1” full plus 3” tapered
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

516-XR(BR) Nomenclature Explained:

- 5 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- XR = Backup Cutters
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202