9-7/8” CR516-XR8(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage, Back Ream)	61,10,5
Blade Count	5
Gage Length (Inches)	3.00
Nozzle Count (Primary, Sec.)	8
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	26.58
Max. TFA (Sq. Inches)	2.97

Operating Parameters:

Max. Hydraulic Flow Rate (GPM)	650
Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	17,399

Nominal Dimensions:

Overall Length (Inches)	16.79
Make Up Length (Inches)	12.73
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	140

Standard Features:

- Premium grade cutters maximize ROP and Life
- Large open face volume assists cuttings removal
- Eight nozzles optimize blade cleaning and cuttings removal
- Selectively positioned bullets for smooth drilling
- PDC inserts for increased gage protection
- 1" full gage, 2" tapered gage at 1°

516-XR8(K)(BR) Nomenclature Explained:

- 5 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- XR = Backup Cutters
- 8 = Number of Nozzles
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202