8-3/4” CR516-XR(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage, Back Ream)	51,10, 5
Blade Count	5
Gage Length (Inches)	3.00
Nozzle Count (Primary, Sec.)	5
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	19.04
Max. TFA (Sq. Inches)	1.86

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	16,488

Nominal Dimensions:

Overall Length (Inches)	15.55
Make Up Length (Inches)	11.49
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	110

Standard Features:

- Large open face volume assists cuttings removal
- Seven nozzles optimize blade cleaning and cuttings removal
- Premium grade cutters maximize ROP and Life
- Selectively positioned bullets for smooth drilling
- 1" full gage, 2" tapered gage at 1°

516-XR(K)(BR) Nomenclature Explained:

- 5 = Number of Blades
- 16 = Primary Cutter Size (16mm)
- XR = Backup Cutters
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202