17-1/2” CR616-SR+9(K)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	5/8”,1/2”
Cutter Count (Total, Gage)	100,12
Blade Count	6
Gage Length (Inches)	7.00
Nozzle Count (Primary, Sec.)	9
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	83.93
Max. TFA (Sq. Inches)	3.34

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	40,500

Nominal Dimensions:

Overall Length (Inches)	24.23
Make Up Length (Inches)	19.36
Bit Breaker	SKB-21036
Connection	Ø6-5/8" API Reg.
Approx. Weight (Lbs.)	590

Standard Features:

- Large open face volume assists cuttings removal
- Nine nozzles optimize blade cleaning and cuttings removal
- Premium grade cutters maximize ROP and Life

616-SR+9(K) Nomenclature Explained:

- 6 = Number of blades
- 16 = Primary Cutter Size (16mm)
- SR+ = Partial Backup Cutters
- 9 = Number of Nozzles
- K = Bullets

**Interchangeable nozzles.*

3446 S. Main
Pearland, TX 77581
1-866-470-4202