8-3/4” CR613-SR+(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary)	1/2”
Cutter Count (Total, Gage, Back Reaming)	64,12,6
Blade Count	6
Gage Length (Inches)	2.00
Nozzle Count (Primary, Sec.)	6
Nozzle Series (Primary, Sec.)	60
JSA (Sq. Inches)	16.45
Max. TFA (Sq. Inches)	2.23

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	60
Make-up Torque (ft/lbs)	16,488

Nominal Dimensions:

Overall Length (Inches)	14.2
Make Up Length (Inches)	10.08
Bit Breaker	SKB-21010
Connection	Ø4-1/2" API Reg.
Approx. Weight (Lbs.)	100

Standard Features:

- Premium grade cutters maximize ROP and Life
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

613-SR+(K)(BR) Nomenclature Explained:

- 6 = Number of blades
- 13 = Primary Cutter Size (13mm)
- SR+ = Partial Backup Row of Cutters
- K = Bullets
- BR = Back Reamers

3446 S. Main
Pearland, TX 77581
1-866-470-4202