6-3/4” CR513M-XR(K)(BR)

Drill Bit Specifications:

Cutter Size (Primary, Sec)	1/2”,7/16”
Cutter Count (Total,Gage,Back Ream)	51,7,5
Blade Count	5
Gage Length (Inches)	4.00
Nozzle Count (Primary, Sec.)	5
Nozzle Series (Primary, Sec.)	55
JSA (Sq. Inches)	9.82
Max. TFA (Sq. Inches)	1.24

Operating Parameters:

Max. Weight on Bit (1,000 Lbs.)	28
Make-up Torque (ft/lbs)	7,611

Nominal Dimensions:

Overall Length (Inches)	13.38
Make Up Length (Inches)	9.64
Bit Breaker	SKB-21012
Connection	Ø3-1/2" API Reg.
Approx. Weight (Lbs.)	120

Tailor-Made Features:

- Premium grade cutters maximize ROP and Life
- Customized gauge design: 4” total gauge length - 1” full, 3” tapered @ 0.8°
- Nozzle configuration and large open face volume optimize blade cleaning and cuttings removal

513M-XR(K)(BR) Nomenclature Explained:

- 5 = Number of Blades
- 13 = Primary Cutter Size (13mm)
- M = Matrix Bit Body
- XR = Backup Cutters
- K = Bullets
- BR = Back Reaming Cutters

3446 S. Main
Pearland, TX 77581
1-866-470-4202